Fujitsu recommends Windows 11 Pro.



Data Sheet Fujitsu Tablet LIFEBOOK U5313X

Your ultimate productivity partner

Unleash your productivity with the Fujitsu LIFEBOOK U5313X, the ultimate convertible notebook. Featuring advanced security, seamless connections, superior performance, and convenient pen and touch options, this device is designed to help you stay productive wherever you go.

Flexible allround champion

Secure flexibility for every task - the whole day long

- Magnesium A-cover
- MIL-STD-810H durability tested
- 16:10 WUXGA 13,3" LCD supporting pen input
- Low power LCD option for 20% longer battery runtime loaded for a full working day

Highly secure system

Advanced security features keep your data safe

- Privacy Camera Shutter to protect your privacy
- PalmSecure[™] as your personal biometric key
- Fingerprint & Full HD IR Camera supporting Windows Hello
- SmartCard reader
- Kensington Lock support

Creative and productive collaboration

Work remotely together and forget about distance

- AES pen with 4K pressure level to get your creative tasks or signing done
- Pen garage with inductive charging have your pen always ready to use
- Optional 5 MP rear camera

Excellent connectivity

Stay connected with ease wherever you are

■ Complete set of full-sized interfaces: HDMI, LAN and USB Type-C with Intel® Thunderbolt™ 4













Components

Base unit	LIFEBOOK U5313X		
Operating systems			
Operating system pre-installed	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home		
Operating system compatible	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home		
Microsoft OS support information	Windows 11 requires for first device setup: - Internet connectivity - Microsoft account for Home editions or organizational account (e.g. ADD) for Pro editions After product end of life, Fujitsu continues to test and support new Windows releases for max. 5 years, depending o extension of hardware services through warranty top ups. For more details please visit our Fujitsu Service Statement under https://support.ts.fujitsu.com/IndexProdSupport.asp?Ing=com&OpenTab=		
Operating system notes	The use of Windows Operating System is subject to acceptance of the End User License Agreement of Microsoft as applicable under the relevant Microsoft program.		
Processor	Intel® Core™ i7-1365U processor (10 Cores, up to 5.2 GHz) * Intel® Core™ i5-1345U processor (10 Cores, up to 4.7 GHz) * Intel® Core™ i5-1335U processor (10 Cores, up to 4.6 GHz) * *Processor only for retail, SMB, education and government		
Hard disk drives	SSD 256GB Value-PCle G4 M.2 2280 SED (FDE/Opal2.0) SSD 512GB Value-PCle G4 M.2 2280 SED (FDE/Opal2.0) SSD 1TB Value-PCle G4 M.2 2280 SED (FDE/Opal2.0) SSD 512GB Performance-PCle G4 M.2 2280 SED (FDE/Opal2.0) SSD 1TB Performance-PCle G4 M.2 2280 SED (FDE/Opal2.0) SSD 1TB Performance-PCle G4 M.2 2280 SED (FDE/Opal2.0) SSD 2TB Performance-PCle G4 M.2 2280 SED (FDE/Opal2.0)		
LCD Display	13.3"WUXGA (1920x1200) AG Touch		
Bluetooth	v5.1 (OS limitation) - HW ready for BT v5.2		
Hard disk drives (internal)	PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 256 GB M.2 NVMe module, SED PCIe-SSD, 2 TB M.2 NVMe module, SED PCIe-SSD, 1 TB M.2 NVMe module, SED		
Hard disk notes	Accessible capacity may vary, also depending on used software.		
Display	33.8 cm (13.3-inch), IPS, WUXGA, 1,920 x 1,200 pixel, Anti-glare touchscreen, 400 cd/m², 1500:1 33.8 cm (13.3-inch), IPS, WUXGA, 1,920 x 1,200 pixel, Anti-glare touchscreen, 300 cd/m², 1000:1		
Multimedia			
Camera	Built-in webcam (Full HD) Out camera: 5 MP with with Status LED autofocus on top of C cover With Status LED Out camera: 5 MP with LED, supporting Window Hello Out camera: 5 MP with autofocus on top of C cove		
Camera notes	1080p, 2 megapixels, 1920 5 MP rear camera on top of without optional rear x 1080, with Privacy Camera C cover camera Shutter		
Microphone	dual digital array microphone		

Base unit

Dana wait	LIFEDOOK LIF212V
Base unit	LIFEBOOK U5313X
General system information	
Chipset	Integrated in CPU
Supported capacity RAM (min.)	8 GB
Supported capacity RAM (max.)	32 GB
Memory slots	LPDDR5
Memory notes	LPDDR5x (4,800 MHz) Dual channel support 8 GB / 16 GB / 32 GB onboard
LAN	10/100/1,000 MBit/s Intel® I219LM
LAN notes	Intel vPro support
Integrated WLAN	Intel Wi-Fi 6E AX211 & BT5.2 vPro, SRD Cat. 2
BIOS version	UEFI Specification 2.8
BIOS features	InsydeH2O BIOS
Audio type	On board
Audio codec	Realtek ALC257
Audio features	2x digital array microphones, 2x built-in speakers (stereo)
MIL-STD tested	Yes, selected MIL-STD-810H tests passed. MIL-STD-810H test results are not a guarantee of future performance under identified test conditions. Accidental damage is not covered under standard international limited warranty.
Color	Dark Silver
Material	Magnesium lid
Display	
Diagonal Size	33.8 cm (13.3-inch)
Display Technology	IPS
Display type	Anti-glare touchscreen
Display Resolution type	WUXGA
Resolution (native)	1,920 x 1,200 pixel
Aspect ratio	16:10
Brightness - typical	300 cd/m² (standard LCD) 400 cd/m² (ultra light LCD)
Contrast - typical	1000:1 (standard LCD) 1500:1 (ultra light LCD)
Viewing angle (h/v) - typical	178°/178°
Display notes	Wide-view high-bright LED display (for enhanced outdoor viewing). With magnesium display lid.
Sensors	3-axis Accelerometer Gyroscope Magnetic Field Sensor Compass
Digitizer / Touch Technology	Wacom Digitizer for pen (AES) input plus capacitive 10 finger multi-touch screen
Pen	AES 4k pressure level Pen garage inductive charging
Graphics	
Base unit	LIFEBOOK U5313X
TFT resolution (HDMI)	up to 4,096 x 2,160 @ 60 Hz
Graphics brand name	Intel® Iris® Xe Graphics (with Dual channel memory)

Graphics	
Graphics features	4 Display Support (3 external, 1 internal) HDCP support DirectX® 12 OpenGL® 4.5
Graphics notes	Shared memory depending on main memory size and operating system 3D accelerator
Interfaces	
DC-in	1
Audio: line-out / headphone	1 (combo port with audio line-in)
Audio: line-in / microphone	1 (combo port with Audio line-out)
Internal microphones	2 x digital array microphones
USB 3.2 Gen1 (5 Gbps) total	2 x Type-A (1 with Anytime USB charging functionality)
USB 4.0 Gen3 (20 Gbps) total	2 x Type-C Intel® Thunderbolt™4 (with Power Delivery functionality)
USB Type-C	2 USB 4 Gen3 Thunderbolt™4, Power Delivery (15W), DP 1.4
HDMI	1 v2.0
Ethernet (RJ-45)	1
Memory card slots	1 (USH-II) SD 4.0 standard SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC/microSDXC card: 2TB Speed Class: up to UHS-II (156MB/s)
SmartCard slot	1
Docking connector for Port Replicator	USB Type-C
Kensington Lock support	1

Port Replicator interfaces (optional)			
	USB Type-C PR	Thunderbolt™ 4 PR	
DC-in	1 (19V/90W required)	1 (20V/170W required)	
Power on switch	1	1	
Audio: comments	1 Combo jack for headset usage	1 Combo jack for headset usage	
DisplayPort	1x V1.2	2x V1.4++	
VGA	1		
HDMI text	1	V 2.0b	
Interface Notes	3x Type-A - 5V/0.9A, 4.5W 1x Type-C - 15W 1x Type-C - Up to 60 W (PD v2.0-1.1) power output to client or 4.5W input	2x Type-A - 5V/0.9A, 4.5W 1x Type-A - 5V/2.4A, 12W 2x Type-C - 5V, 1.5A/4.5W charging port 1x Type-C - TBT4 up to 60 W (PD v2.0-1.1), 5-20V/3.0A upstream (PC), Intel AMT support (vPRO) 1x Type-C - TBT4 up to 15 W (PD v2.0-1.1), 5V/3.0A downstream, power output to client	
Kensington Lock support	no	1	
Ethernet (RJ-45)	1	1 (10/100/1000 Mbit/s, 2,5 Gbps)	
Notes	Number of simultaneous used displays and its possible resolutions and frequencies depend on mobile system and display interface type. Please consult always also the manual of the connected client.		
Keyboard and pointing devices			
	Backlit keyboard w/o touchstick		
	Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.7 mm		
	Multi gesture touchpad with integrated mouse button functionality Touchscreen Tablet Pen (AES), stored in pen garage		
Wireless technologies			
Antennas	2x dual band for WLAN, Bluetooth shared with WLAN		

Wireless technologies	
Bluetooth	v5.1 (OS limitation) - HW ready for BT v5.2
Integrated WLAN	Intel Wi-Fi 6E AX211 & BT5.2 vPro, SRD Cat. 2
WLAN encryption	WPA/WPA2/WPA3 (Wi-Fi Protected Access)
WLAN notes	WiFi 6E is supported by Windows 11 OS only - Windows 10 OS supports WiFi 6 only. Import and usage according to country-specific regulations.
Power supply	
AC Adapter	20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Type-C AC-Adapter slim&light
AC Adapter	20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Type-C AC-Adapter standard
AC adapter	19 V / 65 W (3.42 A) 20 V / 65 W (3.25 A) Type C
Notes	65W AC adapter for usage with system/ min. 90W AC Adapter for usage with Port Replicator
Rated voltage range	100 V - 240 V (AC Input)
Rated frequency range	50 Hz - 60 Hz
1st battery	Lithium polymer battery 4-cell, 64 Wh
Battery features	Quick Charge: 80% in 1h
Runtime 1st battery	tbc
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2018. Refer to www.bapco. com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	304.8 x 217.8 x 19.2 mm
	12 x 8.57 x 0.75 inch
Weight	1,39 kg
Weight (lbs)	3,06 lbs
Weight notes	Weight may vary depending on actual configuration
Operating ambient temperature	5 - 35 °C (41 - 95 °F); Packed -10 - 60 °C (14 - 140 °F)
Operating relative humidity	Running: 20 - 80% (relative humidity); Packed: 20 - 80% (relative humidity)
Compliance	
Product	LIFEBOOK U5313X
Germany	GS (planned)
Europe	CE CB
Global	TCO Certification in progress EPEAT® Gold (dedicated regions) in progress ENERGY STAR® 8.0
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Additional Software	
Additional software (preinstalled)	Adobe® Reader® (pdf reader) CyberLink YouCam (webcam software) Fujitsu Display Manager Fujitsu DeskUpdate (driver and utility tool) ShockSensor Utility Power Saving Utility Fujitsu Plugfree Network (network management utility) EasyGuide online user documentation Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)

Additional Software	
Additional software (optional)	Recovery DVD for Windows®
	Drivers & Utilities DVD (DUDVD) optional
	CyberLink PowerDVD BD (playback software for Blu-ray Disc™)
	CyberLink PowerDVD DVD (playback software for DVD)
	CyberLink YouCam (webcam software) Nero (backup and burning software)
Additional software (notes)	
Additional software (notes)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.
Manageability	
Manageability technology	DeskUpdate Driver management
	PXE 2.1 Boot code
	Wake up from S5 (off mode)
	WoL (Wake on LAN)
	Intel® vPro™ technology
AA Lillin Gr	Intel AMT 16.0 (depending on processor)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	Inventory Management
	BIOS Management
	Driver Management
	Security Management
	Alarm Management
Supported standards	WMI (Windows Management Instrumentation)
	PXE (Preboot Execution Environment)
	DMI (Desktop Management Interface) SMBIOS (System Management BIOS)
	WBEM (Web Based Enterprise Management)
	CIM (Common Information Model)
	BootP (made4you)
Manageability link	https://www.fujitsu.com/global/products/computing/pc/manageability/
Security	
Physical Security	Kensington Lock support
System and BIOS Security	Optional: Trusted Platform Module (TPM 2.0)
	EraseDisk
User Security	Hard disk password
	User and supervisor BIOS password
	Embedded fingerprint sensor (optional)
	Embedded PalmSecure™ sensor (optional) Smartcard reader (integrated)
	AuthConductor Client Basic (secure authentication solution)
Security Notes	The properties of the product provide a baseline for product security and therefore end-customer IT security.
	However, these properties are not sufficient on their own to protect the product from all existing threats, such as
	intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use
	the configuration options as available for the respective product. During operation, the IT security of this product
	is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a
	manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices
	and/or general product operation.
Packaging information	
Warranty	
Warranty period	3 years
Warranty type	Next Business Day Onsite Service

http://www.fujitsu.com/warranty

Warranty Terms & Conditions

Warranty	
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patche for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.
Product Support - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	at least 5 years after shipment, for details see https://support.ts.fujitsu.com/
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

Recommended Accessories

Thunderbolt™ 4 Port Replicator	First Thunderbolt™ Port Replicator on the market providing enhanced security and full support of Intel® AMT (vPro®). The universal port can easily connect almost everything with a single cab and high speed-data transfer. This smart workspace solution keeps your desk clean and tidy.	Order Code: FPCPR401BP ble
USB Type-C Port Replicator 2	Connect to your peripherals. Adapt to the task on demand. The universal USB Type-C interface supports you to get your peripheral devices connected easily. Multiply your USB ports to connect your peripherals as well as your external display via HDMI, DisplayPort or VGA. You also can charge your external USB devices without the need of any additional charger.	S26391-F3327-L100
Pen Holder		Order Code: FPCPN064BP

More information

Fujitsu products, solutions & services

In addition to Fujitsu Tablet LIFEBOOK U5313X, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/ computing/

Software www.fujitsu.com/software/

More information

Learn more about Fujitsu Tablet LIFEBOOK U5313X, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

https://www.fujitsu.com/emeia/products/computing/pc/tablets

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT

Please find further information at http://www.fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2023 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

CONTACT

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2023-04-26 EM-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2023 Fujitsu Technology Solutions GmbH