Fujitsu recommends Windows 11 Pro.

Data Sheet Fujitsu Tablet LIFEBOOK U9313X

Sleek featherweight with integrated pen

The Fujitsu LIFEBOOK U9313X is a durable, lightweight convertible designed for professionals on-the-go. It features 360° foldability, an anti-glare touch display, Intel® Iris® Xe Graphics, and Thunderbolt™ 4 for high performance. With all-day battery life and 5G, it maximizes productivity, and the pen garage with inductive charging keeps the pen ready for use.

Ultra-slim and lightweight Convertible

The very slim and light housing make it very comfortable to carry the device. Thanks to its convertability, it can be immediately turned from a Notebook to a Tablet – and back

- The Intel® Evo[™] vPro[®] platform offers a great thin-and-light notebook experience
- Two fan concept to support high performance CPUs
- Weighing below 1 kg with a robust magnesium housing
- Durability is MIL-STD-810H tested

Security at its best

No compromises in security and data protection – the integrated PalmSecure[™] sensor turns your unique palm vein pattern into your personal key

- Privacy Camera Shutter to keep external eyes away
- PalmSecure[™] as your personal biometrical key
- Fingerprint & Full HD IR Camera supporting Windows Hello
- SmartCard reader
- Kensington Lock support

Excellent connectivity and usability

All ports are full-sized – even the LAN port. No adapters, that can be lost and cause additional costs, needed

- Complete set of full-sized interfaces: HDMI, LAN and USB Type-C with Intel® Thunderbolt™ 4
- 13.3 inch FHD anti-glare touch display supporting pen input
- Ergonomic pen for more natural haptic, stored in a pen garage with inductive charging
- 13 MP rear camera

Convenient mobility supporting usage on the go

Highest productivity on business trips without empty batteries or waste of time

- Advanced battery with improved runtime that extents your mobile working sessions
- Always connected and instantly ready





HOMI







Components

Base unit	LIFEBOOK U9313X
Operating systems	
Dperating system pre-installed	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home
Operating system compatible	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home
Microsoft OS support information	 Windows 11 requires for first device setup: Internet connectivity Microsoft account for Home editions or organizational account (e.g. ADD) for Pro editions After product end of life, Fujitsu continues to test and support new Windows releases for max. 5 years, depending or extension of hardware services through warranty top ups. For more details please visit our Fujitsu Service Statement under https://support.ts.fujitsu.com/IndexProdSupport.asp?Ing=com&OpenTab=
Operating system notes	The use of Windows Operating System is subject to acceptance of the End User License Agreement of Microsoft as applicable under the relevant Microsoft program.
Processor	Intel® Core™ i5-1350P processor (12 Cores, up to 4.7 GHz) *
	Intel® Core™ i5-1335U processor (10 Cores, up to 4.6 GHz) *
	Intel® Core™ i7-1370P processor (14 Cores, up to 5.2 GHz)
	* Processor only for retail, SMB, education and government
Processor	Core i5-1335U/16GB LPDDR5 Core i5-1350P/16GB LPDDR5 Core i7-1370P/16GB LPDDR5 Core i7-1370P/32GB LPDDR5
Memory	16 GB onboard memory LPDDR5 32 GB onboard memory LPDDR5
Hard disk drives	No DIMMSSD 256GB Value-PCle G4 M.2 2280 SED (FDE/Opal2.0)SSD 512GB Value-PCle G4 M.2 2280 SED (FDE/Opal2.0)SSD 1TB Value-PCle G4 M.2 2280 SED (FDE/Opal2.0)SSD 512GB Performance-PCle G4 M.2 2280 SED (FDE/Opal2.0)SSD 1TB Performance-PCle G4 M.2 2280 SED (FDE/Opal2.0)SSD 2TB Performance-PCle G4 M.2 2280 SED (FDE/Opal2.0)SSD 2TB Performance-PCle G4 M.2 2280 SED (FDE/Opal2.0)
LCD Display	13.3" Full-HD (1920x1080) AG Touch
Bluetooth	v5.1 (OS limitation) - HW ready for BT v5.2
Hard disk drives (internal)	
Hard disk notes	Accessible capacity may vary, also depending on used software.
Interface add on cards/components (optional)	
Display	
Multimedia	
Camera	Front: IR Cam (2 MP) with LED, supporting Windows Hello Out camera: 13MP with autofocus on top of C cover

Base unit

Conoral system information	
General system information Chipset	Integrated in CPU
Supported capacity RAM (min.)	16 GB
Supported capacity RAM (min.)	32 GB
Memory slots	LPDDR5
Memory notes	LPDDR5x (4,800 MHz)
Memory notes	Dual channel support
	16 GB onboard
	32 GB onboard
LAN	10/100/1,000 MBit/s Intel® I219LM
LAN notes	Intel vPro support
Integrated WLAN	Intel Wi-Fi 6E AX211 & BT5.2 vPro, SRD Cat. 2
BIOS version	UEFI Specification 2.8
BIOS features	InsydeH2O BIOS
Audio type	On board
Audio codec	Realtek ALC257
Audio features	2x digital array microphones, 2x built-in speakers (stereo)
MIL-STD tested	Yes, selected MIL-STD-810H tests passed.
	MIL-STD-810H test results are not a guarantee of future performance under identified test conditions. Accidental damage is not covered under standard international limited warranty.
Color	Black
Material	Magnesium
Display	
Diagonal Size	33.8 cm (13.3-inch)
Display Technology	IPS
Display type	Anti-glare touchscreen
Display Resolution type	FHD
Resolution (native)	1,920 x 1,080 pixel
Aspect ratio	16:9
Brightness - typical	400 cd/m ²
Contrast - typical	1500:1
Viewing angle (h/v) - typical	178°/178°
Display notes	Wide-view high-bright LED display (for enhanced outdoor viewing). With magnesium display lid.
Sensors	Ambient Light Sensor
	3-axis Accelerometer
	Gyroscope
	Magnetic Field Sensor Compass
Digitizer / Touch Technology	Wacom Digitizer for pen (AES) input plus capacitive 10 finger multi-touch screen
Pen	AES
ren	4k pressure level
	Pen garage
	inductive charging
Graphics	
Base unit	LIFEBOOK U9313X
TFT resolution (HDMI)	up to 4,096 x 2,160 @ 60 Hz
Graphics brand name	Intel [®] Iris [®] Xe Graphics (with Dual channel memory)
Graphics features	4 Display Support (3 external, 1 internal)
	HDCP support
	DirectX® 12
	OpenGL® 4.5
Graphics notes	Shared memory depending on main memory size and operating system 3D accelerator
Interfaces	4
DC-in	1

Interfaces		
Audio: line-out / headphone	1 (combo port with audio line-in)	
Audio: line-in / microphone	1 (combo port with Audio line-out)	
Internal microphones	2 x digital array microphones	
USB 3.2 Gen1 (5 Gbps) total	2 x Type-A (1 with Anytime USB charging functionality)	
USB 4.0 Gen3 (20 Gbps) total	2 x Type-A (1 with Anythine 05b charging functionality) 2 x Type-C Intel® Thunderbolt™4 (with Power Delivery functionality)	
USB Type-C	2 USB 4 Gen3 Thunderbolt [™] 4, Power Delivery (15W), DP	
HDMI	1 v2.0	1.7
Ethernet (RJ-45)	1	
Memory card slots	1 (USH-II) SD 4.0 standard	
	SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC/microSDXC card: 2TB Speed Class: up to UHS-II (156MB/s)	
SmartCard slot	1	
SIM card slot	1 (Nano-SIM, only for models with integrated 5G/LTE mo	odule)
eSIM card	eSIM supported - integrated in 5G Module	
Docking connector for Port Replicator	USB Type-C	
Kensington Lock support	1	
Port Replicator interfaces (optional)		
	USB Type-C PR	Thunderbolt™ 4 PR
DC-in	1 (19V/90W required)	1 (20V/170W required)
Power on switch	1	1
Audio: comments	1 Combo jack for headset usage	1 Combo jack for headset usage
DisplayPort	1x V1.2	2x V1.4++
VGA	1	
HDMI text	1	V 2.0b
Interface Notes	3x Type-A - 5V/0.9A, 4.5W 1x Type-C - 15W 1x Type-C - Up to 60 W (PD v2.0-1.1) power output to client or 4.5W input	2x Type-A - 5V/0.9A, 4.5W 1x Type-A - 5V/2.4A, 12W 2x Type-C - 5V, 1.5A/4.5W charging port 1x Type-C - TBT4 up to 60 W (PD v2.0-1.1), 5-20V/3.0A upstream (PC), Intel AMT support (vPRO) 1x Type-C - TBT4 up to 15 W (PD v2.0-1.1), 5V/3.0A downstream, power output to client
Kensington Lock support	no	1
Ethernet (RJ-45)	1	1 (10/100/1000 Mbit/s, 2,5 Gbps)
Notes	Number of simultaneous used displays and its possible resolutions and frequencies depend on mobile system and display interface type. Please consult always also the manual of the connected client.	
Keyboard and pointing devices		
	Backlit keyboard w/o touchstick	
	Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.5 mm	
	Multi gesture touchpad with integrated mouse button f Touchscreen Tablet Pen (AES), stored in pen garage	unctionality
Wireless technologies		
Antennas	2x dual band for WLAN, 2x for LTE, Bluetooth shared with	h WLAN
Bluetooth	v5.1 (OS limitation) - HW ready for BT v5.2	
Integrated WLAN	Intel Wi-Fi 6E AX211 & BT5.2 vPro, SRD Cat. 2	
WLAN encryption	WPA/WPA2/WPA3 (Wi-Fi Protected Access)	
WLAN notes	WiFi 6E is supported by Windows 11 OS only - Windows 10 OS supports WiFi 6 only. Import and usage according to country-specific regulations.	
	important usage according to country specific regulation	

Wireless technologies		
WWAN notes	Including GPS functionality	
	Import and usage according to country-specific regulations. LTE Connection Manager (if configured with LTE)	
GPS	Embedded in 5G module if configured with WWAN	
	Embedded in 5G module ii conligured with wwAN	
Power supply		
AC Adapter	20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Type-C AC-Adapter slim&light	
AC Adapter	20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Type-C AC-Adapter standard	
AC adapter	20 V / 65 W (3.25 A) Type C	
Notes	65W AC adapter for usage with system/ min. 90W AC Adapter for usage with Port Replicator	
Rated voltage range	100 V - 240 V (AC Input)	
Rated frequency range	50 Hz - 60 Hz	
1st battery	Lithium polymer battery 4-cell, 64 Wh	
Battery features	Quick Charge: 80% in 1h	
Runtime 1st battery	tbc	
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo [®] MobileMark [®] 2018. Refer to www.bapco com for additional details. The BAPCo [®] MobileMark [®] Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.	
Dimensions / Weight / Environmental		
Dimensions (W x D x H)	308.6 x 209 x 16.9 mm	
	12.18 x 8.41 x 0.62 inch	
Weight	0,99 kg	
Weight (lbs)	2,20 lbs	
Weight notes	Weight may vary depending on actual configuration	
Operating ambient temperature	5 - 35 °C (41 - 95 °F); Packed -10 - 60 °C (14 - 140 °F)	
Operating relative humidity	Running: 20 - 80% (relative humidity); Packed: 20 - 80% (relative humidity)	
Compliance		
Product	LIFEBOOK U9313X	
Europe	CE CB	
Global	TCO Certification in progress ENERGY STAR® in progress EPEAT® Gold (dedicated regions) in progress	
Compliance link	https://sp.ts.fujitsu.com/sites/certificates	
Additional Software		
Additional software (preinstalled)	Adobe® Reader® (pdf reader) CyberLink YouCam (webcam software) Fujitsu Display Manager Fujitsu DeskUpdate (driver and utility tool) ShockSensor Utility Power Saving Utility Fujitsu Plugfree Network (network management utility) EasyGuide online user documentation Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)	
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) optional CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) CyberLink YouCam (webcam software) Nero (backup and burning software)	
Additional software (notes)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.	

A A	
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) Intel® vPro™ technology Intel AMT 16.0 (depending on processor)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Supported standards	WMI (Windows Management Instrumentation) PXE (Preboot Execution Environment) DMI (Desktop Management Interface) SMBIOS (System Management BIOS) WBEM (Web Based Enterprise Management) CIM (Common Information Model) BootP (made4you)
Manageability link	https://www.fujitsu.com/global/products/computing/pc/manageability/
Security	
Physical Security	Kensington Lock support
System and BIOS Security	Optional: Trusted Platform Module (TPM 2.0) EraseDisk
User Security	Hard disk password User and supervisor BIOS password Embedded fingerprint sensor (optional) Embedded PalmSecure™ sensor (optional) Smartcard reader (integrated) AuthConductor Client Basic (secure authentication solution)
Security Notes	The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.

Packaging information

Warranty	
Warranty period	3 Years
Warranty type	Next Business Day Onsite Service (Metro areas only)
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu. com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.
Product Support - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	at least 5 years after shipment, for details see https://support.ts.fujitsu.com/
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

Recommended Accessories

Thunderbolt[™] 4 Port Replicator

First Thunderbolt™ Port Replicator on the market providing enhanced
security and full support of Intel® AMT (vPro®).Order Code:
FPCPR401BPThe universal port can easily connect almost everything with a single cable
and high speed-data transfer. This smart workspace solution keeps your
desk clean and tidy.

More information

Fujitsu products, solutions & services

In addition to Fujitsu Tablet LIFEBOOK U9313X, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/ computing/

Software www.fujitsu.com/software/

More information

Learn more about Fujitsu Tablet LIFEBOOK U9313X, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

https://www.fujitsu.com/emeia/products/ computing/pc/tablets

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at http://www. fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/ navigation/terms-of-use.html Copyright 2023 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

CONTACT

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2023-04-26 EM-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/ navigation/terms-of-use.html

Copyright 2023 Fujitsu Technology Solutions GmbH