



DEFENSE INFORMATION SYSTEMS AGENCY

P. O. BOX 4502
ARLINGTON, VIRGINIA 22204-4502

IN REPLY
REFER TO: Network Services (NS3)

16 Jun 2010

MEMORANDUM FOR DISTRIBUTION

SUBJECT: Department of Defense (DoD) Unified Capabilities (UC) Approved Products List (APL) approval of the Fujitsu Network Communications (FNC) Incorporated Flashwave 9500 R3.1 Tracking Number (TN) 0915502, as an Optical Transport System.

Reference: (a) DoDI 8100.3, "DoD Voice Networks," 16 Jan 2004.

1. DoD UC APL approval of the Fujitsu Network Communications (FNC) Incorporated Flashwave 9500 R3.1 TN 0915502, as an Optical Transport System has been granted. This solution achieved Information Assurance (IA) Accreditation from the Defense IA/Security Accreditation Working Group (DSAWG) on 14 Jun 2010. This solution achieved Interoperability Certification (IOC) on 18 Feb 2010 from the Joint Staff (JS). This approval is effective upon the date of this memorandum and expires **16 Jun 2013** unless a critical issue is identified that invalidates either the Interoperability or the IA posture of this product as determined by the JS or the Defense Information Systems Network (DISN) Designated Approving Authority (DAA). Please note that Services and Agencies are required to recertify and reaccredit their systems every three years. Please refer to the UC APL for official posting of this solution at the following URL: <http://jtc.fhu.disa.mil/apl/index.html>.

2. This product/solution must be implemented only in the configuration that was tested and approved. When the system is deployed into an operational environment, the following security measures (at a minimum) must be implemented to ensure an acceptable level of risk for the sites' DAA:

- a. The site must use a SysLog device for auditing purposes.
- b. The configuration must be in compliance with the Fujitsu FLASHWAVE 9500 military-unique features deployment guide.
- c. The site must register the system in the Systems Networks Approval Process Database <https://snap.dod.mil/index.cfm> as directed by the DSAWG and Program Management Office (PMO).
- d. For remote connectivity, a FIPS 140-2 and NIAP approved device must be deployed in conjunction with the NETSMART 1500 server and GNE or alternate GNE, if that NE does not support native encryption (as the FLASHWAVE 9500 does).
- e. If possible, the system should be incorporated into the site's Public Key Infrastructure (PKI). If this is not currently an option, the site's architecture diagram and security policy documents should be modified to reflect this condition.

DISA Memo, NS3, UC APL Approval Memo, Fujitsu Network Communications (FNC)
Incorporated Flashwave 9500 R3.1 Tracking Number (TN) 0915502 16 Jun 2010

3. The IOC letter containing detailed configuration on this product will be available at the following URL: http://jite.fhu.disa.mil/tssi/cert_pdfs/fujitsu_tne_fw9500_31.pdf

4. Due to the sensitivity of the information, the Information Assurance Accreditation Package (IAAP) that contained the approved configuration and deployment guide for this solution must be requested directly from the Unified Capabilities Certification Office (UCCO) by a government civilian or uniformed military personnel.

E-Mail: ucco@disa.mil

UCCO Process Questions: (520) 538-3234 DSN 879

UCCO Process Manager: (703) 365-8801 ext. 534

JESSIE L. SHOWERS, JR.
Chief, Real Time Services Division