

Data Sheet

Fujitsu G60

Multi-Cassette Currency Recycling Module

Evolve Your Currency Management with the G60 Recycler
G60 Combines Slim, Compact Design with High-Capacity and Versatility

Enhanced Functional Features


- Reliable currency recycling at a lower price, broadening the array of potential applications while ensuring a more rapid ROI
- Quickly and accurately verifies currency denominations, detects and separates counterfeit and unfit currency with the best-in-class bill validator.
- Greater capacity, 5 cassettes, (4 recycling cassettes and 1 deposit cassette) and an optional 6th cassette for beginning of day replenishment, added capacity or additional denominations when necessary
- Higher performance with the fastest deposit and dispense transactions in the industry
- Supports major world currencies including mixed and used notes, paper and polymer notes
- CEN XFS service provider is available to enable easy development of application software

Benefits

- Lower cost of ownership by more efficiently managing currency requirements and cash-in-transit costs
- Increased up time with the flexibility of adding a loading cassette for increased capacities, start of day replenishment or additional denominations
- Supports provisional credit on questionable items by capturing the entire image of the note with the bill validator, providing greater flexibility to OEM providers.
- Manages the quality of notes by accepting and separating unfit currency, while dispensing only fit currency to end customers.
- OEMs can demonstrate ROI to customers with Asset Planning Tool™, which enables customers to enter their unique currency handling data and calculate replenishment benchmarks vs. usage.



G60 Product Specifications

Dimensions (W x D x H)	160mm x 340mm x 680mm
Weight (without bills)	Approx. 25kg
Bill Transaction (deposit)	20 Bills
Bill Transaction (dispense)	20 Bills
Recycle Stacker Capacity	100 Bill (Approx.)* x 4 Stackers
Loading Cash Cassette Capacity (Option)	1,000 Bills (Approx.)*
Acceptable Media Range	Maximum (mm) - 78mm x 166mm (TBD) Minimum (mm) - 60mm x 120mm
Thickness (mm)	0.09 ~ 0.20
Processing Performance	Deposit 1 Bill/1.5 sec - 20 Bills/10 sec Dispense 1 Bill/2.0 sec - 20 Bills/12 sec
Interface Specifications	USB 2.0 Full Speed CEN / XFS
Electrical Reuirements	DC +24V +/- 10% MA X 15A
Temperature Operation:	Operation: 0°C to 50°C Stop State: -5°C to 50°C
Relative Humidity	Operation: 10% - 85% Stop State: 8% - 95%
RoHS-compliant unit	Yes
UL Compliance	Yes 



Fujitsu Frontech North America reserves the right to change specifications without notice

*Actual number of notes depends on fitness of currency, new versus used

Contact

FUJITSU
Fujitsu Frontech North America Inc.
Address: 27121 Towne Centre Drive, Suite 100 Foothill Ranch, CA 92610
Phone: 877-766-7545
Email: CHPS.FFNA@us.fujitsu.com
Website: <http://www.fujitsu.com/us/oem/financial/atm>
G60_DS_122716



©2016 Copyright Fujitsu Frontech North America Inc. All rights reserved. Fujitsu and the Fujitsu logo are registered trademarks. All other trademarks are the property of their respective owners. Statements herein are based on normal operating conditions and are not intended to create any implied warranty of merchantability or fitness for a particular purpose. Fujitsu Frontech North America Inc. reserves the right to modify, at any time without notice, these statements, our services, products, and their warranty and performance specifications.