

FUJITSU Image Scanner fi-7030

Evolved entry model suitable for quick scanning



shaping tomorrow with you

fi-7030 Features

Ideal for desktop scanning with its compact size and card scanning capability

The fi-7030 handles the scanning of a wide range of documents reliably from thin documents to thick documents (40-209g/m²), and plastic cards including embossed cards. Long paper scanning of up to 5 meters and over is also available as well as A3 size scanning with a carrier sheet that comes with the scanner as an option.

- •Compact design allowing it to be placed anywhere
- Its noticeable compact size with a sophisticated design suits various environments. The scanner fits in small spaces even smaller than spaces that are A4 in size on a desk.
- •Fast processing performance The fi-7030 scans at a speed of 27 ppm / 54 ipm (A4, portrait, Color, 200 / 300 dpi), which is increased by 35% compared to the previous model. The scanner will not make you or your customers wait with a quick startup time of half a second and a recovery time of 1.0 seconds after resuming from sleep mode.
- •Accurate mixed batch scanning for different types of documents The Skew Reducer prevents the following documents from being skewed when the preceding document is skewed, thus preventing the image from being incomplete with missing parts even in the case of a batch scan with various types of documents. This also reduces the burden of re-scanning.
- mixe d batch Automatically creates the best suited image quality without hassle The PaperStream IP scanner driver, which supports TWAIN/ISIS, avoids the inconvenience of fine adjustments to the settings for OCR processes. It automatically converts the images into exceptionally clean images, accelerating OCR even when scanning
- Advanced software for your work efficiency
- PaperStream Capture Image capture software
- With an intuitive interface, batch scanning with various capture features of PaperStream Capture allows you to incorporate information into your organization's workflow effectively and efficiently. By pre-setting a scanning profile, PaperStream Capture could help you simplify your workflow with easy scanning operation.

wrinkled or soiled documents, or documents with a background pattern.

• Scanner Central Admin - Centralized scanner management software Scanner Central Admin allows the administrator to manage a large number of scanners in the network by delivering simultaneous driver updates and scanner setup information, or monitoring consumable and error statuses via the network.

Option: Carrier Sheets

Carrier Sheets allow you to scan documents, photos or clippings larger than A4 size. Documents larger than A4 (such as A3 or B4) or photos and clippings that can be damaged easily can be digitized when using the A3 Carrier Sheet.



* Carrier Sheets (5 sheets per set) can be purchased separately. (The Carrier Sheet should be replaced approximately every 500 scans)

Description	Parts number	Comments
Carrier Sheets	PA03360-0013	Each package contains 5 carrier sheets. It is recommended that each carrier sheet be replaced after it has been used for 500 scans.

■Consumables

	Description		Parts number	Comments	
Roller Set	Dollar Cat	Brake Roller	PA03706-0001	Lifetime: Every 200,000 sheets or one year. These rollers separate documents as they are being fed into the scanner.	
	KOHEL SEL	Pick Roller		Lifetime: Every 200,000 sheets or one year. These rollers feed documents into the scanner.	

Trademarks

- ABBYY and FineReader are trademarks of ABBYY Software, Ltd. which may be registered in some jurisdictions. ISIS is a registered trademark of EMC Corporation in the United States. Microsoft, Windows, Windows Server, Windows Vista and SharePoint are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. * Other company names and product names are the registered trademarks or trademarks of the respective companies.

Visit the fi Series web site for ordering and purchasing information

http://imagescanner.fujitsu.com



be sure to tarefully recover successfully provide the successfully areas. Using this product under such conditions may result in electrical shock, fire or damage to this product.
Be sure to limit the use of this product to listed power ratings.



Scamercype			
Scanning modes		Simplex / Duplex, Color / Grayscale / Monochrome	
Image sensor type		Color CIS (Charge-coupled device) x 2 (front x 1, back x 1)	
Light source		3 Color LED (Red / Green / Blue) x 2 (front x 1, back x 1)	
Multifeed detection		Ultrasonic multifeed detection sensor x 1, Paper detection sensor x 1	
	Maximum	216 x 355.6 mm (8.5 x 14 in.)	
Document size	Minimum	50.8 x 50.8 mm (2 x 2 in.)	
	Long page scanning ^{*1}	216 x 5,588 mm (8.5 x 220 in.)	
Paper weight (Thickness)	Paper	40 to 209 g/m ² (11 to 56 lb) *A8 size: 127 to 209 g/m ² (34 to 56 lb)	
	Plastic Card	0.76 mm or less, Embossed card: usable, Multiple cards cannot be set at a time	
Ci	Color*3		
Scanning speed (A4 Portrait)* ²	Grayscale*3	Simplex: 27 ppm (200/300 dpi), Duplex: 54 ipm (200/300 dpi)	
	Monochrome*4		
Paper chute capacity (A4 Portrait)*5		50 sheets (A4: 80 g/m² or 20 lb)	
Background colors		White	
Optical resolution		600 dpi	
	Color (24-bit)		
Output resolution*6	Grayscale (8-bit)	50 to 600 dpi (adjustable by 1 dpi increments), 1,200 dpi (driver)*7	
resolution	Monochrome (1-bit)		
	Color	24-bit	
Output format	Grayscale	8-bit	
	Monochrome	1-bit	
Internal video p	processing	1024 levels (10-bit)	
Interface		USB2.0 / USB1.1	
Connector shap	e	B type	
Image processing functions		Deskew, Cropping, Image emphasis, Error diffusion, Dither, Black & Whi Method, Dynamic threshold (IDTC), Static threshold, Advanced DTC, SDT De-Screen, Dropout color (Red / Green / Blue / White / None / Saturatior Custom), Automatic color detection, Multi image output, Blank page detectio SRGB output, Split image, Front/Back Merging	
Power requirem	ients	AC 100 to 240 V ±10%	
Power consumption		Operating: 17 W or less Sleep mode: 1.1 W or less Auto standby (OFF) mode: 0.15 W or less	
Operating environment		Temperature: 5 to 35 °C (41 to 95 °F) Relative humidity: 20 to 80% (Non-condensing)	
Dimensions: Width x Depth x Height*8		290 x 146 x 130 mm (11.41 x 5.74 x 5.11 in.)	
Weight		2.9 kg (6.4 lb)	
Included software / drivers		PaperStream IP (TWAIN /TWAIN x64 /ISIS), PaperStream Captur Software Operation Panel, Error Recovery Guide, ScanSnap Manag for fi Series ¹⁹ , Scan to Microsoft SharePoint ¹⁹ , ABBYY FineReader for ScanSnap ^{M+9} , Scanner Central Admin Agent	
		1	
Environmental	compliance	ENERGY STAR [®] and RoHS	

(220 in.) when the resolution is set to 200 dpi or less. Actual scanning speeds are affected by data transmission and software processing times. Indicated speeds are from using IPEG compression. Indicated speeds are from using IPEG compression. Maximum capacity varies, depending upon paper weight. Selectable maximum density may vary depending on the length of scanned document. When scanning at high resolution (over 600dpi), some limitations apply to the size of the document that could be scanned, depending on metricing environment.

system environment.
 *8 Excluding the ADP paper chute and Stacker.
 *9 The software can be downloaded from the website designated in the Setup DVD-ROM.



Supported operating systems

fi-7030

Windows® 10 (32-bit/64-bit), Windows® 8.1/8 (32-bit/64-bit),

Windows Server® 2012 R2 (64-bit), Windows Server® 2012 (64-bit), Windows Server® 2008 R2 (64-bit), Windows Server® 2008 (32-bit/64-bit)

Windows® 7 (32-bit/64-bit), Windows Vista® (32-bit/64-bit),

Automatic Document Feeder (ADF)

Description

Scanner type



a