

Parameter		Specification
Product name		FI-5000N
Supported fi-series scanners		fi-5530C, fi-4530C, fi-5220C, fi-4220C2, fi-4220C, fi-5120C, fi-4120C2, fi-4120C, fi-5110C
LCD display	Type	Monochrome
	Panel size	4 rows of 20 characters (Japanese: 4 rows of 10 characters)
	Language	English, Germany, French, Spanish, Italian, Japanese
Operator panel keys		Total 17 keys: [ID], [SETUP], [ESC], [ENTER], [↑], [↓], [·], Numeric key (0 to 9)
Buzzer		Yes
User information	User name, send-to PC, PIN	Can be specified by the administrator using PC administration tools
	Fingerprint registration	Can be registered by user using fi-5000N
	Maximum number of users	32
Fingerprint authentication	Fingerprint sensor	Static capacity method / Resolution: 500 dpi
	Finger detection sensor	Yes
	Verification method	Minutiae method
	Verification time	3 seconds or less (Except in the case of extremely dry fingers)
	Finger print registration	Finger is to be placed 3 times
Interface	LAN (Network connection)	IEEE802.3/802.3u Compatible 10BASE-T / 100BASE-TX (auto negotiation)
	USB (Scanner connection)	USB 2.0 / USB1.1compatible (USB 2.0 / 1.1 auto-recognition)
Voltage or voltage range		AC 100 to 240V,+10% / -10%
Power	LCD on	Less than 8W
	LCD off	Less than 5W
Operational environment	Temperature	5 to 35°C (42 to 95°F)
	Relative humidity	20 to 80% (non-condensing)
Dimensions: Width x Depth x Height		125 x 176 x 62 mm
Weight		1 kg
Environmental compatibility *1		RoHS
Included drivers		TWAIN, ISIS™

*1 PFU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005 / 95 / EC).