

Parameter		Specification
Product name		FI-60F
Scanner type		Flatbed
Scanning modes		Simplex, Color / Grayscale / Monochrome
Image sensor type		Color CIS (Contact Image Sensor) (CMOS CIS)
Light source		R,G,B LED (variable light source)
Scanning range		Maximum: A6 (148 x 105 mm or 5.83 x 4.13in.)
Scanning speed (A4 portrait) *1	Color	1.3 seconds (150 dpi)
	Grayscale	
	Monochrome	1 second (200 dpi)
Background colors		Black
Optical resolution		600 dpi
Output resolution	Color (24 bit)	50 to 600 dpi (adjustable by 1 dpi increments)
	Grayscale (8 bit)	
	Monochrome (1 bit)	
Output format		Color: 24 bit, Grayscale: 8 bit, Monochrome: 1 bit
AD converter		65,536 levels (16 bit)
Interface		USB 2.0 / USB 1.1
Connector shape		B type
Output mode (half-tone)		Dither / Error diffusion
Voltage or voltage range		AC 100 to 240V, +10% / -10%
Power		Operating: 8W or less (Sleep mode: less than 2W)
Operational environment		Temperature: 5 to 35°C (42 to 95°F) Relative humidity: 20 to 80% (Non-condensing)
Dimensions: Width x Depth x Height *2		145 x 234 x 40 mm (5.7 x 9.2 x 1.6in.)
Weight		0.9 kg (2 lb)
Included drivers		TWAIN, ISIS™
Environmental compatibility *3		ENERGY STAR® and RoHS
Others	Document cover	Included (removable)
	Document holding pad color	Black
	Power switch	None (unit switches on and off when linked computer does)

*1 Actual scanning speeds are affected by data transmission and software processing times.

*2 Projecting items are not included in these dimensions.

*3 PFU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005 / 95 / EC).