

S2110 Recommended Configurations	
Processor	AMD Turion™ 64 MT-28 (1.60GHz, 512K L2 cache, 1600MHz HTSB®)
OS Supported	Mobile AMD Sempron™ 2600+ (1.60GHz, 128K L2 cache, 1600MHz HTSB®)
Display	Microsoft® Windows® XP Home Edition Microsoft® Windows® XP Professional Edition
Modular Bay Device	13.3" SuperFine XGA TFT, 1024 x 768 pixels
Memory	DVD/CD-RW†
Hard Disk	512MB DDR 333MHz
Battery	80GB
Weight	Up to 3.9hrs¹ (6-cell Li-Ion 4800mAh)
	Up to 3.4hrs¹ (6-cell Li-Ion 4800mAh)
Specifications	
Chipset	ATI RADEON® Xpress 200M + ATI SB400
Max. Memory Supported	2GB DDR 333MHz
Hard Disk Drive	Ultra ATA-100, S.M.A.R.T. support‡
Graphics	ATI RADEON® Xpress 200M, selectable 16/32/64/128MB shared memory¹¹ with PCI Express® 2D/3D graphics performance
High Definition (HD) Audio	SigmaTel STAC9753 AC97 codec with built-in dual stereo speakers
Communication	56K V.92² Global Modem MDC1.5, iDA 1.1 4Mbps³, 100/10Mbps⁴ Fast Ethernet and Super AG™¹ Super G™⁵ wireless connection with Dual Antenna Separate ON/OFF switch for wireless network connection
User Interface	Keyboard: 84-key, 19mm key pitch, 3mm key stroke Intelligent Touchpad with configurable vertical and horizontal scroll functions
Card Slot	PC Card Type II, Smart Card support‡
Connector Interface	Secured Digital/ Memory Stick PRO
Quick Launch Panel	USB 2.0 x 3, VGA (external display), RJ45 (LAN), RJ11 (modem), Mini S-Video out, IEEE1394, Microphone-in, Headphone-out, Power Adapter DC-in, Port Replicator Interface
Media Playback Panel	Four Programmable Application Launch Buttons (Internet, Email and two other softwares)
Security‡	Four Functions: Stop/Eject, Play/Pause, Next, Previous
Dimensions	BIOS Lock, Hard Disk Lock, Anti-theft Lock Slot, Smart Card support‡
	293mm (W) x 236.5mm (D) x 30.5mm min (H)
Bundled Accessories	
AC Adapter	Input AC 100-240V, Output DC 16V 60W
Bundled Software	CyberLink PowerDVD™, CyberLink PowerProducer™ Gold, Sonic RecordNow™ DX, Sonic DLA, Adobe Acrobat Reader 6.0, Fujitsu Update Navi¹⁰, Fujitsu Hardware Diagnostic Tool, Fujitsu Display Manager
Software on CD	1 year Full Licensed Norman Virus Control and Norman Personal Firewall
Optional Accessories	
Port Replicator	Connector Interface: USB 2.0 x 2, VGA (external display), RJ45 (LAN), PS/2 (keyboard/mouse), Serial, Parallel, Power Adapter DC-in
Modular Bay Options	Replaceable with - Bay Battery, 6-cell Li-Ion 3800mAh, up to 6.9hrs¹ battery life (Standard + Bay Batteries) - Dual Layer DVD Super Multi Writer² - DVD/CD-RW Combo Drive - Weight Saver
Floppy Disk Drive	External USB 1.44MB FDD
Mini S-Video Cable	Converts Mini S-Video out port to standard S-Video out port. Use a S-Video Cable for connection to a TV
Mouse	USB Optical Scroll Mouse

The above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

- 1 Results obtained from Ziff Davis (BusinessWinstone 2001) Battery Mark V1.0.1 performed on systems with maximum battery life settings. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences. Modular Bay devices or hard drive usage may also have a significant impact on battery life. Note: Up to 6.9hrs battery life is based on AMD Turion™ 64MT-28 configuration with standard battery and bay battery.
- 2 Maximum 56Kbps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.
- 3 This term does not represent actual data rate of 4Mbps and simply indicates compliance with IrDA standard specification 1.1. Actual maximum data rate depends on local configurations and connected devices.
- 4 This term does not represent actual data rate of 100/10Mbps and simply indicates compliance with IEEE 802.3, IEEE 802.3u and IEEE 802.3ab standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices.
- 5 Smart Card support requires a Smart Card adapter for the PC Card Slot. This is available as an accessory. Fujitsu does not provide the application for Smart Card Solution.
- 6 BIOS Lock needs a supervisor/user password to access BIOS setup. BIOS settings can be configured to prompt for password at every first bootup or all bootup sequences. Access to BIOS setup is needed to configure Hard Disk Lock. Hard Disk Lock requires an access key to retrieve data on the hard disk. This is a Data Confidentiality security feature. Anti-theft Lock Slot allows the use of a lock to physically secure the LifeBook.
- 7 Supports DVD multi formats such as DVD-RAM, DVD+RW, DVD+R DL, DVD+R, DVD-RW, DVD-R, CD-RW, CD-R, CD-ROM and DVD-ROM.
- 8 This refers to HyperTransport™ System Bus (HTSB) up to 1600MHz full duplex.
- 9 Super AG™ and Super G™ are trademarks of Athlon® Communications. Super AG™ and Super G™ modes deliver up to 108 Mbps raw data rate with typical end user throughput exceeding 60 Mbps in a wireless network environment where wirelessly connected equipment are using Athlon Super AG™ or Super G™ enabled chipsets.
- 10 Update Navi is a Fujitsu Proprietary application that updates LifeBook Drivers by connecting automatically to Fujitsu's server. This will help update your LifeBook with the latest software drivers and utilities to ensure compatibility between hardware and software, maintaining smooth operation anytime, anywhere.
- 11 Memory allocation (max. 128MB) can be pre-set in the BIOS setup for optimal graphics and system performance. The memory size available to the Operating System will be less than the total size of installed memory modules.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

†PCI Express™ and the PCI Express design marks are registered trademarks and/or service marks of PCI-SIG.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5° to 35°C / 41 to 95°F (operating), -10° to 60°C / 14 to 140°F (non-operating). Relative humidity: 20% to 80% RH (operating and non-operating).

ATI, MOBILITY and RADEON are used under license and are registered trademarks of ATI Technologies Inc. in the United States and other countries.

Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.



Dealer: