LifeBook S6230

- Ultra-portable at approximately 1.65kg*
- Supports a wide array of hot-swappable modular bay options including DVD Super Multi Drive and bay battery among others
- Superior security features for enhanced data and hardware protection
- Three USB 2.0 ports for easy peripherals connection
- * With weight saver option



	S6230 Recommended Configuration		
Platform	Intel® Centrino™ Mobile Technology		
	- Intel® Pentium® M Processor 725 (1.60GHz, 2MB L2 cache, 400MHz FSB)		
	- Intel® PRO/Wireless 2200BG ⁹ Network Connection		
	- Intel® 855GME Chipset		
OS Supported	Microsoft® Windows® XP Home Edition		
	Microsoft® Windows® XP Professional Edition		
Display	13.3" XGA TFT, 1024 x 768 pixels		
Modular Bay Drive	DVD/CD-RW Combo Drive		
Memory	256MB DDR333		
Hard Disk	60GB		
Battery	Up to 4hrs ¹ (6-cell Li-lon 4400mAh)		
Weight	Approx. 1.65kg (w/ Weight Saver)		
	Specifications		
Secondary Cache	2MB		
Max. Memory Supported	2048MB DDR333		
Hard Disk Drive	Ultra DMA/100 and S.M.A.R.T support		
Graphics	Integrated Intel® Extreme Graphics 2 with DVMT2 delivers low-power, high-performance 2D/3D graphics, video,		
	and display capabilities at a maximum shared memory of 64MB.		
Audio	SigmaTel STAC9751T AC97 codec with built-in dual Stereo Speakers		
Communication	56K V.92 ³ modem, IrDA 1.1 4Mbps ⁵ , 1000/100/10Mbps ⁴ Gigabit Ethernet and Intel [®] PRO/Wireless 2200BG ⁹		
	network connection with Dual Antenna. Separate ON/OFF switch for wireless network connection		
User Interface	Keyboard: 84-key, 19mm key pitch, 3mm key stroke		
	Touch Pad with Scroll Buttons		
Card Slot	PC Card Type I/II x 1, Smart Card support ⁶		
Connector Interface	USB 2.0 x 3, VGA (external display), RJ45 (LAN), RJ11 (modem), Audio Line-in, IEEE1394, Headphone-out, Microphone-in,		
	Power Adapter DC-in, Port Replicator Interface		
Quick Launch Panel	Four Programmable Application Launch Buttons (Internet, Email and two other software)		
Security ⁷	BIOS Lock, Hard Disk Lock, LifeBook Lock, Anti-theft Lock Slot, Smart Card ⁶		
Dimensions	293mm (W) x 236.5mm (D) x 30.5mm <i>min</i> . (H)		
	Bundled Accessories		
AC Adapter	Input AC 100 ~ 240V, Output DC 16V 60W		
Bundled Software	CyberLink PowerDVD™, Sonic RecordNow™ DX, Sonic DLA, Adobe Acrobat Reader 6.0, Fujitsu UPDATE NAVI™,		
	Fujitsu Hardware Diagnostic Tool		
Software on CD	Norman Virus Control & Norman Personal Firewall		
Port Replicator	Connector Interface:		
p	USB 2.0 x 2, VGA (external display), RJ45 (LAN), PS/2 (keyboard/mouse), Serial, Parallel, Power Adapter DC-in		
	Optional		
Modular Bay Options	Replaceable with		
	- Bay Battery, 6-cell Li-lon 3800mAh, up to 7.5hrs1 battery life (Standard + Bay batteries)		
	- DVD Super Multi Drive ⁸		
	- DVD±RW Drive		
	- DVD/CD-RW Combo Drive		
	- DVD-ROM Drive		
	- Weight Saver		
Floppy Disk Drive	External USB 1.44MB FDD		
Mouse	RF Wireless Optical Mouse ¹⁰		
1110000	Till Philodoco Option Microso		

The above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

- Results obtained from Ziff Davis (BusinessWinstone 2001) Battery Mark V1.0.1 performed on systems with maximum battery life settings. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences. Modular Bay devices or hard drive usage may also have a significant

- Hesulis obtained from Zin Lawis (cusinessymisune zour) patienty main v 1.0.1 pointed on settings, turning applications, connected peripherals, power management settings, battery conditioning, and other customer preferences. Modular Bay devices or hard drive usage may also have a significant impact on battery life.

 Dynamic Video Memory Technology (DVMT) dynamically responds to application requirement and efficiently allocates the proper amount of memory (max. 64MB) for optimal graphics and system performance. The memory size available to the Operating System will be less than the size of installed memory module.

 Maximum S6(bbps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.

 This term does not represent actual data rate of 1000/100/10Mbps and simply indicates compliance with IEEE 802.3u and IEEE 802.3u and IEEE 802.3u and IEEE 802.5u transmitted and IEEE 802.5u transmitted and IEEE 802.5u standards. Actual maximum data rate depends on network configurations as well as connected devices.

 This term does not represent actual data rate of 4Mbps and simply indicates compliance with IrDA standards and IEEE 802.3u and IEEE 802.5u and IEEE 802.5u and IEEE 802.5u standards. Actual maximum data rate depends on local configurations as well as connected devices.

 This term does not represent actual data rate of 4Mbps and simply indicates compliance with IrDA standards that in IrDA standards. Actual maximum data rate depends on local configurations as well as connected devices.

 This term does not represent actual data rate of 4Mbps and simply indicates compliance with IrDA standards that in IrDA standards. Actual maximum data rate depends on local configurations and support requires a Standards. Actual maximum data rate depends on local configurations and support requires a Standards. Actual maximum data rate depends on local configurations and support requires a supervisor/user password to access BIOS s

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5 to 35C/24 it 95F (operating). To 60C/14 to 140F (non-operating). Relative humidity: 20% to 80% RH (operating and non-operating).







All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.

ouror.		

SINGAPORE: Fujitsu PC Asia Pacific Pte Ltd Tel: (65) 6776 0688

Fax: (65) 6776 0788 MALAYSIA: Fujitsu PC Asia Pacific Pte Ltd

Tel: (60-3) 2093 3997 Fax: (60-3) 2093 4245

HONG KONG: Fujitsu PC Asia Pacific Ltd

Tel: (852) 3101 8133 Fax: (852) 3101 0633

THAIL AND: Fuiitsu Systems Business (Thailand) Ltd PC Division

Tel: (66-2) 263 7888 Fax: (66-2) 263 7880

AUSTRALIA: Fujitsu PC Australia

Toll Free: 1800 288 283 Tel: (61-2) 9004 7455 Fax: (61-2) 9004 7720 www.lifebook.com.au

CHINA: Fujitsu PC China Division

Tel: (86-21) 3310 0808 Fax: (86-21) 3310 0606 www.pc-cn.fuiitsu.com

PHILIPPINES: Fuiitsu Philippines Inc.

Tel: (63-2) 812 4001 Fax: (63-2) 817 7576

TAIWAN: Fujitsu Taiwan Ltd Tel: (886-2) 2311 2255 Fax: (886-2) 2311 2277

VIFTNAM: Fuiitsu Vietnam Ltd

Tel: (84-4) 831 3895~7 Fax: (84-4) 831 3898

INDONESIA: PT Fujitsu Systems (Indonesia)

Tel : (62-21) 344 2601 Fax: (62-21) 344 2593

listed above, please contact our Singapore office.