LifeBook S7010

- Small 14" footprint, thin and light at less than 2kg
- Peace of mind with superior security features
- Seamless communications with wireless 802.11b/g9 Gigabit Ethernet, IrDA 1.1 and Bluetooth™ v1.2
- Ergonomically designed features comfortable palm rest with full-sized keyboard, front wireless connection ON/OFF switch, three USB 2.0 ports (rear x 2, right x 1) among others



	S7010 Recommended Configurations	
Platform	Intel [®] Centrino™ Mobile Technology	Intel [®] Centrino™ Mobile Technology
	- Intel® Pentium® M Processor 745	- Intel [®] Pentium [®] M Processor 725
	(1.80GHz, 2MB L2 cache, 400MHz FSB)	(1.60GHz, 2MB L2 cache, 400MHz FSB)
	 Intel[®] PRO/Wireless 2200BG⁹ Network Connection 	- Intel [®] PRO/Wireless 2200BG ⁹ Network Connection
	- Intel® 855GME Chipset	- Intel [®] 855GME Chipset
OS Supported	Microsoft® Windows® XP Home Edition	
	Microsoft® Windows® XP Professional Edition	
Display	14" XGA TFT, 1024 x 768 pixels	
Modular Bay Drive	DVD Super Multi Drive ⁸	DVD/CD-RW Combo Drive
Bluetooth™	Integrated (v1.2)	-
Memory	1GB DDR333	256MB DDR333
Hard Disk	80GB	60GB
Battery	Up to 4.2hrs1 (6-cell Li-lon 4800mAh)	Up to 4.4hrs ¹ (6-cell Li-lon 4800mAh)
Weight	Approx. 1.75kg (w/ Weight Saver)	The second secon
	Specifications	
Secondary Cache	2MB	
Max. Memory Supported	2048MB DDR333	
Hard Disk Drive	Ultra DMA/100 and S.M.A.R.T support	
Graphics	Integrated Intel® Extreme Graphics 2 with DVMT ² delivers low-power, high-performance 2D/3D graphics, video,	
	and display capabilities at a maximum shared memory of 64MB.	
Audio	SigmaTel STAC9751T AC97 codec with built-in dual Stereo Speakers	
Communication User Interface	56K V.92 ³ modem, IrDA 1.1 4Mbps ⁵ , 1000/100/10Mbps ⁴ Gigabit Ethernet and Intel [®] PRO/Wireless 2200BG ⁹ network	
	connection with Dual Antenna. Separate ON/OFF switch for wireless network connection	
	Connection with Dual Antenna. Separate ON/OFF switch for wireless network connection Keyboard with Quick Point: 84-key, 19mm key pitch, 3mm key stroke	
	Touch Pad with Fingerprint Sensor	
Card Slot	PC Card Type I/II x 2 or Type III x 1, Smart Card support ⁶	
Connector Interface	USB 2.0 x 3, VGA (external display), RJ45 (LAN), RJ11 (modem), Audio Line-in, IEEE1394, Headphone-out, Microphone-in,	
	Power Adapter DC-in, Port Replicator Interface	
Quick Launch Panel	Four Programmable Application Launch Buttons (Internet, Email and two other software)	
Security ⁷	BIOS Lock, Hard Disk Lock, LifeBook Lock, Anti-theft Lock Slot, Smart Card ⁶ , Fingerprint Sensor	
Dimensions	306mm (W) x 247mm (D) x 25.4mm min (H)	
	Bundled Accessories	
AC Adapter	Input AC 100 ~ 240V, Output DC 19V 60W	
Bundled Software	Softex OmniPass 3.0, CyberLink PowerDVD™, CyberLink PowerProducer™, Sonic RecordNow™ DX, Sonic DLA,	
	Adobe Acrobat Reader 6.0, Fujitsu UPDATE NAVI™, Fujitsu Hardware Diagnostic Tool	
Software on CD	Norman Virus Control & Norman Personal Firewall	
Port Replicator	Connector Interface:	
	USB 2.0 x 4, Headphone-out, Microphone-in, DVI-D, VGA (external display), RJ45 (LAN), PS/2 (keyboard/mouse), Serial,	
	Parallel, Power Adapter DC-in	
	Optional	
Modular Bay Options	Replaceable with	
	- Bay Battery, 6-cell Li-Ion 3800mAh, up to 8hrs ¹ battery life (Standard + Bay batteries)	
	- DVD Super Multi Drive ⁸	
	- DVD±RW Drive	
	- DVD/CD-RW Combo Drive	
	- DVD-ROM Drive	
	- Weight Saver	
Floory Diek Drive	- weight saver External USB 1.44MB FDD	
Floppy Disk Drive	RF Wireless Optical Mouse ¹⁰	
Mouse	UL Milleres Obilcal Monse	

- he above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

 Results obtained from ZIII Davis (Basiness/Winschoe 2001) Battery with VIII A provided in a production of the customer preferences. Modular Bay devices or hard drive usage may also have a significant impact on battery life.

 Connected peripherals, power management settings, battery conditioning, and other customer preferences. Modular Bay devices or hard drive usage may also have a significant impact on battery life.

 The preferences of the control of memory in the less than the size of installed memory modular of the Operating System will be less than the size of installed memory modular of the Operating System will be less than the size of installed memory modular.

 This term does not represent actual data rate of 1000/100/10Mbps and simply indicates compliance with IEEE 802.3, IEEE 802.3u and IEEE 802.3a standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices.

 This term does not represent actual data rate of 4Mfps and simply indicates compliance with IPOA standard specification 1.1. Actual maximum data rate depends on local configurations and connected devices.

 This term does not represent actual data rate of 4Mfps and simply indicates compliance with IPOA standard specification 1.1. Actual maximum data rate depends on local configurations and connected devices.

 This term does not represent actual data rate of 4Mfps and simply indicates compliance with IPOA standard specification 1.1. Actual maximum data rate depends on local configurations and connected devices.

 This term does not represent actual data rate of 4Mfps and simply indicates compliance with IPOA standard specification 1.1. Actual maximum data rate depends on connected devices.

 This term does not represent actual data rate of 4Mfps and simply indicates compliance wi
- Don, Donorbook of the customer.

 Supports DVD-RMA, DVD+RW, DVD-R, DVD-RW, DVD-R, CD-RW, CD-R, CD-ROM and DVD-ROM formats.

 Supports DVD-RAM, DVD+RW, DVD-RW, DVD-RW, DVD-R, CD-RW, CD-R, CD-ROM and DVD-ROM formats.

 Some country configurations may be bundled with 802.1 fb WLAN e.g. Malaysia. Please check the country configuration with your local distributors.

 Available in Hong Kong, Malaysia and Singapore only.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5 to 35°C/41 to 95°F (operating), 10° to 60°C/14 to 10°F (non-operating), Relative humilor). Relative humilor). Relative humilor). Relative humilor). Relative humilor). Relative humilor).







All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.

Dealer:

SINGAPORE: Fuiitsu PC Asia Pacific Pte Ltd Tel: (65) 6776 0688

Fax: (65) 6776 0788 MALAYSIA: Fuiitsu PC Asia

Pacific Pte Ltd Tel: (60-3) 2093 3997 Fax: (60-3) 2093 4245

HONG KONG: Fuiitsu PC Asia Pacific Ltd

Tel: (852) 3101 8133 Fax: (852) 3101 0633

THAIL AND: Fuiitsu Systems Business (Thailand) Ltd PC Division

Tel: (66-2) 263 7888 Fax: (66-2) 263 7880

AUSTRALIA: Fujitsu PC Australia

Toll Free: 1800 288 283 Tel: (61-2) 9004 7455 Fax: (61-2) 9004 7720 www.lifebook.com.au

CHINA: Fujitsu PC China Division

Tel: (86-21) 3310 0808 Fax: (86-21) 3310 0606 www.pc-cn.fuiitsu.com

PHILIPPINES: Fuiitsu Philippines Inc. Tel: (63-2) 812 4001 Fax: (63-2) 817 7576

TAIWAN:

Fujitsu Taiwan Ltd Tel: (886-2) 2311 2255 Fax: (886-2) 2311 2277

VIFTNAM: Fuiitsu Vietnam Ltd

Tel: (84-4) 831 3895~7 Fax: (84-4) 831 3898

INDONESIA: PT Fujitsu Systems (Indonesia)

Tel : (62-21) 344 2601 Fax: (62-21) 344 2593

Note: For countries not listed above, please contact our Singapore office.