

Document Scanners

fi-4340C

departmental



fi-4340C



- 16 ppm colour / 40 ipm mono at 200 dpi
- **Unique** – 600 dpi camera installed
- 100 Page ADF (additional flatbed)
- A8 – A4 scanning
- Dual Interface – Ultra SCSI / USB 2.0 selectable

FUJITSU

THE POSSIBILITIES ARE INFINITE

fi-4340C Specifications

ADOBE® ACROBAT® 9 STANDARD 



fi-4340C

The fi-4340C scanner from Fujitsu is ideally suited for a wide range of departmental applications from document management through to graphic scanning.



Fujitsu's fi-4340C document scanner utilises high quality camera units with an optical resolution of 600 dpi which enables the production of high quality scans opening up the use of the scanner in an array of applications. Typically the scanner could be used for scanning graphics for web or DTP projects.

An imprinter is available as an optional extra that allows for the printing on the backside of the document of up to 40 characters, this serves as a confirmation that the document was scanned.

The fi-4340C can scan in monochrome setting at speeds of up to 40 pages per minute in simplex mode (76 images per minute in duplex) and 16 pages per minute in colour (29 images per minute). The scanner's 100 page ADF can cope with mixed documents ranging in size from A8 up to A4 and with in-built double feed detection, unrecognised double feeds are a thing of the past. The scanner comes equipped with a selectable USB 2.0 or SCSI-2 interface.

The scanner includes a full license of VRS Professional for utmost capturing simplicity and streamlined business process automation. Additionally when scanning high volumes of documents in monochrome mode, Fujitsu's optional Soft IPC software allows the user to select pre-determined scanning profiles to help obtain optimised scanning results. This software is capable of multistreaming images in monochrome and colour within a single scan.

Model	fi-4340C	
Operating method	Flatbed and ADF (automatic document feeder) / duplex	
Image sensor / Light source	CCD (charge-coupled device) image sensor x 2 / Xenon discharge tube (white)	
Optical resolution	ADF 600 dpi, Flatbed 600 dpi	
Output resolution	Up to 600 dpi x 600 dpi (Colour and grayscale), 800 dpi (Binary)	
Video output format	Binary, Grayscale (256 levels), Colour	
Document size	Minimum A8 (52.5 x 74 mm), Maximum A4 (210 x 297 mm)	
Scanning speed	Colour Simplex / Duplex	16 ppm for A4 portrait format at 200 dpi / 29 ipm for A4 portrait format at 200 dpi
	Mono Simplex / Duplex	40 ppm for A4 portrait format at 200 dpi / 76 ipm A4 portrait format at 200 dpi
ADF capacity	Maximum 100 sheets, paper weight: 64 g/m ² , A4	
Halftone patterns	Dither; Error diffusion	
Interface	wSCSI-2 / USB 2.0 / TP-IF	
Power requirements	100 to 120 V AC, 50/60 Hz; 220 to 240 V AC 50/60 Hz	
Power consumption	Operating: 120 W or less, Energy saving mode: 12 W	
Operating environment	Temperature 5°C - 35°C, Relative humidity 20% - 80% (non-condensing)	
Dimensions (H x W x D)	220 x 556 x 423 mm	
Weight	15 kg	
Bundled with	VRS Professional, Adobe® Acrobat® 9.0 Standard	
Typical daily throughput	4,000 pages	

Options	Part number	Remarks
IPC 4D board	CA02919-0521	(1) IPC Functions: Dither pattern download, Automatic binarisation, Automatic separation between photographs and text, Zooming: 25% to 200% by 1% steps, Outline extraction, Image emphasis, Mirror image, Reverse image (2) DTC functions: Spot noise removing, Dynamic threshold, Gamma curve correction, Filtering, Threshold curve selection, Smoothing
Image processing software V2.5	PA43402-C2290	This image processing software enables the scanner to efficiently binarize scanned data prior to transmission.
Video Interface Board	CA02956-2391	
JPEG Compression Board	CA02956-2398	
Imprinter	PA03237-D103	Post scan imprinting of up to 40 alpha-numerical characters on the backside of the document

Consumables	Part number	Remarks
Production Scanner Cleaning Kit	SC-CLE-KIT2	Includes F1 pump spray cleaner fluid, F2 metal parts pump spray cleaner fluid, cleaning sheets and cleaning paper
Ink Cartridge for Endorser	CA00050-0262	Lifetime: every 4,000,000 characters or 6 months
Consumable Kit fi-4340C	CON-3277-005A	2 x Pick Roller; 4 x Pad Assy; total max. lifetime 400,000 documents

All names, manufacturer names, brand and product designations are subject to special trademark rights and are manufacturer's trademarks and/or registered brands of their respective owners. All indications are non-binding. Technical data is subject to change without prior notification.



"Adobe", "Acrobat" and the Adobe PDF logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Fujitsu Europe Limited
Hayes Park Central
Hayes End Road, Hayes
Middlesex UB4 8FE
England
Tel: (+44-(0)20) 8573 4444
Fax: (+44-(0)20) 8573 2643

Fujitsu Deutschland GmbH
Frankfurter Ring 211
80807 Munich
Germany
Tel: (+49-(0)89) 32378-0
Fax: (+49-(0)89) 32378-100

Fujitsu Italia S.p.A.
Via Nazario Sauro, 38
20099 Sesto San Giovanni (MI)
Italy
Tel: (+39) 0226294.1
Fax: (+39) 0226294.201

<http://emea.fujitsu.com/scanners>

FUJITSU

THE POSSIBILITIES ARE INFINITE