

Document Scanners

fi-6750S

production



fi-6750S



- Single side batch scanning ADF plus A3 Flatbed
- 72 ppm in simplex scanning speed at 200 and 300 dpi (A4 landscape)
- Rotatable ADF
- Loaded with intelligent functions
- Bundled with ScandAll Pro
- A8 to A3 scanning, 200 page ADF

FUJITSU

THE POSSIBILITIES ARE INFINITE

fi-6750S Specifications



fi-6750S

Effortless simplex scanning combined with a host of intelligent functionalities

The fi-6750S from Fujitsu is an A3 flatbed and ADF combined scanner offering impressive simplex scanning at speeds of 72 pages per minute in mono and colour (landscape, A4, at up to 300 dpi) and 55 ppm in A4 portrait at up to 300 dpi. Flatbed A4 speeds in landscape are 0.6 seconds and 0.9 seconds at 200 and 300 dpi respectively and in portrait these times are 0.9 and 1.1 seconds.

The fi-6750S can seamlessly scan up to 200 sheets of varying weights, quality and sizes and can also scan paper up to 3 m long. A user positionable ADF ensures optimisation of available space is possible as well as suiting right or left handed operators.

ScandAll Pro comes bundled as standard with the fi-6750S allowing the scanner to effortlessly link with Microsoft Office SharePoint Server for easy digitised document sharing and viewing administration. ScandAll Pro also enables virtual duplex scanning through the ADF by automatically pairing front and back page scans as well as a barcode and patch code reading ability, enabling jobs to be automatically separated.

Operability is further enhanced through intelligent multifeed detection which whilst ensuring documents are not double fed also ensures false misfeed alerts do not occur when e.g. photos or sticky notes are attached.



ENERGY STAR[®] compliant

"Adobe", "Acrobat" and the Adobe PDF logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

| Model | fi-6750S | |
|--|--|--|
| Scanner type | ADF (automatic document feeder) + flatbed | |
| Scanning modes | Simplex, Colour / Grayscale / Monochrome | |
| Image sensor type | Colour CCD (charge-coupled device) image sensor x 2 | |
| Light source | White cold cathode discharge lamp | |
| Scanning range | Maximum: A3 (297 x 420 mm) / Minimum (portrait): A8 (52 x 74 mm) / Flatbed: Maximum: A3 (297 x 420 mm) | |
| Paper weight (no limitation for flatbed) ¹ | A4 or smaller: 31 to 209 g/m ² ; Over A4: 52 to 209 g/m ² ; A8 size: 127 to 209 g/m ² . Card feedability (ADF) ² | |
| Scanning speed (JPEG comp. values / A4 Landscape) ³ | Colour ⁴ / Grayscale ⁵ / Mono ⁵ | Simplex: 72 ppm (200 dpi), (200, 300 dpi) |
| Paper chute capacity ⁴ | 200 sheets (A4: 80 g/m ²) (active loadability) | |
| Background colours | ADF: White or Black (selectable) / Flatbed: White (Black is optional) | |
| Optical resolution | 600 dpi | |
| Output resolution | 50 to 600 dpi (adjust by 1 dpi increments) | |
| Output format | Colour: 24 bit / 8 bit, Grayscale: 8 bit, Monochrome: 1 bit | |
| AD converter | 1024 levels (10 bit) | |
| Interface | USB 2.0 / USB 1.1 | |
| Connector shape | USB: B type | |
| Output mode (half-tone) | Dither / Error diffusion | |
| Voltage range | AC 100 to 240 V, ±10% | |
| Power | Operating: 216W or less (Sleep mode: less than 6W) | |
| Operational environment | Temperature: 5 to 35°C (42 to 95°F); Relative humidity: 20 to 80% (Non-condensing) | |
| Dimensions (W x D x H base unit) ⁶ | 690 x 500 x 342 mm | |
| Weight | 35 kg | |
| Bundled software / drivers | ScandAll Pro, Adobe [®] Acrobat [®] , Quickscan Pro (Trial), Image Processing Software / TWAIN, ISIS [™] | |
| Environmental compliance | ENERGY STAR [®] and RoHS | |
| Others | Multi-feed detection / Long paper scanning | Ultrasonic Multi Feed Detection Sensor / 3048 mm |

| Options | Part number | Remarks |
|-------------------------------|--------------|---|
| Black Document Pad (fi-575BK) | PA03338-D960 | Black flatbed background pads which can be easily replaced by users |

| Consumables | Part number | Remarks |
|------------------------------|---------------|---|
| Desktop Scanner Cleaning Kit | SC-CLE-KIT2 | Includes F1 + F2 pump spray cleaner fluid, cleaning sheets with adhesive surface and cleaning paper |
| Consumable kit | CON-3576-012A | Includes 2 x pick roller and 2 x brake rollers to support scanning of up to 500,000 sheets |

¹ There is no limit of paper weight when document is scanned with the Flatbed.

² The fi-6750S supports ISO 7810 card scanning, but cannot scan embossed cards.

³ Actual scanning speeds are affected by data transmission and software processing times.

⁴ Maximum capacity varies, depending upon paper weight.

⁵ JPEG compressed figures.

⁶ Excluding the ADF paper chute and stacker.

All names, manufacturer names, brand and product designations are subject to special trademark rights and are manufacturer's trademarks and/or registered brands of their respective owners. All indications are non-binding. Technical data is subject to change without prior notification.

Fujitsu Europe Limited

Hayes Park Central
Hayes End Road, Hayes
Middlesex UB4 8FE
England
Tel: (+44-(0)20) 8573 4444
Fax: (+44-(0)20) 8573 2643

Fujitsu Deutschland GmbH

Frankfurter Ring 211
80807 Munich
Germany
Tel: (+49-(0)89) 32378-0
Fax: (+49-(0)89) 32378-100

Fujitsu Italia S.p.A.

Via Nazario Sauro, 38
20099 Sesto San Giovanni (MI)
Italy
Tel: (+39) 0226294.1
Fax: (+39) 0226294.201

<http://emea.fujitsu.com/scanners>



THE POSSIBILITIES ARE INFINITE