

DL3750+

- Printing Speed HDQ: 480 cps (12 cpi)
- Printing Width: 80 columns (10 cpi) / 96 columns (12 cpi)
- Quiet printing at only 49 dBA
- Parallel (Serial optional), Parallel + USB models available
- Optional LAN connectivity through USB model

Compact body, small footprint

DL3850+

- Printing Speed HDQ: 537 cps (12 cpi)
- Printing Width: 136 columns (10 cpi) / 163 columns (12 cpi)
- Quiet printing at only 49 dBA
- Parallel (Serial optional), Parallel + USB models available
- Optional LAN connectivity through USB model

Versatile, High speed, mid-range Printer

DL6400Pro/DL6600Pro

- Printing Speed DQ: 504 / 648 cps (12 cpi)
- Automatic Paper Path Switching
- Automatic Paper Thickness Control (DL6600Pro only)

Heavy Duty for Formats Up To A3

DL9300/DL9400

- Printing Speed DQ: 432 cps (12 cpi)
- Up To 8 Copies Including Original
- Automatic Paper Thickness Control

Flatbed Printer For Flexible Paper Handling

Commitment to the Environment

Fujitsu aims to help create the world of tomorrow positively with intelligent products that make sense – with technical know-how and a sense of responsibility towards the environment.

Fujitsu packaging is made from environment friendly, recyclable materials, and ribbons can be returned to our sales partners for recycling. Fujitsu offers refill cartridges for black and colour ribbons for the following printers: DL3750+, DL3850+, DL6400/DL6600 Pro and DL9300/DL9400. These ribbons can be refilled up to 5 times. All refillable ribbon cartridges carry the “blue environment angel” label.

Fujitsu Europe Limited
 Hayes Park Central
 Hayes End Road
 Hayes Middlesex UB4 8FE
 England
 Tel: (+44-(0)20) 8573 4444
 Fax: (+44-(0)20) 8573 2643
 www.fel.fujitsu.com

Fujitsu Italia S.p.A.
 Via Nazario Sauro, 38
 20099 Sesto San Giovanni (MI)
 Italy
 Tel: (+39) 0226294.1
 Fax: (+39) 0226294.201
 www.fis.fujitsu.com

Fujitsu Deutschland GmbH
 Frankfurter Ring 211
 80807 Munich
 Germany
 Tel: (+49-(0)89) 32378-0
 Fax: (+49-(0)89) 32378-100
 www.fdg.fujitsu.com

Dot Matrix Printers

DL3750+

DL3850+

DL6400Pro

DL6600Pro

DL9300

DL9400

www.fel.fujitsu.com



Fujitsu's DL3750+ office entry printer prints at up to 480 characters per second at 12 cpi and 400 cps at 10 cpi.

Fujitsu's DL3850+ printer offers an exceptional printing speed of up to 537 characters per second at 12 cpi, and 448 cps at 10 cpi. Both the DL3750+ and DL3850+ printers can be connected via a Parallel, Serial (optional) or USB interface. Connection to a Local Area Network via an optional LAN card is also available.

Fujitsu's DL6400 Pro and DL6600 Pro are heavy duty printers and the rugged design coupled with the space saving footprint and a print speed of up to 648 characters per second at 12 characters per inch, means they are in the high speed printer range.

Fujitsu's DL9300 and DL9400 dot matrix printers print at up to 360 cps at 10 characters per inch at relatively quiet printing at 54 dBA.



THE POSSIBILITIES ARE INFINITE



THE POSSIBILITIES ARE INFINITE

		Specifications					
Model		DL3750+	DL3850+	DL6400Pro	DL6600Pro	DL9300	DL9400
Printing technology	24-wire dot matrix, bi-directional	•	•	•	•	•	•
Printing speed	High speed draft quality max. 12cpi/10cpi	480/400	537/448	–	–	–	–
	Draft quality max. 12cpi/10cpi	432/360	432/360	504/420	648/540	432/360	432/360
	Correspondence max. 12cpi/10cpi	270/225	270/225	336/280	432/360	240/200	240/200
	Letter quality max. 12cpi/10cpi	135/113	135/113	168/140	216/180	120/100	120/100
Resolution	max. 360 x 360 dpi	•	•	•	•	•	•
Character sets	IBM PC Set 1 and 2, IBM PS/2 character sets (CP437, 850, 852, 855, 860, 863, 865, 866), ISO 8859-1/ECMA94, 37 national character sets (Slovenia, Croatia, Turkey, CSFR, Poland, Russia, Ukraine and so on) and Barcodes (3 of 9, EAN13, EAN8 etc.)	•	•	•	•	•	•
Resident fonts	Bitmap Courier 10, Prestige Elite 12, Pica 10, Boldface PS, OCR-A, OCR-B, Compression, Correspondence, Draft Outline Courier, Timeless, Nimbus Sans (Outline)	•	•	•	•	•	•
Word processing functions	Outline, Image overlay, Underline, Overline, Subscript, Superscript, Bold, Shadow, Italic, Condensed, Multi-width (up to 11 times), Multi-height (up to 11 times)	•	•	•	•	•	•
Input buffer	max. in kB	128	128	128	128	96	96
Printing width	at 10 cpi/12cpi	80/96	136/163	136	136	80	136
Line feed speed	Milliseconds/line at 6 lpi	<60	<60	<50	<50	60	60
Form feed speed	Inch per second	5.6	5.6	9.0	9.0	6.0	6.0
Number of copies	max. incl. original	5	5	6	6	8	8
Paper thickness	max. in mm	0.35	0.35	0.65	0.65	0.65	0.65
Paper width	Cut sheet mm	102-267	102-420	90-419	90-419	55-267	55-420
	Continuous mm	102-267	102-420	102-419	102-419	102-267	102-420
Paper feeding	Standard Bi-directional push-feed tractor Option Top-cut-sheet feeder	•	•	•	•	•	•
	Front-cut-sheet feeder		•	•	•	•	•
	Rear push-feed tractor			•	•	•	•
	Stacker unit			•	•		
Emulation	Fujitsu DPL 24C PLUS, IBM ProPrinter XL24E, EPSON ESC/P2	•	•	•	•	•	•
Interface	Parallel (IEEE1284), upgradeable to Serial (RS232C)	•	•				
	Parallel (IEEE1284)			•	•	•	•
	Parallel (IEEE1284) + USB 1.1	•	•		•		
	Network connectivity through optional LAN card (USB models only)	•	•				
Paper-park function		•	•	•	•	•	
Auto-load function		•	•	•	•	•	•
Auto Tear-off		•	•	•	•	•	•
Automatic paper thickness control					•	•	•
Host controlled paper path (HCCP)				•	•	•	•
Lock-function of operator panel		•	•	•	•	•	•
Power requirements	220V/240V +6%, -10% (50-60Hz)	•	•	•	•	•	•
Dimensions	Height mm	120	130	325	325	250	250
	Width mm	415	570	600	600	456	598
	Depth mm	330	330	300	300	300	300
Weight	kg	7.3	9.7	25	25	12	14
Acoustic noise level	dB(A)	49	49	55	56	54	54
MTBF (Mean time between failures)	hours at 25% duty cycle	20,000	20,000	8,000	8,000	8,000	8,000
Print head life	million strokes for each wire	400	400	400	400	300	300
Ribbon life Black	million characters (at DQ)	5	5	18	18	5	5