

DESKPOWER TX



- 32" Wide Screen Home Entertainment PC with HDD/DVD³ video recording capability
- Designed for Windows[®] XP Media Center Edition 2005
- Massive storage on 600GB Hard Disk to record up to 450 hours of video
- Wireless multimedia keyboard and optical scroll mouse with maximum 10 meter usability
- Bundled with Gaming Plugin Software for absolute video console gaming enjoyment
- Dual TV Tuner card for watching and recording different TV Channels¹ simultaneously
- Teletext support for real time information at your fingertips

DESKPOWER TX Recommended Configuration	
Processor	Intel [®] Pentium [®] 4 Processor 630 (3GHz, 2MB L2 cache, 800MHz FSB) supporting Hyper Threading and EM64T ² Technology
OS Supported	Windows [®] XP Media Center Edition 2005
Display	32" Wide Screen LCD Display ³ , 1366 x 768 pixels, 500cd/m ² Luminance, 800:1 Contrast Ratio
Graphics	Intel [®] Graphics Media Accelerator 900 with DVMT 3.0
Memory	512MB (256MB x 2), DDR2 533MHz
Hard Disk	600GB (300GB x 2), S-ATA, 7200rpm
Optical Device	Dual Layer DVD Super Multi Writer ⁴
Specifications	
Max. Memory Supported	1GB DDR2 533MHz, Dual Channel (2 Slots)
Chipset	Intel [®] 915GV
Hard Disk Drive	Serial ATA-150, S.M.A.R.T. support
Graphics	Integrated Intel [®] Graphics Media Accelerator 900 with DVMT 3.0 delivers low-power, high-performance 2D/3D graphics, video, and display capabilities at a maximum shared memory of 128MB
Sound	RealTek ALC655, Six channel audio CODEC designed for PC multimedia systems
Speaker	5 Watts x 2 built-in Satellite Speakers + 10 Watt built in Sub-Woofer
Network Interface	RealTek RTL8100C, 100/10Mbps ⁵ Fast Ethernet, supporting Wake-on-LAN and remote wake-up
Card Slot	Secured Digital / Memory Stick [®] PRO / xD PC Card Type I/II x 2, Type III x 1
Connector Interface	USB 2.0 x 6 (Front x 2, Rear x 4), RJ45 (LAN), IEEE1394, AC Power in, Mic-in, Headphone out x 2 (front and rear), Line-in, Line-out
TV Interface	Application: Windows [®] XP Media Center Edition 2005 Input 1+2 (rear): Composite RCA A/V input x 2 sets, S-Video input x 2, 75Ω coaxial F-Connector x 2 (For Analogue terrestrial Antenna input) Input 3 (front): Composite RCA A/V input x 1 set, S-Video input x 1 Audio Output: Optical Digital Square plug TV System Supported: PAL B/G
Expansion Slots [Free]	Half size PCI x 2 [0]
Drive Bays [Free]	Front Access: 5.25" x 1 [0] Internal: 3.5" x 2 [0]
Security ⁶	BIOS Lock, Hard Disk Lock, Anti-theft Lock Slot
Power	Source: AC 100~240V, 50/60Hz Consumption: Approx. 266W (typical), 360 (max) Standby: Approx. 8W
Dimensions	Approx. 944mm (W) x 311mm (D) x 644mm (H)
Weight	Approx. 42Kg
User Interface	
Keyboard	Fujitsu RF Wireless 105-key Multimedia Keyboard ⁷ with Anti Bacteria Protection Five Programmable Application Quick Launch Buttons (Internet, Email and three other software) LED Display of Wireless Keyboard and Mouse Battery Life
Mouse	Fujitsu RF Wireless Optical Scroll Mouse ⁷
Remote Control	Fujitsu Media Center Infrared Remote Control with External USB Remote Sensor
Bundled Accessories	
Bundled Software	CyberLink PowerDVD [™] , CyberLink PowerProducer [™] , Sonic RecordNow [™] DX, Adobe Acrobat Reader 6.0, Fujitsu Update Navi ⁸ , Fujitsu Hardware Diagnostic Tool, Video Colour Adjust Plug-in, Gaming Input Plugin
Software on CD	1 year Full Licensed Norman Virus Control with Sandbox Technology and Norman Personal Firewall, Acronis True Image 8.0 Personal Edition
Cables	AC Power Cable, F-Connector Cable (10cm) x 2, F-Connector Cable (2 metre), F-Connector Video Splitter, F-Connector to IEC
Optional Accessories	
Floppy Disk Drive	External USB 1.44MB FDD
Mouse	USB Optical Scroll Mouse

The above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

1 When TV Channel source is controlled by Setup-box, only 1 channel can be received at any time.

2 For EM64T technology functionality, it requires the installation of a future 64bit Operating System.

3 It is natural for all liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

4 Supports DVD multi formats such as DVD-RAM, DVD+RW, DVD+R DL, DVD+R, DVD-RW, DVD-R, DVD-ROM, CD-RW, CD-R, CD-ROM.

5 This term does not represent actual data rate of 100/10Mbps and simply indicates compliance with IEEE 802.3, IEEE 802.3u and IEEE 802.3ab standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices.

6 BIOS Lock needs a supervisor/user password to access BIOS setup. BIOS settings can be configured to prompt for password at every first bootup or all bootup sequences. Access to BIOS setup is needed to configure Hard Disk Lock. Hard Disk Lock requires an access key to retrieve data on the hard disk. This is a Data Confidentiality security feature. Anti-theft Lock Slot allows the use of a lock to physically secure the DESKPOWER.

7 A Maximum of 10 meters from the PC (less than 3 meters is recommended), within 45 degrees on either side of the PC

8 Update Navi is a Fujitsu Proprietary application that updates DESKPOWER drivers by connecting automatically to Fujitsu's server. This will help update your DESKPOWER with the latest software drivers and utilities to ensure compatibility between hardware and software, maintaining smooth operation anytime, anywhere.

9 For DVD video recording capability, the source file must be residing in the HDD.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 10° to 35°C / 50 to 95°F (operating), 10° to 60°C / 50 to 140°F (non-operating). Relative humidity: 20% to 80% RH (operating and non-operating).

