

15" TFT LCD DISPLAY

- Advanced Picture Quality Using Fujitsu ASV* Technology
- Wide Viewing Angle
- High Contrast and High Brightness
- User Friendly Functions



FPC-TFTAED		
Advance Picture Quality	Sharp ASV* TFT LCD Panel Technology	Wide viewing angle High contrast and high brightness
	Best Scaled Picture	Resolutions lower than the native resolution, XGA
		One touch auto-adjustment Automatic start of auto-adjusting for newly detect modes
User Friendly Functions		
LCD Panel	Type	Sharp ASV* TFT LCD
	Back Light	Cold-cathode flourescent lamp x 4 (top/bottom 2 each) Edge lighting
	Surface Treatment	Anti-glare treatment (Hayes value 25%, hardness 3H)
Panel Size		Diagonal 15-inch
Number of Pixels		1024 x 768 (XGA)
Pixel Pitch		(0.099 x 3)mm x 0.297mm
Display Size		304.1mm(H) x 228.1mm(V)
Response Time		25ms (TYP)
Viewing Angle	Horizontal	170° (TYP)
	Vertical	170° (TYP) (>CR_10)
Luminance	Typical	250cd/m ²
	Minimum	170cd/m ² at the center of the screen
Contrast Ratio	Typical	400 : 1
	Minimum	200 : 1 at the center of the screen
Scanning Frequency	Horizontal	31.5 to 60kHz
	Vertical	56 to 75Hz
Display Mode	Supported Modes	VGA : 640 x 400/480 dots
		SVGA : 800 x 600 dots
		XGA : 1024 x 768 dots
		Others : 720 x 400 dots
Display Colours		16,770,000 colours
Screen Size		15.0-inch type (diagonal: 38.0cm)
Tilting Angle		Frontward: 0°, Rearwards: 30°
Swiveling Angle		90° clockwise and counterclock wise each
I/O Interface (USB)	Power Supply Method	Self-Powered
	Port-Connector	1 Up-stream (Series B), 1 Down-stream (Series A)
Power Supply	Voltage	100/240V AC
	Frequency	50Hz/60Hz
Dimensions		390mm(W) x 189mm(D) x 364mm(H)
Weight		Approx. 5kg (including AC adaptor)
Operating Condition		Temperature: 5° to 35°C
		Humidity: 10 to 90% (Must be free from frosting)

* Advance Super View TFT LCD Panel Technology

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Some pictures are expressed in creative manners which may differ from the actual unit. Please check with your local distributor on any specifics.

Dealer:

SINGAPORE:
Fujitsu PC Asia
Pacific Pte Ltd
Tel : (65) 6776 0688
Fax: (65) 6776 0788

MALAYSIA:
Fujitsu PC Asia
Pacific Pte Ltd
(Malaysia Branch)
Tel : (60-3) 253 3997
Fax: (60-3) 253 4245

HONG KONG:
Fujitsu PC Asia
Pacific Ltd
Tel : (852) 3101 8133
Fax: (852) 3101 0633

THAILAND:
Fujitsu Systems
Business (Thailand) Ltd
PC Division
Tel : (66-2) 658 0350
Fax: (66-2) 658 0356

PHILIPPINES:
Fujitsu Philippines Inc.
Tel : (63-2) 812 4001
Fax: (63-2) 817 7576

VIETNAM:
Fujitsu Vietnam Ltd
Tel : (84-4) 831 3895-7
Fax: (84-4) 831 3898

INDONESIA:
PT Fujitsu Systems
(Indonesia)
Tel : (62-21) 344 2601
Fax: (62-21) 344 2593

Website: www.fujitsu-pc-asia.com Webmail: www.fujitsu-pc-asia.com/contactus

Note: For countries not listed above, please contact our Singapore office.