

THE POSSIBILITIES ARE INFINITE **FUJITSU**

17" TFT LCD PD-TFT17A
Built-In Confidence

17" TFT LCD

- 17" TFT LCD monitor with Super energy saving feature.
Operating Mode at only 29W max.
- Display Area equivalent to a 19" CRT Monitor
- Space Saving Base design to fit more in less space.
- Flicker Free Screen



SINGAPORE:
Fujitsu PC Asia
Pacific Pte Ltd
Tel : (65) 6776 0688
Fax : (65) 6776 0788

MALAYSIA:
Fujitsu PC Asia
Pacific Pte Ltd
(Malaysia Branch)
Tel : (60-3) 2093 3997
Fax : (60-3) 2093 4245

HONG KONG:
Fujitsu PC
Asia Pacific Ltd
Tel : (852) 3101 8133
Fax : (852) 3101 0633

THAILAND:
Fujitsu Systems
Business (Thailand) Ltd
PC Division
Tel : (66-2) 263 7888
Fax : (66-2) 263 7880
www.fujitsu-pcap.in.th

AUSTRALIA:
Fujitsu PC Australia
Toll Free: 1800 288 283
Tel : (61-2) 9004 7455
Fax : (61-2) 9004 7720
www.lifebook.com.au

CHINA:
Fujitsu PC China Division
Tel: (86-21) 3310 0808
Fax: (86-21) 3310 0606
www.pc-cn.fujitsu.com

PHILIPPINES:
Fujitsu Philippines Inc.
Tel : (63-2) 812 4001
Fax : (63-2) 817 7576

TAIWAN:
Fujitsu Taiwan Ltd
Tel : (886-2) 2311 2255
Fax : (886-2) 2311 2277

VIETNAM:
Fujitsu Vietnam Ltd
Tel : (84-4) 831 3895-7
Fax : (84-4) 831 3898

INDONESIA:
PT Fujitsu Systems
Indonesia
Tel : (62-21) 570 9330
Fax : (62-21) 573 5150
www.fujitsu.com/id

Note: For countries not listed above, please contact our Singapore office.

PD-TFT17A		
LCD	Type	TFT Color SXGA
	Screen Size	17 Inches
PC Input	Signal	RGB Analog
	Type	15 Pin D-Sub
Sync	H-Freq	31.5 ~ 80KHz
	V-Freq	56 ~ 75Hz
Brightness		250cd/m ²
Response Time		13ms
Contrast Ratio		350 : 1
Max Resolution Supported		1280 x 1024 @ 75Hz
Display	Color	16,777,216 (24bit)
Viewing Angle		R/L: 75/75, T/B: 65/60
OSD Controls Support		Auto Adjust, Brightness & Contrast, Size & Position, Colour Control, Language Selection, OSD Position
Power Management System		VESA DPMS
Plug & Play Support		DDC 1/2B
Compatibility		PC: VESA Standard VGA to SXGA 75Hz
Power Consumption	Normal Mode	29 Watts (Max)
	DPMS Mode	< 4 Watts
Power Supply	Input	AC 100 ~ 240V, 50 ~ 60 Hz
	Output	DC 12V, 4.5A
Temperature	Operating	0°C ~ 40°C
	Storage	-10°C ~ 50°C
Humidity	Operating	30% ~ 80%
	Storage	5% ~ 90%
Dimension		399 x 415 x 160 (mm)
Weight		5.2kg

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Some pictures are expressed in creative manners which may differ from the actual unit. Please check with your local distributor on any specifics.

All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.

Dealer:

www.pc-ap.fujitsu.com