LifeBook C1320

- Express performance with DDR2-533 memory, SATA-150 hard disk, Integrated PCI Express® x1 Gigabit LAN, ExpressCard™ /34 /54 slot and Intel® PRO/Wireless 2915ABG
- Comprehensive connectivity with four USB 2.0, SD, PC card, ExpressCard™, IEEE1394, Serial, Parallel and S-Video out
- Long Battery Life of up to 10.8hrs¹ with standard battery and optional bay battery



	C1320 Recommended Configurations	
Platform	Intel [®] Centrino™ Mobile Technology	
	- Intel® Pentium® M Processor 740 (1.73GHz, 2MB L2 cache, 533MHz FSB)	
	- Intel® PRO/Wireless 2915ABG/2200BG network connection	
	- Intel® 915GM Express Chipset	
OS Supported	Microsoft® Windows® XP Home Edition	
• •	Microsoft® Windows® XP Professional Edition	
Display	15.4" Wide XGA TFT, 1280 x 800 pixels	15" SuperFine XGA TFT, 1024 x 768 pixels
Modular Bay Device	DVD/CD-RW Combo Drive	DVD/CD-RW Combo Drive
Memory	256MB DDR2 533MHz	256MB DDR2 533MHz
Hard Disk	40GB	40GB
Battery	Up to 6.0hrs1 (6-cell Li-lon 5200mAh)	Up to 6.0hrs1 (6-cell Li-lon 5200mAh)
Weight	Approx. 2.63kg (w/ Weight Saver Option)	Approx. 2.65kg (w/ Weight Saver Option)
	Specifications	· · · · · · · · · · · · · · · · · · ·
Max. Memory Supported	2GB DDR2 533MHz, Dual Channel	
Hard Disk Drive	SATA-150 5400rpm, S.M.A.R.T. support, Two Partitions - 50/50 ⁸	
Graphics	Integrated Intel® Graphics Media Accelerator 900 with DVMT ⁵ 3.0 delivers low-power, high-performance 2D/3D graphics, video, and display capabilities	
Ciapilics	at a maximum shared memory of 128MB	
High Definition (HD) Audio	RealTek ALC260 HD audio codec with built-in dual stereo speakers	
	HD Audio-in: Mic-in, Line-in	
	HD Audio-out: Headphone-out, Line-out	
Communication	56K V92 ² Global Modern MDC1.5, IrDA 1.1 4Mbps ³ , 1000/100/10Mbps ⁴ PCI Express [®] x1 Gigabit Ethernet and Intel [®] PRO/Wireless 2915ABG/	
Communication	2200BG network connection with Dual Antenna. Separate ON/OFF switch for wineless network connection	
User Interface	Zeoubal network collinection with Dual Antenina. Separate On/Orr switch for wheless network collinection. Keyboard: 84-9k, 19mm key pitch, 3mm key stroke	
	Touch Pad with Scroll Buttons	
Card Slot	TOUCH FAU WITH SCHOOL BUTTON STATE OF THE SCHOOL STATE OF THE SCHO	
	ExpressCard ^{1M} /34 /54 support	
	Expressora (*** 754 754 support Secured Digital	
Connector Interface	USB 2.0 x 4, VGA (external display), RJ45 (LAN), RJ11 (modem), S-Video out, IEEE1394, Serial, Parallel, HD Audio-in, HD Audio-out, Power Adapter	
	USB 2.0 X 4, VGA (EXternal display), H343 (LAN), H311 (modern), S-video out, IEEE1394, Senai, Parallel, HD Audio-in, HD Audio-out, Power Adapter DC-in, Port Replicator Interface	
Quick Launch Panel	Four Propriaction internace Four Programmable Application Launch Buttons (Internet, Email and two other softwares)	
Media Playback Panel	Four Frunctions: Stop/Eject, Play/Pause, Next, Previous	
Security ⁶	FOUR FUNCTIONS SUBJECTION, FAILY FAILY FUNDS BIOS Lock, Hard Disk Lock, Anti-theft Lock Slot	
Dimensions	50 LOCA, Hard DISK LOCA, All CHIERT LOCA SIGN 360mm (H) 360mm (M) x 272mm (D) x 38.8mm (H)	
Diffierisions	Southin (w) x 2/2/min (D) x 36.0mm (n) Bundled Accessories	
AC Adapter	Input A Coessones Input A Coes	
Rundled Software	input Ac 100-240V, Output De 194 000V. CyberLink PowerDVD™, CyberLink PowerProducer™ Gold, Sonic RecordNow™ DX, Sonic DLA, Adobe Acrobat Reader 6.0, Fujitsu Update Navi ⁹ ,	
Duriuled Software	CyberLink PowerDVD:, CyberLink PowerFroducer Gold, Sonic necordinow: DX, Sonic DLA, Adobe Acrobat neader 6.0, Fujitsu Dipotate Navi-, Fujitsu Hardware Diagnostic Tool, Fujitsu Display Manager	
Software on CD	Fujitsu Hardware Diagnostic Tool, Fujitsu Display Manager 1 year Full Licensed Norman Virus Control with Sandbox Technology and Norman Personal Firewall	
Software on CD	Tyear ruin Literateur Norman virus Control with Sandbox Technology and Norman Personal Priewaii Optional Accessories	
Dest Beeliesten	Opinional recessiones Connector Interface:	
Port Replicator	USB 2.0 x 4, Headphone-out, Microphone-in, DVI-D, VGA (external display), RJ45 (LAN), PS/2 (keyboard/mouse), Serial, Parallel, Power Adapter DC-in	
Madulas Bass Outland	USB 2.0 x 4, Headphone-out, Microphone-in, DVI-D, VGA (external display), HJ45 (LAIN), PS/2 (keyboard/mouse), Serial, Parallel, Power Adapter DC-in Replaceable with	
Modular Bay Options	repiaceable with - Bay Battery, 6-cell Li-lon 3800mAh, up to 10.8hrs¹ battery life (Standard + Bay Batteries)	
	- Dual Layer DVD Super Multi Writer ⁷	
	- DVD/CD-RW Combo Drive	
E	- Weight Saver	
Floppy Disk Drive	External USB 1.44MB FDD	
Mouse	USB Optical Scroll Mouse	

The above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

- Results obtained from Ziff Davis (BusinessWinstone 2001) Battery Mark V1.0.1 performed on systems with maximum battery life settings. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences. Modular Bay devices or hard drive usage may also have a significant impact on battery life.
- Impact on battery line.

 Maximum 56kbps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.

 This term does not represent actual data rate of 4Mbps and simply indicates compliance with IrDA standard specification 1.1. Actual maximum data rate depends on local configurations and connected devices.

 This term does not represent actual data rate of 1000/100/10Mbps and simply indicates compliance with IEEE 802.3, IEEE 802.3u and IEEE 802.3ab standards. Actual maximum data rate depends on network
- configurations, cable conditions as well as connected devices.
- Dynamic Video Memory Technology (DVMT) dynamically responds to application requirement and efficiently allocates the proper amount of memory (max.128MB) for optimal graphics and system performance. The memory size available to the Operating System will be less than the size of installed memory module. BIOS Lock needs a supervisor/user password to access BIOS Setup, BIOS settings can be configured to prompt for password at every first bootup or all bootup sequences. Access to BIOS setup is needed to configure Hard Disk Lock. Hard Disk Lock requires an access key to retrieve data on the hard disk. This is a Data Confidentiality security feature. Anti-theft Lock Slot allows the use of a lock to physically secure
- Supports DVD multi formats such as DVD-RAM. DVD+RW. DVD+R. DL. DVD+R. DVD-RW. DVD-R. CD-RW. CD-R. CD-ROM and DVD-ROM.
- Supplies but mini interast such as DVP-And, in DVP-AN, DVP-AN,
- It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of

TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

"PCI Express" and the PCI Express design marks are registered trademarks and/or service marks of PCI-SIG.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5° to 35°C / 41 to 95°F (operating), -10° to 60°C / 14 to 140°F (non-operating). Relative humidity: 20% to 80% RH (operating and non-operating).

Dolby and the double-D symbol are registered trademarks of Dolby Laboratories

VIETNAM: Fujitsu Vietnam Ltd

SINGAPORE: Fujitsu PC Asia Pacific Pte Ltd Tel: (65) 6776 0688 Fax: (65) 6776 0788 MALAYSIA: Fujitsu PC Asia Pacific Pte Ltd Tel: (60-3) 2093 3997 Fax: (60-3) 2093 4245 HONG KONG: Fujitsu PC Asia Pacific Ltd Tel: (852) 3101 8133 Fax: (852) 3101 0633 THAILAND: Fujitsu Systems Business (Thailand) Ltd PC Division Tel: (66-2) 263 7888 Fax: (66-2) 263 7880 AUSTRALIA: Fujitsu PC Australia

Tel : (84-4) 831 3895~7 Fax: (84-4) 831 3898

Toll Free: 1800 288 283

Tel: (61-2) 9004 7455 Fax: (61-2) 9004 7720

www.lifebook.com.au

Fujitsu PC China

PHILIPPINES: Fujitsu Philippines Inc. Tel: (63-2) 812 4001

Fax: (63-2) 817 7576

Fujitsu Taiwan Ltd

Tel: (886-2) 2311 2255

Fax: (886-2) 2311 2277

CHINA:

Division Tel: (86-21) 3310 0808 Fax: (86-21) 3310 0606 www.pc-cn.fujitsu.com

INDONESIA: PT Fujitsu Systems Indonesia

Tel: (62-21) 570 9330 Fax: (62-21) 573 5150 www.fujitsu.com/id

Note: For countries not listed above, please contact our Singapore office















All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed. as may be expressly agreed.

Dealer: