

**SINGAPORE:**

**Fujitsu PC Asia  
Pacific Pte Ltd**  
Tel : (65) 6776 0688  
Fax : (65) 6776 0788

**MALAYSIA:**

**Fujitsu PC Asia  
Pacific Pte Ltd**  
Tel : (60-3) 2093 3997  
Fax : (60-3) 2093 4245

**HONG KONG:**

**Fujitsu PC  
Asia Pacific Ltd**  
Tel : (852) 3101 8133  
Fax : (852) 3101 0633

**THAILAND:**

**Fujitsu Systems  
Business (Thailand) Ltd  
PC Division**  
Tel : (66-2) 263 7888  
Fax : (66-2) 263 7880

**AUSTRALIA &  
NEW ZEALAND:**

**Fujitsu PC Australia**  
Toll Free: 1800 288 283  
Tel : (61-2) 8877 9500  
Fax : (61-2) 9889 3360  
[www.lifebook.com.au](http://www.lifebook.com.au)

**CHINA:**

**Fujitsu PC China  
Division**  
Tel : (86-21) 3310 0808  
Fax : (86-21) 3310 0606  
[cn.fujitsu.com/pc](http://cn.fujitsu.com/pc)

**PHILIPPINES:**

**Fujitsu Philippines Inc.**  
Tel : (63-2) 812 4001  
Fax : (63-2) 817 7576

**TAIWAN:**

**Fujitsu Taiwan Ltd**  
Tel : (886-2) 2311 2255  
Fax : (886-2) 2311 2277

**VIETNAM:**

**Fujitsu Vietnam Ltd**  
Tel : (84-4) 831 3895  
Fax : (84-4) 831 3898

**INDONESIA:**

**PT. Fujitsu Indonesia**  
Tel : (62-21) 570 9330  
Fax : (62-21) 573 5150

**INDIA:**

**Fujitsu India Limited**  
Tel : (91-11) 2370 6070  
Fax : (91-11) 2370 6079

**Note:** For countries not listed above, please contact our Singapore office.

P7010 Recommended Configurations	
Platform	Intel® Centrino® Mobile Technology - Intel® Pentium® M Processor ULV 753 (1.20GHz, 2MB L2 cache, 400MHz FSB) - Intel® PRO/Wireless 2915ABG Network Connection - Intel® 855GME Chipset
OS Supported	Genuine Windows® XP Home Edition Genuine Windows® XP Professional
Display	10.6" SuperFine Wide XGA TFT, 1280 x 768 pixels
Modular Bay Device	Dual Layer DVD Super Multi Writer <sup>5</sup>
Memory	512MB DDR333
Hard Disk	80GB
Battery	Up to 7.6hrs <sup>1</sup> (6-cell Li-Ion 4800mAh)
Weight	Approx. 1.5kg
Colour	Pearl White, Stone Black, Ruby Red, Sapphire Blue and Amber Yellow
Specifications	
Max. Memory Supported	1024MB DDR333, 2 µDIMM slot
Hard Disk Drive	Ultra DMA/100 and S.M.A.R.T. support, Max. 100GB
Graphics	Integrated Intel® Extreme Graphics 2 with DVM <sup>2</sup> delivers low-power, high-performance 2D/3D graphics, video and display capabilities at a maximum shared memory of 64MB
Audio	RealTek ALC203 codec with Built-In Stereo Speakers and Sound Effect Manager; Internal Microphone
Communication	56K V.92 <sup>3</sup> modem, 100/10Mbps <sup>4</sup> Fast Ethernet and Intel® PRO/Wireless 2915ABG Network Connection with Dual Antenna Separate ON/OFF switch for wireless network connection
User Interface	Keyboard: 82-key, 18mm key pitch, 2mm key stroke Touch Pad with Fingerprint Sensor
Security	AuthenTec TruePrint™ Technology with Softex OmniPass 3.0
Card Slot	PC Card Type I/II x 1 SD Card/ Memory Stick PRO x 1 Compact Flash (CF-Type II) Slot x 1
Connector Interface	USB 2.0 x 2, VGA (external display), RJ45 (LAN), RJ11 (modem), IEEE1394, Headphone-out/SPDIF, Microphone-in, S-Video terminal, Power Adapter AC-in
Dimensions	261mm (W) x 199mm (D) x 32mm min (H)
Bundled Accessories	
AC Adapter	Input AC 100 ~ 240V, Output DC 16V 60W
Bundled Software	Softex OmniPass 3.0, CyberLink PowerDVD™, CyberLink PowerProducer™ Gold, Sonic RecordNow™ DX, Sonic DLA, Adobe Acrobat Reader 6.0, Fujitsu Update Navi <sup>6</sup> , Fujitsu Hardware Diagnostic Tool
Software on CD	Norman Virus Control & Norman Personal Firewall
Optional Accessories	
Modular Bay Options	Replaceable with - Bay Battery, 3-cell Li-Ion 2300mAh, up to 11.2hrs <sup>1</sup> battery life (Standard + Bay Batteries) - Dual Layer DVD Super Multi Writer <sup>5</sup> - DVD/CD-RW Combo Drive - Weight Saver
Floppy Disk Drive	External USB 1.44MB FDD
Mouse	USB Optical Scroll Mouse

The above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

- Results obtained from Ziff Davis (BusinessWinstone 2001) Battery Mark V1.0.1 performed on systems with maximum battery life settings. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences. Modular Bay devices or hard drive usage may also have a significant impact on battery life.
- Dynamic Video Memory Technology (DVM<sup>2</sup>) dynamically responds to application requirement and efficiently allocates the proper amount of memory (max. 64MB) for optimal graphics and system performance. The memory size available to the Operating System will be less than the size of installed memory module.
- Maximum 56Kbps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.
- This term does not represent actual data rate of 100/10Mbps and simply indicates compliance with IEEE 802.3 and IEEE 802.3u standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices.
- Supports DVD multi formats such as DVD-RAM, DVD+RW, DVD+R DL, DVD+R, DVD-RW, DVD-R, CD-RW, CD-R, CD-ROM and DVD-ROM.
- Update Navi is a Fujitsu Proprietary application that updates LifeBook drivers by connecting automatically to Fujitsu's server. This will help update your LifeBook with the latest software drivers and utilities to ensure compatibility between hardware and software, maintaining smooth operation anytime, anywhere.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5° to 35°C/41 to 95°F (operating), -10° to 60°C/14 to 140°F (non-operating). Relative humidity: 20% to 80% RH (operating and non-operating). Please note that, GB=billion bytes.



[www.pc-ap.fujitsu.com](http://www.pc-ap.fujitsu.com)

All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.

Dealer: