

LifeBook S6210

- Ultra-portable at approximately 1.65kg*
- Designed for Microsoft® Windows® operating systems
- Intel® Centrino™ Mobile Technology
- Latest Intel® PRO/Wireless 2200BG network connection 802.11b/g with Dual Antenna
- Equipped with a wide array of hot-swappable modular bay options that include DVD±RW Drive and bay battery among others
- Three USB 2.0 ports for peripherals connection



Fujitsu recommends Microsoft® Windows® XP Professional for Mobile Computing.

S6210 Recommended Configuration	
Processor	Intel® Pentium® M Processor 1.50 GHz (w/Enhanced SpeedStep® Technology)
OS Supported	Microsoft® Windows® XP Home Edition Microsoft® Windows® XP Professional Edition Microsoft® Windows® 2000 Professional Edition
Display	13.3" XGA TFT, 1024 x 768 pixels
Modular Bay Drive	DVD/CD-RW Combo Drive
Wireless LAN	Intel® PRO/Wireless 2200BG network connection 802.11b/g with Dual Antenna
Memory	256MB DDR333
Hard Disk	60/40GB ⁸
Standard Battery Life	4.2hrs ¹
Weight	Approx. 1.65kg (w/Weight Saver)
Specifications	
Chipset	Intel® 855GME
Secondary Cache	1MB
Max. Memory Supported	2048MB DDR333
Hard Disk Drive	Ultra DMA/100 and S.M.A.R.T Support
Graphics	Integrated Intel® Extreme Graphics 2 with DVMT ² delivers low-power, high-performance 2D/3D graphics, video and display capabilities at a maximum shared memory of 64MB
Audio	SigmaTel STAC9751T AC 97 codec with built-in dual Stereo Speakers
Communication	56K V.92 ³ modem, IrDA 1.1 4Mbps ⁵ , 1000/100/10 Mbps ⁴ Gigabit Ethernet and Intel® PRO/Wireless 2200BG network connection 802.11b/g with Dual Antenna. Separate ON/OFF switch for wireless network connection
User Interface	Keyboard: 84-key, 19mm key pitch, 3mm key stroke Touch Pad with Scroll Button
Card Slot	PC Card Type I/II x 1, Smart Card support ⁶
Connector Interface	USB 2.0 x 3, VGA (external display), RJ45 (LAN), RJ11 (modem), Audio Line-in, IEEE1394, Headphone-out, Microphone-in, Power Adapter DC-in, Port Replicator Interface
Quick Launch Panel	Four Programmable Application Launch Buttons (Internet, E-mail and two other software)
Security ⁷	BIOS Lock, Hard Disk Lock, LifeBook Lock, Anti-theft Lock Slot, Smart Card ⁶
Dimensions	293mm (W) x 236.5mm (D) x 30.5mm min. (H)
Bundled Accessories	
AC Adapter	Input AC 100~240V, Output DC 16V 60W
Software on CD	Norman Virus Control & Norman Personal Firewall
Port Replicator	Connector Interface: USB 2.0 x 2, VGA (external display), RJ45 (LAN), PS/2 (keyboard/mouse), Serial, Parallel, Power Adapter DC-in
Optional	
Modular Bay Options	Replaceable with Bay Battery (Approx. 8.0hrs ¹ - Standard + Bay Batteries), DVD Super Multi Drive ⁹ , DVD±RW Drive, DVD/CD-RW Combo Drive, DVD-ROM Drive and Weight Saver
Floppy Disk Drive	External USB 1.44MB FDD
Mouse	USB Optical Scroll Mouse

* with weight saver

- ¹ Results obtained from Ziff Davis (BusinessWinstone 2001) Battery Mark V1.0.1. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences. DVD or hard drive usage may also have a significant impact on battery life.
- ² Dynamic Video Memory Technology (DVMT) dynamically responds to application requirement and efficiently allocates the proper amount of memory (max. 64MB) for optimal graphics and system performance. The memory size available to the Operating System will be less than the size of installed memory module.
- ³ Maximum 56Kbps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.
- ⁴ This term does not represent actual data rate of 1000/100/10Mbps and simply indicates compliance with IEEE 802.3, IEEE 802.3u and IEEE 802.3ab standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices.
- ⁵ This term does not represent actual data rate of 4Mbps and simply indicates compliance with IrDA standard specification 1.1. Actual maximum data rate depends on local configurations and connected devices.
- ⁶ Smart Card support requires a Smart Card adapter for the PC Card Slot. This is available as an accessory. Fujitsu does not provide the application for Smart Card Solution.
- ⁷ BIOS Lock needs a supervisor/user password to access BIOS setup. BIOS settings can be configured to prompt for password at every first bootup or all bootup sequences. Access to BIOS setup is needed to configure Hard Disk Lock. Hard Disk Lock requires an access key to retrieve data on the hard disk. This is a Data Confidentiality security feature. LifeBook Lock requires a supervisor/user password to bootup the LifeBook when it powers up or resumes last session from suspends/hibernate mode. This is an anti-theft feature with more than 800,000 password combinations using the buttons on the Quick Launch Panel. Anti-theft Lock Slot allows the use of a lock to physically secure the LifeBook. SmartCard usage is dependent on customer's solution. Full security unlock sequence - LifeBook Lock, Bootup Lock (BIOS Lock), Hard Disk Lock. NOTE: Loss of password requires the LifeBook to be returned to Japan factory for system refresh. Cost of shipment and lost data will be borne by the customer.
- ⁸ Please check with your local distributor for specific country configuration.
- ⁹ Supports DVD-RAM, DVD±RW, DVD±R, DVD-RW, DVD-R, CD-RW, CD-R, CD-ROM and DVD-ROM formats.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performance and weights as these are dependent on factors such as operating temperature, type of operating system and applications used, connected devices and accessories as well as hardware configurations of the notebook.



All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.

Dealer:

SINGAPORE:

Fujitsu PC Asia
Pacific Pte Ltd
Tel : (65) 6776 0688
Fax : (65) 6776 0788

MALAYSIA:

Fujitsu PC Asia
Pacific Pte Ltd
Tel : (60-3) 2093 3997
Fax : (60-3) 2093 4245

HONG KONG:

Fujitsu PC
Asia Pacific Ltd
Tel : (852) 3101 8133
Fax : (852) 3101 0633

THAILAND:

Fujitsu Systems
Business (Thailand) Ltd
PC Division
Tel : (66-2) 263 7888
Fax : (66-2) 263 7880
www.fujitsu-pcap.in.th

AUSTRALIA:

Fujitsu PC Australia
Toll Free: 1800 288 283
Tel : (61-2) 9004 7455
Fax : (61-2) 9004 7720
www.lifebook.com.au

CHINA:

Fujitsu PC China Division
Tel : (86-21) 3310 0808
Fax : (86-21) 3310 0606
cn.fujitsu.com

PHILIPPINES:

Fujitsu Philippines Inc.
Tel : (63-2) 812 4001
Fax : (63-2) 817 7576

TAIWAN:

Fujitsu Taiwan Ltd
Tel : (886-2) 2311 2255
Fax : (886-2) 2311 2277

VIETNAM:

Fujitsu Vietnam Ltd
Tel : (84-4) 831 3895-7
Fax : (84-4) 831 3898

INDONESIA:

PT Fujitsu Systems
(Indonesia)
Tel : (62-21) 344 2601
Fax : (62-21) 344 2593

Note: For countries not listed above, please contact our Singapore office.