LifeBook T4020

- Full featured Tablet PC at less than 2kg*
- Equipped with a wide array of hot-swappable modular bay options that include Dual Layer DVD Super Multi Writer⁹ and bay battery among others
- Superior security features for enhanced data and hardware protection
- * With weight saver option



	T4020 Recommended Configuration					
Platform	Intel [®] Centrino™ Mobile Technology					
	- Intel® Pentium® M Processor 750 (1.86GHz, 2MB L2 cache, 533MHz FSB)					
	- Intel® PRO/Wireless 2915ABG Network Connection					
	- Intel® 915GM Chipset					
OS Supported	Windows® XP Tablet PC Edition					
Display	12.1" XGA TFT, 1024 x 768 pixels					
Modular Bay Device	Dual Layer Super Multi Writer ⁹					
Memory	512MB DDR2 533					
Hard Disk	80GB					
Bluetooth™	Integrated v1.2					
Battery	Up to 5hrs ¹ (6-cell Li-lon 5200mAh)					
Weight	Approx. 1.95kg (w/Weight Saver Option)					
	Specifications					
Max. Memory Supported	2048MB DDR2 533					
Hard Disk Drive	SATA 150					
Graphics	Integrated Intel® Extreme Graphics 2 with DVMT ² delivers low-power, high-performance 2D/3D graphics, video,					
diapilios	and display capabilities at a maximum shared memory of 128MB					
High Definition (HD) Audio	SigmaTel STAC9753A AC97 codec with built-in dual Stereo Speakers and dual Microphones					
Communication	56K V.92 modem, IrDA 1.1 4Mbps ⁵ , 1000/100/10Mbps ⁴ Gigabit Ethernet and Intel [®] PRO/Wireless 2915ABG					
Communication	network connection 802.11a/b/g with Dual Antenna. Separate ON/OFF switch for wireless network connection					
H I d						
User Interface	Keyboard: 84-key, 19mm key pitch, 2.7mm key stroke					
0101.1	Touch Pad with Scroll Buttons					
Card Slot	PC Card Type I/II x 1, Smart Card ⁶ x 1, MS/SD x 1					
Connector Interface	USB 2.0 x 2, VGA (external display), RJ45 (LAN), RJ11 (modem), IEEE1394, Headphone-out, Microphone-in,					
	Power Adapter DC-in, Port Replicator Interface					
Quick Launch Panel	Tablet PC buttons and 2 Programmable Application Launch Buttons					
Security ⁷	BIOS Lock, Hard Disk Lock, LifeBook Lock, Anti-theft Lock Slot, Smart Card ⁶ , Fingerprint Sensor					
Dimensions	293mm (W) x 244mm (D) x 35mm <i>min</i> (H)					
	Bundled Accessories					
AC Adapter	Input AC 100 ~ 240V, Output DC 19V 60W					
Software	Fujitsu Update Navi ⁸ , Fujitsu Hardware Diagnostic Tool, Cyberlink Power DVD, Power Producer, Sonic RecordNow DX,					
	Sonic DLA, Adobe Acrobat Reader 6.0, Norman Virus Control & Norman Personal Firewall, Acronis True Image,					
	Microsoft® Experience Pack for Tablet PC					
	Optional Accessories					
Modular Bay Options	Replaceable with					
	- Bay Battery, 6-cell Li-lon 3800mAh, up to 8.5hrs battery life (Standard + Bay batteries)					
	- DVD±RW Drive					
	- DVD/CD-RW Combo Drive					
	- CD-ROM Drive					
	- Weight Saver					
Port Replicator	Connector Interface:					
	USB 2.0 x 4, VGA (external display), RJ45 (LAN), DVI-D, Power Adapter DC-in					
Charger	External USB 1.44MB FDD					
Mouse	USB Optical Scroll Mouse					
INIOUSE	OOD Option ocion iniouse					

- e above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

 Results obtained from Mobile 2002 performed on systems with maximum battery life settings. Actual battery life will vary based on screen brightness, sound volume settings, nunning applications, connected peripherals, power management settings, battery conditioning, and other customer preferences. Modular Bay devices or hard drive usage may also have a significant impact on battery life. Up to 9hrs battery life is based on Intel® Pentium® M Processor 725 configuration with standard battery and bay battery.

 Dynamic Video Memory Technology (DWAT) dynamically responds to application requirement and efficiently allocates the proper amount of memory (max. 64MB) for optimal graphics and system performance. The memory size available to the Operating System will be less than the size of installed memory module.

 Maximum 656/bbps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.

 This term does not represent actual data rate of 1000/100/10Mbps and simply indicates compliance with IFEE 802.3, IEEE 802.3 and IEEE 802.3 ab standards. Actual maximum data rate depends on network configurations as well as connected devices.

 This term does not represent actual data rate of 4Mbps and simply indicates compliance with IrDA standard specification 1.1. Actual maximum data rate depends on local configurations and connected devices.

 Filists unders not provide the application for Smart Card ostution.

 BIOS Lock needs a supervisor/user password to access BIOS setup, BIOS settings can be configured to prompt for password at every first bootup or all bootup sequences. Access to BIOS setting is needed to configuration and positions of a bock to physical password to bootup the LifeBook when it powers up or re
- compatibility between hardware and software, maintaining smooth operation anytime, anywhere.

 9 Supports DVD-RAM, DVD+RW, DVD+R, DVD-RW, DVD-R, CD-RW, CD-R, CD-ROM and DVD-ROM formats.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature; 5 to 35°C/41 to 95°C/14 to 95°C/14 to 105°C/14 to 95°C/14 to 105°C/14 to 95°C/14 to 95°C/1





Вluetooth™ BLUETOOTH is a trademark owned by its proprietor and used by Fujitsu under license. All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.

aler:			

SINGAPORE: Fujitsu PC Asia Pacific Pte Ltd Tel: (65) 6776 0688

Fax: (65) 6776 0788 MALAYSIA: Fujitsu PC Asia

Pacific Pte Ltd Tel: (60-3) 2093 3997 Fax: (60-3) 2093 4245

HONG KONG: Fujitsu PC Asia Pacific Ltd

Tel: (852) 3101 8133 Fax: (852) 3101 0633

THAILAND: Fujitsu Systems Business (Thailand) Ltd PC Division

Tel: (66-2) 263 7888 Fax: (66-2) 263 7880

AUSTRALIA & **NEW ZEALAND:** Fujitsu PC Australia

Toll Free: 1800 288 283 Tel: (61-2) 9004 7455 Fax: (61-2) 9004 7720 www.lifebook.com.au

CHINA: Fujitsu PC China Division

Tel: (86-21) 3310 0808 Fax: (86-21) 3310 0606 www.pc-cn.fuiitsu.com

PHILIPPINES:

Fuiitsu Philippines Inc. Tel : (63-2) 812 4001 Fax: (63-2) 817 7576

TAIWAN: Fujitsu Taiwan Ltd Tel: (886-2) 2311 2255

Fax: (886-2) 2311 2277 VIETNAM:

Fujitsu Vietnam Ltd Tel: (84-4) 831 3895~7 Fax: (84-4) 831 3898

INDONESIA: PT Fujitsu Systems (Indonesia)

Tel : (62-21) 344 2601 Fax: (62-21) 344 2593

listed above, please contact our Singapore office.