THE POSSIBILITIES ARE INFINITE



Windows®. Life without Walls™. Fujitsu recommends Windows.

LifeBook T5010

- 13.3-inch SuperFine WXGA Tablet PC with dual digitizer for greater convenience Bi-directional hinge for better screen sharing
- Superior security features for enhanced data and hardware protection
- Optimised VoIP communications using built-in digital dual microphones
- Health and Environment friendliness with RoHS compliance

	Specifications	
Platform	Intel® Core™2 Duo Processor T9550¹⁶ (2.66GHz, 6MB, 1066MHz)/ Intel® Core™2 Duo Processor T9400¹⁶ (2.66GHz, 6MB, 1066MHz)/	
	Intel® Core™2 Duo Processor P8700 ¹⁶ (2.53GHz, 3MB, 1066MHz)	
	- Intel® WiFi Link 5300AGN (3x3) network connection	
Operating System	Genuine Windows Visita® Business	
Display ¹⁸	(or Genuine Windows Vista® Home Premium) 13.3-inch Superfine WXGA TFT with Active Digitizer, 1280 x 800 pixels	13.3-inch WXGA TFT with Dual Digitizer 1280 x 800 pixels
Display	(300nits Brightness, 500:1 Contrast Ratio, Indoor/ Outdoor [Glare with AR])	(300nits Brightness, 500:1 Contrast Ratio, Anti-glare)
Modular Bay Device	Dual Layer Super Multi Writer ^{6,16} / Combo drive ¹⁶	(Journal Brightness, Joo. 1 Goritrast Hatto, Anti-glare)
Memory	2GB DDR3 1066MHz ¹⁶ / 1GB DDR3 1066MHz ¹⁶ Max. Memory Supported ¹¹ - 4GB DDR3 1066MHz, Dual Channel	
iviernory		
Hard Disk ¹⁶	waz memory dopported "4GB BB16 1600km12; Bdar Chamiler 320GB/250GB/160GB	
Bluetooth®	v2.1 + EDR (Enhanced Data Rate)	
Battery	Up to 3.90hrs¹ (6cell Li-Ion 5200mAh)	
Weight	Approx. 1.98kg (w/ weight saver option)	Annual Oddin (/inkt annual anti-a)
vveignt	1 1	Approx. 2.14kg (w/ weight saver option)
11 15:15:	Detailed Specifications	- ": OD OL 1 O 12
Hard Disk Drive	SATA-150 5400rpm, S.M.A.R.T support, Two Partitions - 50/50 ¹⁰ protected by Fujitsu 3D Shock Sensor ¹²	
Graphics	Integrated Intel® Graphics Media Accelerator 4500MHD with Intel® Clear Video Technology ¹³ and DVMT ⁸ 5.0 delivers low-power,	
	high-performance 2D/3D graphics with Shader Model 4.0, video and display capabilities at a max. shared memory ¹⁷ of 825MB/ 313MB.	
High Definition (HD) Audio	RealTek ALC269 HD audio codec with Dual Built-in Stereo Speakers HD Audio-in: External Mic-in, Dual Built-in Stereo Microphone	
	HD Audio-in: External mic-in, Dual Built-in Stereo Microphone HD Audio-out: Headphone-out	
Communication	Bluetooth® v2.1+EDR, 56K V.92², Global Modern MDC1.5, 1000/100/10Mbps³ Gigabit Ethernet PCI Express® x 1 and	
Communication	Bioletouti V.2.1+EDN, 300 V.92*, Global Modern MIDC1.3, 1000/1001/1001/0001/0001/Enterted Enterted Enterted Express * 1 and Intel® WiFi Link 5300AGN (3x3) network connection with three antenna. Separate ON/OFF switch for wireless network connection.	
	Built-in 1.3 Mega Pixel camera	
User Interface	Spill-resistant Keyboard ^a : 84-key, 19mm key pitch, 3.0mm key stroke	
	Intelligent Touch Pad with configurable vertical and horizontal scroll functions	
	Fingerprint Sensor with vertical scroll functions	
Card Slots	ExpressCard TM /34/54	
	Secured Digital/ Memory Stick®	
Connector Interface	USB 2.0 x 3, IEEE 1394 (firewire), VGA (external display), RJ45 (LAN), RJ11 (modem), HDA-in, HDA-out, Power Adapter DC-in,	
	Port Replicator Interface	
Quick Launch Panel	Tablet PC buttons and 2 Programmable Application Launch Buttons	
Security ⁵	BIOS Lock, 2-password Hard Disk Lock, LifeBook Lock, Anti-theft Lock Slot, Dedicated Smartcard* slot, Fingerprint Sensor,	
	Trusted Platform Module v1.2 (Optional)	
Dimensions	319mm (W) x 244mm (D) x 36.5/38.5mm (H)	319mm (W) x 244mm (D) x 37.0/39.0mm (H)
	Bundled Accessories	
AC Adapter	Input AC 100~240V, Output DC 19V 80W	
Bundled Software	Softex Omnipass, CyberLink PowerDVD™, CyberLink PowerDirector™, Roxio	
	Reader, Fujitsu UpdateNavi ¹⁴ , Fujitsu 3D Shock Sensor Utility, Fujitsu Power Saving Utility, Fujitsu Hardware Diagnostic Tool, Fujitsu Display Manager, Sun Microsystems Java Runtime, Microsoft Office Professional 2007 60-day Convertible Trial ¹⁵	
		•
Other Software	1 year Full Licensed Norman Virus Control with Sandbox Technology and Norman Personal Firewall, Acronis True Image	
	Optional Accessories	
Port Replicator	Connector Interface:	
	USB 2.0 x 4, Power Adapter DC-in, Line Out, DVI-D, VGA (external display), RJ45 (LAN), Power Adapter DC-in, HDMI port	
Modular Bay Options	Replaceable with	
	- Bay Battery, 6cell Li-ion 3800mAh, up to 7hrs¹ battery life (Standard + Bay Batteries) - Dual Laver DVD Super Multi writer ^{6,16}	
	- Dual Layer DVD Super multi writer DVD/CD-RW Combo drive ¹⁶	
	- Beint Saver	
Floppy Disk Drive	External USB 1.44MB FDD	
Mouse	USB Optical Black Mouse (Retractable)	
	1	













- Deciamers:

 1 Results obtained from BAPCo* MobileMark* 2007/Productivity Workbadl performed on systems with maximum battery life settings under laboratory testing environment. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other custome preferences in the adlie Statuburo. Bull-In buy device or hard drive usage may also have a significant impact to battery life. Note: Up to 3 Silves testing life and This battery life and This testing life and This battery life and This testing life and This battery lif



Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Architect interpenature. 5' to 38°C 4' to 38°C (Peperating), -15' to 80°C / 5 to 140°F (non-operating). Please note that CB = billion bytes. TGB is equivalent to 1,073-71,284 bytes.