

Using Solid State Disks in VDI Environments

This whitepaper describes a proof-of-concept in which solid state disks were used in a virtual desktop infrastructure for Windows 7 desktops based on VMware View 4.5. The results of the tests and investigations enable our consultants to define an optimum architecture and do the right sizing. Existing problems such as boot storms can easily be solved. Furthermore, financial aspects are considered and a future outlook of SSD technology is given.



SSD (Solid State Disks)

Solid state disks are becoming increasingly popular. It all started several years ago with the so-called memory sticks. These were available in versions from 4 to 64 MB; they were small and could be easily connected via a USB interface. The information was written to a flash memory. Today, memory sticks have completely replaced the floppy disk drives. There is no better alternative to transport data quickly with regard to price, size, easy usage, reliability, robustness and capacity. Today's USB sticks are available in sizes between 2 and 64 GB; the price is approx. €2 per GB and decreasing.

A further use case for solid state disks was storing images on SMART or flash cards in digital cameras. Capacities ranged between 16 and 256 MB. If 1 GB memory and more was required, then very small conventional disks were used, the so-called micro drives.

This triggered fast technological developments that have resulted in ever-increasing memory capacities at reduced prices, driven mainly by the usage in mobile phone and digital camera applications.

As soon as memory chip capacities had reached a certain size, constructing fast memory disks became interesting. There was a development earlier where part of the computer's memory or a separate card was configured as a so-called RAM disk. However, use cases of such a "high-speed memory" were rather limited, because of low capacities but high costs. Today, it is still usual to integrate solid state disks as a cache on conventional disk drives in order to increase throughput.

Today, solid state disks range from 100 to 400 GB with prices between €200 and €1,400 in the consumer segment and €1,000 to €4,000 in the business segment. It is technically possible to have sizes of more than 1 TB in a 2.5" form factor.

Solid State Disks have the following features:

- They are robust and can withstand vibrations.
- They have no moving parts and have therefore a longer life span with lower failure rates (and tremendously improved MTBF)
- Compared to standard disks, their I/O throughput is 10 to 30 times higher
- They use less power and thus generate less heat
- They are less sensitive to environmental influences, such as magnetic fields, pressure fluctuations, vibrations and extreme temperatures.

The following disadvantages exist today:

- At a certain extent, the limited number of write cycles
- Lower capacities (in comparison to conventional disks)
- High price

There is a difference between SSDs for the consumer segment and those for the business segment. The disks for the consumer segment are relatively inexpensive today, but have a notably lower number of maximum write cycles. The disks for the business segment have a notably higher number of write cycles which is also reflected in the price. The type of memory chips used also plays a role, especially with regard to the quality-related features. SSDs are available as flash memories and SDRAM memories. There are further differences (e.g. NOR/NAND-based). Generally, special chips are selected in the business segment, which justifies the higher price in comparison to the consumer segment.

Summary of typical use cases:

- Flash-based memories in MP3 players and cameras
- Flash memories are also used as USB sticks and as BIOS memories in PCs
- SDRAM-based SSDs in storage systems, notebooks and servers

Due to the parameters mentioned above, the price of SSDs today makes them interesting in data centers with:

- Clear and manageable data quantities
- Densely populated data centers with cooling and power requirement problems
- Short load and start phases (system start)
- Availability (MTBF)
- Special environmental requirements

Note:

In this document we speak of virtual desktops, workloads and VMs, which is basically one and the same thing.

Can SSD be helpful in Virtual Desktop Infrastructures?

In order to figure out, if and which situations Solid State Disks are a recommendable alternative in virtual desktop infrastructures, Fujitsu decided to perform a number of tests. In this context, not only technical viability, advantages and impacts of SSD technology should be considered, but also financial aspects, such as costs per virtual machine, potential savings and economic benefits.

Test infrastructure

For the purpose of the tests, a test infrastructure based on VMware View 4.5 with View Composer was built up.

Using "linked clone" technology, VMware View Composer reduces storage requirements by up to 70% and simultaneously optimizes desktop image administration by enabling fast creation and updates of desktop images which use a virtual hard disk together with a master image. View Composer is used by IT organizations to manage several hundred or thousand desktops with one single image. New virtual machines simply link to the virtual hard disk of the master VM (Replica VM). Any changes at runtime are saved in a delta file which can be automatically deleted when a user logs off.

The VSI (Virtual Session Indexer) benchmark tool from Login Consultants was used for the measurement, once using conventional hard disks and once using SSD. A more detailed explanation is provided later in this document.

To be clear: all results are related to the chosen test infrastructure. And of course there will always be discussions, whether to use SSD internally in the servers or in a central storage system. This question will strongly depend on the general architecture and should be considered separately. However, the results from this test can be used in the decision process.

The test infrastructure looks as follows:



Two Fujitsu PRIMERGY RX300 S6 industry standard servers are connected with each other via a GB Ethernet switch. For administration purposes, a workstation device is additionally integrated in the network. One of the Fujitsu PRIMERGY RX300 servers is used as an infrastructure server for services, such as domain controller, DHCP and DNS server, and the other Fujitsu PRIMERGY RX300 (desktop server) is used for hosting the virtual desktop machines.

Hardware configuration of the infrastructure server

Fujitsu PRIMERGY RX300 S6

- 12 cores 2.66 GHz, Hyperthreading Enabled
- 72 GB RAM
- 2 GB Ethernet network adapter (onboard) •
- 4x 300 GB SAS HD RAID-6 as logical drives for the hypervisor and all required virtual servers

Software on the infrastructure server

Hypervisor ESX-4.1.0-Update01-348481.iso

- DC Windows Server 2008 R2 AD. DNS. DHCP
- Windows Server 2008 R2 vCenter VMware-VIMSetup-all-4.1,0-345042,iso VMware-viewcomposer-2.6.0-349155.exe Windows Server 2008 R2 SQL MS SQL Server 2008 + SP1 Windows Server 2008 R2 View VMware-viewconnectionserver-x86 64-4.6.0-366101.exe

VSI Login 3.0 Express (Medium workload, RDP protocol)

Launcher1	Windows 7 Enterprise Edition VSI Login 3.0
Launcher2	Windows 7 Enterprise Edition VSI Login 3.0
Launcher3	Windows 7 Enterprise Edition VSI Login 3.0

All virtual machines at a glance:



VMware View Manager
Domain Controller
SQL Server Data store
VMware vCenter
Windows 7 Clients as Launcher

Installation process

- DC with Active Directory, DNS, DHCP, VSI AD configuration
- SQL Server

- vCenter with configuration DB on SQL Server •
- ConnectionServer with configuration to vCenter and SQL Server
- VMware View Composer on vCenter Server with configuration to SQL Server
- 3 Windows 7 Clients (Launch1-3) with VMware tools and VSI launch configuration.
- VSI Analyser additionally on Launch 1

Hardware configuration of the desktop server

Fujitsu PRIMERGY RX300 S6

- 12 Cores 2.66 GHz, Hyperthreading Enabled
- 144 GB RAM
- 2 GB Ethernet network adapter (onboard)
- 2x 300 GB SAS HD RAID-1 as logical drives for the hypervisor and the virtual desktop machine based on the Windows 7 template.
- 2x 300 GB SAS HD RAID-0 as logical drives
- 2x 200 GB SSD RAID-0 as logical drives

Software on the desktop server

нурегизог	ESX-4.1.0-0p0ale01-348481.ls0
W7Template	Windows 7 Enterprise Edition (32 Bit) En VMware tools Optimization according to the document: VMware-View-Optimization GuideWindows7-EN.pdf
View Agent:	VMware-viewagent-4.6.0-366101.exe Office 2007 Enterprise Edition En
Installation W7Template	Windows 7 Enterprise VMware tools Office 2007 Enterprise En VMware Optimizations for Windows 7 VMware View Agent 4.60 VSI target configuration Ipconfig /Release 1 vCPU 1024 MB RAM 30 GB HD DHCP

Allgemein	
Gastbetriebssystem:	Microsoft Windows 7 (32-Bit)
VM-Version:	7
CPU:	1 vCPU
Arbeitsspeicher:	1024 MB
Arbeitsspeicher-Overhead:	105,91 MB
VMware Tools:	ок
IP-Adressen:	192.168.44.215
DNS-Name:	WIN7-115.test.local
EVC-Modus:	Nicht verfügbar
Zustand:	Eingeschaltet
Host:	192.168.44.10
Aktive Aufgaben:	

Test software

The VSI (Virtual Session Indexer) Analyser from Login Consultants was used as a benchmark tool. It is independent of platform and hypervisor; thus our test could be replicated on other platforms at any time. The tool is easy to install and can be downloaded free of charge from http://www.loginconsultants.com/.

The VSI Analyzer supports:

- Windows-based Presentation Virtualization platforms (Server Based Computing)
- Windows-based Virtual Desktop Infrastructures
- Windows-based Application Virtualization platforms (Application Streaming)
- Windows 32 Bit and Windows x64
- Windows XP, 2003, Vista, Win7 and 2008 & 2008R2
- Office 2003, 2007 (Preferred) and 2010 Technical Preview
- Citrix, VMware, ProVision IT and other presentation or desktop virtualization vendors through a custom command line to launch sessions.

Various applications are used and measured as workload, such as Notepad, zip, and so on. A description (Admin Manual) is also available on the homepage of Login Consultants.

Subsequently we show a short excerpt of VSI operation and an interpretation of the results:

VSI is specifically not a steady state test. VSI, a solution for benchmarking TS (Terminal Services) or VDI (Virtual Desktop Infrastructure) workloads, loads the system with simulated user workloads. VSI focuses on how much users can run on the system before it saturates. VSI is similar to investigating the maximum amount of seats on the bus, airplane or lifeboat by trial and error through system saturation. This is the "Virtual Session Index (VSI)". With VDI and TS workloads this is very valid and useful information. This index simplifies comparisons and makes it possible to understand the true impact of configuration changes at hypervisor host or guest level.

Use the analysis tool to determine the VSImax, which is the maximum capacity of the tested system expressed in the amount of VSI sessions. With VSImax, this means the following:

- VSImax corrected value = VSImax without hanging VMs
- VSImax uncorrected value = VSImax with hanging VMs

Ideally, if both values are identical, then nothing is hanging. With regards to sizing, the corrected value should always be used or calculated.

There are two **ways to calculate VSImax**, the dynamic way and the classic way.

Dynamic – Is the new, more precise calculation method as of VSI 3.x. The average response time of the first 15 VMs (under the tab "VSIMax Data" in the column "VSIIndex_avg") is defined as the baseline, e.g. 1500ms. An additional fixed value is added to the baseline (Analyzer Default + 3000ms). In this example, the VSImax would activate at 4500ms; this value should be in a steep climbing curve for the response time pattern. Otherwise the impact (3000ms) would be more sensible as selection (however, it usually works).

All default parameters for the analyser calculations can be seen in the analyser tool under "File" \rightarrow "Preferences" in the value "Dynamic VSIMax" and "VSIMax Calculation".

Classic – Is the old calculation method from VSI 2.x, which should no longer be used.

Old logs can also be analyzed with the new analyzer and determined according to the dynamic method

A typical result (taken from Login Consultants) looks as follows:

Vertical axis: Response time in milliseconds Horizontal axis: Total active sessions

Minimum response	Best response time of an individual measurement within a single session
Maximum response	Worst response time of an individual measurement within a single session
Average response	Average response time within all sessions
VSI Index Average	Maximum capacity of the tested system expressed in the amount of VSI sessions.



Virtual machines on SSD data store

Test preparation Create 120 virtual machines based on W7Template and View Composer for deployment on SSD data store (floating users)

Edit Pool1		0	Edit Pool1					?
General Pool Settings Provisionin	g Settings VCenter Settings Guest Custon	mization	General Pool S	ettings Provision	ning Settings VC	Center Settings	Guest Customization	1
Pool Attributes: Automated, linked clone, flo	pating		Basic					
Pool Naming			 Enable provisio 	ning				
Pool ID: Pool1			Stop provisionir	ng on error				
Display name:			Virtual Machine Na	mina				
View Folder: /	•		Naming Type: U	Ise a naming pattern	1			
Description:	1.1		Naming Pattern:	Win7-{n:fixed=3}				
			Pool Sizing					
			Max number of des	sktons: 126				
View Composer Disks			Number of spare (nowered on) desktor	ns: 125			
Disposable disk size: 1536 MB (r	minimum 512 MB)		Rrovision desk	tons on demand	120			
			Min number of		_			
				aditana un frant				
				esktops up-front				
L		OK Cancel					ОК	Cancel
			Edit Pool1					0
General Pool Settings Provisionin	ng Settings VCenter Settings Guest Custor	mization	General Pool S	ettings Provision	ning Settings VC	Center Settings	Guest Customization	1
General			Changing the vCente virtual machines.	r settings affects ne	wly created virtual r	machines only. Th	e new settings do not	affect existing
State:	Enabled V		Virtual Machine Set	ttings				
Connection Server restrictions:	None Browse		Default image:	W7Template - Fina	alV1		Browse	
Remote Settings			VM folder:	/Neues Datencente	er/vm/Pool1			
Remote Desktop Power Policy:	Ensure desktops are always powered on	3						
Automatically logoff after disconnect:	Never 🔻		Resource Settings					
Allow users to reset their desktops:	No 🗸		Host or cluster:	/Neues Datencent	ter/host/192.168.44	.10	Browse	
Allow multiple sessions per user:	No		Resource pool:	/Neues Datencent	ter/host/192.168.44	.10/Resources	Browse	
Delete or refresh desktop on logoff:	Never 🤉		Datastores:	Name	Capacity (GB)	Free (GB)	Browse	
Remote Display Protocol				SSD Datastore	371.5	205.87		
Default display protocol:	Microsoft RDP							
Allow users to choose protocol:	Yes 🛛 🔻							
Max number of monitors:	1 🔻 🔞							
Max resolution of any one monitor:	1920×1200 🔻 🔇							
Adobe Flash Settings for Remote Sess	ions							
Adobe Flash quality:	Do not control 🔻 🔇							
Adobe Flash throttling:	Disabled 🛛							
1								
1								
		OK Cancel					OK	Cancel

dit Pool1								6
General	Pool Sett	ings P	rovisioning Settings	vCenter Set	tings	Guest Custo	omization	
Domain:			test.local(vInstall)	•				
AD contair	ner:		OU=Computers,OU=L	.ogin_VSI	Browse.			
💿 Use Qu	lickPrep							
Power-	off script:							
Post-sy	nchronizatio	on script:						
🔵 Use a d	customizatio	n specifica	tion (Sysprep)					
Sho	w incompati	ble custom	ization specifications					2
P	Name	Guest O	S	D	escriptio	n		
							ок	Cancel

Connection Settings		
Servemame:	Win7-	
Usemame:	VSI1	
Password:	•••••	••
	•••••	••
Domain:	test.local	
Interval Settings		
Connect:	Machine	•
Start number:	1 🚔	
Sessions:	120 🚔	Enabled capacity: 135
Formatting length:	3 🌲	Example: 001
Interval:	10 🊔	
Save test settings		

VSI Login Analyser

30000

Analysis of the test result using VSI Login Analyser:

Evaluation type: Dynamic





Test results

Everything (replica and linked clones) on SSD data store. Time required for completion: ~35 minutes.

Configuration of the VSI Login management console

All launchers rebooted. All virtual machines rebooted

 Launcher name
 Enabled
 Capacity

 1
 Launch1
 Enabled
 45

 2
 Launch2
 Enabled
 45

 3
 Launch3
 Enabled
 45

Test Configuration



Evaluation type: Classic



Minimum Response Average Response Maximum Response VSI Index Average

After having analyzed the results, delete the virtual machines on the SSD data store.

Virtual machines on SAS data store

Test preparation

Create 120 virtual machines based on W7Template and View Composer for deployment on SAS data store (floating users)





Everything (replica disk and linked clones) on SAS data store.

Time required for completion: ~3.5 to 4 hours.

Configuration of the VSI Login Management console

All launchers rebooted. All virtual machines rebooted.

Connection Settings	3
Servemame:	Win7-
Usemame:	VSI1
Password:	•••••
	•••••
Domain:	test.local
Interval Settings	
Connect:	Machine
Start number:	1
Sessions:	120 🚔 Enabled capacity: 135
Formatting length:	3 🛓 Example: 001
Interval:	10 🚔
Save test settings	

New test with less virtual desktops on SAS data store

The test with 120 VM with linked clones on SAS data store always aborted with an error message (too many I/O). The number of virtual machines thus had to be reduced to 50 in order to ensure a successful operation of the VSI Login Test.

Two results can be determined in the meantime. With SSD, the deployment of 120 virtual desktops is six times faster than with conventional disks in the same environment. It can also be said that the limit of possible workloads with conventional disks could occur earlier due to I/O. In order to obtain comparable figures, the test was continued with a reduced number of workloads.

Reconfiguration of the VSI Login Test

All launchers rebooted. All virtual machines rebooted.

Laund	hers		
	Launcher name	Enabled	Capacity
1.			
2.	Launch2	Enabled	30
3.	Launch3	Enabled	30

Test Configurat	tion	
Launcher Settings		
Workload:	Medium	
Workload mashup:		
Launcher Settings		
Auto start launcher:	\checkmark	
Launch type:	Sequential launching 👻	
Reset locked sessions		
Auto logoff:		
Auto logoff timeout:	60 🚖	
Create profiles:		
Connection type:	RDP •	
Custom Commandline		
Specify Custom Com	mandline:	
Specify CSV File:		
		Browse

Enabled

Enabled

Enab

Capacity

45

lest Configura	
Launcher Settings	1
Workload:	Medium 👻
Workload mashup:	
Launcher Settings	1
Auto start launcher:	
Launch type:	Sequential launching -
Reset locked session	s:
Auto logoff:	
Auto logoff timeout:	60
Create profiles:	
Connection type:	RDP 👻
- Custom Commandlin	e
Specify Custom Co	mmandine:
Specify CSV File:	
	Bro

Test result

Launchers

3.

Launcher name

Launch2

Launch3

White Paper Using SSD in VDI Environments

Connection Setting	s
Servemame:	Win7-
Usemame:	VSI1
Password:	•••••
	•••••
Domain:	test local
Interval Settings	
Connect:	Machine 👻
Start number:	1
Sessions:	80 🚔 Enabled capacity: 90
Formatting length:	3 Example: 001
Interval:	10
0	

VSI Login Analyzer

Analysis of the test result using VSI Login Analyser:

Evaluation type: Dynamic



Evaluation type: Classic



After having analyzed the results, delete the virtual machines on the SAS data store.

Results of the test

With SSD, 75 workloads are possible on the same system. If conventional disks are used, it will be only 31 workloads. The bottleneck is neither the CPU nor memory, but the I/O.

Replicas on SSD, linked clones on SAS

Finally, another test was performed as a comparison whereby each virtual machine is configured with 2 GB RAM. While preventing memory over-commitment, the number of possible virtual machines was set to 70 VMs in the hypervisor, having 144 GB RAM in the server.

Create virtual machines





Desktop

Allgemein		
Gastbetriebssystem:	Microsoft Windows 7 (32-Bit)	
VM-Version:	7	
CPU:	1 vCPU	
Arbeitsspeicher:	2048 MB	
Arbeitsspeicher-Overhead:	118,00 MB	
VMware Tools:	ок	
IP-Adressen:	192.168.44.138	
DNS-Name:	WIN7-039.test.local	
EVC-Modus:	Nicht verfügbar	
Zustand:	Eingeschaltet	
Host:	192.168.44.10	
Aktive Aufgaben:		

Create 70 virtual machines based on W7Template and View Composer for deployment, whereby replica is configured on SSD data store and everything else on SAS data store (floating users).

White Paper Using SSD in VDI Environments

Edit Pool1			ିତ	Edit Pool1						0
				LUIC POOL			1			
General Pool Settings Provisioning	Settings VCenter Settings	Guest Customization		General Pool S	ettings Prov	isioning Settin	igs vCente	r Settings	Guest Customiza	tion
Pool Attributes: Automated, linked clone, floa	ating			Basic						
Pool Naming				Enable provisio	ning					
Pool ID: Pool1				Stop provisioning	ng on error					
Display name:				Virtual Machine Na	ming					
View Folder: /				Naming Type: U	se a naming pat	tern				
Description:				Naming Pattern:	Win7-{n:fixed=	=3}				
				Pool Sizing						
	-			Max number of der	ktone: 71	_				
View Composer Disks	Θ			Number of second						
Disposable disk size: 1536 MB (m	ninimum 512 MB)			Number of spare (powered on) des	sktops: 70				
				Provision desk	tops on demand					
				Min number of	desktops: 70	D				
				 Provision all de 	esktops up-front					
		ок	ancel						OK	Cancel
、									OK	Cancer
Edit Pool1			ଡ	Edit Pool1						0
		Court Contractor			1		1			
General Pool Settings Provisionin	g Settings VCenter Settings	Guest Customization		General Pool S	ettings Prov	isioning Settin	igs vCente	r Settings	Suest Customizat	ion
General				Changing the vCente virtual machines.	r settings affects	s newly create	d virtual mach	nes only. The n	ew settings do n	ot affect existing
State:	Enabled V			Virtual Machine Se	Itinos					
Connection Server restrictions:	None Browse			Default imperi		-				
Remote Settings				Derault image:	W7Template -	FinalV2_2GB	6 200		Browse	
Remote Desktop Power Policy:	Ensure desktops are always power	ered on 🛛 💌 🕜		VM folder:	/Neues Datend	center/vm/Poo	11			
Automatically logoff after disconnect:	Never			Resource Settings						
Allow users to reset their desktops:	No 🗸 🔻			Host or cluster:	/Neues Daten	center/host/1	92 168 44 10		Browse	
Allow multiple sessions per user:	No 🛛 🔻			Resource mode	(Maura Poter	and the second			Baswas	
Delete or refresh desktop on logoff:	Never 🔹 🧿			Detector	/weues Daten	Lenver/nost/1	FE.100.44.10/F	eeuruds	browse	
Remote Display Protocol				Datastores:	Name SSD Datacto	Capacity (Free (GB)	Use For	Browse	
Default display protocol:	Microsoft RDP				SAS HD Datasto	557.5	398,95	Linked cloper		
Allow users to choose protocol:	Yes							annead storige		
Max number of monitors:										
Max resolution of any one monitor										
	1920X1200									
Adobe Flash Settings for Remote Sessi	ons									
Adobe Flash quality:	Do not control									
Adobe Flash throttling:	Disabled 🔻 🔇									
		ОК	Cancel						OF	Cancel
									UK	

	tings Pr	ovisioning Settings VCenter Settings Guest Customizatio	n
Domain:	[test.local(vInstall)	
AD container:	[OU=Computers,OU=Login_VSI Browse	
 Use QuickPrep 			
Power-off script:			
Post-synchronizati	ion script:		
Use a customizatio	on specificat	ion (Sysprep)	
Show incompat	tible custom	ization specifications	æ
Show incompat	tible custom Guest OS	Zation specifications Description	2
Name	Guest OS	ization specifications 5 Description	æ
Show incompat	Guest OS	ization specifications 5 Description	\$
Show incompat	Guest O	ization specifications Description	e
Show incompat	Guest OS	ization specifications Description	2
Name	Guest O	ization specifications Description	2
Name	Guest O	zation specifications	2

Test result:

Replica on SSD, everything else on SAS data store. Time required for completion: ~40 minutes.

Reconfiguration of the VSI Login Test

All launchers rebooted. All virtual machines rebooted.



Connection Setting	s
Servemame:	Win7-
Usemame:	VSI1
Password:	•••••
	•••••
Domain:	test.local
Interval Settings	
Connect:	Machine
Start number:	1
Sessions:	80 🚖 Enabled capacity: 90
Formatting length:	3 🚖 Example: 001
Interval:	10 🜩

VSI Login Analyser

Analysis of the test result using VSI Login Analyser:

Evaluation type: Dynamic



Evaluation type: Classic



After having analyzed the results, delete the virtual machines on the SSD data store.

The non-attainment of VSIMax indicates that the results remain within the same range as with the test "replica and linked clones" which scaled up to 76 VMs as VSIMax.

Technical conclusion

The use of SSD drives for local caching with pooled desktops can - on account of the higher throughput - significantly improve the density of VMs on the hypervisor as well as the user experience of individual VMs.

It was also noticed (but not measured) that SSD drives handle the boot storm significantly better than the SAS disks, again on account of the higher I/O.

Technical limitations

During the proof-of-concept with SSD, 144 GB of main memory size turned out to be the limit. More than 75 workloads would have been theoretically possible with a larger memory size; then however we would have had to use the much more expensive 16 GB modules, which is not advisable from a price / performance perspective. Also by assuming less RAM per VM higher densities could have been achieved.

We decided deliberately against memory over-subscription / over-commitment as this means higher swap requirements on the SSDs.

In the test with conventional disks, I/O performance proved to be the limit. The maximum number of workloads was 31; additional memory did not improve the situation.

I/O considerations

The determined workloads and required disk space was checked for plausibility when using linked clones using a sizing guideline from VMware. The following tables were available:

Disk type	Size	Possible IOPS (mixed read / write)
15K RPM FC	146GB or 300GB	150
10K RPM FC	146GB or 300GB	125
SSD	160GB or 320GB	> 5,000

Attributes	Required IOPS
VMs per data store	250
IOPS per VM (normal user)	10
IOPS per VM (heavy user)	15
Total IOPS	175 x 10 + 75 x 15
(70% normal / 30% heavy users,	= 1750 + 1125
or 175 normal / 75 heavy users)	= 2875

With 75 normal users, 750 IOPS are needed. An SSD providing more than 5000 IOPS can easily meet this requirement. Two conventional RAID-1 disks with 15K rpm stop at 150 IOPS. More IOPS can only be provided, if you use RAID systems with a higher number of spindles.

Price comparison

As the basis for a cost comparison, the EURO list prices of the June 2011 price list were used. As the software was identical in both cases, it was completely ignored.

Configuration sheet with conventional disks

Total price				9.455 €
S26361-F2735-E101	RMK-F1_1-2U Server	1	55,00€	55€
S26361-F2735-E7	Cable management for 19" PC rack	1	30,00€	30€
S26361-F3554-E512	RAID Ctrl SAS 6G 5/6 512MB (D2616)	1	385,00€	385€
S26361-F4482-E130	HD SAS 6G 300GB 10K HOT PL 2.5" EP	2	210,00€	420€
S26361-F3604-E515	8 GB DDR3 1333 MHz PC3-10600 rg d	18	255,00€	4.590€
S26361-F3619-E266	Intel Xeon X5650 6C/12T 2.66 GHz 12 MB	2	1.250,00€	2.500€
S26361-K1344-V301	PY RX300S6 12x2.5 gold SV	1	1.475,00€	1.475€

Configuration sheet with SSD disks

-		_		
S26361-K1344-V301	PY RX300S6 12x2.5 gold SV	1	1.475,00€	1.475€
S26361-F3619-E266	Intel Xeon X5650 6C/12T 2.66 GHz 12 MB	2	1.250,00€	2.500€
S26361-F3604-E515	8 GB DDR3 1333 MHz PC3-10600 rg d	18	255,00€	4.590€
S26361-F3298-E64	SSD SATA 3G 64GB SLC HOT PLUG 2.5" EP	4	1.130,00€	4.520€
S26361-F3554-E512	RAID Ctrl SAS 6G 5/6 512MB (D2616)	1	385,00€	385€
S26361-F2735-E7	Cable management for 19" PC rack	1	30,00€	30€
S26361-F2735-E101	RMK-F1_1-2U Server	1	55,00€	55€
Total price				13.555 €

Important note:

The test was performed with the new SSD which should be included in the System Architect as of October 2011. However, in order to make a price statement already at the time of the proof-of-concept, the prices of the two 100 GB SSD disks are shown with those of the available 64 GB disks. To be fair, the price of the conventional 300 GB disk was also adapted, because the disk utilization was identical; although no 146 GB disk as the smallest size was available.

To determine the hardware cost per workload, the server costs were divided by the number of workloads.

- Solid State Disk €181
- Traditional Disk €305

These results show a clear price advantage of using SSD, irrespective of the technical advantages (e.g. six times lower deployment outlay), which could also be regarded as a cost advantage. Then the advantages of SSDs become even more obvious.

The results determined here, are certainly a valuable basis for the design of a virtual desktop infrastructure. However, they should not be generally transferred to any other situation without further ado. It is always recommendable to check the real-life situation in detail including all aspects influencing operational costs.

Price outlook

According to analysts' opinions and our own estimations, the price of SSDs will decrease by between 15 and 20% within the next year so that SSDs are now becoming an ever-increasing implementation reality.

SSD capacities

In our scenario, we had gained the most from the SSD configuration, even including a reserve. More users would mean more or larger SSD disks. In this situation, when using double the disk capacity, the hardware costs would equal \in 241 per VM, which is still more efficient than conventional disks.

This important and sensitive topic regarding SSD prices means, we have also considered whether we could have used the cheaper SATA SSD disks instead of SAS SSD disks. We have looked at the I/O log files and determined that there had been a very high number of bursts which had been cleanly accepted by the SAS SSD. A SATA SSD would not have done so and would thus have generated short-term bottlenecks. The maximum number of write cycles to a memory cell is evident when viewing the datasheets and comparing SATA and SAS SSD. This is notably lower with SATA SSD which also explains the price. We thus recommend the more expensive SAS SSDs and advice against the cheaper SATA SSDs.

Storage sizing for local SSD data stores

Our collection of data impressively shows that local SSD data stores are a high performance and attractively priced alternative to shared storage or local data stores with classic hard disks.

Linked clones are the choice in this selection. All the changes concerning the replica disk are written during a user session to a delta file which constantly increases in size. However, as the delta file is deleted when logging off, only small file sizes have to be calculated. The next user of the virtual desktop still receives a "fresh" system.

For the storage sizing we consider server-based profiles, but no user data. The size of the Windows 7 template is assumed to be 30 GB, with a 2 GB RAM per VM.

A fundamental decision is required concerning the storage location of the swap file of the virtual machine. This is stored per default in the VM folder. These results, with 2 GB RAM without reservation, in a swap file size of 2 GB per VM.

If another data store with normal hard disks is available in the server, this swap file can be relocated, which considerably reduces memory requirements for SSD data stores.

If shared storage is also available in the environment, the swap files can be relocated there. Shared storage simplifies the storage of templates which all ESX servers can then centrally access.

SSD storage capacity (pure SSD data store:)

Storage capacity = (number of VMs * (delta size + swap + log) + replica^{*} + template + overhead)

SSD with relocated swap files

Storage capacity = (number of VMs * (delta size + log) + replica^{*} + template + overhead)

SSD storage capacity with relocated swap files and templates

Storage capacity = (number of VMs * (delta size + log) + replica* + overhead)

* The replica VM is created per data store as a clone of the "golden" template

Summary of the results

	Hard disks	SSD
Deployment of 120 VMs	210 min	35 min
Maximum number of VMs	31	75
Hardware costs per VM	€305	€181

With a scenario with identical workloads where a master is replicated by linking via View Composer, SSDs make sense if the architecture has a block structure with local disks. With an external storage system, the I/O performance can be much better, but network connection capacities must be taken into account. This paper does not attempt to make general architecture recommendations, but simply to provide suggestions. Numerous options are available regarding the location choice for data, images and swap area, and more.

Contact FUJITSU LIMITED Website: www.ts.fujitsu.com 2011-08-30 WW-EN © Copyright 2011 Fujitsu limited. Fujitsu, the Fujitsu logo are trademarks or registered trademarks of Fujitsu Limited in Japan and other countries. Other company, product and service names may be trademarks or registered trademarks of their respective owners. Technical data subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designation s may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.