

THE POSSIBILITIES ARE INFINITE

FUJITSU

A3 COLOR
DUPLEX
DOCUMENT
SCANNER

fi-5900C

Image Scanner

A3 Scanner



A3	ADF	DUPLEX	COLOR	Ultra sonic sensor	Ultra wide SCSI	USB 2.0	Mono. 200 A4 ipm	Color 200 A4 ipm	600 dpi
-----------	------------	---------------	--------------	---------------------------	------------------------	----------------	-------------------------	-------------------------	----------------

WinVista*	Win XP	Win Server 2003*	Win 2000 Professional	WinNT4.0 (SCSI Only)	Win Me (SCSI/USB Only)	Win98SE (SCSI/USB Only)	Win 98 (SCSI/USB Only)	Win 95 (SCSI Only)
-----------	--------	------------------	-----------------------	----------------------	------------------------	-------------------------	------------------------	--------------------

* Windows Vista™ and Windows Server™ 2003 compatible TWAIN drivers are only available as web downloads.



Adobe® Bundled!
Acrobat®
Standard

● Convert any document to a PDF file

for Microsoft® Windows® Operating Systems




● FUJITSU TWAIN Driver



QUALITY SCANNER

As an ENERGYSTAR® partner, PFU Limited, a Fujitsu company, has determined that this product meets the ENERGYSTAR® guidelines for energy efficient. ENERGYSTAR® is a registered trademark in the United States.



New and improved features

■ Able to scan an incredible 100 double-sided pages per minute! (300dpi)

Use of high speed CCD image sensors along with the latest in image processing circuitry enables the fi-5900C to scan color A4 documents at a speedy 100ppm/200ipm (300dpi). Incorporating all of this technology into the fi-5900C enables it to digitize an incredible one hundred thousand pages a day.

■ Efficient pre and post scanning processing!

The fi-5900C's ability to scan mixed batch documents containing paper of varying sizes, weights and colors virtually eliminates pre-scanning preparation needs. Also, the fi-5900C is equipped with an "active stacking tray" that automatically maintains a constant height, ensuring that scanned documents are always stacked in a neat and orderly fashion. The result is ever greater scanning efficiency for the user.



■ Eliminates multi-feed caused lost scanning time

The fi-5900C is armed with ultrasonic multi-feed detection sensors that detect whenever two or more sheets of paper have been simultaneously fed into the scanner. These sensors detect multi-feeds, even when scanning mixed batches containing paper of varying weights, sizes, colors and tones, thus guarding against potential scanning time losses before they even occur.

■ Image processing functions

The included Virtual ReScan (VRS) and unique image processing board enables users to:

- Convert documents containing colored backgrounds or shaded areas into highly legible monochrome images.
- Automatically delete blank pages, rotate images so that each one is facing the proper orientation and automatically control contrast.
- Suppress background noise and gradation to generate cleaner images that require less file size.
- Create excellent images—even if they are not imaging experts.

■ Pre and post imprinter options

Imprinter options have been offered for users with demanding document management and verification needs. The fi-5900C supports both an pre-imprinter (which prints on the front side of documents) and post-imprinter (which prints on the reverse-side of documents) option, both of which will greatly increase scanner usability.

*Microsoft, Windows, Windows Server and Windows Vista are registered trademarks of Microsoft Corporation in the United States and/or other countries.

*Adobe and Adobe Acrobat are registered trademarks of Adobe Systems Incorporated in the United States and/or other countries.

*ISIS is registered trademark of EMC Corporation of the United States.

*Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies.

*Specifications are subject to change without notice. For the latest information, contact your local Fujitsu representative. First edition April 2007.

Japan contact

PFU LIMITED

International Sales Dept., Imaging Business Div.
Solid Square East Tower, 580 Horikawa-cho, Saiwai-ku,
Kawasaki-city, Kanagawa 212-8563, Japan
Phone: (81-44) 540-4668 Fax: (81-44) 540-4639
<http://imagscanner.fujitsu.com/>

XXXXXXXX contact

FUJITSU x x x x x x
x x x x x x x x x x
x x x x x x x x x x
x x x x x x x x x x
x x x x x x x x x x
x x x x x x x x x x
Phone: (1-23) 456-7890 Fax: 123-456
<http://www.xxxxx.com/>

TECHNICAL SPECIFICATIONS

Product name		FI-5900C	
Scanner type		ADF (Automatic Document Feeder) + Manual Feed	
Scanning modes		Simplex / Duplex, Color / Grayscale / Monochrome	
Image sensor type		Color CCD (Charge-coupled device) x 2	
Light source		White cold cathode discharge lamp	
Scanning range		Maximum: A3 (portrait) (297 x 420mm or 12 x 17in.) Minimum: A8 (portrait) (53 x 74mm or 2 x 3in.)	
Paper weight (Thickness)		A4 / Letter size or Smaller: 31 to 209 g/m ² (8 to 56lb) Over A4 / Letter size: 52 to 157 g/m ² (14 to 42lb)	
Scanning speed (A4, landscape) *1	Color *2	200dpi	125ppm / 250ipm (120ppm / 230ipm) *3
	Grayscale *2	200dpi	125ppm / 250ipm (120ppm / 240ipm) *3
	Monochrome	300dpi	125ppm / 250ipm (120ppm / 160ipm) *3
Scanning speed (A4, portrait) *1	Color *2	200dpi	100ppm / 200ipm (100ppm / 200ipm) *3
	Grayscale *2	300dpi	100ppm / 200ipm (100ppm / 160ipm) *3
	Monochrome	200dpi	100ppm / 200ipm (100ppm / 200ipm) *3
Paper chute capacity (A4, landscape) *4		500 sheets (A4: 80g/m ² or 21 lb)	
Background colors		Black / White (switchable on command)	
Optical resolution		600dpi	
Output resolution *5	Color (24bit)	50 to 600dpi (adjustable by 1dpi increments)	
	Grayscale (8bit)	VRS: 100 / 150 / 200 / 240 / 300 / 400dpi	
	Monochrome (1 bit)		
Output format		Color: 24 bit , Grayscale: 8bit, Monochrome: 1bit	
AD converter		1024 levels (10bit)	
Interface *6		Ultra-wide SCSI / USB2.0 / VRS *7 (Selectable)	
Connector shape		SCSI: Shield type 68pin (pin type) , USB: B type	
Output mode (half-tone)		Dither / Error diffusion	
Voltage or voltage range		AC 100 to 240V, +10% / -10%	
Power		Operating: 250W or less (Sleep mode: less than 7W)	
Operational environment		Temperature: 15 to 35°C (59 to 95°F) Relative humidity: 20 to 80% (Non-condensing)	
Dimensions: Width x Depth x Height *8		540 x 540 x 500mm (21.3 x 21.3 x 19.7in.)	
Weight		50 kg (110lb)	
SCSI Terminator		Built-in	
Included drivers *9		TWAIN, ISIS™	
Environmental compatibility *10		ENERGY STAR® and RoHS	
Others	Multi-feed detection	Yes (Standard) ultrasonic multi-feed detection sensors x 3	
	Long paper scanning *11	863mm (34 in.)	
Included items		Document smoother, AC cable, USB cable, Setup CD-ROM, Adobe Acrobat CD-ROM, Getting Started, QuickScan, Pro brochure, Operator panel overlay, fi-5900C Convenient Operation, VRS CD-ROM	

*1 Actual scanning speeds are affected by data transmission and software processing times.

*2 JPEG compressed figures.

*3 Actual scanning speed when using VRS.

*4 Maximum capacity varies, depending upon paper weight.

*5 Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex.

*6 Ultra-wide SCSI interface cannot be used simultaneously with USB2.0.

*7 VRS is supported by Windows XP Professional and Windows 2000 Professional operating systems.

*8 Excluding the ADF paper chute and stacker.

*9 ISIS™ does not support Windows 95.

*10 Pfu Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005/95/EC).

*11 The fi-5900C is capable of scanning documents that exceed A3 sheets in length.

Options

Description	Parts number	Comments
Pre Imprinter (fi-59OPRF)	PA03450-D700	The imprinter option enables users to print information on original documents for document management purposes. While the FI-59OPRF (pre imprinter) prints information on the front of documents prior to scanning, the FI-59OPRB (post imprinter) prints information on the back of the original documents after they have been scanned. Although both the FI-59OPRF and the FI-59OPRB may be attached to the same scanner unit, both imprinters cannot be used simultaneously.
Post Imprinter (fi-59OPRB)	PA03450-D710	

Consumables

Description	Parts number	Comments
Pick Roller	PA03450-K011	Lifetime: Every 600,000 sheets or one year These rollers feed documents into the scanner.
Separator Roller	PA03450-K012	Lifetime: Every 600,000 sheets or one year These rollers feed documents through the scanner.
Brake Roller	PA03450-K013	Lifetime: Every 600,000 sheets or one year These rollers separate documents as they are being fed into the scanner.
Pad Assy	PA03450-K014	Lifetime: Every 600,000 sheets or one year These rubber parts separate documents.
Print Cartridge	CA00050-O262	Lifetime: 4,000,000 printed characters For use with fi-59OPRF and fi-59OPRB imprinters.