

K750 (Kitchen Video System)

[New Technology]


- Ultra slim, 48 mm thickness
- VESA Hole maximizes the space utilization.
- Three-Piece metal housing and IP65 dust & water proof display front

[Easy and Simple Service]

- MSR, Smart Card Reader, RFID, Scanner, and Handset.
- Rich I/O ports provides excellent peripheral Connectivity.



■ Features



Ultra Slim, 48 mm Thickness



Three-Piece Metal Housing and IP65 Dust & Water Proof Display Front



True Flat Resistive Gesture Touch
True Flat Projected Capacitive Multi-Touch



Rich I/O Ports Provide Excellent Peripheral Connectivity



Full Range of Display Sizes
15.6", 18.5" and 21.5"



Optional Accessory Includes MSR, Smart Card Reader, RFID, Scanner, Handset

■ Specification

Model Name	K750
Motherboard	C54
Processor	Intel Cedarview D2550 Dual Core 1.86G, L2 1M, 10W
Chipset	CPU integrated graphic + NM10, 2W
System Memory	1 x DDR3 DIMM socket up to 4G, FSB 1066MHz
Graphic Memory	Intel GMA 3650 (Gfx frequency up to 640MHz), DX9
LCD / Touch Panel	
LCD Size	15.6" LED LCD
Brightness	220 cd/m ²
Resolution	1366x768
Touch Screen	True flat resistive touch / True flat projected capacitive touch
Storage Device	
Hard Drive	1 x 2.5" SATA HDD bay 320GB
Flash Memory	SATA pSSD (option)
Expansion	
Mini PCI-E Slot	1
External I/O Ports	
USB 2.0	4
Serial Port	4 x RJ45 COM ports (COM1/2 standard RS232; COM3/4 powered RS232; COM3 default 5V; COM4 default 12V, power enabled by BIOS setting)
Parallel Port	1
GigaLAN(10/100/1000)	1(RJ45)
2 nd VGA	1(DB15 Female)
DC Jack	1(8V ~ 36V)
Audio Jack	1 x Mic-in, 1 x Line-out
E-SATA	1(Option)
Audio	
Internal Speaker	2 x 2w internal speaker (option)
Power	65W/19V
Control / Indicator	
Power Button	1
Certificate	
EMC & Safety	FCC Class A / CE Mark / LVD
Environment	
Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	20% ~ 85% RH non-condensing
Physical Characteristics	
Weight	4.5Kg(9.9lbs)
Dimension(W x D x H)	396 x 48 x 245mm (15.6" x 1.9" x 9.6")
Mounting	75 x 75 mm standard VESA holes
OS Supported	Windows XP, POS Ready 2009, XP Embedded, XP professional for Embedded, Linux, Windows 7 (32bit), POSReady 7 (32bit)

Product specifications subject to change without prior notice.

FUJITSU KOREA LIMITED

Jongno, Jongno-gu, Seoul, Republic of Korea
 URL: www.fujitsu.com/kr
 Phone: +82-2-3787-5762 FAX : +82-2-738-1355

June 2013

Page 2/2

All rights reserved. Copyright © FUJITSU KOREA LIMITED 2013