

	PRIMEPOS 1500	PRIMEPOS 1000
Specification	<ul style="list-style-type: none"> Intel Celeron 733 MHz, Pentium III 800/850 MHz 128 MB Standard. Expandable up to 512 MB Disk-On-Chip expandable to 288MB, share with SSD (Optional) Share memory programmable from 2MB to 64MB 3.5" IDE hard drive or 2.5" IDE hard drive (Optional) 12.1" LCD Panel, Color, TFT, Spill Proof Touch Panel Resistive or Capacitive Infrared Keyboard Receiver 	<ul style="list-style-type: none"> Intel Celeron 733 MHz, Pentium III 800.850 MHz 128 MB Standard. Expandable up to 512 MB BIOS 2MB award BIOS with full ACPI, APM, DMI, PNP, Green ASIC Intel 815EG FSB Support 66/100 MHz 1.44 MB 3.5" FDD HDD Support Ultra DMA/100 HDD (3.5")
Interfaces	<ul style="list-style-type: none"> 4 RS232C Port, 3 external with D9 Pin Connector with +5VDC/+12VDC 1 x Parallel Port Ethernet, 10/100 Base LAN Port PS/2 Keyboard Port PS/2 Mouse Port External SVGA Port (CRT support up to 1024x768) Cash Drawer Port (24 VDC) (capable of 2 drawers) 2 USB Audio Out 	<ul style="list-style-type: none"> 6 COM Ports (4*D-sub,2*RJ45)(2*D-sub9 & 2*RJ45 with 5V or 12V power supply by jumper setting) 2 Parallel ports 1 VGA port 2+2 USB ports (2 option at front) 1 Microphone input 1 Line out 1 RJ45 LAN port (1+1 optional) 2 Cash draw control (24V) 1 optional PCI slot (not available for with FDD condition)
Option Peripherals	<ul style="list-style-type: none"> Magnetic Card Reader, dual/ tracks CCD/Laser Hand Held Scanner Customer Pole or Rear Customer Display PCMCIA or Fax/Modem (PC104) Internal Floppy or CD-ROM Drive Internal Smart Card Reader Cash drawer Thermal/Receipt Printers 	<ul style="list-style-type: none"> Magnetic Card Reader, dual track CCD/Laser Hand Held Scanner Pole Customer Display 12.1 TFT LCD Panel or 9" Monochrome 128 Programmable Keyboard Cash Drawer Thermal/Receipt Printer
Other Specifications	<ul style="list-style-type: none"> Support DOS, Windows 95/98/2000, Windows NT, OS/2, Unix and Linux Safety & EMI: US, CUL, FCC, CE, VCCI Class B Dimension (W x D x H): 12.8" x 13.4" x 12.4" (325 mm x 340 mm x 315 mm), (Packaging Size: 18.3" x 23.2" x 16.3") Net weight: 7.2 kg, Gross Weight: 12.8 kg 	<ul style="list-style-type: none"> Support DOS, Windows 95/98/2000, Windows NT, OS/2, Unix and Linux Certification: VCCI, BSMI, FCC, CE, CCC, CB-Report Dimension: WxDxH= 296 x 272 x 64 mm

For more information please contact:



Baltazar H. Sabado Jr
PrimePOS Product Owner
WeSolv Open Computing Inc.
 3/F Fujitsu House Bldg., A.Arnaiz Ave., Makati City
 Tel: 632-893-7155 Fax: 632-8936785

