

Table of corrections in PRIMEQUEST 520A/520/420 Installation Planning Manual (C122-H002-07EN)

2008/12/18

Erroneous descriptions that were found in the manual have been corrected as shown below.

No.	Page	Item	Description																																																											
1	1-5 to 1-7	Table 1.2 PRIMEQUEST 520A/520 main unit installation specifications (Model name: MC3B0R211x)	Addition	(Excerpt from Table 1.2)																																																										
<table><tr><th colspan="4">Item</th></tr><tr><td rowspan="14">Air conditioning</td><td colspan="3">Maximum heat dissipation [kJ/h (BTU/h)]</td><td></td></tr><tr><td colspan="2" rowspan="2">Exhaust air flow (*8) [m³/min (ft³/min)]</td><td colspan="2">With fans operating at low speed</td></tr><tr><td colspan="2">With fans operating at high speed</td></tr><tr><td rowspan="9">Temperature and humidity (*3)</td><td rowspan="3">Operating</td><td colspan="2">Temperature [°C (°F)]</td></tr><tr><td colspan="2">Humidity [%RH]</td></tr><tr><td colspan="2">Maximum wet bulb temperature [°C (°F)]</td></tr><tr><td rowspan="3">Stand-by</td><td colspan="2">Temperature [°C (°F)]</td></tr><tr><td colspan="2">Humidity [%RH]</td></tr><tr><td colspan="2">Maximum wet bulb temperature [°C (°F)]</td></tr><tr><td rowspan="3">Not operating (*5)</td><td colspan="2">Temperature [°C (°F)]</td></tr><tr><td colspan="2">Humidity [%RH]</td></tr><tr><td colspan="2">Maximum wet bulb temperature [°C (°F)]</td></tr><tr><td colspan="4">Noise [dB (A)] (*6) (*8)</td></tr><tr><td colspan="4">Sound power level [B(A)] (*6) (*8)</td></tr><tr><td rowspan="2">Allowable vibration [m/s²]</td><td colspan="3">Operating (including standby)</td></tr><tr><td colspan="3">Not operating (*5)</td></tr><tr><td colspan="4">Allowable dust [mg/m³]</td></tr></table>							Item				Air conditioning	Maximum heat dissipation [kJ/h (BTU/h)]				Exhaust air flow (*8) [m³/min (ft³/min)]		With fans operating at low speed		With fans operating at high speed		Temperature and humidity (*3)	Operating	Temperature [°C (°F)]		Humidity [%RH]		Maximum wet bulb temperature [°C (°F)]		Stand-by	Temperature [°C (°F)]		Humidity [%RH]		Maximum wet bulb temperature [°C (°F)]		Not operating (*5)	Temperature [°C (°F)]		Humidity [%RH]		Maximum wet bulb temperature [°C (°F)]		Noise [dB (A)] (*6) (*8)				Sound power level [B(A)] (*6) (*8)				Allowable vibration [m/s²]	Operating (including standby)			Not operating (*5)			Allowable dust [mg/m³]			
Item																																																														
Air conditioning	Maximum heat dissipation [kJ/h (BTU/h)]																																																													
	Exhaust air flow (*8) [m³/min (ft³/min)]		With fans operating at low speed																																																											
			With fans operating at high speed																																																											
	Temperature and humidity (*3)	Operating	Temperature [°C (°F)]																																																											
			Humidity [%RH]																																																											
			Maximum wet bulb temperature [°C (°F)]																																																											
		Stand-by	Temperature [°C (°F)]																																																											
			Humidity [%RH]																																																											
			Maximum wet bulb temperature [°C (°F)]																																																											
		Not operating (*5)	Temperature [°C (°F)]																																																											
			Humidity [%RH]																																																											
			Maximum wet bulb temperature [°C (°F)]																																																											
	Noise [dB (A)] (*6) (*8)																																																													
	Sound power level [B(A)] (*6) (*8)																																																													
Allowable vibration [m/s²]	Operating (including standby)																																																													
	Not operating (*5)																																																													
Allowable dust [mg/m³]																																																														
<p>*1: This value does not include any projection.</p> <p>*2: Value for the case with the maximum number of optional units allowed installed.</p> <p>Value not including the rack-mounting rails and cable management.</p> <p>The weight of the unit based on the equipment configuration can be calculated from the following formula:</p> <div>$\text{Unit weight} = 103 + (11 \times A) + (17 \times B) + (4 \times C) + (4 \times D)$</div> <p>- A = Number of SBs mounted: From a minimum of one to a maximum of two</p> <p>- B = Number of IOUs mounted: From a minimum of zero to a maximum of one</p> <p>- C = Number of IOXs mounted: From a minimum of zero to a maximum of one</p>																																																														

No.	Page	Item	Description																																											
1	1-5 to 1-7	Table 1.2 PRIMEQUEST 520A/520 main unit installation specifications (Model name: MC3B0R211x)	Addition	<div>- D = Number of Dual Power Feed Options mounted: From a minimum of zero to a maximum of one</div> <div>*3: There must be no condensation.</div> <div>*4: The temperature requirement depends on the installation altitude. - 5 to 35 °C (41 to 95.0 °F) [if installed at an altitude of 0 to 1500 m (0 to 4921.2 ft)] - 5 to 33 °C (41 to 91.4 °F) [if installed at an altitude of 1500 to 2000 m (4921.2 to 6561.6 ft)] - 5 to 32 °C (41 to 89.6 °F) [if installed at an altitude of 2000 to 2500 m (6561.6 to 8202 ft)] - 5 to 30 °C (41 to 86 °F) [if installed at an altitude of 2500 to 3000 m (8202 to 9842.4 ft)]</div> <div>*5: "Not operating" means the time when the equipment is stored.</div> <div>*6: The noise and sound power level vary on the ambient temperature.</div> <div>*7: These values are for each power cable.</div> <div>*8: If the intake air temperature is high (within the normal temperature) in normal operation, the FAN rotate at high speed.</div>																																										
2	1-8, 1-9	Table 1.3 PRIMEQUEST 420 main unit installation specifications (Model name: MC3A0R111x)	Addition	<div>(Excerpt from Table 1.3)</div> <table><tr><th colspan="4">Item</th></tr><tr><td rowspan="17">Air conditioning</td><td colspan="3">Maximum heat dissipation [kJ/h (BTU/h)]</td></tr><tr><td colspan="2" rowspan="2">Exhaust air flow (*8) [m³/min (ft³/min)]</td><td>With fans operating at low speed</td></tr><tr><td>With fans operating at high speed</td></tr><tr><td rowspan="9">Temperature and humidity (*3)</td><td rowspan="3">Operating</td><td>Temperature [°C (°F)]</td></tr><tr><td>Humidity [%RH]</td></tr><tr><td>Maximum wet bulb temperature [°C (°F)]</td></tr><tr><td rowspan="3">Stand-by</td><td>Temperature [°C (°F)]</td></tr><tr><td>Humidity [%RH]</td></tr><tr><td>Maximum wet bulb temperature [°C (°F)]</td></tr><tr><td rowspan="3">Not operating (*5)</td><td>Temperature [°C (°F)]</td></tr><tr><td>Humidity [%RH]</td></tr><tr><td>Maximum wet bulb temperature [°C (°F)]</td></tr><tr><td colspan="3">Noise [dB (A)] (*6) (*8)</td></tr><tr><td colspan="3">Sound power level [B(A)] (*6) (*8)</td></tr><tr><td rowspan="2">Allowable vibration [m/s²]</td><td colspan="2">Operating (including standby)</td></tr><tr><td colspan="2">Not operating (*5)</td></tr><tr><td colspan="3">Allowable dust [mg/m³]</td></tr></table> <div>*1: This value does not include any projection.</div>				Item				Air conditioning	Maximum heat dissipation [kJ/h (BTU/h)]			Exhaust air flow (*8) [m³/min (ft³/min)]		With fans operating at low speed	With fans operating at high speed	Temperature and humidity (*3)	Operating	Temperature [°C (°F)]	Humidity [%RH]	Maximum wet bulb temperature [°C (°F)]	Stand-by	Temperature [°C (°F)]	Humidity [%RH]	Maximum wet bulb temperature [°C (°F)]	Not operating (*5)	Temperature [°C (°F)]	Humidity [%RH]	Maximum wet bulb temperature [°C (°F)]	Noise [dB (A)] (*6) (*8)			Sound power level [B(A)] (*6) (*8)			Allowable vibration [m/s²]	Operating (including standby)		Not operating (*5)		Allowable dust [mg/m³]		
Item																																														
Air conditioning	Maximum heat dissipation [kJ/h (BTU/h)]																																													
	Exhaust air flow (*8) [m³/min (ft³/min)]		With fans operating at low speed																																											
			With fans operating at high speed																																											
	Temperature and humidity (*3)	Operating	Temperature [°C (°F)]																																											
			Humidity [%RH]																																											
			Maximum wet bulb temperature [°C (°F)]																																											
		Stand-by	Temperature [°C (°F)]																																											
			Humidity [%RH]																																											
			Maximum wet bulb temperature [°C (°F)]																																											
		Not operating (*5)	Temperature [°C (°F)]																																											
			Humidity [%RH]																																											
			Maximum wet bulb temperature [°C (°F)]																																											
	Noise [dB (A)] (*6) (*8)																																													
	Sound power level [B(A)] (*6) (*8)																																													
	Allowable vibration [m/s²]	Operating (including standby)																																												
		Not operating (*5)																																												
	Allowable dust [mg/m³]																																													

No.	Page	Item	Description																									
2	1-8, 1-9	Table 1.3 PRIMEQUEST 420 main unit installation specifications (Model name: MC3A0R111x)	Addition	<div>*2: Value for the case with the maximum number of optional units allowed installed. Value not including the rack-mounting rails and cable management. The weight of the unit based on the equipment configuration can be calculated from the following formula: <div>Unit weight = 103 + (11 x A) + (17 x B) + (4 x C) + (4 x D)</div><div>- A = Number of SBs mounted: From a minimum of one to a maximum of two</div><div>- B = Number of IOUs mounted: From a minimum of zero to a maximum of one</div><div>- C = Number of IOXs mounted: From a minimum of zero to a maximum of one</div><div>- D = Number of Dual Power Feed Options mounted: From a minimum of zero to a maximum of one</div> *3: There must be no condensation. *4: The temperature requirement depends on the installation altitude.<div>- 5 to 35 °C (41 to 95.0 °F) [if installed at an altitude of 0 to 1500 m (0 to 4921.2 ft)]</div><div>- 5 to 33 °C (41 to 91.4 °F) [if installed at an altitude of 1500 to 2000 m (4921.2 to 6561.6 ft)]</div><div>- 5 to 32 °C (41 to 89.6 °F) [if installed at an altitude of 2000 to 2500 m (6561.6 to 8202 ft)]</div><div>- 5 to 30 °C (41 to 86 °F) [if installed at an altitude of 2500 to 3000 m (8202 to 9842.4 ft)]</div> *5: "Not operating" means the time when the equipment is stored. *6: The noise and sound power level vary on the ambient temperature. *7: These values are for each power cable. *8: If the intake air temperature is high (within the normal temperature) in normal operation, the FAN rotate at high speed.</div>																								
3	1-10, 1-11	Table 1.4 PCI_Box installation specifications (Model name: MC-07PBa1x)	Addition	<div>(Excerpt from Table 1.4)</div> <table><tr><th colspan="4">Item</th></tr><tr><td rowspan="9">Air conditioning</td><td colspan="3">Maximum heat dissipation [kJ/h (BTU/h)]</td></tr><tr><td rowspan="2">Exhaust air flow (*7) [m³/min (ft³/min)]</td><td></td><td>With fans operating at low speed</td></tr><tr><td></td><td>With fans operating at high speed</td></tr><tr><td rowspan="6">Temperature and humidity (*3)</td><td rowspan="3">Operating</td><td>Temperature [°C (°F)]</td></tr><tr><td>Humidity [%RH]</td></tr><tr><td>Maximum wet bulb temperature [°C (°F)]</td></tr><tr><td rowspan="3">Stand-by</td><td>Temperature [°C (°F)]</td></tr><tr><td>Humidity [%RH]</td></tr><tr><td>Maximum wet bulb temperature [°C (°F)]</td></tr></table>			Item				Air conditioning	Maximum heat dissipation [kJ/h (BTU/h)]			Exhaust air flow (*7) [m³/min (ft³/min)]		With fans operating at low speed		With fans operating at high speed	Temperature and humidity (*3)	Operating	Temperature [°C (°F)]	Humidity [%RH]	Maximum wet bulb temperature [°C (°F)]	Stand-by	Temperature [°C (°F)]	Humidity [%RH]	Maximum wet bulb temperature [°C (°F)]
Item																												
Air conditioning	Maximum heat dissipation [kJ/h (BTU/h)]																											
	Exhaust air flow (*7) [m³/min (ft³/min)]		With fans operating at low speed																									
			With fans operating at high speed																									
	Temperature and humidity (*3)	Operating	Temperature [°C (°F)]																									
			Humidity [%RH]																									
			Maximum wet bulb temperature [°C (°F)]																									
		Stand-by	Temperature [°C (°F)]																									
			Humidity [%RH]																									
			Maximum wet bulb temperature [°C (°F)]																									

No.	Page	Item	Description					
3	1-10, 1-11	Table 1.4 PCI_Box installation specifications (Model name: MC-07PBa1x)	Addition					
						Not operating (*5)	Temperature [°C (°F)]	
							Humidity [%RH]	
							Maximum wet bulb temperature [°C (°F)]	
					Noise [dB (A)] (*7)			
					Sound power level [B(A)] (*7)			
					Allowable vibration [m/s ²]	Operating (including standby)		
						Not operating (*5)		
				Allowable dust [mg/m ³]				
				*1: This value does not include any projection.				
*2: Value for the case the maximum allowable number of optional units is mounted.								
*3: There must be no condensation.								
*4: The temperature requirement depends on the installation altitude.								
- 5 to 35 °C (41 to 95.0 °F)								
[if installed at an altitude of 0 to 1500 m (0 to 4921.2 ft)]								
- 5 to 33 °C (41 to 91.4 °F)								
[if installed at an altitude of 1500 to 2000 m (4921.2 to 6561.6 ft)]								
- 5 to 32 °C (41 to 89.6 °F)								
[if installed at an altitude of 2000 to 2500 m (6561.6 to 8202 ft)]								
- 5 to 30 °C (41 to 86 °F)								
[if installed at an altitude of 2500 to 3000 m (8202 to 9842.4 ft)]								
*5: "Not operating" means the time when the equipment is stored.								
*6: These values are for each power cable.								
*7: If the intake air temperature is high (within the normal temperature) in normal operation, the FAN rotate at high speed.								

No.	Page	Item	Description						
4	1-12	SAS Expansion File Unit installation specifications (Model name: MC-03F131x)	Addition	(The following table added below Table 1.5)					
SAS Expansion File Unit installation specifications (Model name: MC-03F131x)									
				Item		Value			
Dimensions [mm (in.)]		Width					482.6 (19.0)		
		Depth					490.2 (19.3)		
		Heights					88.9 (3.5)		
Weight [kg (lb)] (*1)							25 (55.1)		
Air conditions		Maximum heat dissipation [kJ/Hr (BTU/h)]						1368 (1298)	
		Temperature and humidity (*2)		Operating	Temperature [°C]		5 to 40		
					Humidity [%RH]		20 to 80		
				Not operating	Temperature [°C]		-40 to 60		
					Humidity [%RH]		5 to 95		
Power supply		Input voltage tolerance and No. of phases						100 to 240VAC, ± 10 % 1φ	
		Frequency and tolerance						50/60 Hz, ± 3 Hz	
		Maximum power consumption/apparent power						380 W/384 VA	
*1: Value for the case the maximum allowable number of optional units (maximum configuration with 20 hard disk drive units) is mounted.									
*2: There must be no condensation.									

(End of table)