

# TeamPoS® 3000 XL



Powerful performance for the long run

If you require a high-performance POS terminal that will grow with your business, *Fujitsu's TeamPoS 3000 XL* delivers. This powerful system features Intel® processors and a host of features designed to drive down your total cost of ownership. From standalone point of sale to *mission-critical* applications such as loyalty, merchandising, and *customer relationship management*, the TeamPoS 3000 XL meets the demanding needs of today's Pervasive Retailing™ environment.



**Long-term performance** Offers powerful architecture and a stable platform based on Intel's embedded roadmap for long-term support.



**Unmatched serviceability** Components are easy to replace and can be accessed through the front of the unit without removing cables or unstacking peripherals. Ease of maintenance reduces on-site service calls.

**Easy to upgrade** Several Intel Celeron® M and Pentium® M processor options let you upgrade as your requirements become more demanding, and open architecture design lowers the cost of future upgrades.

**Advanced power management** Provides an efficient balance of power consumption, CPU utilization and performance. Reduces your power consumption and allows energy conservation when terminal is inactive.

**Industry-standard design** Lowers development costs for new and existing systems through compliance with industry standard operating systems, OPOS/JPOS, PC tools and utilities.

**System flexibility** Compact and standard controllers and extensive peripheral options provide flexibility for location and footprint of system.

**Remote management** Industry-standard remote diagnostics and remote management capabilities reduce your help desk calls and service call visits, enabling you to perform maintenance before a device fails.

**Environmental compliance** Meets RoHS and WEEE compliance standards that protect your investment and ensure a long, useful life.



TeamPoS 3000 XL Technical Specifications		
<b>Processor</b> <ul style="list-style-type: none"> <li>Intel® Celeron® M 1.3 up to 1.5 GHz</li> <li>Intel Pentium® M 1.6 up to 2.0 GHz</li> </ul>	<b>Optional I/O</b> <p><b>Option I:</b></p> <ul style="list-style-type: none"> <li>2 x RS232, +24 VDC</li> <li>3 x RS232, +5 VDC</li> <li>6 x powered USB, +12 VDC</li> </ul> <p><b>Option II:</b></p> <ul style="list-style-type: none"> <li>3 x powered USB, +12 VDC</li> </ul> <p><b>Option III:</b></p> <ul style="list-style-type: none"> <li>6 x powered USB, +12 VDC</li> </ul>	<b>Battery Backup</b> <p><b>Option I:</b></p> <ul style="list-style-type: none"> <li>Backup PC board functions – 3 year</li> </ul> <p><b>Option II:</b></p> <ul style="list-style-type: none"> <li>Backup PC board functions – 6 year</li> </ul> <p><b>Option III:</b></p> <ul style="list-style-type: none"> <li>Extended back up – full system</li> </ul>
<b>Motherboard</b> <ul style="list-style-type: none"> <li>Up to 2 MB L2 cache</li> <li>Enhanced Speed Step Technology (Pentium M only)</li> </ul> <p><b>Core chipset:</b></p> <ul style="list-style-type: none"> <li>855GME and ICH4</li> </ul> <p><b>Integrated Ethernet LAN:</b></p> <ul style="list-style-type: none"> <li>10/100 Mb/s with wake on LAN support</li> </ul> <p><b>Integrated audio:</b></p> <ul style="list-style-type: none"> <li>Intel® High Definition Audio</li> </ul>	<b>Memory</b> <ul style="list-style-type: none"> <li>256 MB to 2 GB Error Correcting (ECC) memory</li> <li>2 x 184 DIMM DDR slots</li> <li>333MHz memory</li> </ul>	<b>Dimensions</b> <p><b>Compact:</b></p> <ul style="list-style-type: none"> <li>34.0 cm x 46.5 cm x 11.9 cm (13.4 in. x 18.3 in. x 4.7 in.)</li> </ul> <p><b>Standard:</b></p> <ul style="list-style-type: none"> <li>45.0 cm x 46.5 cm x 11.9 cm (17.7 in. x 18.3 in. x 4.7 in.)</li> </ul>
<b>Graphics/Video</b> <ul style="list-style-type: none"> <li>Integrated video with up to 128 MB of memory</li> <li>Analog/digital display support</li> <li>Dual independent display support</li> <li>Digital DVI, DVI-D interface</li> <li>UXGA support, up to 1600 x 1200 resolution</li> </ul>	<b>Award BIOS</b> <ul style="list-style-type: none"> <li>Support latest versions of APM, ACPI, WfM</li> <li>Boot from LAN</li> <li>Local and remote Flash</li> <li>Password protected</li> <li>PXE network boot</li> </ul>	<b>Operating Systems</b> <ul style="list-style-type: none"> <li>Windows® 2000</li> <li>Windows XP Pro</li> <li>Windows XPe</li> <li>Windows Embedded for Point of Sale (WEPOS)</li> <li>Windows Pro Server 2003</li> <li>Linux</li> </ul>
<b>Standard I/O Ports</b> <ul style="list-style-type: none"> <li>2 x PS/2</li> <li>1 x Audio (in/out)</li> <li>1 x LAN 10/100/1000</li> <li>1 x VGA</li> <li>1 x DVI</li> <li>2 x standard COM (supports +5V or +12V)</li> <li>2 x standard USB (in rear)</li> <li>2 x additional USB ports (in front)</li> <li>1 x +24V USB powered (printer)</li> <li>1 x cash drawer (supports up to 2 cash drawers)</li> </ul>	<b>Expansion Slots</b> <ul style="list-style-type: none"> <li>1 x 1/2 height PCI Slot</li> <li>1 x Mini-PCI</li> </ul>	<b>Power Management</b> <ul style="list-style-type: none"> <li>APM</li> <li>ACPI</li> </ul>
	<b>Disk Support</b> <ul style="list-style-type: none"> <li>80 GB laptop 2.5" SATA (up to 2)</li> <li>Removable hard drive with zero-insertion connectors</li> <li>Hot swappable</li> </ul> <p><b>Options:</b></p> <ul style="list-style-type: none"> <li>CD-R</li> <li>CD-RW/DVD</li> <li>Onboard RAID supports RAID 0, 1, Auto Recovery</li> </ul>	<b>Remote Management</b> <ul style="list-style-type: none"> <li>WfM</li> <li>DMI</li> </ul>
	<b>Power Supply</b> <ul style="list-style-type: none"> <li>100 to 240 VAC, 50/60 Hz</li> <li>Auto sensing</li> <li>270 watts DC output</li> <li>1 x AC outlet (IEC connector)</li> <li>Fan Alarm</li> </ul>	<b>Additional Features</b> <ul style="list-style-type: none"> <li>Plug 'N Play</li> <li>CPU fan failure alarm</li> <li>Optional Wireless LAN 802.11 b/g</li> </ul>
		<b>Color Options</b> <ul style="list-style-type: none"> <li>Fujitsu Black or Fujitsu White</li> </ul>

Specifications subject to change.