

U-SERV™ 100 Kiosk

Self-ordering that fits your business

FUJITSU

Add a self-ordering option at your establishment without making significant renovations or costly improvements. Fujitsu's *streamlined* U-Serv 100 lets customers place orders from a standalone kiosk that takes up no more floor space than a promotional display. A *perfect complement* to your existing POS system, the U-Serv 100 helps you improve service and *lower costs* by alleviating peak time traffic and redeploying labor to *more productive* activities.



INTOUCH
WITH RETAILING™

Space-saving format Streamlined, all-in-one pedestal kiosk takes up minimal space, so you can position it anywhere without obstructing traffic.

Rugged design Built to withstand the toughest elements of a typical food environment — even spilled food and drinks.

Easy to use Approachable design and familiar touch-screen interface encourages frequent usage.

Easy maintenance Serviceable parts that are accessed from the front make maintenance quick and simple, while an optional high-capacity printer requires infrequent replenishment.

No remodeling required Optional wireless communication means you can set it up anywhere without running cables, for a hassle-free installation.

Quick payment Accepts credit and loyalty cards for fast, secure payment without the need for cash and coin handling.

Open systems Easily integrates into any in-store POS.



For more information about Fujitsu's U-Serv 100 Kiosk, contact us today.

800-340-4425 • us.fujitsu.com/retailing



FUJITSU TRANSACTION SOLUTIONS INC., 2801 Network Blvd., Frisco, TX 75034, Phone: (800) 340-4425, (858) 457-9900, us.fujitsu.com/retailing

© 2006 Fujitsu Transaction Solutions Inc. All rights reserved. Registered trademarks and trademarks are property of their respective owners. Specifications subject to change without notice. Fujitsu endeavors to ensure that the information in this document is correct and fairly stated but does not accept liability for any error or omissions. The development of Fujitsu products and services is continuous, and published information may not be up to date. It is important to check the current position with Fujitsu.

USERV 100-DS-5/06

U-Serv 100 Kiosk Technical Specifications

Customer Interface <ul style="list-style-type: none"> • Front service • Easy access 	S	Scanner <ul style="list-style-type: none"> • Omni-directional scanner • 4-directional scan fields • Supports most commonly encoded symbols (Code 128, 39, 32, EAN128...) 	0
Hardware PC <ul style="list-style-type: none"> • 1.6 GHz Intel® Pentium® • 512MB RAM Memory • I/O board with (7) powered RS232 and USB ports • CD reader 	S	Printers <ul style="list-style-type: none"> • Thermal receipt printer <ul style="list-style-type: none"> - Supports 80mm paper stock - 5,000 receipt capacity 6" roll capacity 	0
Communications <ul style="list-style-type: none"> • Intel 82562ET PHY 10/100Mbps 	S	Speakers <ul style="list-style-type: none"> • TBD 	S
Consumer LCD Display <ul style="list-style-type: none"> • 17" touch screen, SVGA (800 x 600) resolution • High impact resistance • Sealable against dust, splashing liquids, and other contaminants 	S	Card Reader <ul style="list-style-type: none"> • Swipe track 1-2 	S
Card Dispenser <ul style="list-style-type: none"> • Dispenses magnetically encoded cards • 100 card bin capacity 	0	Communications <ul style="list-style-type: none"> • Ethernet • Wireless 	S 0
		Installation <ul style="list-style-type: none"> • Pedestal w/ bolt down kit 	S

Physical/Power Specifications

Dimensions <ul style="list-style-type: none"> • Base: 12.0" W x 11.3" D x 48.8" H • w/ LCD: 17.8" W 	Relative Humidity <ul style="list-style-type: none"> • 10% to 85%
Weight <ul style="list-style-type: none"> • 124.73 lbs 	Power Supply <ul style="list-style-type: none"> • 110V-120V: 50Hz/60Hz
Temperature <ul style="list-style-type: none"> • 0° to 40° C 	Power Conditions <ul style="list-style-type: none"> • 0.25KVA: 1.6-2.1 amps: 120Vac

S = Standard 0 = Optional