

FUJITSU Image Scanner SP25



■ Equipped with the paper feeding mechanism of fi Series with cost effective high performance

- Supports scanning a wide range of documents
- High speed and reliable scanning when scanning large volume or mixed batch of documents
- compact size suitable for desk use
- Bundled with ready-to-use software
 - PaperStream IP Software driver that supports TWAIN/ISIS [™] - Presto! [™] PageManager [™] – Image data management/editing
- application developed by NewSoft Technology Corp.

- ABBYY TM Fine Reader TM Sprint – OCR application developed by ABBYY Ltd.



Main features

Equipped with the paper feeding mechanism of fi Series with cost effective high performance

Supports scanning a wide range of documents

SP25 is equipped with straight path paper feeding mechanism for reliable scanning and high precision separation mechanism using brake rollers. This means SP25 is able to scan a wide range of documents including non-standard documents, such as thin documents (41g/m² or above) and plastic cards (up to 1.4mm in thickness).

- High speed and reliable scanning when scanning large volume or mixed batch of documents

The SP25 is able to scan A4 documents at an impressive 25ppm (color, duplex, 200/300dpi). To further improve work efficiency, it is also armed with ultrasonic sensor to detect multi-feed to ensure reliable scanning even when scanning large volume or mixed batch of documents.



- Compact size suitable for desk use

The SP25 is compact in size and does not occupy your valuable desktop space (301mm(W) x 160mm(D) x 158mm(H)), so it is always ready to be used any time.

Bundled with ready-to-use software

- PaperStream IP – Driver software

The SP25 is equipped with automated functions such as auto size recognition and blank page removal to simplify scanning operations and pre-scan sorting. In addition, the image can be automatically converted into B & W image which is optimized OCR (Optical Character Recognition). To this end, the scanner can be integrated with a wide range of applications that fits any usage scenario.

- Presto! Page Manager – Image data management/editing application developed by NewSoft Technology Corp.

This software allows user to save image data in PDF format and add password to the file for managing and editing scanned data easily.

- ABBYY Fine Reader Sprint – OCR application developed by ABBYY Ltd.

This software can convert scanned images into text documents, such as searchable PDF or Microsoft[®] Word file to be utilized for other work tasks.

Models		SP25	
Supported operating systems		Windows [*] 8 / 8.1 (32-bit / 64-bit), Windows [*] 7(32-bit / 64-bit), Windows Vista [*] (32-bit / 64-bit), Windows [*] XP (32-bit / 64-bit), Windows Server [*] 2012, Windows Server [*]	
		2008(32-bit / 64-bit)	
Scanner type		ADF (Automatic Document Feeder)	
Scanning modes		Simplex / Duplex, Color / Grayscale / Monochrome	
Image Sensor Type Light source		Color CCD (Charge-Coupled Device) x 2 (Front x 1,Back x 1)	
		White Cold Cathode Discharge Lamp x 2 (Front x 1,Back x 1)	
Multi-feed detection		Ultrasonic multi-feed detection sensor x 1	
Document size	ADF Maximum *1	A4 Portrait: 210 x 297 mm, Legal: 216 x 355.6 mm (8.5 x 14 in.)	
	ADF Minimum	A8: 52 x 74 mm (2 x 3 in.)	
Document size	Long document (Maximum) *2	210 x 863 mm (8.27 x 34 in.), or 210 x 3,048 mm (8.27 x 120 in.)	
ADF Feeding Paper Wei	abt (Thickness)	41 to 209 g/m ² (11 to 56.2 lb) and only supports 127 to 209 g/m ² (34 to 56.2 lb) for A8	
ADF reeding raper we		size. Plastic card types (ADF): Portrait / Landscape, 1.4 mm thickness or less *3	
Scanning speed	Color *5	Simplex: 25 ppm, Duplex: 50 ipm (200 dpi / 300 dpi)	
(A4,Portrait) *4	Grayscale *5		
1 1 1	Monochrome		
ADF Capacity *6		50 sheets (A4: 80 g/m ² or 20 lb) (Active loadable ADF)	
Expected daily volume		3,000 sheets/day	
Background color		White	
Optical resolution		600 dpi	
	Color (24-bit)	4	
Output Resolution *7	Grayscale (8-bit)	50 to 600 dpi (adjustable by 1 dpi increments), 1200 dpi *8	
	Monochrome (1-bit)		
Output format	Color Grayscale	24-bit 8-bit	
Output format	Monochrome	1-bit	
Internal video processi	ıg	1,024 levels (10-bit)	
Interface		USB2.0 / USB1.1	
Connector shape		B type	
	Hardware-based	Dropout color (R, G, B)	
Image processing function	Software-based	Deskew & Cropping, Image Emphasis, Error diffusion, Dither, Simplified DTC, Smoothing, Droput cloor (None, Specified, White, Color Saturation), Multi-image, Blank page skip, Advanced-DTC, sRGB, Auto color detection, Upper lower separation,	
D		Vertical Streaks Reduction, Digital-Endorser, Edge Filler	
Power requirements	Oneration	AC 100 to 240V ± 10%	
	Operating	38 W or less	
Power consumption	Sleep mode	2.2 W or less	
	Standby	0.35 W or less	
Operating	Temperature	5 to 35 deg. C (42 to 95 deg. F)	
environment	Relative humidity	20 to 80% (Non-condensing)	
Dimensions: Width x De	epth x Height *9	301 x 160 x 158 mm (11.8 x 6.4 x 6.2 in.) Installation space: 400 x 700 x 380 mm (15.8 x 27.6 x 15.0 in.)	
Weight Bundled software / drivers		4.2 kg (9.24 lb) or less	
		PaperStream IP (TWAIN) Driver, PaperStream IP (TWAIN x64) Driver,	
		PaperStream IP (ISIS™) Driver, Presto!™ PageManager™,	
		ABBYY [™] FineReader [™] Sprint	
Environmental Compatibility		ENERGY STAR® and RoHS	
Inbox Contents		ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM, Quick Installation Sheet	

*1: Document sizes larger than A4, but not exceeding A3, can be scanned (single-side) using a Carrier Sheet. *2: Capable of scanning documents that exceed A4 size in length. However, the scanning of documents that exceed

863 mm (34 in.) in length will be limited to using TWAIN at 200 dpi or less.
*3: Supports continuous scanning of up to three cards. (Multi-embossed cards are not supported).

supports continuous scanning of up to three cards, (white introsect cards are not su
*4: Both data transmission and software processing times affect actual scanning speeds.
*5: Indicated speeds are from using JPEG compression.
 *6: Maximum capacity varies, depending upon paper thickness.

*7: Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex.
*8: Scanning limitations brought about by scanning mode, document size and available memory may occur when

scanning at high resolutions (600 dpi or higher). *9: Indicated dimensions exclude the ADF paper chute and stacker.

Environmental Compatibility



Technical Specifications

PFU LIMITED, as a member of the International Energy Star Program, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.

Option List

Product name	Parts number	Remarks
A3 Carrier Sheet	PA03360-0013	Carrier Sheets come in sets of five. Each Carrier Sheet has a lifespan of 500 scans.

Consumables

Description	Parts number	Recommended replacement cycle
Brake roller		Every 200,000 sheets or one year These rollers separate documents as they are being fed into the scanner.
Pick roller		Every 200,000 sheets or one year These rollers feed documents into the scanner.

This scanner is designed to digitize materials that can be reproduced lawfully, in accordance with applicable copyright regulations and other laws. Users are responsible for how they use this scanner. It is imperative that users comply with all applicable local rules and laws, including, without limitation, copyright laws when using this scanner. * Microsoft, Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Word is the product of Microsoft Corporation in

* Anclosalt, windows are either registered trademarks of trademarks of microsoft Corporation in the binted States the United States. * ABBYY and FineReader are trademarks of ABBYY Software, Ltd. which may be registered in some jurisdictions. *NewSoft, Prestol and PageManager are either registered trademarks or trademarks of NewSoft Technology Corp. * ISIS is a registered trademark of EMC Corporation in the United States. * Other company names and product names are the trademarks or registered trademarks of the respective companies.

Specifications are subject to change without notice.

PFU LIMITED

Safety Precautions

Be sure to carefully read all safety precautions prior to using this product and use this device as instructed. Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product. Be sure to limit the use of this product to listed power ratings.