

ObettPOS325

[All-In One POS]

- 15" display with True Flat touch technology
- Ivy Bridge Mobile Processors supported
- HDD easy to swap
- Slim type peripherals design

[Features and Benefit]

- Slim, compact smart ID design
- Low power consumption
- A fanless design to reduce noise and prevent dust inside the unit



■ Main Function



15" LED LCD display with
True Flat touch technology



A fan-less design to reduce noise
and prevent dust inside the unit



15" 2nd display supported



HDD easy to swap



Main board removable
for easy service



Slim type peripherals,
MSR, VFD, iButton

Model Name	OBETT 325
Motherboard	C76
Processor	Intel® Ivy Bridge Celeron 1037U Dual Core 1.86GHz
Chipset	CPU integrated graphic + HM76, 4.1W
System Memory	1 x DDR3 SO-DIMM up to 8GB, 1600MHz
Graphic Memory	Intel HD graphic DX 11 and OCL1.1
LCD / Touch Panel	
LCD Size	15" TFT LCD
Brightness	250~300 cd/m2
Resolution	1024x768
Touch Screen	True flat resistive touch
Tilt Adjustment	0° ~ 90°
Storage Device	
Hard Drive	1 x 2.5" SATA HDD bay 320GB
Flash Memory	SATA SSD flash card (option)
Expansion	
Mini PCI-E Slot	1
External I/O Ports	
USB	6 x USB Type A (USB 3.0 / 2.0 x 2, USB 2.0 x 4)
Serial Port	3xRJ45 COM Ports (COM1/2/3 powered RS232; COM1 default 5V; COM2 default 5V; COM3 default 12V by BIOS setting)
Parallel Port	1 x RJ-45
Giga LAN (10/100/1000)	1
DC Jack	1
2 nd VGA	1 (DB15 Female)
Cash Drawer Port	1 (RJ11)
Audio	
Internal Speaker	2 x 2w internal speaker (option)
Power supply	90W/19V-4 pin Lock
Control / Indicator	
Power Button	1
Indicator LED	1
Peripheral	
MSR	3 Tracks (USB)
Customer display	LCM display 2 x 20 characters (USB) / Tilt angle: 10° (Up), 24° (Down), 25° (Right), 25° (Left)
Second display	Option 15" 2nd display without touch
iButton	iButton (USB)
Environment	
Operating Temperature	0° C ~ 35° C (32° F ~ 95° F)
Storage Temperature	-20° C ~ 60° C (-4° F ~ 140° F)
Operating Humidity	20% ~ 85% RH non-condensing
Communication	
Wireless LAN	802.11 b/g/n WLAN card
Dimensions (W x D x H)	LCD 90° tilt angle: 360 x 210 X 360 mm (14.2" x 8.3" x 14.2")
Weight	4.8kg (10.6lbs)
OS Supported	Windows Embedded POSReady 2009, Windows XP Professional for Embedded, Windows 7

FUJITSU KOREA LIMITE

Jongno1, Jongno-gu, Seoul, Republic of Korea
 URL: www.fujitsu.com/kr
 Phone: +82-2-3787-5595 FAX : +82-2-738-1355