

ObettPOS485

[New Technology]

- P-CAP Multi Touch
- Fingerprint & iButton selectable

[Easy and Simple Service]]

- Slide in/out HDD replacement
- Stand with adapter housing and cable management



■ Features



P-CAP Multi Touch



Fingerprint & iButton Selectable



Magnetic Strip Card Reader



Slide in/out HDD Replacement



Variety of Peripherals



Stand with Adapter Housing and Cable Management

■ Specification

Model Name	OBETT 485
Motherboard	C56
Processor	Intel Celeron G540 2.5G, L2 2M, 65W
Chipset	Intel H61 PCH, 6.1W (AMT/RAID disabled)
System Memory	1 x DDR3 Long-DIMM up to 8GB, FSB 1066/1333MHz
Graphic Memory	Intel HD Graphics 3000/2000, integrated in CPU, frequency 850MHz (dynamic up to 1.1GHz)
LCD / Touch Panel	
LCD Size	15" TFT LCD
Brightness	250 cd/m ²
Resolution	1024x768
Touch Screen	True-Flat Resistive touch or True-Flat Projected-Capacitive touch
Tilt Adjustment	0° ~ 90°
Storage Device	
Hard Drive	1 x 2.5" SATA HDD bay 160GB
Flash Memory	SATA SSD flash card (option)
Expansion	
Mini PCI-E Slot	1
External I/O Ports	
USB 2.0	4
Serial Port	4 x RJ45 COM ports (COM1 standard RS232; COM2/3/4 powered RS232; COM2 default 0V; COM3 default 5V; COM4 default 12V, power enabled by BIOS)
Parallel Port	1
Giga LAN (10/100/1000)	1 x RJ-45
DC Jack	1 x (19V-IN)
E-SATA interface	DC-OUT, E-SATA
Second Display	1 (Option)
Cash Drawer Port	Support cash drawer 1 x (12V / 24V)
Audio	
Internal Speaker	2 x 2w internal speaker (option)
Power	120W/19V (NB type plug)
Control / Indicator	
Power Button	1
Indicator LED	1
Peripheral	
MSR	MSR (PS2)
Customer display	Flush mount VFD display 2 x 20 characters (COM)
Second display	8.4" / 15" without touch
	Certificate
EMC & Safety	FCC Class A / CE Mark / LVD
Environment	
Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	20% ~ 85% RH non-condensing
Communication	
Wireless LAN	Mini PCI-E 802.11 b/g/n wireless LAN card & antenna (option)
Dimensions (W x D x H)	LCD 90° tilt angle: 361 x 248 x 337 mm (14.2" x 9.8" x13.3")
Weight	8kg (17.6lbs)
Mouning	100 x 100 mm VESA mounting hole for panel PC type
OS Supported	Windows XP, POS Ready 2009, XP Embedded, XP professional for Embedded, Linux, Windows 7, POSReady 7

Product specifications subject to change without prior notice.

FUJITSU KOREA LIMITED

Jongno1, Jongno-gu, Seoul, Republic of Korea
 URL: www.fujitsu.com/kr
 Phone: +82-2-3787-5762 FAX : +82-2-738-1355

June 2013

Page 2/2

All rights reserved. Copyright © FUJITSU KOREA LIMITED 2013