


THE POSSIBILITIES ARE INFINITE **FUJITSU**

**A6** COLOR DOCUMENT SCANNER

*fi* Image Scanner  
**-60F**

# A6 Scanner



for Microsoft® Windows® Operating Systems

**QUALITY SCANNER**

As an ENERGYSTAR® Partner, Fujitsu has determined that this product meets the ENERGYSTAR® guidelines for energy efficiency. ENERGYSTAR is a U.S. registered mark.



# QUALITY SCANNER



## TECHNICAL SPECIFICATIONS

The fi-60F image scanner's small footprint expands the scanning market. These features will insure Fujitsu's customers' productivity well into the future.

- World's fastest A6 scanner
  - Only requires 1 second to scan a document in grayscale or monochrome (200dpi)
  - Color scans completed in 1.3 seconds (150dpi)
- Easy to use
  - Auto-de-skew and auto-cropping produce perfect scans every time, even with the cover left open
  - USB2.0 and USB1.1 interfaces facilitate easy connectability
- Smallest scanner in its class
  - 145 mm (Width) x 234mm (Depth) x 40mm (Height)
  - Its lightweight and small size is ideal for front desks, counters and offices
  - Perfect for scanning ID cards, passports, etc
- Excellent image quality
  - 600dpi optical resolution



Original image



Cropped image

Scanner type	Flatbed		
Image sensor type	Color CIS (Contact Image Sensor) (CMOS CIS)		
Light source	R,G,B LED (variable light source)		
Optical resolution	600dpi		
Output resolution	Color (24bit)	50-600dpi (settings can be adjusted in 1dpi increments)	
	Grayscale (8bit)		
	Monochrome (1bit)		
AD converter	65,536 levels (16bit)		
Gray scale level	Color	24 bit / pixel	
	Grayscale	8 bit / pixel	
	Monochrome	1 bit / pixel	
Scanning speed *1	Color	150 dpi	1.3 seconds
	Grayscale	200 dpi	1 second
	Monochrome		
Document size	Maximum A6 (148mm x 105mm)		
Interface	USB2.0/USB1.1		
Connector shape	USB (TypeB)		
Image processing	Image emphasis, simplified DTC, error diffusion, dither, moire removal, auto de-skew, auto-cropping, dropout color (R, G, B, None)		
Voltage or voltage range	AC100 to 240V, +10% / -10%		
Power	Operating	Less than 8W	
	Sleep mode	Less than 2W	
	Turned off while plugged in	Less than 1W	
Operational environment	Temperature	5 to 35 degree C (42 to 95 degree F)	
	Relative humidity	20 to 80% (non-condensing)	
Dimensions *2	Width	145 mm (5.7 in)	
	Depth	234mm (9.2 in)	
	Height	40mm (1.6 in)	
Weight	0.9kg (1.98 lb)		
Drivers	TWAIN, ISIS™		
Others	Document cover	Included (removable)	
	Document holding pad color	Black	
	Power switch	None (unit switches on and off when linked computer does)	

Note 1: These figures refer to the maximum scanning speeds achievable with this hardware. Actual scanning speeds may vary due to external factors, such as transmission time and software processing time.

Note 2: Projecting items are not included in these dimensions.

### Options

Image Processing Software Option V2.5	PA43402-C22901	Processes monochrome images, much like an image processing board does
---------------------------------------	----------------	---

Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States and/or other countries. ISIS, QuickScan and their respective logos are trademarks or registered trademarks of Pixel Translations, a division of Captiva Software Corporation. Other product names are the trademarks or registered trademarks of the respective companies. Specifications are subject to change without notice. For the latest information, contact your local Fujitsu representative. First edition December 2004

### Japan contact

PFU LIMITED  
International Sales Dept., Imaging Business Div.  
Products Group  
Solid Square East Tower, 580 Horikawa-cho, Saiwai-ku,  
Kawasaki-city, Kanagawa 212-8563, Japan  
Phone: (81-44) 540-4658 Fax: (81-44) 540-4639  
<http://imagescanner.fujitsu.com/>

### xxxxxxx contact

FUJITSU xxx xxx  
xxx xxx xxx xxx  
xxx xxx xxx xxx  
xxx xxx xxx xxx  
xxx xxx xxx xxx  
Phone: (1-23) 456-7890 Fax: 123-456  
<http://www.xxxx.com/>

