

shaping tomorrow with you

GX4000 E-Band Radio



Featuring patented Fujitsu Impulse Radio Technology, this system offers a compact footprint; speedy, simple deployment; and high-speed transmission.

GX4000 E-Band Radio

Multi-Gigabit Wireless Transport

A Simple, Powerful E-Band Solution

Traditional microwave frequency bands are increasingly congested. Since the bands have been largely used up to enhance mobile backhaul networks, it is becoming difficult to find available spectrum.

At the same time, as Radio Access Network (RAN) technology evolves towards LTE/LTE-Advanced, much higher capacity is going to be required in mobile backhaul and fronthaul networks. Hence, the growing importance of the 70/80 GHz frequency band, called E-band.

E-band is an ideal spectrum to deliver multi-gigabit capacity transport in future networks, for the following reasons:

- Wideband spectrum availability (71–76 GHz and 81–86 GHz)
- The acceptance of shorter reach hops for small-cell mobile networks
- Virtually no interference between links
- Flexible network engineering
- Quick, low-cost frequency licensing process (light license policy)





Cell site



The Fujitsu Advantage

Fujitsu, one of the world's leading microwave radio providers, has developed an innovative, patented impulse radio technology for millimeter-wave radio transmission. This technology, incorporated in highly compact outdoor radio equipment, makes it possible to achieve the ultra-high data rate of >3 Gbps for a wireless link.

Impulse radio is a breakthrough technology that provides real advantages over traditional carrier-based transmission. Just a few of these advantages are: reduced power demand, allowing the units to be solar powered; reduced size and weight due to a reduced number of components used; low latency due to direct data to impulse modulation. These advantages make the GX4000 platform a perfect fit for systems that need to be mounted on small poles to provide latency sensitive traffic such as CPRI.

All GX4000 systems operating in the E-band frequency feature Fujitsu impulse radio technology, and thus provide quick and easy solutions for building multigigabit wireless networks.

Meanwhile, thanks to their simple architecture, GX4000 systems offer not just high-speed transmission but also low power consumption—so you can establish and maintain a green network.

A Fujitsu GX4000 E-band radio solution will redefine your network for tomorrow.



Event hall

Backhaul in Mobile and Fixed Broadband Networks

To deliver various types of content-rich services over a 3G/4G mobile network or fixed broadband network, the choice of backhaul solution is the key to success. An E-band link is an ideal complement to wired backhaul technology, as it provides enough transmission capacity to support radically increased data traffic demands within a short timeframe.

Backhauling Fixed Broadband Network



GX4000 E-Band Radio

Versatile, Portable, Efficient Interconnections



Fronthaul in Future Mobile Networks (CPRI Transport)

In the age of LTE and LTE-Advanced, the architecture of a radio access network will be quite different from that of today. In that age small cells will be widely deployed on a macrocell layer for overall network operations efficiency. Thus the most serious challenge for mobile network operators will no longer be the backhaul, but rather the fronthaul: i.e., how to secure inter-connections between a centralized-BBU and multiple RRH in the most efficient way. With the arrival of GX4000 technology from Fujitsu, you can meet that challenge—while at the same time reducing CAPEX—with a flexible, environmentally-friendly wireless solution.



Hospital





Telecom office

Portable Networks for Disaster Recovery and Latency-Sensitive Applications

Wireless transport solutions can be extremely important if a communications network is heavily damaged by disaster and infrastructures must be quickly restored. With its compact body and user-friendly operation, the GX4000 represents a very flexible and powerful solution for emergency recovery of data traffic. The GX4000 is also an ideal solution for latency-sensitive but capacity-demanding applications like HDTV transport.





Residential area

GX4000 E-Band Radio

Specifications

| Frequency | 71-76/81-86 GHz, FDD |
|---------------------|--|
| Channel Size | 4,500 MHz |
| Modulation | "Impulse Radio" method |
| Ethernet Throughput | 3.0 Gbps |
| Traffic Interface | Optical (10 GbE/CPRI-2.4576G, 3.0720G) Electrical (1 GbE) |
| Latency (one way) | Less than 50 μs (Ethernet) Less than 20 μs (CPRI) |
| Antenna Size | Parabolic antenna 1 ft (30 cm) or 2 ft (60 cm) |
| Tx Output Power | 0 to +10 dBm (ATPC, MTPC) |
| Temperature | -27 to 131 °F (-33 to +55 °C) |
| Humidity | 4 to 100% |
| Power Supply | -48 VDC or 100-240 VAC (50/60 Hz) |
| Power Consumption | 25 W |
| EMC, EMI | FCC compliant ETSI EN 301 489-1, 4 |
| Dimensions | 9 x 9 x 2.2" (23 ×23 × 5.6 cm) |
| Weight | 6.6 lb (3 kg) |
| Management | NETSMART 1500, SNMP, HTTP, in-band management |
| | |



E-band Link Budget Simulations



Fujitsu Network Communications, Inc.

2801 Telecom Parkway, Richardson, TX 75082 Tel: 888.362.7763

us.fujitsu.com/telecom

© Copyright 2014 Fujitsu Network Communications Inc. FUJITSU (and design)* and "shaping tomorrow with you" are trademarks of Fujitsu Limited in the U.S. and other countries. All Rights Reserved. All other trademarks are the property of their respective owners. Configuration requirements for certain uses are described in the product documentation. Features and specifications subject to change without notice.