Fujitsu recommends Windows 11 Pro.



# Data Sheet Fujitsu Desktop ESPRIMO G6012

Mini, Mighty | Takes up your challenges, not your space

The Fujitsu ESPRIMO G6012 is a stylish Mini PC that offers desktop functionality in an ultra-compact, space-saving design. The latest Intel chipset and 12th Gen Intel® Core™ processors provide the performance for daily office needs. Flexible mounting options like attach to displays, wall mount, under table mount, its size, and many interfaces make it an ideal device where space saving is critical.\

A stylish Mini PC with ultra-compact design

Energy and space-saving for clean, clutter-free desk with convenient access to ports and ODD

- Fully equipped PC with a volume of only ~0.87 liters
- Impressive performance/volume ratio and is easy to set up in minutes
- Benefit of DVD- and Bluray drive option in a slightly bigger chassis

#### Ultimate usability

Flexible mounting and wide range of usage scenarios

- Can be used for horizontal or vertical operations and easy upgrade of major components
- Best prepared for VESA mount usage

#### Small yet grand

High performance in a small Mini PC design

- Latest Intel® chipset technology and 12th Generation Intel® Core™ processor family
- Legacy support for standard Mini PC interfaces

Perfect fit for modern offices and workplaces of tomorrow

The PC which can transform your workplace for the next generation

■ Supports new workplace scenarios with a single Type-C connection

#### Feature-rich and energy-efficient

Do a lot more with this Mini PC and also get lesser energy bill

- Improved energy efficiency
- Next generation INTEL integrated graphics
- Type-C connector with front access to support peripherals like Type-C USB sticks or headsets
- Highly efficient AC adapter or be operated by the power from peripherals, e.g. port rep or displays
- Sum of post-consumer recycled content for plastic per weight is 57% (22% are from ITE derived post-consumer material and 35% are any other post-consumer material)









## Components

	ESPRIMO G6012	ESPRIMO G6012 ESTAR	
Processor	Intel® Core™ i7-12700T processor (12 Cores (8+4) / 20 Threads, 1.4 GHz, 20 MB, Intel® UHD Graphics 770) ** Intel® Core™ i5-12500T processor (6 Cores / 12 Threads, 2.0 GHz, 12 MB, Intel® UHD Graphics 770) *	Intel® Core™ i7-12700T processor (12 Cores (8+4) / 20 Threads, 1.4 GHz, 20 MB, Intel® UHD Graphics 770) ** Intel® Core™ i5-12500T processor (6 Cores / 12 Threads, 2.0 GHz, 12 MB, Intel® UHD Graphics 770) *	
	Intel® Core™ i5-12400T processor (6 Cores / 12 Threads, 1.8	Intel® Core™ i5-12400T processor (6 Cores / 12 Threads, 1.8	
	GHz, 12 MB, Intel® UHD Graphics 730) *	GHz, 12 MB, Intel® UHD Graphics 730) *	
	Intel® Core™ i3-12100 processor (4 Cores / 8 Threads, 3.3	Intel® Core™ i3-12100 processor (4 Cores / 8 Threads, 3.3	
	GHz, 12 MB, Intel® UHD Graphics 730) *	GHz, 12 MB, Intel® UHD Graphics 730) *	
	*With Intel® Turbo Boost Technology 2.0 (clock speed and performance will vary depending on workload and other variables)		
	**with Intel® Turbo Boost Max Technology 3.0 (clock spe other variables)	eed and performance will vary depending on workload and	
Operating systems			
Operating system pre-installed	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home		
	Windows 10 Pro. Fujitsu recommends Windows 11 Pro for b	ousiness.	
Operating system notes	# Windows 11 requires for first device setup:		
	- Internet connectivity	1/ ADD\( D   E)	
	- Microsoft account for Home editions or organizational a	ccount (e.g. ADD) for Pro editions	
	# After the product end of life, Fujitsu continues to test and support new Windows releases for max. 5 years, dependin		
	on the extension of hardware services through warranty top-ups.		
	For more details, please visit our Fujitsu Service Statement at https://support.ts.fujitsu.com/IndexProdSupport.		
	asp?lng=com&OpenTab=		
	applicable under the relevant Microsoft program.	cceptance of the End User License Agreement of Microsoft as	
	ESPRIMO G6012	ESPRIMO G6012 ESTAR	
Memory modules	32 GB (1 module(s) 32 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM		
, , , , , , , , , , , , , , , , , , , ,	16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM		
	8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM		
	4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 3,200		
Craphics	ESPRIMO G6012	ESPRIMO G6012 ESTAR	
Graphics	ECDDIMO CANTO	FCDDIMO CAMA FCTAD	
	ESPRIMO G6012	ESPRIMO G6012 ESTAR	
Mass storage 2.5-inch size	HDD SATA III, 5,400 rpm, 2000 GB, 2.5-inch		
Mass Storage M.2 technology	SSD PCIe, 1024 GB M.2 NVMe module (Gen4), SED	SSD PCIe, 1024 GB M.2 NVMe module (Gen4), SED SSD	
	SSD PCIe, 2048 GB M.2 NVMe module (Gen4), SED	PCIe, 2048 GB M.2 NVMe module (Gen4), SED	
	SSD PCIe, 256 GB M.2 NVMe Module (Gen4), Value, SED	SSD PCIe, 256 GB M.2 NVMe Module (Gen4), Value, SED	
	SSD PCIe, 512 GB M.2 NVMe module (Gen4), SED	SSD PCIe, 512 GB M.2 NVMe module (Gen4), SED	
Hard disk notes	One Gigabyte equals one billion bytes, when referring to SSD (Solid State Disk)	hard disk drive capacity.	
	SED (Self-Encrypting Drive)		
	2.5-inch bay for devices with 7mm height		
	Durability in accordance with the manufacturer's indicati		
	ESPRIMO G6012	ESPRIMO G6012 ESTAR	
	DVD Super Multi ultra slim (tray), SATA	ESFICITIO COOTE ESTAIC	

Page 2 / 8

ECDDIMO CA013	ESPRIMO G6012 ESTAR
Intel® Wi-Fi 6E AX211 (2x2/160) Gig+ and Bluetooth 5.2; SRI	D cat.1 (dedicated regions only)
WI-FI 6E: The device does not operate in 6GHz band in all countries, due to national regulations.	
see flexible interface options	
ESPRIMO G6012	ESPRIMO G6012 ESTAR
The listed product components and optional functions	The listed product components and optional functions are
are not available in all region/countries.	not available in all region/countries.
	Energy Star certification only with Windows operating
System is available in 2 different housing versions:	system
Small version (0.87 Liter)	Base unit for TCO Certified generation 9;
ODD bay version (1.23 Liter)	•
	System is available in 2 different housing versions:
	Small version (0.87 Liter)
	ODD bay version (1.23 Liter)
	see flexible interface options  ESPRIMO G6012  The listed product components and optional functions are not available in all region/countries.  System is available in 2 different housing versions: Small version (0.87 Liter)

## Base unit

Base unit	ESPRIMO G6012 ESPRIMO G6012 ESTAR
Mainboard	
Mainboard type	D4014-B
Formfactor	proprietary
Chipset	Intel® B660
Processor socket	LGA1700
Processor quantity maximum	1
Supported capacity RAM (max.)	64 GB
Memory slots	2 DIMM (DDR4)
Memory frequency	3,200 MT/s
Memory notes	Dual channel support  For dual-channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the sam 3200 MHz may be clocked down to 2933/2400MHz depending on processor and memory configuration
LAN	10/100/1,000 MBit/s Intel® I219V
Integrated WLAN	optional
BIOS version	AMI Aptio V UEFI Specification 2.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	Onboard
Audio codec	Realtek ALC257N
Audio features	Internal speaker supports audio playback, High-Definition audio
I/O controller on board	
Serial ATA total	2
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI
Interfaces	
Front audio: headset	1 1

Interfaces		
Flexible Interface Options	One of following flexible Interface options can be added to the system  HDMI™ 2.1  DisplayPort™ 1.4a  2.5 Gigabit Ethernet (Intel 225LM)  Serial port (9pin, 16 byte FIFO, 16550 compatible)  2x USB 2.0 Type A	One of following flexible Interface options can be added to the system HDMI™ 2.1 DisplayPort™ 1.4a Serial port (9pin, 16 byte FIFO, 16550 compatible) 2x USB 2.0 Type A
USB front	1x USB 3.2 Gen 1 (5 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-C (provides up to 15W)	1x USB 3.2 Gen 1 (5 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-C (provides up to 15W)
USB rear	2x USB 2.0 Type-A 1x USB 3.2 Gen 1 (5 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2 Type-C (10 Gbps, supports DisplayPort 1.4 and power delivery sink **) see flexible interface options	2x USB 2.0 Type-A 1x USB 3.2 Gen 1 (5 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2 Type-C (10 Gbps, supports DisplayPort 1.4 and power delivery sink **) see flexible interface options
DisplayPort	1 (DisplayPort 1.4)	1 (DisplayPort 1.4)
HDMI	1 (HDMI 2.1)	1 (HDMI 2.1)
Ethernet (RJ-45)	1	1
Interface Module notes	**With power delivery sink support, the system is operated by the power from peripherals, e.g. port replicators or displays. An extra power supply for the system is not needed. Peripherals must provide min. 60Watt or 90Watt (for maximum CPU performance).	**With power delivery sink support, the system is operated by the power from peripherals, e.g. port replicators or displays. An extra power supply for the system is not needed. Peripherals must provide min. 60Watt or 90Watt (for maximum CPU performance).
Kensington Lock support	1	1
Input device / components		
Input devices (optional)	Keyboard Mouse	
Drive bays		
Drive bays total	2	
2.5-inch internal bays	1	
5.25-inch external bays	1	
Drive bay notes	5.25" bay: for slim optical disc drive only as an option with ODD bay housing version;	
M.2-2280	1 x on mainboard (PCIe 4.0 x4; up to 64Gbit/s) and 1 x option	al (PCIe 3.0 x4; up to 32Gbit/s)
Mini PCI slots		
M.2-2230	on the mainboard for WLAN module	
Graphics on board		
Graphics brand name	Intel® UHD Graphics 770, Intel® UHD Graphics 730, Intel® UHI	O Graphics 710
Shared video memory	Up to half the size of the total system memory	
TFT resolution (DisplayPort)	Up to 4,096 x 2,304 pixel	
TFT resolution (HDMI)	Up to 4,096 x 2,304 pixel	
Graphics features	Support for up to four independent displays DirectX® 12.1 HDCP support OpenCL 3.0 OpenGL ® 4.6 Vulkan™ DisplayPort interface supports Ver. 1.4 incl. Multi-Stream HDMI™ 2.1 Digital audio formats are supported, including Dolby Digita see flexible interface options	l Plus (7.1 channels)
Base unit	ESPRIMO G6012	ESPRIMO G6012 ESTAR
Electrical values		
Power efficiency note	90-Watt AC adapter: power supply efficiency at 115/230V: 8	9% average efficiency
Rated voltage range	100 V - 240 V	

Electrical values		
Rated frequency range	50 Hz - 60 Hz	
Operating voltage range	90 V - 264 V	
Operating line frequency range	47 Hz - 63 Hz	
Max. output of single power supply	AC Adapter: 90 W	
Base unit	ESPRIMO G6012	ESPRIMO G6012 ESTAR
Power consumption		
Power consumption note	See white paper Energy Consumption	
Noise emission		
Standard noise emission	According to ISO 7779:2010, ECMA-74	
Standard noise notes/description	A-weighted sound power level Lwad (in B) / Workplace r	related A-weighted sound pressure level LpAm (in dB(A))
Dimensions / Weight / Environmen	tal	
Dimensions (W x D x H)	146.5 x 164.5 x 36 mm	
	5.77 x 6.48 x 1.42 inch	
Dimension notes	With ODD drive bay, the dimensions are: 146.5 x 164.5 x 51	mm (5.77 x 6.48 x 2.01 inch)
Operating position	Vertical / horizontal (feet included)	,
Weight	Small:	
- <b>3</b> ···-	Min:0.85kg; 1x mem.,1x SDD	
	Max:1.015kg; 2x mem.,2x SSD,HDD,Flexi,WLAN	
	ODD version: Min:1.185kg / Max:1.275kg	
	AC adapter (0.32kg) and power cord 0.175kg) are not part of min/max	
Weight (lbs)	Base: Min: 1.88 lbs / Max: 2.24 lbs	
	ODD version: Min:2.62 lbs / Max:2.82 lbs	
	AC adapter (0.71lbs) and power cord 0.39lbs) are not part of min/max lbs	
Weight notes	Actual weight may vary depending on configuration	
Operating ambient temperature	10 - 35 °C (50 - 95 °F)	
Operating relative humidity	5 - 85 % (relative humidity)	
Compliance		
Product	ESPRIMO G6012	ESPRIMO G6012 ESTAR
Model	MPCG	
Germany	GS	
,	TÜV NRTL	
Europe	CE	
Global	RoHS (Restriction of hazardous substances)	RoHS (Restriction of hazardous substances)
	WEEE (Waste electrical and electronic equipment)	WEEE (Waste electrical and electronic equipment)
	Microsoft Operating Systems (HCT / HCL entry / WHQL)	Microsoft Operating Systems (HCT / HCL entry / WHQL)
		ENERGY STAR® 8.0
		EPEAT® in progress (dedicated regions)
		TCO Certification in progress
Compliance link	https://sp.ts.fujitsu.com/sites/certificates	
Additional Software		
Additional software (preinstalled)	McAfee® LiveSafe™ (provides award-winning antivirus p	rotection for your PC and much more. 30 days trial pre-
	installed)	
	Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)	
Additional software (optional)	Recovery DVD for Windows® Drivers &	
	Utilities DVD (DUDVD)  CyberLink PowerDVD DVD (playback software for DVD) Nero	
	Essentials XL	
	Essentials XL Microsoft® Office Professional 2021 Microsoft®	
	Microsoft® Office Professional 2021 Microsoft® Office Home and Business 2021 (Need to buy license to activate the pre-installed Microsoft Office	ce. Purchase and activation only in the region in which it
Additional coffuser (t)	Microsoft® Office Professional 2021 Microsoft® Office Home and Business 2021 (Need to buy license to activate the pre-installed Microsoft Office was acquired.)	
Additional software (notes)	Microsoft® Office Professional 2021 Microsoft® Office Home and Business 2021 (Need to buy license to activate the pre-installed Microsoft Office was acquired.)  Use of accompanying and/or additional Software is subject to	proactive acceptance of the respective License Agreements
Additional software (notes)	Microsoft® Office Professional 2021 Microsoft® Office Home and Business 2021 (Need to buy license to activate the pre-installed Microsoft Office was acquired.)  Use of accompanying and/or additional Software is subject to /EULAs/ Subscription and support terms of the Software manufa	

Base unit	ESPRIMO G6012 ESPRIMO G6012 ESTAR	
Security		
Physical Security	Kensington Lock support Eye for padlock	
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVME) Modern Standby and Legacy Standby selectable Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately	
User Security	Control of external interfaces  User and supervisor BIOS password  Hard disk password  Access protection via external SmartCard reader (optional)  AuthConductor Client Basic (secure authentication solution)	
Security Notes	The properties of the product provide a baseline for product security and therefore end-customer IT security. However these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.	
Manageability	<u> </u>	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)	
Manageability software	DeskView Client DeskView Instant BIOS Management	
DeskView components	BIOS Management incl. Security Inventory Management Driver Management Alarm Management	
Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management)	
Manageability link	CIM (Common Information Model)  http://www.fujitsu.com/fts/manageability	
	Tittp://www.fojitso.com/rts/manageablitty	
Miscellaneous	Keyboard on with one key (Fujitsu Keyboards KB521, KB955)  Keyboard on with two keys (CTRL+CTRL; special Fujitsu USB keyboards required)  Keyboard on with any key (USB)  Thermal management  Extended lifetime	
Accessories information	Further helpful options  Desktop Accessories: http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/	
	http://www.fujitsu.com/global/products/computing/peripheral/accessories/connectivity/  Stands and Mounting kits: http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/ums/index.html Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf	
Packaging information		
Packaging notes	printed user documentation is bleached in chlorine free process; Bulk packaging for projects (optional)	

Warranty		
Warranty period	3 years	
Warranty type	Next Business Day Onsite	
Warranty Terms & Conditions	https://www.fujitsu.com/au/imagesgig5/Fujitsu-Computer-Products-Warranty-Information-2021%20AU.pdf	
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.	
Product Support - the perfect	c extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day	
Service Lifecycle	5 years	
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/	

### Recommended Accessories

Thunderbolt™ 4 Port Replicator



First Thunderbolt™ Port Replicator on the market providing enhanced security and full support of Intel® AMT (vPro®).

The universal port can easily connect almost everything with a single cable and high speed data transfer. This smart workspace solution keeps your desk clean and tidy.

USB Type-C Port Replicator 2



Connect to your peripherals. Adapt to the task on demand. The universal USB Type-C interface supports you to get your peripheral devices connected easily. Multiply your USB ports to connect your peripherals as well as your external display via HDMI, DisplayPort or VGA.

You also can charge your external USB devices without the need of any additional charger.

Mounting Kit for Height Adjustable FUJITSU Displays



The FUJITSU Mounting Kit for Height Adjustable FUJITSU Displays has been specifically designed for use with ESPRIMO Q/G Mini PCs, FUTRO Thin Clients and FUJITSU Displays. By mounting an ESPRIMO Mini PC or a FUTRO Thin Client behind a display, you can save space on the desk, reduce clutter on desk and realize a clean desk working environment.

### More information

#### Fujitsu products, solutions & services

In addition to Fujitsu Desktop ESPRIMO G6012, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, knowhow and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud

offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers

to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products <a href="https://www.fujitsu.com/global/products/">www.fujitsu.com/global/products/</a> computing/

Software www.fujitsu.com/software/

#### More information

Learn more about Fujitsu Desktop ESPRIMO G6012, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

https://www.fujitsu.com/au/products/computing/pc/desktops/

#### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT

Please find further information at http://www.

fujitsu.com/global/about/environment



#### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use, and ordinary industrial use.

#### Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2022-08-25 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2020 Fujitsu Technology Solutions GmbH