Fujitsu recommends Windows 11 Pro.



Data Sheet

Fujitsu Tablet LIFEBOOK U9312X

World's Lightest Convertible With A Pen

Available in red and black, the Fujitsu LIFEBOOK U9312X is an attractively slim and lightweight 360-degree convertible. All-day battery runtime and global LTE ensure the highest productivity in any place. Enterprise-grade security such as the integrated PalmSecure $^{\text{TM}}$ sensor, powerful performance, and utmost connectivity via Intel® Thunderbolt $^{\text{TM}}$ 4 ensure a best-in-class user experience.

Ultra-slim and lightweight Convertible

The very slim and light housing makes it very comfortable to carry the device. Thanks to its 360° foldability, it can be immediately turned from a Notebook to a Tablet – and back.

- Available in red or black
- Weighing just 1 kg with a robust magnesium housing
- Durability is MIL-STD-810H tested
- Intel® Iris® Xe Graphics

Security at its best

No compromises in security and data protection – the integrated PalmSecure™ sensor turns your unique palm vein pattern into your personal key.

- Privacy Camera Shutter to keep external eyes away
- PalmSecure™ as your personal biometrical key
- Fingerprint & Full HD IR Camera supporting Windows Hello
- SmartCard reader
- Kensington Lock support

Excellent connectivity and usability

Newest interfaces and convenient features. All ports are full-sized – even the LAN port. No adapters, that can be lost and cause additional costs, are needed.

- Complete set of full-sized interfaces: HDMI, LAN and USB Type-C with Intel® Thunderbolt™4
- 13.3-inch FHD anti-glare touch display supporting pen input
- Pen garage with inductive charging function
- 5 MP rear camera

Convenient mobility supporting usage on the go

Highest productivity on business trips without empty batteries or waste of time

- New advanced battery with improved runtime that extents your mobile working sessions
- Anytime USB charging functionality for your peripheral devices, even when the system is turned off
- Always connected and instantly ready















Components

Base unit	LIFEBOOK U9312X black	LIFEBOOK U9312X red
Operating systems		
Operating system pre-installed	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home	
Operating system compatible	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home	
Microsoft OS support information	After the end of the product life Fujitsu will continue to test and support all upcoming Windows releases for a perior of maximum 5 years, depending on the available extension of hardware services through Fujitsu Warranty top ups. For details please see "Fujitsu Service Statement for Windows General Availability Channel" at www.fujitsu.com/au/support/	
Operating system notes	The use of Windows Operating System Microsoft as applicable under the rele	m is subject to acceptance of the End User License Agreement of vant Microsoft program.
Processor	Intel Core i7-1265U/32GB vPro (10 Core	es, up to 4.8 GHz)
	Intel Core i7-1265U/16GB vPro (10 Cores, up to 4.8 GHz) Intel® Core™i5-1245U processor (10	
	Cores, up to 4.4 GHz) Intel® Core™ i5-	1235U processor (10 Cores, up to 4.4 GHz) *
	*Processor only for retail, SMB, educat	on and government
Memory	8 GB onboard memory LPDDR4 16 (LPDDR4 32 GB onboard memory LPI No DIMM	
LCD Display	13.3"Full-HD (1920x1080) AG Touch	
Bluetooth	V5.2	
Hard disk drives (internal)	PCIe-SSD, 512 GB M.2 NVMe module,	SED
	PCIe-SSD, 256 GB M.2 NVMe module,	SED PCIe-
	SSD, 2TB M.2 NVMe module, SED PC	e-SSD,1TB
	M.2 NVMe module, SED	
Hard disk notes	Accessible capacity may vary, also dep	pending on the used software.
Interface add on cards/components (optional)		
3G/4G (optional)	Quectel EM120R-GL (4G Cat.12) (Downlink speed 600 MB/s, Uplink speed 150 MB/s)	
Display	33.8 cm (13.3-inch), IPS, FHD, 1,920 x 1,08	30 pixel, Anti-glare touchscreen, 400 cd/m², 1000:1
Multimedia		
Camera	Front IR Cam (2 MP) with LED, support Out camera: 5 MP with autofocus on t	

Base unit

Base unit	LIFEBOOK U9312X black	LIFEBOOK U9312X red	
General system information			
Chipset	Integrated in CPU		
Supported capacity RAM (min.)	8 GB		
Supported capacity RAM (max.)	32 GB		
Memory slots	LPDDR4		

General system information				
Memory notes	8 GB /16 GB /32 GB onboard LPDDR4x (4,266 MHz) Dual channel support			
LAN	10/100/1,000 MBit/s Intel® 1219LM			
LAN notes	· · · · · · · · · · · · · · · · · · ·			
	• • • • • • • • • • • • • • • • • • • •	Intel vPro support		
Integrated WLAN	Intel Wi-Fi 6E AX211 & BT52 vPro, SRD Cat. 2			
BIOS (see Lease	UEFI Specification 2.8			
BIOS features	InsydeH2O BIOS			
Audio type	On board			
Audio codec	Realtek ALC257			
Audio features	2x digital array microphones, 2x built-in speakers (stere	0)		
MIL-STD tested	MIL-STD-810H test results are not a guarantee of futur	Yes, selected MIL-STD-810H tests passed. MIL-STD-810H test results are not a guarantee of future performance under identified test conditions. Accidental damage is not covered under a standard international limited warranty.		
Color	Black	Red		
Material	Magnesium	Magnesium		
Display				
Diagonal Size	33.8 cm (13.3-inch)			
Display Technology	IPS			
Display type	Anti-glare touchscreen			
Display Resolution type	FHD			
Resolution (native)	1,920 x 1,080 pixel			
Aspect ratio	16:9			
Brightness - typical	400 cd/m ²			
Contrast -typical	1000:1			
Viewing angle (h/v) - typical	178°/178°			
Display notes	Wide-view high-bright LED display (for enhanced out	door viewing). With magnesium display lid.		
Sensors	3-axis Accelerometer Gyroscope Magnetic Field Sensor Compass	<u> </u>		
Diaitizer/TouchTechnology	Wacom Digitizer for pen (AES) input plus capacitive 10	finger multi-touch screen		
Digitizer /Touch Technology Pen	Wacom Digitizer for pen (AES) input plus capacitive 10 AES	finger multi-touch screen		
Digitizer /Touch Technology Pen	Wacom Digitizer for pen (AES) input plus capacitive 10 AES 4k pressure level Pen garage inductive charging	finger multi-touch screen		
	AES 4k pressure level	finger multi-touch screen		
Pen	AES 4k pressure level	finger multi-touch screen LIFEBOOK U9312X red		
Pen Graphics	AES 4k pressure level Pen garage inductive charging			
Pen Graphics Base unit TFT resolution (HDMI)	AES 4k pressure level Pen garage inductive charging LIFEBOOK U9312X black up to 4,096 x 2,160 @ 60 Hz	LIFEBOOK U9312X red up to 4,096 x 2,160 @ 60 Hz		
Pen Graphics Base unit	AES 4k pressure level Pen garage inductive charging LIFEBOOK U9312X black up to 4,096 x 2,160 @ 60 Hz Intel® Iris® Xe Graphics (with Dual channel memory)	LIFEBOOK U9312X red up to 4,096 x 2,160 @ 60 Hz Intel® iris® Xe Graphics (with Dual channel memory)		
Graphics Base unit TFT resolution (HDMI) Graphics brand name	AES 4k pressure level Pen garage inductive charging LIFEBOOK U9312X black up to 4,096 x 2,160 @ 60 Hz Intel® Iris® Xe Graphics (with Dual channel memory) 4 Display Support (3 external, 1 internal) HDCP suppor	LIFEBOOK U9312X red up to 4,096 x 2,160 @ 60 Hz Intel® Iris® Xe Graphics (with Dual channel memory) t 4 Display Support (3 external,1 internal) HDCP support DirectX® 12 OpenGL® 4.5		
Graphics Base unit TFT resolution (HDMI) Graphics brand name Graphics features	AES 4k pressure level Pen garage inductive charging LIFEBOOK U9312X black up to 4,096 x 2,160 @ 60 Hz Intel® Iris® Xe Graphics (with Dual channel memory) 4 Display Support (3 external,1 internal) HDCP suppor DirectX® 12 OpenGL® 4.5	LIFEBOOK U9312X red up to 4,096 x 2,160 @ 60 Hz Intel® Iris® Xe Graphics (with Dual channel memory) t 4 Display Support (3 external,1 internal) HDCP support DirectX® 12 OpenGL® 4.5		
Pen Graphics Base unit TFT resolution (HDMI) Graphics brand name Graphics features Graphics notes	AES 4k pressure level Pen garage inductive charging LIFEBOOK U9312X black up to 4,096 x 2,160 @ 60 Hz Intel® Iris® Xe Graphics (with Dual channel memory) 4 Display Support (3 external,1 internal) HDCP suppor DirectX® 12 OpenGL® 4.5	LIFEBOOK U9312X red up to 4,096 x 2,160 @ 60 Hz Intel® Iris® Xe Graphics (with Dual channel memory) t 4 Display Support (3 external,1 internal) HDCP support DirectX® 12 OpenGL® 4.5		
Graphics Base unit TFT resolution (HDMI) Graphics brand name Graphics features Graphics notes Interfaces DC-in	AES 4k pressure level Pen garage inductive charging LIFEBOOK U9312X black up to 4,096 x 2,160 @ 60 Hz Intel® Iris® Xe Graphics (with Dual channel memory) 4 Display Support (3 external, 1 internal) HDCP suppor DirectX® 12 OpenGL® 4.5 Shared memory depending on main memory size and	LIFEBOOK U9312X red up to 4,096 x 2,160 @ 60 Hz Intel® Iris® Xe Graphics (with Dual channel memory) t 4 Display Support (3 external,1 internal) HDCP support DirectX® 12 OpenGL® 4.5		
Pen Graphics Base unit TFT resolution (HDMI) Graphics brand name Graphics features Graphics notes Interfaces DC-in Audio: line-out /headphone	AES 4k pressure level Pen garage inductive charging LIFEBOOK U9312X black up to 4,096 x 2,160 @ 60 Hz Intel® Iris® Xe Graphics (with Dual channel memory) 4 Display Support (3 external,1 internal) HDCP support DirectX® 12 OpenGL® 4.5 Shared memory depending on main memory size and 1 1 (combo port with audio line-in)	LIFEBOOK U9312X red up to 4,096 x 2,160 @ 60 Hz Intel® Iris® Xe Graphics (with Dual channel memory) t 4 Display Support (3 external,1 internal) HDCP support DirectX® 12 OpenGL® 4.5		
Pen Graphics Base unit TFT resolution (HDMI) Graphics brand name Graphics features Graphics notes Interfaces DC-in Audio: line-out /headphone Audio: line-in /microphone	AES 4k pressure level Pen garage inductive charging LIFEBOOK U9312X black up to 4,096 x 2,160 @ 60 Hz Intel® Iris® Xe Graphics (with Dual channel memory) 4 Display Support (3 external,1 internal) HDCP suppor DirectX® 12 OpenGL® 4.5 Shared memory depending on main memory size and 1 1 (combo port with audio line-in) 1 (combo port with Audio line-out)	LIFEBOOK U9312X red up to 4,096 x 2,160 @ 60 Hz Intel® Iris® Xe Graphics (with Dual channel memory) t 4 Display Support (3 external,1 internal) HDCP support DirectX® 12 OpenGL® 4.5		
Pen Graphics Base unit TFT resolution (HDMI) Graphics brand name Graphics features Graphics notes Interfaces DC-in Audio: line-out /headphone	AES 4k pressure level Pen garage inductive charging LIFEBOOK U9312X black up to 4,096 x 2,160 @ 60 Hz Intel® Iris® Xe Graphics (with Dual channel memory) 4 Display Support (3 external,1 internal) HDCP support DirectX® 12 OpenGL® 4.5 Shared memory depending on main memory size and 1 1 (combo port with audio line-in)	LIFEBOOK U9312X red up to 4,096 x 2,160 @ 60 Hz Intel® Iris® Xe Graphics (with Dual channel memory) t 4 Display Support (3 external,1 internal) HDCP support DirectX® 12 OpenGL® 4.5 d operating system 3D accelerator		

Interfaces			
USB Type-C	2 USB 4 Gen3 Thunderbolt™4, Power Delivery (15W), D	P1.4	
HDMI	1v2.0		
Ethernet (RJ-45)	1		
Memory card slots	1 (USH-II) SD 4.0 standard SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC/microSDXC card: 2TB Speed Class: up to UHS-II (156MB/s)		
SmartCard slot	1		
SIM card slot	1 (Nano-SIM, only for models with integrated 4G/LTE m	nodule)	
eSIM card	eSIM supported - integrated in 4G/LTEModule		
Docking connector for Port Replicator	USB Type-C		
Kensington Lock support	1		
Port Replicator interfaces (optional)			
	USBType-C PR	Thunderbolt™4PR	
DC-in	1 (19V/90W required)	1 (20V/170W required)	
Power on switch	1	1	
Audio: comments	1Combo jackfor headset usage	1 Combo jack for headset usage	
DisplayPort	1xV1.2	2x	
VGA	1	⊻ 1.4++	
HDMI text	1	∀2.0b	
Interface Notes	3xType-A - 5V/0.9A, 4.5W 1xType-C - 15W 1xType-C - Up to 60 W (PD v2.0-1.1) power output to client or 4.5W input	2x Type-A - 5V/0.9A, 4.5W 1x Type-A - 5V/2.4A, 12W 2x Type-C - 5V, 1.5A/4.5W charging port 1x Type-C - TBT4 up to 60 W (PD v20-11), 5-20V/3.0A upstream (PC), Intel AMT support (vPRO) 1x Type-C - TBT4 up to 15 W (PD v20-1.1), 5V/3.0A downstream, power output to client	
Kensington Lock support	no	1	
Ethernet (RJ-45)	1	1 (10/100/1000 Mbit/s, 2,5 Gbps)	
Notes	Number of simultaneous used displays and its possible system and display interface type. Please consult always also the manual of the connecte	·	
Keyboard and pointing devices			
	Backlit keyboard w/o touch stick		
	Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.5 mm Multi gesture touchpad with integrated mouse button functionality Touchscreen Tablet Pen (AES), stored in pen garage		
Wireless technologies			
Antennas	2x dual band for WLAN, 2x for LTE, Bluetooth shared wit	thWLAN	
Bluetooth	V5.2		
Integrated WLAN	Intel Wi-Fi 6E AX211 & BT52 vPro, SRD Cat. 2		
WLAN encryption	WPAWPA2WPA3 (Wi-Fi Protected Access)		
WLAN notes	WiFi 6E is supported by Windows 11 OS only - Windows 10 OS supports WiFi 6 only. Import and usage according to country-specific regulations.		
Integrated WWAN	LTE Quectel EM120R-GL (Cat 12) - UMTS,LTE		
WWAN notes	Including GPS functionality Import and usage according to country-specific regulations. LTE Connection Manager (if configured with 4G/LTE)		
GPS	Embedded in 4G module if configured with WWAN		
Power supply			
AC Adapter	20 V /65 W (3.25 A),100 V - 240 V,50 Hz - 60 Hz,3-pin (grounded) Type-C AC-Adapter slim&light	20 V /65 W (325 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Type-C AC-Adapter slim&light	

Power supply			
AC	20 V /65 W (3.25 A),100 V - 240 V,50 Hz - 60 Hz,3-pin	20 V /65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pir	
Adapter	(grounded) Type-C AC-Adapter standard	(grounded) Type-C AC-Adapter standard	
AC .	19V/65W(3.42A)	19V/65W(3.42A)	
dapter 	20V/65W(325A)TypeC	20 V /65 W (325 A) Type C	
Vote	65W AC adapter for usage with system/ min. 90W AC Adapter for usage with Port Replicator		
Rated voltage range	100V-240V(ACInput)	100V-240V(ACInput)	
Rated frequency range	50 Hz - 60 Hz	50 Hz - 60 Hz	
st battery	Lithium polymer battery 4-cell, 64 Wh	Lithium polymer battery 4-cell, 64 Wh	
Battery features	Quick Charge: 80% in 1h	Quick Charge: 80% in 1h	
Runtime 1st battery	11h	11h	
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2018. Refer to www.bapco. com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.		
Dimensions /Weight /Environmental			
Dimensions (WxDxH)	309 x 214.8 x 16.9 mm		
•	12.18 x 8.41 x 0.62 inch		
Weight	1,015 kg		
Veight (lbs)	223 lbs		
Weight notes	Weight may vary depending on actual configuration		
Operating ambient temperature	5-35 °C (41-95 °F); Packed -10-60 °C (14-140 °F)		
Operating relative humidity	Running: 20 - 80% (relative humidity); Packed: 20 - 80% (relative humidity)		
Product	LIFEBOOK U9312X		
Europe	CE CB		
Compliance link	https://sp.ts.fujitsu.com/sites/certificates		
Additional Software			
Additional software (preinstalled)	Adobe® Reader® (pdf reader) CyberLink YouCam (w Fujitsu Display Manager Fujitsu DeskUpdate (driver and utility tool) ShockSenso Power Saving Utility	or Utility	
	Fujitsu Plugfree Network (network management utility documentation Microsoft Office (1 month trial for now Microsoft®) Office	•	
	Microsoft Office (1 month trial for new Microsoft® Office	Se 300 Custon iers, day microson Onice.)	
Additional software	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) optional		
(optional)	CyberLink PowerDVD BD (playback software for Blu-ra	у	
	Disc™) CyberLink PowerDVD DVD (playback software		
	DVD) CyberLink YouCam (webcam software)		
	Nero (backup and burning software)		
Additional software (notes)	Use of accopanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.		
 Manageability			
Manageability technology	DeskUpdate Driver management PXE 21 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) Intel® vPro™ technology iAMT 15.0 (depending on processor)		

Manageability		
Manageability	DeskView Client	
software	DeskView Instant BIOS Management	
DeskView	Inventory Management BIOS Management	
components	Driver Management Security Management Alarm Management	
Supported standards	WMI (Windows Management Instrumentation) PXE (Preboot Execution Environment)	
stal idal ds	DMI (Desktop Management Interface) SMBIOS (System Management BIOS)	
	WBEM (Web Based Enterprise Management) CIM (Common Information Model)	
Manageability link	BootP (made4you) DeskView Client : Fujitsu Australia	
Security		
Physical Security	Kensington Lock support	
System and BIOS Security	Absolute Persistence® technology capable BIOS Optional: Trusted Platform Module (TPM 2.0) EraseDisk	
User Security	Hard disk password User and supervisor BIOS password Embedded fingerprint sensor (optional) Embedded PalmSecure™sensor (optional) Smartcard reader (integrated)	
	AuthConductor Client Basic (secure authentication solution)	
Security Notes	The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.	
Packaging information		
Warranty		
Warranty period	3 years Next Business Day	
Warranty type	Onsite Service within metro areas	
Warranty Terms & Conditions	https://www.fujitsu.com/au/support/client-computing-devices/notebooks/	
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving	
	patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu. com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.	
Product Support Services - the per	fect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day	
Spare Parts availability	5 years after the end of product life	
Service Weblink	https://www.fujitsu.com/au/support/client-computing-devices/notebooks/	

Recommended Accessories

Thunderbolt™4 Port Replicator



First Thunderbolt[™] Port Replicator on the market providing enhanced security and full support of Intel® AMT (vPro®).

The universal port can easily connect almost everything with a single cable and high speed-data transfer. This smart workspace solution keeps your desk clean and tidy.

USB Type-C Port Replicator 2



Connect to your peripherals. Adapt to the task on demand. The universal USB Type-C interface supports you to get your peripheral devices connected easily. Multiply your USB ports to connect your peripherals as well as your external display via HDMI, DisplayPort or VGA

USB Type-C AC Adapter



Recharge your notebook or tablet at work, at home or on the road with this USB Type-C power source easily.

AES Pen with replacement stylus tips



Take your creativity to the next level, with the most natural pen experience with the AES Pen with replacement stylus tips. With pen nibs that are very thin, you can experience the writing and signing behavior of an ink pen.

More

information

Fujitsu products, solutions & services

In addition to Fujitsu Tablet LIFEBOOK U9312x, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how, and worldwide partnerships.

Fujitsu Portfolio

Building on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions, and cloud offerings, ranging from clients to data center solutions and including the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to leverage alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/computing/

Software "

https://www.fujitsu.com/au/ support/client-computingdevices/notebooks/

More information

Learn more about Fujitsu Tablet LIFEBOOK U9312x please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

https://www.fujitsu.com/global/products/computing/pc/tablets/index.html

Fujitsu green policy

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at Sustainable Manufacturing - Fujitsu Uvance : Fujitsu Australia



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual, or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use, and ordinary industrial use.

CONTACT
Fujitsu Product Team
Fujitsu Product Portfolio Website:

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery is subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Copyright 2022 Fujitsu Product