

Fujitsu recommends Windows 11 Pro.

# Data Sheet

## Fujitsu Desktop ESPRIMO D7012

### Small form factor PC in a more compact and space-saving design

The Fujitsu ESPRIMO D7012 is a high performance, secure small form factor Desktop PC with ultimate expandability, along with best-in-class connectivity. Faster operations and a small housing helps in space saving to create the perfect working desk. The USB Type-C, flexible graphics options, offers great connectivity. The 80Plus GOLD and 80Plus PLATINUM power supply helps to reduce environmental impact and energy bills.

#### Latest Intel® chipset technology and higher memory speed

High performance ensures faster operations and lower system response time

- Intel® Q670 chipset with higher memory frequency of 3,200 MT/s
- Intel® vPro™ Enterprise and Intel® vPro™ Essentials technology as BTO (depending on processor)

#### Ultimate expandability with easy serviceability

Space saving design for your future computing needs

- 3x low profile (LP) or 1x LP/ 1x full height (riser) via BTO
- Space saving in width and depth with 8.3 liters volume
- Tool-less access to components, easy change and screw-less add on cards

#### Best-in-class connectivity

Be flexible and stay productive in a hyper-connected world

- Support of new USB Type-C in front
- Flexiport options (VGA, DVI-D, HDMI, Type-C, DP, Serial LAN, 2x USB Type-A)
- USB Type-C support of 60 W (optional to power a display)
- Legacy PS2, serial port connectors as option

#### High security with integrated options

Designed to protect data and hardware components against manipulation and theft

- Cable cover in addition to existing Smartcard reader, Erasedisk software
- Integrated cabinet lock with master key option
- Hole for pad lock and Kensington as standard for security

#### Low power consumption and environmental impact

Reduced environmental impact and reduced energy bills

- 80Plus GOLD and 80Plus PLATINUM power supply efficiency with monitor outlet
- Sum of post-consumer recycled content for plastic per weight is 61% (18% are from ITE derived post-consumer material and 43% are any other post-consumer material)



# Components

	ESPRIMO D7012	ESPRIMO D7012 ESTAR
<b>Processor</b>	Intel® Core™ i7-13700 processor (16 Cores(8+8) / 24 Threads, 2.1 GHz, 30 MB, Intel® UHD Graphics 770) ** Intel® Core™ i7-12700 processor (12 Cores (8+4) / 20 Threads, 2.1 GHz, 25 MB, Intel® UHD Graphics 770) ** Intel® Core™ i5-13500 processor (14 Cores (6+8) / 20 Threads, 2.5 GHz, 24 MB, Intel® UHD Graphics 770) * Intel® Core™ i5-13400 processor (10 Cores (6+4) / 16 Threads, 2.5 GHz, 20 MB, Intel® UHD Graphics 730) * Intel® Core™ i5-12500 processor (6 Cores / 12 Threads, 3.0 GHz, 18 MB, Intel® UHD Graphics 770) * Intel® Core™ i5-12400 processor (6 Cores / 12 Threads, 2.5 GHz, 18 MB, Intel® UHD Graphics 730) * Intel® Core™ i3-13100 processor (4 Cores / 8 Threads, 3.4 GHz, 12 MB, Intel® UHD Graphics 730) * Intel® Core™ i3-12100 processor (4 Cores / 8 Threads, 3.3 GHz, 12 MB, Intel® UHD Graphics 730) *	Intel® Core™ i7-13700 processor (16 Cores(8+8) / 24 Threads, 2.1 GHz, 30 MB, Intel® UHD Graphics 770) ** Intel® Core™ i7-12700 processor (12 Cores (8+4) / 20 Threads, 2.1 GHz, 25 MB, Intel® UHD Graphics 770) ** Intel® Core™ i5-13500 processor (14 Cores (6+8) / 20 Threads, 2.5 GHz, 24 MB, Intel® UHD Graphics 770) * Intel® Core™ i5-13400 processor (10 Cores (6+4) / 16 Threads, 2.5 GHz, 20 MB, Intel® UHD Graphics 730) * Intel® Core™ i5-12500 processor (6 Cores / 12 Threads, 3.0 GHz, 18 MB, Intel® UHD Graphics 770) * Intel® Core™ i5-12400 processor (6 Cores / 12 Threads, 2.5 GHz, 18 MB, Intel® UHD Graphics 730) * Intel® Core™ i3-13100 processor (4 Cores / 8 Threads, 3.4 GHz, 12 MB, Intel® UHD Graphics 730) * Intel® Core™ i3-12100 processor (4 Cores / 8 Threads, 3.3 GHz, 12 MB, Intel® UHD Graphics 730) *
	Intel® vPro® Platform Logo (optional) with Intel® Core™ i5-12500, Intel® Core™ i5-13500 and Intel® Core™ i7 *with Intel® Turbo Boost Technology 2.0 (clock speed and performance will vary depending on workload and other variables) **with Intel® Turbo Boost Max Technology 3.0 (clock speed and performance will vary depending on workload and other variables)	
<b>Operating systems</b>		
Operating system pre-installed	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home Windows 10 Pro. Fujitsu recommends Windows 11 Pro for business.	
Operating system compatible	Certified for Red Hat® Enterprise Linux	
Operating system notes	Windows 11 requires for first device setup: - Internet connectivity - Microsoft account for Home editions or organizational account (e.g. ADD) for Pro editions After product end of life, Fujitsu continues to test and support new Windows releases for max. 5 years, depending on extension of hardware services through warranty top ups. For more details please visit our Fujitsu Service Statement under <a href="https://support.ts.fujitsu.com/IndexProdSupport.asp?lng=com&amp;OpenTab=">https://support.ts.fujitsu.com/IndexProdSupport.asp?lng=com&amp;OpenTab=</a> The use of Windows Operating System is subject to acceptance of the End User License Agreement of Microsoft as applicable under the relevant Microsoft program.	
	ESPRIMO D7012	ESPRIMO D7012 ESTAR
<b>Memory modules</b>	32 GB (1 module(s) 32 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, UDIMM 16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, UDIMM 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, UDIMM 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, UDIMM	
	ESPRIMO D7012	ESPRIMO D7012 ESTAR
<b>Graphics</b>	Entry 3D: NVIDIA® T400, 4 GB, PCIe x16, 3 x miniDP Entry NVIDIA T600 LP Others: MiniDP to DP Adapter Cable	
	ESPRIMO D7012	ESPRIMO D7012 ESTAR
<b>Mass storage 3.5 inch size</b>	HDD SATA III, 7,200 rpm, 1000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 2000 GB, 3.5-inch	

<b>Mass Storage M.2 technology</b>	SSD PCIe, 1024 GB M.2 NVMe module (Gen4), SED SSD PCIe, 2048 GB M.2 NVMe module (Gen4), SED SSD PCIe, 256 GB M.2 NVMe Module (Gen4), Value, SED SSD PCIe, 512 GB M.2 NVMe module (Gen4), SED	SSD PCIe, 1024 GB M.2 NVMe module (Gen4), SED SSD PCIe, 2048 GB M.2 NVMe module (Gen4), SED SSD PCIe, 256 GB M.2 NVMe Module (Gen4), Value, SED SSD PCIe, 512 GB M.2 NVMe module (Gen4), SED
<b>Hard disk notes</b>	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. SSD (Solid State Disk) SED (Self-Encrypting Drive) Durability in accordance with the manufacturer's indications on read and write cycles.	
<b>Optical drive</b>	ESPRIMO D7012 DVD Super Multi ultra slim (tray), SATA SD Card reader, USB 3.0	ESPRIMO D7012 ESTAR DVD Super Multi ultra slim (tray), SATA SD Card reader, USB 3.0
<b>Interfaces add on cards / components</b>	ESPRIMO D7012 Parallel Card (1 Port) Intel® Wi-Fi 6E AX211 (2x2/160) Gig+ and Bluetooth 5.2; SRD cat.1 (dedicated regions only) Intel® Wi-Fi 6E AX211 (2x2/160) Gig+ and Bluetooth 5.2 vPro; SRD cat.1 (dedicated regions only) Dual serial card PCIe x1 LP Dual 2.5 Gigabit Ethernet PCIe x1 2.5 Gigabit Ethernet PCIe x1	ESPRIMO D7012 ESTAR Intel® Wi-Fi 6E AX211 (2x2/160) Gig+ and Bluetooth 5.2; SRD cat.1 (dedicated regions only) Intel® Wi-Fi 6E AX211 (2x2/160) Gig+ and Bluetooth 5.2 vPro; SRD cat.1 (dedicated regions only)
<b>LAN Notes</b>	Wi-Fi 6E: The device does not operate in 6GHz band in all countries, due to national regulations. see flexible interface options Bluetooth 5.2: Bluetooth® 5.2 operation requires Microsoft OS support. Until Microsoft OS support is available, Bluetooth® 5.2 will function as Bluetooth® 5.1 or lower	
<b>Component notes</b>	ESPRIMO D7012 The listed product components and optional functions are not available in all region/countries	ESPRIMO D7012 ESTAR The listed product components and optional functions are not available in all region/countries; Energy Star certification only with Windows operating system Base unit for TCO Certified generation 9

## Base unit

<b>Base unit</b>	ESPRIMO D7012	ESPRIMO D7012 ESTAR
<b>Mainboard</b>		
Mainboard type	D4023-A2	
Formfactor	proprietary	
Chipset	Intel® Q670	
Processor socket	LGA1700	
Processor quantity maximum	1	
Supported capacity RAM (max.)	128 GB (32GB BTO)	
Memory slots	4 DIMM (DDR4)	
Memory frequency	3,200 MT/s	
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 3200 MT/s may be clocked down to 2933/2400 MT/s depending on processor and memory configuration	
LAN	10/100/1,000 MBit/s Intel® I219LM	
Integrated WLAN	1 (optional)	
BIOS version	AMI Aptio V UEFI Specification 2.8	

**Mainboard**

BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Realtek ALC897
Audio features	Internal speaker supports audio playback, High Definition audio, 5.1 surround sound

**I/O controller on board**

Serial ATA total	4
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI SATA RAID Support

**Interfaces**

Audio: line-in	1	1
Audio: line-out	1	1
Front audio: headset	1	1
Flexible Interface Options	One of following flexible Interface options can be added to the system HDMI™ (supports 4k@60Hz as specified in HDMI™ 2.1) DisplayPort™ 1.4a (external HDMI- and DVI adapters not supported) DVI-D VGA USB 3.2 Gen 2 (10Gbps) Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 60W. Occupies in addition PCIe x16 slot) USB 3.2 Gen 2 (10 Gbps) Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 15W) 2.5 Gigabit Ethernet (Intel 225LM) Serial port (9pin, 16 byte FIFO, 16550 compatible)	One of following flexible Interface options can be added to the system HDMI™ (supports 4k@60Hz as specified in HDMI™ 2.1) DisplayPort™ 1.4a (external HDMI- and DVI adapters not supported) DVI-D VGA USB 3.2 Gen 2 (10 Gbps) Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 15W)
USB front	3x USB 2.0 Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2x2 (20 Gbps) Type-C (supports up to 15W)	3x USB 2.0 1x USB 3.2 Gen 2 1x USB 3.2 Gen 2x2 Type-C (supports up to 15W)
USB rear	4x USB 2.0 Type-A 2x USB 3.2 Gen 1 (5 Gbps) Type-A see flexible interface options	4x USB 2.0 Type-A 2x USB 3.2 Gen 1 (5 Gbps) Type-A see flexible interface options
USB internal	1x USB 2.0 or 1x USB 3.2 Gen 1 (5Gbps) Type-A	1x USB 2.0 or 1x USB 3.2 (Gen 1) Type A
DisplayPort	2 (DisplayPort 1.4; DP++)	2 (DisplayPort 1.4; DP++)
Ethernet (RJ-45)	1	1
Interface Module notes	Anytime USB charge functionality	Anytime USB charge functionality
Kensington Lock support	1	1

**Input device / components**

Input devices (optional)	Keyboard Mouse
--------------------------	-------------------

**Drive bays**

Drive bays total	3
2.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	optional: 1x internal 3.5" bay (screwless) can be used via adapter for 1x or 2x 2.5" drives (screwless); 5.25" bay: for slim optical disc drive only;
M.2-2280	2 x On mainboard for SSD NVMe (PCIe 4.0 x4; up to 64Gbit/s)

**Slots**

PCI-Express 3.0 x1	1 x (110 mm / 4.33 inch) Low profile
PCI-Express 3.0 x4 (mech. x16)	1 x (150 mm / 5.91 inch)

<b>Slots</b>		
PCI-Express 4.0 x16	1 x (210 mm / 8.27 inch) Low profile	
Slots optional configuration	Optional slot versions: Rear wall with FH riser: 1x LP PCIe x4 = 150mm (5.9 inch), 1x FH PCIe x16 = 203mm (7.99 inch); CELSIUS Edition with special heatsink: 1x LP PCIe x4 = 150mm (5.9 inch), 1x LP PCIe x16 slot = 170 mm (6.69 inch) and 1x LP PCIe x1 = 170mm (6.69 inch)	
M.2-2230	on mainboard for WLAN module	
<b>Graphics on board</b>		
Graphics brand name	Intel® UHD Graphics 770, Intel® UHD Graphics 730, Intel® UHD Graphics 710	
Shared video memory	Up to half size of total system memory	
TFT resolution (VGA)	Up to 1,920 x 1,080 pixel	
TFT resolution (DVI)	Up to 1,920 x 1,200 pixel	
TFT resolution (DisplayPort)	Up to 4,096 x 2,304 pixel	
TFT resolution (HDMI)	Up to 4,096 x 2,304 pixel	
Graphics features	Support for up to four independent displays DirectX® 12.1 HDCP support OpenCL 3.0 OpenGL® 4.6 Vulkan™ For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.4 incl. Multi-Stream Digital audio formats are supported, including Dolby Digital Plus (7.1 channels) DVI-D interface supports audio output if connected to the HDMI interface of a display via suitable adapter cables (not included) see flexible interface options	
Base unit	ESPRIMO D7012	ESPRIMO D7012 ESTAR
<b>Electrical values</b>		
Power efficiency note	Power supply efficiency in % at 10% / 20% / 50% / 100% load 80Plus GOLD: for 230V ; 87/90/92/91 for 115V ; 86/89/91/88  80Plus PLATINUM: for 230V ; 88/92/94/93 for 115V ; 87/91/92/91	
Rated voltage range	100 V - 240 V	
Rated frequency range	50 Hz - 60 Hz	
Operating voltage range	90 V - 264 V	
Operating line frequency range	47 Hz - 63 Hz	
Max. output of single power supply	GOLD: 280W; PLATINUM: 300 W	
Power factor correction/active power	active	
Monitor outlet	Switched for PLATINUM power supply	
Base unit	ESPRIMO D7012	ESPRIMO D7012 ESTAR
<b>Power consumption</b>		
Power consumption note	See white paper Energy Consumption	See white paper Energy Consumption
Link to Energy White Paper		<a href="https://docs.ts.fujitsu.com/dl.aspx?id=1911002d-a189-4633-a6ea-f73f01b58fa1">https://docs.ts.fujitsu.com/dl.aspx?id=1911002d-a189-4633-a6ea-f73f01b58fa1</a>
<b>Noise emission</b>		
Related Processors for noise	Intel® Core™ i5-12500 processor and 8GB, ODD; Windows 11 (tower position)	
Standard noise emission	According to ISO 7779:2010, ECMA-74	
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))	
Standard noise operation mode: CPU 50% load	Bystander; Operator position PLATINUM PSU: 3.3 B / 19 dB(A); 20 dB(A) (SSD M.2) GOLD PSU: 3.4 B / 20 dB(A); 21 dB(A) (3.5" HDD)	

**Noise emission**

Standard noise operation mode: HDD load	Bystander; Operator position PLATINUM PSU: 3.3 B / 19 dB(A); 21 dB(A) (SSD M.2) GOLD PSU: 3.6 B / 22 dB(A); 24 dB(A) (3.5" HDD)
Standard noise operation mode: Idle mode	Bystander; Operator position PLATINUM PSU: 3.2 B / 19 dB(A); 20 dB(A) (SSD M.2) GOLD PSU: 3.6 B / 22 dB(A); 23 dB(A) (3.5" HDD)
Standard noise operation mode: ODD load	Bystander; Operator position PLATINUM PSU: 4.6 B / 31 dB(A); 35 dB(A) (SSD M.2) GOLD PSU: 4.5 B / 31 dB(A); 35 dB(A) (3.5" HDD)
Standard noise operation mode: Office applications 2.0	Bystander; Operator position PLATINUM PSU: 3.2 B / 19 dB(A); 20 dB(A) (SSD M.2) GOLD PSU: 3.6 B / 22 dB(A); 23 dB(A) (3.5" HDD)

**Dimensions / Weight / Environmental**

Dimensions (W x D x H)	314 x 296 x 89 mm 12.36 x 11.65 x 3.51 inch
Operating position	horizontal / vertical (optional, feet needed)
Weight	Min: 5.7kg; 1x mem, 1xSDD Max: 6.0kg; power cord (0.2kg) is not part of min/max
Weight (lbs)	approx. 17.64 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)

**Compliance**

Product	ESPRIMO D7012	ESPRIMO D7012 ESTAR
Model	DTG	
Germany	GS TÜV NRTL	
Europe	CE	
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 8.0 EPEAT® Gold (dedicated regions) TCO Certified, generation 9
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>	

**Additional Software**

Additional software (preinstalled)	McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)	
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) Nero Essentials XL Microsoft® Office Professional 2021 Microsoft® Office Home and Business 2021 (Need to buy license to activate the pre-installed Microsoft Office. Purchase and activation only in the region in which it was acquired.)	
Additional software (notes)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.	
Base unit	ESPRIMO D7012	ESPRIMO D7012 ESTAR

<b>Security</b>	
Physical Security	Kensington Lock support Eye for padlock Integrated cabinet lock (optional) Cable Cover (optional; covers and secures the ports and cables on rear side)
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVME) Modern Standby (Windows 11 only) and Legacy Standby selectable Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces NIST SP800-147 BIOS Protection supported NIST SP800-155 BIOS Integrity Measurement supported NIST SP800-193 Platform Firmware Resiliency supported
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional)
Security Notes	The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.
<b>Manageability</b>	
Manageability technology	Intel® vPro® Essentials (optional) Intel® vPro® Enterprise (optional) Intel AMT 16.0 (optional; depending on processor) DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	BIOS Management incl. Security Inventory Management Driver Management Alarm Management
Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)
Manageability link	<a href="https://www.fujitsu.com/global/products/computing/pc/manageability/">https://www.fujitsu.com/global/products/computing/pc/manageability/</a>
<b>Miscellaneous</b>	
	Keyboard on with one key (Fujitsu Keyboards KB521, KB955) Keyboard on with two keys (CTRL+CTRL; special Fujitsu USB keyboards required) Keyboard on with any key (USB) Thermal management Extended lifetime Internal dust filter (optional)
<b>Packaging information</b>	
Packaging dimension (mm)	499 x 296 x 439 mm
Packaging dimension (inch)	19.65 x 11.65 x 17.28 inch
Max. quantity / pallet	24

**Packaging information**

Material - Weight (g) Carton	1114 g
Material - Weight (lbs) Carton	2.46 lbs
Material - Weight (g) PE	263 g
Material - Weight (lbs) PE	0.58 lbs
Packaging notes	printed user documentation is bleached in chlorine free process; Bulk packaging for projects (optional)

**Warranty**

Warranty period	4 years
Warranty type	Next Business Day On-site Service (Metro Areas only)
Warranty Terms & Conditions	<a href="http://www.fujitsu.com/warranty">http://www.fujitsu.com/warranty</a>
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: <a href="https://support.ts.fujitsu.com/">https://support.ts.fujitsu.com/</a> free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.

**Product Support - the perfect extension**

Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	<a href="http://www.fujitsu.com/emeia/products/product-support-services/">http://www.fujitsu.com/emeia/products/product-support-services/</a>



## More information

### Fujitsu products, solutions & services

In addition to Fujitsu Desktop ESPRIMO D7012, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about Fujitsu Desktop ESPRIMO D7012, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/emeia/products/computing/pc/desktops/](http://www.fujitsu.com/emeia/products/computing/pc/desktops/)

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>  
Copyright 2023 Fujitsu Technology Solutions GmbH

### Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

### Contact

Fujitsu Technology Solutions GmbH  
Website: [www.fujitsu.com](http://www.fujitsu.com)  
2023-06-02 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>  
Copyright 2023 Fujitsu Technology Solutions GmbH