

LifeBook E4010

Latest Intel[®] Centrino[™] Mobile Technology

E4010

Intel® Pentium® M processor 1.60GHz

(w/Enhanced SpeedStep™)

- Wi-Fi Connectivity
- Hot Swappable Modular Bay
- Full-Sized Keyboard

CPU

• Peak Performance. Compact Styling.



Intel® Pentium® M processor 1.40GHz

(w/Enhanced SpeedStep®)

SINGAPORE: Fujitsu PC Asia Pacific Pte Ltd Tel: (65) 6776 0688 Fax: (65) 6776 0788

MALAYSIA: Fujitsu PC Asia Pacific Pte Ltd (Malaysia Branch) Tel: (60-3) 2093 3997 Fax: (60-3) 2093 4245

HONG KONG: Fujitsu PC Asia Pacific Ltd Tel: (852) 3101 8133 Fax: (852) 3101 0633

THAILAND: Fujitsu Systems Business (Thailand) Ltd PC Division Tel: (66-2) 658 0350

Tel: (66-2) 658 0350 Fax: (66-2) 658 0356 www.fujitsu-pcap.in.th

AUSTRALIA:

Fujitsu PC Australia
Toll Free: 1800 288 283
Tel: (61-2) 9004 7455
Fax: (61-2) 9004 7720
www.lifebook.com.au

CHINA:

Fujitsu PC China Division
Tel: (86-21) 2890 9622
Fax: (86-21) 2890 9999
www.cn.fujitsu.com

PHILIPPINES:

Fujitsu Philippines Inc. Tel: (63-2) 812 4001 Fax: (63-2) 817 7576

TAIWAN

Fujitsu Taiwan Ltd
Tel: (886-2) 2311 2255
Fax: (886-2) 2311 2277

VIETNAM:

Fujitsu Vietnam Ltd Tel: (84-4) 831 3895~7 Fax: (84-4) 831 3898

INDONESIA: PT Fujitsu Systems (Indonesia)

Tel: (62-21) 344 2601 Fax: (62-21) 344 2593

Note: For countries not listed above, please contact our Singapore office.

Secondary Cache	1MB				
Chipset	Intel® 855GM				
Memory	512MB DDR266, max. 1024MB	256MB DDR266, max. 1024MB			
Hard Disk Drive	60GB (Ultra DMA/100 and S.M.A.R.T. Support)	40GB (Ultra DMA/100 and S.M.A.R.T. Support)			
Display	15.0" Super XGA+ TFT Colour (Max. 1400 x 1050 pixels)	14.1" XGA TFT Colour (Max. 1024 x 768 pixels)			
Graphics	Integrated Intel® Graphics (w/Dynamic Video Memory Technology) with 3D Graphics Accelerator and MPEG-2 Support (for DVD)				
Sound	AC Link Audio (AC97 compliance: SigmaTel STAC9767) with Internal Speakers (Stereo)				
Communication	V.92 ³ Modem & 10/100 Base-T LAN				
Wireless LAN	Intel® PRO/Wireless 2100 - 802.11b with Dual Antenna				
Bluetooth™	PC Card Option				
Storage Device	External USB FDD				
Modular Bay ²	Combo Drive (DVD & CD-RW)	CD-RW Drive			
(Hot Swappable)	Replaceable with options: Combo Drive, DVD-ROM Drive, 2nd Li-Ion Battery, Weight Saver				
External I/O Interface	1 x VGA, 2 x USB 2.0, 1 x Serial, 1 x Parallel, 1 x RJ45, 1 x RJ11, S-Video out,				
	Audio (Headphone-out, Microphone-in), Docking for Port Replicator, AC Adapter Power Input				
Port Replicator	1 x VGA, 4 x USB 2.0, 2 x PS/2 KB/Mouse Port, 1 x Serial, 1 x Parallel, 1 x RJ45,				
	Audio (Line-in, Line-out), AC Adapter Power Input				
Card Slot	PC Card Slot Type I/II x 2 or Type III x 1				
IR Interface	IrDA1.1 (Max. 4Mbps)				
Security Panel	Application Mode : 4 Programmable Application Launch Buttons				
	Security Mode : Unique Numeric Buttons for Security Lock (More than 800,000 possible password				
	combinations)				
Keyboard	87-key w/19mm Key Pitch, 2.7mm Key Stroke				
Pointing Device	Touch Pad with Scroll Button				
AC Adapter	Input: AC100-240V, Output: DC19V 60W				
Battery ¹	Approx. 5.0 hours, Lithium Ion				
OS Supported	Microsoft® Windows® XP Home Edition				

- Results obtained from Ziff Davis (BusinessWinstone 2001) Battery Mark V1.0. Actual battery life will vary based on screen brightness, applications, features, power management settings, battery conditioning, and other customer preferences. DVD or hard disk drive usage may also have a significant impact on battery life.
- 2 Hot swap feature is only supported with Windows XP OS. Standard optical drive may vary between countries and is not user changeable. Please check with your local distributor for actual configuration.
- 3 Dependent on local service provider.

Other Software Bundled

Dimensions

Weight

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels. Some pictures are expressed in creative manners which may differ from the actual unit. Please check with your local distributor on any specifics.

Microsoft® Windows® XP Professional Edition

Microsoft® Windows® 2000 Professional Edition

325.5mm (W) x 272.5mm (D) x 36.5mm min. (H)

Approx. 2.80kg (w/weight saver option)





Fujitsu recommends Microsoft® Windows® XP Professional for Mobile Computing

Norman Virus Control

Norman Personal FireWall

8	Blu	eto	oth"
W	DIU	IGIU	Ulli

BLUETOOTH is a trademark owned by its proprietor and used by

All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.

Dealer:			

Approx. 2.65kg (w/weight saver option)