




P3PC-1582-01EN

fi-5015C Image Scanner

Getting Started



FUJITSU

CONTENTS

■ Regulatory Information	ii
■ Note, Liability	iii
■ Safety Precautions	v
Chapter1 PREPARING THE SCANNER.....	1
1.1 Checking the Contents of the Scanner Package.....	1
1.2 Names of Parts	1
1.3 Operator panel.....	1
Chapter2 INSTALLATION OF THE SCANNER.....	3
2.1 Installing the Scanner Application	3
2.2 Installing the Scanner	9
2.3 Connecting the Scanner to Your PC.....	10
2.4 Confirming Installation	11
Appendix1 TROUBLESHOOTING.....	AP-1
Appendix2 DAILY CARE	AP-4
Appendix3 REPLACING CONSUMABLES.....	AP-5

INTRODUCTION

Thank you for purchasing the fi-5015C Color Scanner. This document describes how to use fi-5015C and basic operation methods. Before you start using fi-5015C be sure to thoroughly read this manual to ensure correct use.

The "Operator's Guide" stored on the Setup CD Rom provides useful and detailed information on Operations when you would like to use advanced features, Daily Care for maintenance of the scanner, and Replacing Consumables to maintain conditions for smooth scanning. Please also read the Operator's Guide for further information.

■ Regulatory Information

FCC declaration

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is located.
- Consult your dealer or an experienced radio/TV technician.

FCC warning: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTICE

The use of a shielded interface cable is required to comply with the Class B limits of Part 15 of FCC rules.
The length of the AC cable must be 3 meters (10 feet) or less.

Canadian DOC Regulations

This digital apparatus does not exceed the Class B limit for radio noise emissions from digital apparatus set out in the Radio interference Regulations of the Canadian Department of Communications.

This Class B digital apparatus complies with Canadian ICES-003.

Le présent appareil numérique n'émet pas de parasites radioélectriques dépassant les limites applicables aux appareils numériques de la classe B et prescrites dans le Règlement sur le brouillage radioélectrique dictées par le Ministère des Communications du Canada.

Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.

Bescheinigung des Herstellers / Importeurs

Für den fi-5015C wird folgendes bescheinigt:

- In Übereinstimmung mit den Bestimmungen der EN45014(CE) funktentstört
- Maschinenlärminformationsverordnung 3.GPSGV: Der höchste Schalldruckpegel beträgt 70 dB (A) oder weniger, gemäß EN ISO 7779.

International ENERGY STAR® Program

As an ENERGY STAR® Partner, PFU LIMITED has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. The International ENERGY



STAR® Office Equipment Program is an international program that promotes energy saving through the penetration of energy efficient computers and other office equipment. The program backs the development and dissemination of products with functions that effectively reduce energy consumption. It is an open system in which business proprietors can participate voluntarily. The targeted products are office equipment such as computers, monitors, printers, facsimiles, copiers, scanners, and multifunction devices. Their standards and logos are uniform among participating nations.

■ Note, Liability

READ ALL OF THIS MANUAL CAREFULLY BEFORE USING THIS PRODUCT. IF THIS PRODUCT IS NOT USED CORRECTLY, UNEXPECTED INJURY MAY BE CAUSED TO USERS OR BYSTANDERS.

Also, keep this manual in a safe place so that it can be easily referred to during use of this product.

While all efforts have been made to ensure the accuracy of all information in this manual, PFU assumes no liability to any party for any damage caused by errors or omissions or by statements of any kind in this manual, its updates or supplements, whether such errors are omissions or statements resulting from negligence, accidents, or any other cause. PFU further assumes no liability arising from the application or use of any product or system described herein; nor any liability for incidental or consequential damages arising from the use of this manual. PFU disclaims all warranties regarding the information contained herein, whether expressed, implied, or statutory.

Use in High-safety Applications

This product has been designed and manufactured on the assumption that it will be used in office, personal, domestic, regular industrial, and general-purpose applications. It has not been designed and manufactured for use in applications (simply called "high-safety applications" from here on) that directly involve danger to life and health when a high degree of safety is required, for example, in the control of nuclear reactions at nuclear power facilities, automatic flight control of aircraft, air traffic control, operation control in mass-transport systems, medical equipment for sustaining life, and missile firing control in weapons systems, and when provisionally the safety in question is not ensured. The user should use this product with adopting measures for ensuring safety in such high-safety applications. PFU LIMITED assumes no liability whatsoever for damages arising from use of this product by the user in high-safety applications, and for any claims or compensation for damages by the user or a third party.

About the use of mercury



Lamp(s) inside this product contain mercury and must be recycled or disposed of according to local, state, or federal laws.

To avoid unexpected injuries;

- Do not put the substance contained in the lamp in your mouth as it has mercury.
- Do not breathe the chemical liquid contained in the scanner lamps.
- Do not incinerate, crush, or shred the lamps or scanner parts.

Trademarks

Microsoft, Windows, and Windows NT are registered trademarks of Microsoft Corporation in the United States and/or other countries. ISIS, QuickScan and their respective logos are trademarks or registered trademarks of EMC Corporation in the United States. Adobe, the Adobe logo, and Acrobat are either registered trademarks of Adobe Systems Incorporated in the United States and/or other countries. Other product names are the trademarks or registered trademarks of the respective companies.

How Trademarks Are Indicated In This Manual

References to operating systems (OS) are indicated as follows:

Windows 98	Microsoft® Windows® 98 operating system.
Windows Me	Microsoft® Windows® Millennium Edition operating system.
Windows 2000	Microsoft® Windows® 2000 Professional operating system.
Windows XP	Microsoft® Windows® XP Professional operating system, Microsoft® Windows® XP Home Edition operating system.

Where there is no distinction between the different versions of the above operating system, the general term "Windows " is used.

Adobe Acrobat Adobe® Acrobat®

All the descriptions in this manual assume the usage of Adobe Acrobat bundled with this product. However, Adobe Acrobat may be upgraded without notice. If the descriptions differ from the screens actually displayed, refer to the Acrobat's "Help".

Manufacturer

PFU LIMITED
International Sales Dept., Imaging Business
Division, Products Group
Solid Square East Tower, 580 Horikawa-cho,
Saiwai-ku, Kawasaki-shi Kanagawa 212-8563,
Japan
Phone : (81-44) 540-4538

All Rights Reserved, Copyright© PFU LIMITED 2006

About Maintenance

The user must not perform repairs on this scanner.
Contact the store where you purchased the scanner
or an authorized FUJITSU Image Scanner service
provider to make repairs to this product.

Warning Indications Used In This Manual



This indication alerts operators to an operation that, if not strictly observed, may result in severe injury or death.



This indication alerts operators to an operation that, if not strictly observed, may result in safety hazards to personnel or damage to equipment.

Symbols Used In This Manual



This symbol alerts operators to particularly important information. Be sure to read this information.



This symbol alerts operators to helpful advice regarding operation.



A TRIANGLE symbol indicates that special care and attention is required.
The drawing inside the triangle shows the specific caution.



A CIRCLE with a diagonal line inside shows action which users may not perform.
The drawing inside or under the circle shows the specific action that is not allowed.



Outline characters on a colored background show instructions users should follow.
It may also include the drawing that shows the specific instruction.

Warning Label



The glass surface inside the ADF becomes hot during the operation. Be careful not to touch the glass surface inside the ADF.



Do NOT remove, stain or scratch the warning labels from the scanner.



Screen Examples In This Manual

The screen examples in this manual are subject to change without notice in the interest of product improvement. If the actual displayed screen differs from the screen examples in this manual, operate by following the actual displayed screen while referring to the User's Manual of the scanner application you are using.
The screenshots in this manual were captured from FUJITSU TWAIN32 scanner driver, ScandAll 21 Image Capturing Utility Software, FUJITSU ISIS scanner driver, QuickScan Pro™ image capturing software and Adobe Acrobat.

■ Safety Precautions



Do not damage the AC cable.



A damaged AC cable may cause fire or electric shock. Do not place heavy objects on AC cables, or pull, bend, twist, heat, damage or modify AC cables.
Do not use damaged AC cables or power plugs, or install any cables or power plugs to loose wall sockets.

Use only specified AC cables and connector cables



Use only specified AC cables and connector cables. Failure to use the correct cables might cause electric shock and/or equipment failure. Please don't use the AC cable provided with this scanner for other devices, since this might cause equipment failure and other troubles or an electric shock.

Use this scanner only at the indicated power voltage. Do not connect to multiple-power strips.



Use this scanner only at the indicated power voltage and current. Improper power voltage and current might cause fire or electric shock. Do not connect to multiple-power strips.

Do not touch the AC cable with wet hands.



Do not touch the power plug with wet hands. Doing so might cause electric shock.

Wipe any dust from the power plug.



Wipe off any dust from metal parts on the power plug or metal fittings with a soft, dry cloth. Accumulated dust might cause fire or electric shock.

Do not install the device in locations that has oil smoke, steam, humidity, and dust.



Do not install the scanner in locations subject to oil smoke, steam, humidity, and dust. Doing so might cause a fire or electric shock.

Turn the scanner OFF if it is damaged.



If the scanner is damaged for any reason, disconnect immediately the power plug in order to turn out the scanner. Contact the store where you purchased the scanner.

Do not put liquids inside the scanner.



Do not insert or drop metal objects in to the scanner. Do not scan wet documents or documents with paper clips or staples. Do not splash or allow the scanner to get wet.



If foreign objects (water, small metal objects, liquids, etc.) get inside the scanner, immediately turn off the scanner and disconnect the power plug from the power outlet, then contact the store where you bought the scanner or the Maintenance Service Center. Pay particular attention to this warning in households where there are small children.



Do not touch the inside of the scanner unless necessary.



Do not take apart or modify the scanner. The inside of the scanner contains high-voltage components. Touching these components might cause fire or electric shock.

Do not use the scanner if there is a strange odor.



If you detect excessive heat coming from the device or detect other problems such as smoke, strange smells or noises, disconnect immediately the power plug in order to turn out the scanner. Make sure that any smoke coming from it has stopped, before contacting the store where you bought the scanner or an authorized FUJITSU scanner service provider.



Do not install the scanner on unstable surfaces.



Make sure that the scanner is installed on a flat, level surface and that none of its parts extend beyond the surface top, such as a desk or table. Do not install the scanner on unstable surfaces. Install the scanner on a level surface that is free of vibration to prevent it from falling.

Install the scanner on a strong surface that will support the weight of the scanner and other devices.

Do not block the ventilation ports.



Do not block the ventilation ports. Blocking the ventilation ports generates heat inside of scanner, which may results in fire or scanner failure.

Do not place heavy objects or stand on top of the scanner.



Do not place heavy objects on the scanner or use the scanner's surface top to perform other work. Improper installation might cause injuries and equipment failure.

Firmly insert the power plug.



Firmly insert the power plug as far it can go into the power outlet.

Avoid any contact when scanner is in use.



Avoid touching any scanner mechanism during scanning since this may cause injuries.

Do not use the scanner immediately after moving it from a cold place into a warm room.



Do not use the device immediately after moving it from a cold place into a warm room. This may cause condensation, which might lead to scanning errors. Let the device dry about one or two hours before you use it.

Before moving the scanner, disconnect the power plug from the power outlet.



Do not move the scanner with the power and interface cables connected as this might damage the cables, causing fire, electric shock or injuries. Before moving the scanner, be sure to disconnect the power plug from the power outlet, and all other data cables. Make sure that the floor is free of any obstruction.

Protect the scanner from static electricity.



Install the scanner away from strong magnetic fields and other sources of electronic noise. Also, protect the scanner from any static electricity as this might cause the scanner to malfunction.

Do not use aerosol sprays near the scanner.



Do not use aerosol sprays to clean the scanner. Aerosol sprays cause dirt and dust to enter the scanner, resulting scanner failure and malfunction.

Disconnect the power plug from the power outlet when the scanner is not used for a long period of time.



When the scanner is not going to be used for a long period of time, be sure to disconnect the power plug from the power outlet for safety.

Do not install the scanner in the direct sunlight.



Do not install the scanner under direct sunlight or near heating apparatus. Doing so might cause excessive heat to build up inside the scanner, which can cause scanner trouble or even fire. Install the scanner in a well-ventilated location.

Before moving the scanner, make sure the shipping lock is locked.



When moving the scanner, be sure to lock the shipping lock in order to prevent damages to the scanner.

Chapter1



PREPARING THE SCANNER

1.1 Checking the Contents of the Scanner Package

When you unpack the scanner package, make sure that the package contains all the parts on the list included in the package.
If any parts are missing or defective, contact your scanner dealer or an authorized FUJITSU scanner service provider. Handle the scanner and accessories with care.


1.2 Names of Parts

This section describes the names of parts.



1.3 Operator panel

The operator panel is located on the front side of the scanner. The panel consists of a Function Number Display, four buttons and a LED.



Name		Function
Function Number Display (2)		Indicates the state of the scanner. The meaning of the numbers and alphabets indicated are explained later in this section.
Buttons	Function (1)	Changes the Function activated by the Send to button.
	Send to (3)	Launches the linked application software (*).
	Scan (4)	
	Power button (6)	Turns the scanner ON and OFF.
Power LED(5)		Lights when the scanner is turned ON.

*) About the settings on the launcher, refer to FUJITSU TWAIN32 scanner driver help and the "fi-5015C Operator's Guide" on the Setup CD-ROM.

■ Indications on the Function Number Display

The following shows the indications on the Function Number Display.

No.	Descriptions
8	Lights only one time upon turning on the scanner.
P	Indicates that the scanner has been turned ON and is being initialized.
0	Indicates that initialization will soon be completed.
1	Indicates that initialization has been completed successfully. This status is called "Ready Status".
U	Indicates that a temporary error (that users can solve) has occurred during the initialization or scanning of documents. "U" and an error number (0, 1, 9) are displayed alternately. Refer section "Temporary error" on page. AP-3. To return the scanner to the ready status ("1"), press the "Scan" or "Send to" button while the error is indicated. Refer section "Temporary error" on page. AP-3.
E	Indicates that a device alarm (that users can not solve) has occurred during the initialization or scanning of documents. "E" and an alarm number (0, 2, 7, b, c, d) are indicated alternately. To return the scanner to the ready status ("1"), press "Scan" or "Send to" button. If this alarm occurs, turn the power off and then on again. If the alarm is indicated after turning on the power again, contact your service engineer.


Chapter2 INSTALLATION OF THE SCANNER

2.1 Installing the Scanner Application

For scanning documents with this scanner, both scanner driver and image capturing application software (called "application" hereafter) must be installed on your PC. The following scanner drivers and applications are provided:

- Scanner Driver:
FUJITSU TWAIN 32 Scanner Driver
FUJITSU ISIS Scanner Driver
- Scanning application:
ScandAll 21 (for FUJITSU TWAIN 32)
QuickScan Pro™ (Trial) (for FUJITSU ISIS)

Install the appropriate scanner driver for the application you will use. The following sections describe installation of each driver and application.




Please install the scanner driver before connecting the scanner to your PC. If you connect the scanner before installing the scanner driver, the scanner will not operate correctly. If you have connected the scanner beforehand, the "Found New Hardware Wizard" screen appears (this screen might differ slightly according to the used OS). On this screen, click the [Cancel] button to close the Wizard screen and install the scanner driver first.

For FUJITSU TWAIN32 Scanner Driver

■ Preparation


Confirm the following items before installing the application.

- Take out the Setup CD-ROM from its package, but do not insert the Setup CD-ROM into the CD driver yet.
- Uninstall any older version of FUJITSU TWAIN 32 driver if already installed.




Uninstall [Scanner Utility for Microsoft Windows] from [Add/Remove Programs] of the control panel.

■ Installing the FUJITSU TWAIN32 Scanner Driver




Windows XP screenshots are used in this section as examples. The windows and operations may slightly vary depending on your OS.

1. Turn on your PC and log on to Windows.




When using Windows 2000 or Windows XP, log on as a user with "Administrator" privileges.

2. Insert the Setup CD-ROM into the CD drive.
⇒ <SETUP DISK START UP SCREEN> appears.



This screen may not appear when the "Autoplay" setting of your PC is OFF. In this case, run "Install.exe" in this CD-ROM directly from the "Explorer" or "My Computer".

3. Click [INSTALL PRODUCTS].



4. Click [TWAIN Driver] on the window below.



5. Error Recovery Guide Installation window appears.
Error Recovery Guide is a software that displays troubleshooting information on screen when any scanner error occurs. Although this software's installation is highly recommended, it can be installed later if you do not install it in this step.




When you select [Yes] for installing the Error Recovery Guide, [Choose Setup Language] window appears. Select a language and follow the instructions on the window. Error Recovery Guide will automatically continue finishing its installation. Please wait until the installation of TWAIN driver automatically starts.



6. Select a language used for installation on [Choose Setup Language] window and click [OK].



7. Follow the instructions on the window to install the application.
8. When the [InstallShield Wizard Complete] window appears, click [Finish].



Your computer will be restarted.
Do not remove the Setup CD-ROM from the CD drive until your PC has completely restarted.
Installation of the scanner driver is completed.

■ Installing ScandAll 21


"Scandall 21" is an image capturing software that complies with the TWAIN standard.



When using Windows 2000 or Windows XP, log on as a user with "Administrator" privileges.



1. Insert the Setup CD-ROM into the CD drive.
⇒ <SETUP DISK START UP SCREEN> appears.
2. Click [INSTALL PRODUCTS].



3. Click [ScandAll 21] on the window below.





4. Select a language used for installation on [Choose Setup Language] window and click [OK].



5. Install the application following the instructions on the window.

- When the [InstallShield Wizard Complete] window appears, click [Finish].




For FUJITSU ISIS Scanner Driver


■ Preparation

Take out the Setup CD-ROM from its package, but do not insert the Setup CD-ROM into the CD drive yet.


■ Installing the FUJITSU ISIS Scanner Driver




- Turn your PC on and log on to Windows.



- Insert the "Setup CD-ROM" into the CD drive.
⇒ <SETUP DISK START UP SCREEN> appears.




- Click [INSTALL PRODUCTS].



- Click [ISIS Driver] on the window below.



- Error Recovery Guide Installation window appears.
Error Recovery Guide is a software that displays troubleshooting information on screen if any scanner error occurs. Although this software's installation is highly recommended, it can be installed later if you do not install it in this step.



- Select a language used for installation on [Choose Setup Language] window and click [OK].



7. Follow the instructions on the window to install the application.
8. When the [InstallShield Wizard Complete] window appears, click [Finish].

Your computer will be restarted. Do not remove the Setup CD-ROM from the CD drive until your PC has completely restarted.
Now the installation of the scanner driver is completed.

■ Installing QuickScan Pro™ (Trial)


"QuickScan Pro™ (Trial)" is an image capturing software that complies with the ISIS standard.



- When using Windows 2000 or Windows XP, log on as a user with "Administrator" privileges.



1. Insert the Setup CD-ROM into a CD drive.
⇒ <SETUP DISK STARTUP SCREEN> appears.
2. Click [INSTALL PRODUCTS].




3. Click [QuickScan PRO (Trial)] on the window below.



4. Continue to install the application following the instructions on the window.



5. Enter the required information, then click [Next >] button.



"QuickScan Pro™" included in the Setup CD-ROM is a trial version. For further use after the expiration of its trial period of up to 30 launches, it is necessary to purchase a fully functional version of QuickScan Pro™. (When you install the trial version, do not change the Serial Number already displayed.)



6. Install the application following the instructions on the window.


Error Recovery Guide

Error Recovery Guide is a software that displays troubleshooting information on screen if any scanner error occurs.

If you did not install together the Error Recovery Guide with the driver, please proceed with the procedures given below for installing it.

1. Insert the Setup CD-ROM in your CD drive.
The <SETUP DISK STARTUP SCREEN> will appear.

- Click [Install Products].



- Click [Error Recovery Guide] on the next screen.



- Select a language to use for the installation in the <Choose Setup Language> window and click [OK].



- Install the application following the instructions in the window.
- When the [InstallShield Wizard Complete] screen displays, click [Finish].



Image Processing Software Option (Trial)

For details on the installation of the Image Processing Software Option, refer to the "Image Processing Software Option USER'S GUIDE".

Adobe® Acrobat®

Install Adobe Acrobat from the "Adobe Acrobat CD-ROM" provided with this scanner.

ATTENTION Adobe Acrobat is not supported by Microsoft Windows 95, Microsoft Windows 98/98SE, Microsoft Windows NT4.0, Microsoft Windows Me.

HINT Adobe Acrobat is required for displaying the manuals stored in the CD-ROM.
* Installation of Adobe Acrobat is not necessary if it has already been installed in your PC.

- Insert the "Adobe Acrobat CD-ROM" into the CD-ROM drive.

⇒ The "Adobe Acrobat" window appears.

ATTENTION This window is not displayed automatically when the "Auto play" setting of your computer is deactivated. In this case, please run "Auto play.exe" of this CD-ROM directly from "Explore" or "My computer".


2. Select the language and Click [OK] button.



3. Select "Install Adobe Acrobat".



4. Click the [Next] button. The set up window appears.



5. Follow the instructions to install the software.



Select "How to install" on the "Adobe Acrobat" window to learn more about Adobe Acrobat installation. Refer to "Adobe Acrobat Help" about how to use Adobe Acrobat.



Notes for using Adobe Acrobat

When scanning a paper document and converting the image to PDF using Acrobat unexpected images may be output when:

1. Setting "Edge Shadow Removal" in Acrobat, and setting "Digital Endorser" or "Black Background" options in the TWAIN driver at the same time. Letter strings embedded in the image or the background may be missed.

Solution 1: Set "Edge shadow removal" to "OFF" or set any option other than "Adaptive" for "Color/Grayscale" and/or "Monochrome" under "Compression" by selecting [File]->[Create PDF]-> [From Scanner...]-> [Image Settings...] in Acrobat.

Solution 2: Adjust the scanning density in the TWAIN driver.

2. Setting "Adaptive" for "Color/Grayscale" and/or "Monochrome" under "Compression" in Acrobat and scanning in a resolution lower than the resolution recommended for Acrobat.

Solution: Set OPTION to something other than "Adaptive" under "Compression."

*As for detailed usage and information of Acrobat, refer to "Create a PDF file from a scanned document" in Acrobat Help.



Support and User registration for Adobe products:

Refer to the technical support information stored in the [Customer Support] folder on Adobe Acrobat CD-ROM. (Note that free person-to-person support is not available for this bundled product.)

Uninstalling Supplied Programs

Follow the procedure below to uninstall supplied programs.



Windows XP screenshots are used in this section. The windows and operations may slightly vary depending on your OS.

1. Start up your PC.



When using Windows NT 4.0, Windows 2000 or Windows XP, log on as a user with "Administrator" privileges (privileges of the administrator of your PC).

2. Exit all currently running programs.
3. Select [Control Panel] - [Add or remove Programs] from the [Start] menu.
 - ⇒ This displays the "Add or remove Programs" screen which displays a list of the currently installed applications.
4. Select the application to uninstall.
 - When uninstalling FUJITSU TWAIN 32 scanner driver, select "**Scanner Utility for Microsoft Windows**".
 - When uninstalling Scandall 21, select "**ScandAll 21**".
 - When uninstalling FUJITSU ISIS scanner driver, select "**Fujitsu ISIS Drivers**".
 - When uninstalling QuickScan Pro™, select "**QuickScan 3.0**".
 - When uninstalling Error Recovery Guide, select "**Error Recovery Guide**".
 - When uninstalling Image Processing Software Option, select "**Image Processing Software Option**".
 - When uninstalling Software Operation Panel, select "**Software Operation Panel**".



When uninstalling Adobe Acrobat, refer to the installation procedure described in the Adobe Acrobat CD-ROM.



5. Click the [Change/Remove] or [Remove] button.
6. When the confirmation dialogbox appears, Click the [OK] or [Yes] button.
 - ⇒ This executes the uninstallation.



Screen displays may vary slightly according to the operation system (OS) you are using. Follow the on screen instructions of the OS.

Example: When the OS Windows 2000

- "Add or Remove Programs" - "Add/Remove Applications"
- [Changel/Remove] button - [Add/Remove] button.



2.2 Installing the Scanner

After the computer has been restarted, connect the scanner.


1. Place the scanner at its installation site.

For details on the scanner's dimensions and required installation space, refer to "fi-5015C Operator's Guide" "Appendix A Installation Specifications" in the Setup CD-ROM.

2. Unlock the shipping lock

The carrier unit inside the scanner is fixed in place by the shipping lock to prevent the scanner from becoming damaged during transportation from factory.

After transporting and placing the scanner, release the shipping lock.



3. Installation of the ADF paper chute, Extension and Document stopper.

Attach Extension to ADF paper chuter, and then mount it on the scanner; attach Document stopper to the scanner.

ADF paper chute Extension Document stopper



4. Connect the ADF cable to the ADF cable connector on the scanner, and secure it with screws.



Screw


5. Connect the AC adapter.



Use only the AC adapter provided by the manufacturer.



- 1) Connect the AC cable to the AC adapter.



- 2) Connect the AC adapter connector to the scanner's DC inlet.



- 3) Plug the AC cable into the outlet.



The Function Number Display and the LED may flash for an instant when plugging the AC cable into the outlet.



2.3 Connecting the Scanner to Your PC

Follow the procedure below to connect the USB cable.

1. Connect the USB interface cable to the USB interface connector.



2. Connect the other end of the USB interface cable to the PC.



- Be sure to use the USB cable which comes as an accessory with this scanner. Correct operation with commercially available cables is not guaranteed.
- When connecting to an USB hub, use the first stage USB hub that is closest to the computer. If you use the second or later hub stages, the scanner may not operate correctly.
- If you connect the scanner with USB 2.0, it is required that the USB port and Hub are compliant with USB 2.0. The scanning speed may slow down if it is connected with USB1.1.



3. Press the "I" side of the main power switch to turn on the scanner.
4. Press the power button to turn ON the scanner.

Your scanner will be automatically detected.

For Windows 98:

When a request for inserting the CD-ROM for Windows 98 appears, insert it into the CD drive and click the [OK] button.

For Windows 2000:

When [Digital Signature not Found] appears, click [Yes].

The installation of the scanner is completed.

2.4 Confirming Installation

To confirm whether the installation was successful, perform a scanning operation with an application that complies with either the TWAIN regulations, such as ScandAll 21 or the ISIS regulations such as QuickScan Pro™.

■ Confirming with ScandAll 21

1. Load the documents on the scanner.


For details on loading documents, refer to "2.2 Loading Documents on the ADF for Scanning" in the fi-5015C Operator's Guide on the Setup CD-ROM.

2. Start ScandAll 21.


Select [Start] - [Programs] - [Scanner Utility for Microsoft Windows] - [ScandAll 21].

3. Specify the scanner (that you will use)



Select [Select Source...] from the [Scan] menu of ScandAll 21.



4. Select "FUJITSU fi-5015C" on the dialog box.




5. Select [To View...] from the [Scan] menu.
6. Set scanning resolution, document size, etc. on the [TWAIN driver] window (for setting details of scanning) and click the [Scan] button.



For details on [TWAIN driver], refer to the "FUJITSU TWAIN32 Scanner Driver User's Guide" provided in the Setup CD-ROM.

7. Documents are scanned, and the scanned images are displayed on the [ScandAll 21] window.



If the scanning completes without any trouble, the installation performed successfully.

For details on various types of scanning, refer to the "fi-5015C Operator's Guide" on the Setup CD-ROM.

■ Confirming with QuickScan Pro™

1. Load the documents on to the scanner.



For details on loading documents, refer to "2.2 Loading Documents on the ADF" in the fi-5015C Operator's Guide on the Setup CD-ROM.

2. Start QuickScan Pro™.


From the [Start] menu, select [Programs]-[Quick-Scan]-[QuickScan].

3. Select [Select Scanner...] from [Scan] menu in QuickScan Pro™.


And, select fi-5015C from the list of [Scanner:], and then click the [OK] button.



4. Select [Preview Settings...] from the [Scan] menu. Set the scan resolution, paper size and other scanning requirements, and then click [OK].



5. Select [Preview Scan] from the [Scan] menu. And then the document is scanned.



If the scanning completes without any trouble, the installation performed successfully.

Appendix1 TROUBLESHOOTING

■ Troubleshooting checklist

Symptom	Check this item	Remedy
Scanner does not turn on.	Is the main switch turned on?	Turn the main switch on.
	Have you pushed the power button?	Push the power button.
	Are the AC cable and AC adapter properly connected to the scanner?	Correctly connect the AC cable and the AC adapter.
		Disconnect the AC cable and the AC adapter from the scanner, then connect them again. If this does not restore the power supply, contact the store where you purchased the scanner or an authorized FUJITSU scanner service provider.
	Is Windows normally started up?	Push the power button again after completely starting up Windows.
Scanning does not start.	Are the documents loaded correctly on the ADF paper chute?	Load the document correctly on ADF paper chute.
	Is the ADF closed completely?	Close the ADF completely.
	Is the USB cable properly connected?	Correctly connect the cable. (When a USB hub is used, check the hub's power supply.)
	Does the Function Number Display indicate an alarm or an error?	When the Function Number Display indicates an alarm or an error, refer to the "Chapter 4. TROUBLESHOOTING" in the fi-5015C Operator's Guide for removing the alarm or the error.
	Does the alarm state remain displayed even after the scanner has been turned off and back on again?	Turn off and on the power button. If this does not eliminate the alarm state, contact the store where you purchased the scanner or an authorized FUJITSU scanner service provider.
Vertical lines appear in the generated image of the scanned image.	Is the glass dirty?	Clean the glass following the instructions in the Operator's Guide "3 Maintenance".
The generated image shifts or is distorted.	Are the documents loaded correctly?	Load the documents correctly.
Quality of generated image is unsatisfactory.	Are the glass or sheet guides (a white location) clean?	Clean dirty locations.
Multi feed frequently occurs. (*)	Do the documents satisfy the "Document Quality" in the section 2.2.1 of the fi-5015C Operator's Guide?	Scan the document by Flatbed.
	Are the documents set properly in the ADF paper chute?	Fan the documents before scanning. Correctly align the document stack and load them on the ADF paper chute. Refer to Section 2.2.2 of the fi-5015C Operator's Guide.
	Is the document stack thicker than 4mm?	Reduce the number of sheets in the document stack to 4 mm thickness or less.
	Is the Pad ASSY dirty?	Clean the Pad ASSY. Refer to the Operator's Guide "3.2.3 Cleaning the ADF".
	Is the Pad ASSY worn out?	Replace the Pad ASSY. Refer to the Operator's Guide "3.3.3 Replacing the Pad ASSY".

Symptom	Check this item	Remedy
Paper is not fed (pick error occurs frequently, or document stops midway).	Do the documents satisfy the "Document Quality" in Section 2.3.1 of the fi-5015C Operator's Guide?	Scan the document by Flatbed.
	Is the thick document placed on the Flatbed?	Is the thick document placed on the Flatbed?
	Is the Pick roller unit dirty?	Clean the Pick roller unit. Refer to the Operator's Guide "3.2.3 Cleaning the ADF".
	Is the Pick roller unit worn out?	Replace the Pick roller unit. Refer to the Operator's Guide "3.3.4 Replacing the Pick roller unit".
The generated images are elongated.	Are the Pick roller unit dirty?	Clean the Pick roller unit. Refer to the Operator's Guide "3.2.3 Cleaning the ADF".
There is a shadow on the leading edge of the generated image?	Are the Pick roller unit dirty?	Clean the Pick roller unit. Refer to the Operator's Guide "3.2.3 Cleaning the ADF".
	Have you adjusted the offset (the scanning starting position)?	Adjust the [Sub-scan Setting] on [Scanners and Cameras] in the control panel.

* "Multi feed" means that more than 2 papers are fed at the same time.

■ Temporary error

Indication	Description
U0	Shipping lock error occurred.
U1	A paper feed error occurred.
U9	ADF error.

The following shows the procedure for releasing of each temporary error.

- "U0" error
Confirm that the shipping lock is released.
Refer to "2.2 Installing the Scanner" (page 9)
- "U1" error
 1. Remove jammed documents.
(Refer to fi-5015C Operator's Guide "3.1 How to clear the paper jam" on the Setup CD-ROM.)
 2. Confirm that the documents meet the paper conditions for scanning.
(Refer to fi-5015C Operator's Guide "2.2.1 Checking document condition" on the Setup CD-ROM.)
- "U9" error
Turn off the scanner power. Confirm / Connect the ADF cable, then turn on the scanner power.
* Be sure of switching off the main switch, in case you make any operation with ADF cable.

■ Device alarm (Permanent error)

Indication	Description
E0	Flatbed motor malfunction.
E2	Trouble in the optical system.
E7	Trouble occurred in the internal memory (EEPROM).
Eb	An LSI error.
Ec	An error in the memory.
Ed	An error with USB

When you encounter any alarm, turn off and on the scanner. If the alarm is still displayed on the Function Number Display, contact the store where you purchased the scanner or an authorized FUJITSU scanner service provider.

Appendix2 DAILY CARE



When operating the scanner, the ADF's inside glass becomes very hot.
Before you clean inside the scanner, turn off its power and unplug the AC adapter from the outlet. Wait for at least 15 minutes.



Cleaning Materials

Cleaning Materials	Parts No.	Remarks
Cleaner F1 (or isopropyl alcohol)	CA99501-0013	1 bottle Moisten a cloth with this fluid and wipe the scanner clean.
Lint-free dry cloth	- Commercially available one	

For details about the cleaning materials, contact the FUJITSU scanner dealer where you purchased the scanner.

Cleaning Method

The ADF must be cleaned with a lint-free cloth moistened with the Cleaner F1.

Locations and Cycle for Cleaning

Part to clean	Standard Cleaning Cycle
Pad ASSY	Clean these parts after every 1,000 scans.
Pick roller unit	
Pinch roller	
Glass	



The scanner must be cleaned more frequently if you scan any of the following type of sheets:

- Documents of coated paper
- Documents that are almost completely covered with printed text or graphics
- Chemically treated documents such as carbonless paper
- Documents containing a large amount of calcium carbonate
- Documents written by pencil
- Documents with not enough fixed a toner.



For details on the cleaning the ADF, refer to "3.2 cleaning the ADF" in fi-5015C Operator's Guide on the Setup CD-ROM".

Appendix3 REPLACING CONSUMABLES



During its operation, the inside glass of the ADF becomes very hot .

Before replacing the consumables, turn its power off and unplug the AC adapter from the outlet. Wait at least 15 minutes.



■ Consumables and Replacement Cycle

The followings are the specifications of consumables and their recommended replacement cycles.

Description	Parts No.	Standard Replacement Cycle
Pad ASSY	PA03209-0550	After 20,000 scans or one year
Pick roller unit	PA03209-0551	After 100,000 scans or one year

To purchase consumables, contact the store where you purchased the scanner or an authorized FUJITSU scanner service provider.

The replacement cycles above are rough guidelines when using the following type of paper:
Woodfree paper or Plain paper.

This cycle varies according to the type of the used paper and how frequently the scanner is used and cleaned.




Use only the specified consumables.




The following illustrations show the locations of the consumables. Refer to "Chapter 4 Replacing Consumables" fi-5015C Operator's Guide on the Setup CD-ROM.

■ Replacing the Pad ASSY



Pad ASSY

■ Replacing the Pick Roller unit



fi-5015C Image Scanner Getting Started

P3PC-1582-01EN

Date of issuance: February, 2006

Issuance responsibility: PFU LIMITED

- Copying of the contents of this manual in whole or in part and copying of the scanner application is forbidden under the copyright law.
- The contents of this manual are subject to change without notice.
- PFU LIMITED is not liable whatsoever for any damages resulting from use of this scanner and procedures described in this manual, profit loss due to defects, and any claims by a third party.