

Data Sheet

Fujitsu Headphone TH series

Headphone

Accessories Headphone

Slim

Fujitsu Headphone include Microphone and support smart phone for Answer/end button call.

- (1). Convenient design for long term use
- (2). Answer/end button call
- (3). Comfortable earmuffs
- (4). 360-degree omni-directional microphone



Headphone Series

Part Number	HLHPH0002A-01	HLHPH0002B-01	HLHPH0002C-01
Color	Yellow	Blue	Red
Frequency Response	12Hz-22KHz	12Hz-22KHz	12Hz-22KHz
Impedance	38.0Ω±5.0%	38.0Ω±5.0%	38.0Ω±5.0%
Rated power/Mix input power	20.0(mW)/100.0(mW)	20.0(mW)/100.0(mW)	20.0(mW)/100.0(mW)
Channel balance	3.0 dB AT 1KHz	3.0 dB AT 1KHz	3.0 dB AT 1KHz
Insulation impedance	≥1MΩ	≥1MΩ	≥1MΩ
Average Sensitivity Output	100±3dB AT 1000Hz	100±3dB AT 1000Hz	100±3dB AT 1000Hz
Microphone Spec			
Impedance	2.2KΩ	2.2KΩ	2.2KΩ
Sensitivity	-48dB+3dB	-48dB+3dB	-48dB+3dB
Omnidirectional	Omni - Directional 360 degree	Omni - Directional 360 degree	Omni - Directional 360 degree
Current Consumption	Max 0.5mA	Max 0.5mA	Max 0.5mA
Plug type	3.5mm jack	3.5mm jack	3.5mm jack
Weight	133 g	133 g	133 g
Dimension	17(L)*14.5(W)*7(H) cm	17(L)*14.5(W)*7(H) cm	17(L)*14.5(W)*7(H) cm

Contact

Fujitsu PC Asia Pacific Ltd.
 Website: www.fujitsu.com/hk
 2014

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data illustrations are complete, actual or correct is excluded.
 Designations maybe trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
 For further information see www.fujitsu.com/terms
 Copyright © Fujitsu PC Asia Pacific Ltd.