LifeBook S2110

- Value-priced ultra-portable at less than 1.7kg*
- Health and Environment friendliness with RoHS¹² compliance
- Superb wireless performance with Super AG® 9/Super G® 9 network connection up to 108Mbps9
- Brilliant SuperFine display for excellent movie and picture viewing



	S2110 Recommended Configurations					
Processor	AMD Turion™ 64 MT-30	Mobile AMD Sempron™ 3000+				
	(1.60GHz, 1MB L2 cache, 1600MHz HTSB8)	(1.80GHz, 128K L2 cache, 1600MHz HTSB8)				
OS Supported	Windows® XP Home Edition					
	Windows® XP Professional					
Display	13.3" SuperFine XGA TFT, 1024 x 768 pixels					
Modular Bay Device	DVD/CD-RW Combo Drive					
Memory	512MB DDR 333MHz	256MB DDR 333MHz				
Hard Disk	80GB	40GB				
Battery	Up to 3.8hrs1 (6-cell Li-lon 5200mAh)	Up to 3.3hrs1 (6-cell Li-lon 5200mAh)				
Weight	Approx. 1.65kg (w/ Weight Saver Option)					
	Specifications					
Chipset	ATI RADEON® Xpress 200M + ATI SB400					
Max. Memory Supported	2GB DDR 333MHz					
Hard Disk Drive	Ultra ATA-100, S.M.A.R.T. support ⁵					
Graphics	ATI RADEON® Xpress 200M, selectable 16/32/64/128MB shared memory ¹¹ with PCI Express® 2D/3D graphics performance					
High Definition (HD) Audio	SigmaTel STAC9753 AC97 codec with built-in dual stereo speakers					
Communication	56K V.922 Global Modern MDC1.5, IrDA 1.1 4Mbps3, 100/10Mbps4 Fast Ethernet and Super AG®9 Vsuper G®9 wireless connection with Dual Antenna					
	Separate ON/OFF switch for wireless network connection					
User Interface	Keyboard: 84-key, 19mm key pitch, 3mm key stroke					
	Intelligent Touch Pad with configurable vertical and horizontal scroll functions					
	Scroll Buttons					
Card Slot	PC Card Type II, Smart Card support ⁵					
	Secured Digital/ Memory Stick PRO					
Connector Interface	USB 2.0 x 3, VGA (external display), RJ45 (LAN), RJ11 (modem), Mini S-Video out, IEEE1394, Microphone-in, Headphone-out, Power Adapter DC-in,					
	Port Replicator Interface					
Quick Launch Panel	Four Programmable Application Launch Buttons (Internet, Email and two other software)					
Media Playback Panel	Four Functions: Stop/Eject, Play/Pause, Next, Previous					
Security ⁶	BIOS Lock, Hard Disk Lock, Anti-theft Lock Slot, Smart Card support ⁵					
Dimensions	293mm (W) x 236.5mm (D) x 30.5mm min (H)					
	Bundled Accessories					
AC Adapter	Input AC 100~240V, Output DC 16V 60W					
Bundled Software	CyberLink PowerDVD™, CyberLink PowerProducer™ Gold, Sonic RecordNow™ DX, Sonic DLA, Adobe Acrobat Reader 6.0, Fujitsu Update Na					
	Fujitsu Hardware Diagnostic Tool, Fujitsu Display Manager					
Software on CD	1 year Full Licensed Norman Virus Control with Sandbox Technology, Norman Personal Firewall, Acronis True Image 8.0 Personal Edition					
	Optional Accessories					
Port Replicator	Connector Interface:					
	USB 2.0 x 2, VGA (external display), RJ45 (LAN), PS/2 (keyboard/mouse), Serial, Parallel, Power Adapter DC-in					
Modular Bay Options	Replaceable with					
	- Bay Battery, 6-cell Li-lon 3800mAh, up to 6.5hrs¹ battery life (Standard + Bay Batteries)					
	- Dual Layer DVD Super Multi Writer ⁷					
	- DVD/CD-RW Combo Drive					
	- Weight Saver					
Floppy Disk Drive	External USB 1.44MB FDD					
Mini S-Video Cable	Converts Mini S-Video out port to standard S-Video out port. Use a S-Video Cable for connection to a TV					
Mouse	USB Optical Scroll Mouse					

The above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

- Results obtained from Mobile Mark 2002 performed on systems with maximum battery life settings. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences. Modular Bay devices or hard drive usage may also have a significant impact on battery life. Note: Up to 6.5hrs batery life is based on AMD Turion™ 64MT-30 configuration with standard battery and bay battery.

- Maximum 56Kbps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.

 This term does not represent actual data rate of 4Mbps and simply indicates compliance with IrDA standard specification 1.1. Actual maximum data rate depends on local configurations and connected devices.

 This term does not represent actual data rate of 100/10Mbps and simply indicates compliance with IEEE 802.3, IEEE 802.3u and IEEE 802.3a standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices.
- cable conditions as well as commected devices.

 5 Smart Card support requires a Smart Card adapter for the PC Card Slot. This is available as an accessory. Fujitsu does not provide the application for Smart Card Solution.

 6 BIOS Lock needs a supervisor/user password to access BIOS setup. BIOS settings can be configured to prompt for password at every first bootup or all bootup sequences. Access to BIOS setup is needed to configure Hard Disk Lock. Hard Disk Lock requires an access key to retrieve data on the hard disk. This is a Data Confidentiality security feature. Anti-theft Lock Slot allows the use of a lock to physically secure the LifeBook. SmartCard usage is dependent on customer's solution.

 NOTE: Loss of password requires the LifeBook to be returned to Japan factory for system refresh. Cost of shipment and lost data will be borne by the customer.

 Supports DVD multi formats such as DVD-RAM, DVD-RAW, DVD-RW, DVD-

- of the system and its internal components.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5° to 35°C / 41 to 95°F (operating), -10° to 60°C / 14 to 140°F (non-operating). Relative humidity: 20% to 80% RH (operating and non-operating).

ATI, MOBILITY and RADEON are used under license and are registered trademarks of ATI Technologies Inc. in the United States and other countries.

Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.


Super G and Super AG are registered trademarks of Atheros® Communications. Inc











Dealei.		

Doolor

Information is correct at time of printing.

2005.

Pacific Pte Ltd in December

: 6312 • Printed by Fujitsu PC Asia

8

108

SINGAPORE: Fujitsu PC Asia Pacific Pte Ltd

Tel: (65) 6776 0688 Fax: (65) 6776 0788

MALAYSIA: Fujitsu PC Asia Pacific Pte Ltd

Tel: (60-3) 2093 3997 Fax: (60-3) 2093 4245

HONG KONG: Fujitsu PC Asia Pacific Ltd

Tel: (852) 3101 8133 Fax: (852) 3101 0633

THAILAND: Fujitsu Systems Business (Thailand) Ltd PC Division

Tel: (66-2) 263 7888 Fax: (66-2) 263 7880

AUSTRALIA & NEW ZEALAND: Fuiitsu PC Australia

Toll Free: 1800 288 283 Tel: (61-2) 8877 8500 Fax: (61-2) 9889 3360 www.lifebook.com.au

CHINA: Fujitsu PC China

Tel: (86-21) 3310 0808 Fax: (86-21) 3310 0606 www.pc-cn.fujitsu.com

PHILIPPINES: Fujitsu Philippines Inc.

Tel: (63-2) 812 4001 Fax: (63-2) 817 7576

TAIWAN: Fujitsu Taiwan Ltd

Tel: (886-2) 2311 2255 Fax: (886-2) 2311 2277

Fujitsu Vietnam Ltd

Tel: (84-4) 831 3895~7 Fax: (84-4) 831 3898

INDONESIA: PT Fujitsu Systems Indonesia

Tel: (62-21) 570 9330 www.fujitsu.com/id

listed above, please contact our Singapore office







^{*} with weight saver option