

LifeBook  
A3130

- Value-priced, full-featured 15.4-inch notebook
- Brilliant SuperFine Wide XGA display for excellent movie and picture viewing
- Comprehensive connectivity with USB 2.0 x 5, Secured Digital/ Memory Stick® PRO/ xD, PCMCIA Type I/II, ExpressCard™, IEEE1394 and S-Video out
- Health and environment friendliness with RoHS compliance<sup>8</sup>
- 7-button Easy-access Panel (Internet, Email, three other softwares, Volume Up, Volume Down)

	Specifications	
Platform	AMD Turion™ 64 X2 Mobile Technology TL-56 (1.80GHz, 512KB x 2 L2 cache, 1600MHz HTSB <sup>(2)</sup> )	Mobile AMD Sempron™ Processor 3400+ <sup>(5)</sup> (1.80GHz, 256KB L2 cache, 1600MHz HTSB <sup>(2)</sup> )
Operating System	Genuine Windows Vista™ Home Premium (or Genuine Windows Vista™ Home Basic)	
Display	15.4-inch SuperFine WXGA TFT, 1280 x 800 pixels (300nits Brightness, 350:1 Contrast Ratio, 45% Colour Gamut)	
Built-in Bay Device	Dual Layer Super Multi Writer™/ DVD/CD-RW Combo Drive	
Memory	1GB DDR2 667MHz Max. Memory Supported <sup>(1)</sup> - 4GB DDR2 667MHz, Dual-Channel	
Hard Disk	120GB SATA 5400rpm	
Battery	Up to 1.8hrs <sup>(1)</sup> (6-cell Li-Ion 4000mAh)	Up to 1.0hrs <sup>(1)</sup> (6-cell Li-Ion 4000mAh)
Weight	Approx. 2.9kg (w/ 6-cell battery)	
	Detailed Specifications	
Chipset	ATI Radeon® Xpress 1150 + SB450	
Hard Disk Drive	SATA-150 5400rpm, S.M.A.R.T support, Two Partitions - 50/50 <sup>(10)</sup> , protected by Fujitsu 3D Shock Sensor <sup>(4)</sup>	
Graphics	ATI Radeon® Xpress 1150, selectable 32/64/128/256MB shared memory <sup>(5)</sup> with PCI Express® 2D/3D graphics performance	
High Definition (HD) Audio	RealTek ALC262 HD audio codec with dual built-in stereo speakers HD Audio-in: External Mic-in HD Audio-out: Headphone-out	
Communication	56K V.92 <sup>(2)</sup> Global Modem MDC1.5, 1000/100/10Mbps <sup>(3)</sup> Gigabit Ethernet PCI Express x 1 and Super AG™/ Super G™ <sup>(4)</sup> wireless network connection with dual antenna. Separate ON/OFF switch for wireless connection, Bluetooth® v2.0 + EDR (Optional)	
User Interface	Spill-resistant Keyboard <sup>(9)</sup> : 86-key, 19mm key pitch, 2.7mm key stroke Intelligent Touch Pad <sup>(16)</sup> with configurable vertical and horizontal scroll functions Active Digitizer <sup>(16)</sup> (Optional)	
Card Slot	PCMCIA Type I/II, ExpressCard™ /34 /54 support Secured Digital/ Memory Stick®/ Memory Stick® PRO/ xD	
Connector Interface	USB 2.0 x 5, VGA (external display), RJ45 (LAN), RJ11 (modem), IEEE1394, S-Video out, HD Audio-in, HD Audio-out, Power Adapter DC-in	
Easy Access Panel	7-button Easy-access Panel (Internet, Email, three other softwares, Volume Up, Volume Down)	
Security <sup>(6)</sup>	BIOS Lock, Hard Disk Lock, Anti-theft Lock Slot, Fingerprint Sensor (Optional)	
Dimensions	360mm (W) x 265mm (D) x 39.3mm (H)	
	Bundled Accessories	
AC Adapter	Input AC 100~240V, Output DC 19V 80W	
Bundled Software	CyberLink PowerDVD™, CyberLink PowerProducer™, Roxio Easy Media Creator, Adobe Acrobat Reader, Fujitsu UpdateNavi <sup>(13)</sup> , Fujitsu Hardware Diagnostics Tool, Fujitsu Display Manager, Fujitsu 3D Shock Sensor Utility, Sun Microsystems Java Runtime	
Software on CD	1 year Full Licensed Norman Virus Control with Sandbox Technology and Norman Personal Firewall, Acronis True Image	
	Optional Accessories	
Floppy Disk Drive	External USB 1.44MB FDD	
Mouse	USB Optical Scroll Mouse	



The above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

- 1 Results obtained from BAFCO MobileMark2005 (Productivity Workload 2002SE) performed on systems with maximum battery life settings. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences. Built-in bay devices or hard drive usage may also have a significant impact on battery life. Note: Up to 1.8hrs battery life is based on AMD Turion™ 64 X2 Mobile Technology TL-56 configuration with standard 6-cell battery. Up to 1.0hrs battery life is based on Mobile AMD Sempron™ processor 3400+ configuration with standard 6-cell battery.
- 2 Maximum 56Kbps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.
- 3 This term does not represent actual data rate of 1000/100/10Mbps and simply indicates compliance with IEEE 802.3, IEEE 802.3u and IEEE 802.3ab standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices.
- 4 Super AG™ and Super G™ are trademarks of Atheros® Communications. Super AG™ and Super G™ modes deliver up to 108 Mbps raw data rate with typical end user throughput exceeding 60 Mbps in a wireless network environment where wirelessly connected equipment are using Atheros Super AG™ or Super G™ enabled chips.
- 5 Memory allocation (max. 256MB) can be pre-set in the BIOS setup for optimal graphics and system performance. The memory size available to the Operating System will be less than the total size of installed memory modules.
- 6 BIOS Lock needs a supervisor/user password to access BIOS setup. BIOS settings can be configured to prompt for password at every first bootup or all bootup sequences. Access to BIOS setup is needed to configure Hard Disk Lock. Hard Disk Lock requires an access key to retrieve data on the hard disk. This is a Data Confidentiality security feature. Anti-theft Lock Slot allows the use of a lock to physically secure the LifeBook. Fingerprint sensor uses AuthenTec TruePrint™ Technology and Softex OmniPass to remember customer list of user IDs and passwords. Full security unlock sequence - Bootup Lock (BIOS Lock), Hard Disk Lock, Fingerprint Windows Logon.
- NOTE: Loss of password requires the LifeBook to be returned to Japan factory for system refresh. Cost of shipment and lost data will be borne by the customer. Backup your user's profile before changing HDD. Without the user's profile associated with a document at the point of encryption, Softex OmniPass cannot decrypt the encrypted document. Loss of the Hard Disk Lock password means the HDD content cannot be retrieved. It is the customer's responsibility to ensure the safe keeping of the password for retrieval of data from the locked HDD.
- 7 Supports DVD multi formats such as DVD-RAM, DL DVD±R, DVD±RW, DVD±R, CD-RW, DVD-ROM, CD-R and CD-ROM.
- 8 RoHS (Restriction on Hazardous Substances) compliance means the system and its internal components comply with the EU RoHS directive (2002/95/EC) on the restricted use of six hazardous substances in the production of the system and its internal components.
- 9 Spill-resistant keyboard does not imply the system is water-proof. If liquid is spilt onto the keyboard, power off the system immediately and turn the notebook upside down to drain off the liquid.
- 10 This refers to Windows Vista™ hard disk drives C:\ and D:\. 50/50 refers to approximate 50% allocation of user accessible hard disk storage to C:\ and D:\ drives.
- 11 The system can support up to 4GB of physical memory, but the system will use up to only 3GB (1GB ~ 1024MB) accessible memory.
- 12 This is refers to HyperTransport™ System Bus (HTSB) up to 1600MHz full duplex.
- 13 UpdateNav is a Fujitsu Proprietary application that updates LifeBook drivers by connecting automatically to Fujitsu's server. This will help update your LifeBook with the latest software drivers and utilities to ensure compatibility between hardware and software, maintaining smooth operation anytime, anywhere.
- 14 Fujitsu 3D Shock Sensor of a powered-up unit retracts hard disk read-write head to a secured zone upon detection of excessive vibrations or shocks. This greatly reduces the possibility of damage to the hard disk and its contents - example in the event of a sudden drop or impact. The sensor monitors movement from three axes and its sensitivity can be adjusted by user to accommodate different working environments using the Fujitsu 3D Shock Sensor Utility.
- 15 This model number indicates relative software performance among Mobile AMD Sempron processors.
- 16 Touch Pad may come with Active Digitizer. Please check with your local distributor on the local configurations and bundled OS. For Active Digitizer models, it comes with Fingerprint Sensor.

ATI, MOBILITY and RADEON are used under license and are registered trademarks of ATI Technologies Inc. in the United States and other countries.

Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.

AMD, the AMD Arrow logo, AMD Turion, Mobile AMD Sempron and combinations thereof, are trademarks of Advanced Micro Devices, Inc.

Atheros, the Atheros logo, Super G and Super AG are registered trademarks of Atheros Communications.

PCI Express™ and the PCI Express design marks are registered trademarks and/or service marks of PCI-SIG.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discolored dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5° to 35°C / 41 to 95°F (operating), -15° to 60°C / 5 to 140°F (non-operating). Relative humidity: 20% to 85% RH (operating), 8% to 85% RH (non-operating). Please note that GB = billion bytes.