

## Fujitsu L1010

- 14.1-inch Wide Intel® Centrino® 2 Processor Technology at approximately 2.5kg
- Genuine Windows Vista® Business
- Instant converged communications using built-in 1.3 Mega Pixel camera and built-in microphones
- Superb 2D/3D graphics performance with NVIDIA GeForce 9300M GS Graphics\* and HDMI output
- High brightness SuperFine LCD<sup>18</sup> for perfect pictures and movie viewing
- Extended battery life for mobile computing by using ECO button
- Health and Environment friendliness with RoHS compliance<sup>10</sup>

\* Depends on the configurations.



Specifications		
Platform	Intel® Centrino® 2 Processor Technology - Intel® Core™2 Duo Processor P8700 <sup>1</sup> - Intel® PM45 Express Chipset - Intel® WiFi Link 5300AGN (3x3) network connection	Intel® Centrino® Processor Technology - Intel® Core™2 Duo Processor T6500 <sup>3</sup> - Intel® PM45 Express Chipset - Intel® WiFi Link 5100AGN (1x2) network connection
Operating System	Genuine Windows Vista® Business (or Genuine Windows Vista® Home Premium) (or Genuine Windows Vista® Home Basic)	
Display	14.1-inch SuperFine WXGA LCD <sup>18</sup> , 1280 x 800 pixels	
Modular Bay Device	Dual Layer DVD Super Multi Writer <sup>2</sup>	
Memory <sup>14</sup>	2GB DDR3 1066MHz	1GB DDR3 1066MHz
Hard Disk	320GB	
Battery	Up to 3.5 hrs <sup>1</sup> (6-cell Li-Ion 5200mAh)	
Weight	Approx. 2.5kg	
<b>Detailed Specifications</b>		
Hard Disk Drive	SATA-150 5400rpm, S.M.A.R.T support, Two Partitions - 50/50 <sup>13</sup>	
Graphics	NVIDIA GeForce 9300M GS with Total Available Graphics Memory <sup>6</sup> of 1023MB	
High Definition (HD) Audio	RealTek ALC269 HD audio codec with dual built-in stereo speakers HD Audio-in: External Mic-in, Built-in Microphone HD Audio-out: Headphone-out	
Communication	1.3 Mega Pixel camera, Bluetooth® v2.1+EDR, 56K V.92 <sup>2</sup> Global Modem MDC1.5, 1000/100/10Mbps* Gigabit Ethernet PCI Express® x 1 and Intel® WiFi Link 5300AGN (3x3) network connection with three antenna. Separate ON/OFF switch for wireless network connection	1.3 Mega Pixel camera, Bluetooth® v2.1+EDR, 1000/100/10Mbps* Gigabit Ethernet PCI Express® x 1 and Intel® WiFi Link 5100AGN (1x2) network connection. Separate ON/OFF switch for wireless network connection
User Interface	Spill-resistant Keyboard <sup>12</sup> : 84-key, 19mm key pitch, 2.7mm key stroke Intelligent Touch Pad with configurable vertical and horizontal scroll functions Fingerprint Sensor with vertical scroll functions	
Card Slots	ExpressCard™/34, Secured Digital/SDHC/ Memory Stick®/ Memory Stick® PRO	
Connector Interface	USB 2.0 x 3, VGA (external display), RJ45 (LAN), RJ11 (modem), IEEE1394, HDMI out, HDA-in, HDA-out, Power Adapter DC-in	USB 2.0 x 3, VGA (external display), RJ45 (LAN), IEEE1394, HDMI out, HDA-in, HDA-out, Power Adapter DC-in
Quick Launch Panel	Five Programmable Application Launch Buttons (Support, Internet, Mail, ECO and Camera)	
Security <sup>8</sup>	BIOS Lock, Hard Disk Lock, Anti-theft Lock Slot, Fingerprint Sensor	
Dimensions	339mm (W) x 250mm (D) x 39mm (H)	
<b>Bundled Accessories</b>		
AC Adapter	Input AC 100-240V, Output DC 19V 80W	
Bundled Software	Softex Omnipass, CyberLink PowerDVD™, CyberLink PowerDirector™, Roxio Easy Media Creator, Adobe Acrobat Reader, Fujitsu UpdateNavi <sup>15</sup> , Fujitsu 3D Shock Sensor Utility, Fujitsu Power Saving Utility, Fujitsu Hardware Diagnostic Tool, Fujitsu Display Manager, Sun Microsystems Java Runtime, Microsoft Office Professional 2007 60-day Convertible Trial <sup>16</sup>	
Other Software	1 year Full Licensed Norman Virus Control with Sandbox Technology and Norman Personal Firewall, Acronis True Image, ArcSoft WebCam Companion™ 2	
<b>Optional Accessories</b>		
Floppy Disk Drive	External USB 1.44MB FDD	
Mouse	Optical USB Black Mouse (Retractable)	

The above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

### Disclaimers:

- Results obtained from EAPCo's MobileMark™2007/Productivity Workload performed on systems with maximum battery life settings under laboratory testing environment. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences in the real life situation. Built-in bay device or hard drive usage may also have a significant impact on battery life. Note: Battery life is based on Intel® Core 2 Duo Processor P8700.
- Maximum 56Kbps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.
- Please check actual bundling with country local distributor. P8700 refers to (2.53GHz, 3MB L2 cache, 1466MHz), T6500 refers to (2.1GHz, 2MB L2 cache, 800MHz).
- This term does not represent actual data rate of 1000/100/10Mbps and simply indicates compliance with IEEE 802.3, IEEE 802.3u and IEEE 802.3ab standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices.
- Maximum shared memory depends on system memory capacity and system configuration. 313MB refers to 1GB system memory capacity.
- 1023MB Total Available Graphics Memory is available on 2GB system memory. It refers to a total of 256MB dedicated video memory and 767MB shared system memory. The memory size available to the Operating System will be less than the total size of the installed memory modules.
- Dynamic Video Memory Technology (DVMT) dynamically responds to application requirements and efficiently allocates the proper amount of memory (max. 1759MB for 4GB system memory) for optimal graphics and system performance. The memory size available to the Operating System will be less than the size of installed memory module.
- BIOS Lock needs a supervisor/user password to access BIOS setup. BIOS settings can be configured to prompt for password at every first bootup or all bootup sequences. Access to BIOS setup is needed to configure Hard Disk Lock. Hard Disk Lock requires an access key to retrieve data on the hard disk. This is a Data Confidentiality security feature. Anti-theft Lock Slot allows the use of a lock to physically secure the notebook. Fingerprint Sensor uses AuthenTec TruePrint™ Technology and Softex OmniPass to remember customer list of user IDs and passwords.
- NOTE: Loss of password requires the notebook to be returned to Japan factory for system refresh. Cost of shipment and lost data will be borne by the customer. Backup your user's profile before changing HDD. Without the user's profile associated with a document at the point of encryption, Softex OmniPass cannot decrypt the encrypted document.
- Supports DVD multi formats such as DVD-RAM, DL DVD-R, DVD-RW, DVD+R, CD-RW, DVD-ROM, CD-R and CD-ROM.
- RoHS (Restriction on Hazardous Substances) compliance means the system and its internal components comply with the EU RoHS directive (2002/95/EC) on the restricted use of six hazardous substances in the manufacture of the system and its internal components.
- Intel® Clear Video Technology is a combination of video processing hardware and software technologies that delivers enhanced high-definition video playback, sharper images, precise colour control and advanced support for a wide range of digital displays interfaces, including High-Definition Multimedia Interface (HDMI).
- Spill-resistant Keyboard does not imply the system is water-proof. If liquid is spilled onto the keyboard, power off the system immediately and turn the notebook upside down to drain off the liquid.
- 4GB DDR3 1066MHz max. memory is supported when Fujitsu recommended 2GB DDR3 1066MHz memory module is made available.
- UpdateNavi is a Fujitsu Proprietary application that updates notebook drivers by connecting automatically to Fujitsu's server. This will help update your notebook with the latest software drivers and utilities to ensure compatibility between hardware and software, maintaining smooth operation anytime, anywhere.
- Microsoft Office Professional 2007 60-day Convertible Trial needs online activation to begin. 60-day starts from day of activation.
- Atheros® and the Atheros® logo are registered trademarks of Atheros Communications, Inc. Signal-Sustain Technology (SST), XSPAN™ and XSPAN™ logo are trademarks of Atheros® Communications, Inc. Atheros XSPAN™ 802.11ABGN deliver up to 300Mbps raw data rate with typical end user throughput between 150Mbps to 180Mbps in a wireless network environment where wirelessly connected equipment are using the Atheros XSPAN-enabled technology products. SST (Signal-Sustain Technology) is the technology developed to more effectively sustain the 802.11n radio signals, and connections, resulting in very high connection reliability and greater coverage area.
- It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discolored dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

\*PCI Express™ and the PCI Express design marks are registered trademarks and/or service marks of PCI-SIG. Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5° to 35°C / 41 to 95°F (operating), -15° to 60°C / 5 to 140°F (non-operating). Relative humidity: 20% to 85% RH (operating), 8% to 85% RH (non-operating). Please note that GB = billion bytes, 1GB is equivalent to 1,073,741,824 bytes.

Note: For countries not listed above, please contact our Hong Kong office.

All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or license save in so far as may be expressly agreed.

**HONG KONG (Head Office):**  
Fujitsu PC Asia Pacific Ltd  
Tel : (852) 3101 8133  
Fax : (852) 3101 0633  
hk.fujitsu.com/pc

**CHINA:**  
Fujitsu PC China Division  
Tel : (86-21) 3310 9888  
Fax : (86-21) 3310 0606  
cn.fujitsu.com/pc

**TAIWAN:**  
Fujitsu Taiwan Ltd  
Tel : (886-2) 2311 2255  
Fax : (886-2) 2311 2277  
tw.fujitsu.com/pc

**VIETNAM:**  
Fujitsu Vietnam Ltd  
Tel : (84-4) 831 3895  
Fax : (84-4) 831 3898  
vn.fujitsu.com/pc

**THAILAND:**  
Fujitsu Systems  
Business(Thailand) Ltd  
PC Division  
Tel : (66-2) 263 7888  
Fax : (66-2) 263 7880  
th.fujitsu.com/pc

**MALAYSIA:**  
Fujitsu PC Asia Pacific Pte Ltd  
Tel : (60-3) 7728 4868  
Fax : (60-3) 7728 4830  
my.fujitsu.com/pc

**SINGAPORE:**  
Fujitsu PC Asia Pacific Pte Ltd  
Tel : (65) 6776 0688  
Fax : (65) 6776 0788  
sg.fujitsu.com/pc

**INDONESIA:**  
Fujitsu Indonesia  
Tel : (62-21) 570 9330  
Fax : (62-21) 573 5150  
id.fujitsu.com/pc

**PHILIPPINES:**  
Fujitsu Philippines Inc.  
Tel : (63-2) 812 4001  
Fax : (63-2) 817 7576  
ph.fujitsu.com/pc

**AUSTRALIA & NEW ZEALAND:**  
Fujitsu PC Australia  
Toll Free: (AU) 1800 288 283  
(NZ) 0800 288 283  
Fax : (61-2) 9889 3360  
au.fujitsu.com/pc

Dealer: