THE POSSIBILITIES ARE INFINITE

LifeBook A3110

- Value-priced, full-featured 15.4-inch notebook
- · Brilliant SuperFine Wide XGA display for excellent movies and pictures viewing
- Comprehensive connectivity with USB 2.0 x 3, Secured Digital/ Memory Stick®/ Memory Stick® PRO/ xD,
- PC card, ExpressCard™, IEEE1394 and S-Video out
- Health and environment friendliness with RoHS compliance8
- Windows Vista[™] Capable¹⁴

AUSTRALIA & NEW ZEALAND: Fujitsu PC Australia Toll Free: 1800 288 283 Tel : (61-2) 8877 9500 Fax : (61-2) 9889 3360 www.lifebook.com.au

CHINA: Fujitsu PC China Division Tel : (86-21) 3310 0808 Fax : (86-21) 3310 0606 cn.fujitsu.com/pc HONG KONG: Fujitsu PC Asia Pacific Ltd Tel : (852) 3101 8133 Fax : (852) 3101 0633

INDIA:

Fujitsu India Limited Tel : (91-11) 2370 6070 Fax : (91-11) 2370 6079 INDONESIA:

Fujitsu Indonesia Tel : (62-21) 570 9330 Fax: (62-21) 573 5150 MALAYSIA:

Fujitsu PC Asia Pacific Pte Ltd Tel : (60-3) 2093 3997

Fujitsu PC Asia Pacific Pte Ltd

TAIWAN:

VIETNAM: Fujitsu Vietnam Ltd Tel : (84-4) 831 3895 Fax : (84-4) 831 3898

Note: For countries not

listed above, please contact our Singapore office.

Tel : (65) 6776 0688

Fax : (65) 6776 0788

Fujitsu Taiwan Ltd Tel : (886-2) 2311 2255 Fax : (886-2) 2311 2277 THAILAND: Fujitsu Systems Business (Thailand) Ltd PC Division Tel : (66-2) 263 7888 Fax : (66-2) 263 7880

Fax: (60-3) 2093 4245 PHILIPPINES: Fujitsu Philippines Inc. : (63-2) 812 4001 Fax : (63-2) 817 7576 SINGAPORE:



| | Recommended Configurations | |
|-------------------------------------|---|---|
| Platform | AMD Turion [™] 64 X2 Mobile Technology TL-50 | Mobile AMD Sempron [™] processor 3200+ ¹⁶ |
| | (1.60GHz, 256KB x 2 L2 cache, 1600MHz HTSB ¹²) | (1.60GHz, 512KB L2 cache, 1600MHz HTSB ¹²) |
| OS Supported | Genuine Windows® XP Professional | |
| | (or Genuine Windows [®] XP Home Edition) | |
| Display | 15.4-inch SuperFine WXGA TFT, 1280 x 800 pixels | |
| Built-in Bay Device | Dual Layer Super Multi Writer ⁷ / DVD/ CD-RW Combo Drive | |
| Memory | 512MB DDR2 667MHz | |
| Hard Disk | 80GB | |
| Battery | Up to 1.9hrs ¹ (4-cell Li-ion 2000mAh) | Up to 2.0hrs1 (4-cell Li-ion 2000mAh) |
| | Up to 3.1hrs ¹ (6-cell Li-ion 4000mAh) | Up to 3.2hrs1 (6-cell Li-ion 4000mAh) |
| Weight | Approx. 2.75kg (w/ 4-cell battery) | |
| | Specifications | |
| Chipset | ATI Radeon® Xpress 1150 + SB450 | |
| Max. Memory Supported ¹¹ | 4GB DDR2 667MHz, Dual Channel | |
| Hard Disk Drive | Ultra ATA-100, S.M.A.R.T support, Two Partitions - 50/50 ¹⁰ , protected by Fujitsu 3D Shock Sensor ¹⁵ | |
| Graphics | ATI Radeon [®] Xpress 1150, selectable 32/64/128/256MB shared memory ⁵ with PCI Express 2D/3D graphics performance | |
| High Definition (HD) Audio | RealTek ALC262 HD audio codec with dual built-in stereo speakers | |
| | HD Audio-in: External Mic-in, Line-in | |
| | HD Audio-out: Headphone-out, Line-out | |
| Communication | 56K V.92 ² Global Modern MDC1.5, 1000/100/10Mbps ³ Gigabit Ethernet PCI Express x 1 and Super AG [™] / Super G ^{™ 4} wireless connection with dual antenn | |
| | Separate ON/OFF switch for wireless network connection, Bluetooth® v2.0 (optional) | |
| User Interface | Spill-resistant Keyboard ⁹ : 87-key, 19mm key pitch, 2.7mm key stroke | |
| | Intelligent Touch Pad with configurable vertical and horizontal scroll functions | |
| Card Slot | PC Card Type II, ExpressCard [™] / 34/ 54 support | |
| | Secured Digital/ Memory Stick® / Memory Stick® PRO/ xD | |
| Connector Interface | USB 2.0 x 3, VGA (external display), RJ45 (LAN), RJ11 (modem), S-Video out, IEEE1394, HD Audio-in, HD Audio-out, Power Adapter DC-in | |
| Quick Launch Panel | Four Programmable Application Launch Buttons (Internet, Email and two other softwares) | |
| Security ⁶ | BIOS Lock, Hard Disk Lock, Anti-theft Lock Slot, Fingerprint Sensor (optional) | |
| Dimensions | 360mm (W) x 265mm (D) x 37.8mm (H) | |
| | Bundled Accessories | |
| AC Adapter | Input AC 100~240V, Output DC 19V 80W | |
| Bundled Software | CyberLink PowerDVD™, CyberLink PowerProducer™, Roxio Easy Media Creator, Sonic DLA, Adobe Acrobat Reader 6.0, Fujitsu UpdateNavi13, | |
| | Fujitsu Hardware Diagnostic, Fujitsu Display Manager, Fujitsu 3D Shock Sensor Utility, Fujitsu FlashAid, Sun Microsystems Java Runtime | |
| Software on CD | 1 year Full Licensed Norman Virus Control with Sandbox Technology and Norman Personal Firewall | |
| | Optional Accessories | |
| Floppy Disk Drive | External USB 1.44MB FDD | |
| Mouse | USB Optical Scroll Mouse | |

The above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

- 4

- above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors. Results obtained from BAPCO MobileMark2002 (Reader Workkad) performed on systems with maximum battery life settings. Actual battery life with availability applications, connected peripherals, power management settings, battery confitioning, and other customer preferences. Built have drive usage may also have a significant integration battery. Up to 3. This battery life is based on AMD Turion[™] 64 X2 TL-50 Mobile Technology TL-50 configuration with standard 4-cell battery. Up to 3. This battery life is based on AMD Turion[™] 64 X2 TL-50 Mobile Technology TL-50 configuration with standard 4-cell battery. Up to 3. This battery life is based on AMD Turion[™] 64 X2 TL-50 Mobile Technology TL-50 configuration with standard 4-cell battery. Up to 3. This battery life is based on AMD Turion[™] 64 X2 TL-50 Mobile Technology TL-50 configuration with standard 4-cell battery. Up to 3. This battery life is based on AMD Turion[™] 64 X2 TL-50 Mobile Technology TL-50 configuration with standard 4-cell battery. Up to 3. This battery life is based on AMD Turion[™] 64 X2 TL-50 Mobile Technology TL-50 configuration with standard 4-cell battery. Up to 3. This battery life is based on AMD Turion[™] 46 X2 TL-50 Mobile Technology TL-50 configuration with standard 4-cell battery. Up to 3. This battery life is based on AMD Turion[™] 46 X2 TL-50 Mobile Technology TL-50 configuration with standard 4-cell battery. Up to 3. This battery life is based on AMD Turion[™] 46 X2 TL-50 Mobile Technology TL-50 configuration with standard 4-cell battery. Up to 3. This battery life with standard 5-cell battery. Up to 3. This battery life battery under Hard Dack Security. If HDD Lock prompt is enabled, only the User Password can be used to boot up the unit. Loss of these 2 passwords means the HDD content cannot be retrieved. It is the outsome's responsibility to ensure the asile keeping of these 2 passwords means the HDD content cannot be retrieved. It is the outsome's responsibility to ensure the asile keeping of these 2 passwords means the HDD content cannot be retrieved. It is the outsome's responsibility to ensure the asile keeping of these 2 passwords means the HDD content cannot be retrieved. It is the outsome's responsibility to ensure the asile keeping of these 2 passwords means the HDD content cannot be retrieved. It is the outsome's responsibility to ensure the asile keeping of these 2 passwords means the HDD content cannot be retrieved. It is the outsome's responsibility to ensure the asile keeping of these 2 passwords means the HDD content cannot be retrieved. It is the outsome's responsibility to ensure the asile keeping of these 2 passwords means the HDD content cannot be retrieved. It is the outsome's the production of the system and its internal compones 4 password does not imply the system is wateryoot. If key it is splt onto the keybaad, power off the system immediately and turn the noteboot upside down to drain off the liqud.
 This referse to Hypor/masport WS subschede (Sourd DA) Soft for the system and its internal compones 4 DG DDP2 667MHz maximum memory is supported when fujits uncommended 2GB DDP2 667MHz memory module is made available.
 UndateNavi is a Fujitsu Pontenav application that updates UseBook drivers by connecting automatically to Fujitsu's server. This will help update your LifeBook with the latest software drivers and utilities to ensure compatibility between hardware and software, maintaining amond paratine and findsor Mindows Vista Capable PCA. All Windows Vista Capable PCA will nut the core experiences of Wridows Vista, such as inovations in organizing and finding information, se

ATI, MOBILITY and RADEON are used under license and are registered trademarks of ATI Technologies Inc. in the United States and other countries.

Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.

AMD, the AMD Arrow logo, AMD Turion, Mobile AMD Sempron and combinations thereof, are trademarks of Advanced Micro Devices, Inc.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5° to 35°C / 41 to 95°F (operating), +15° to 60°C / 5 to 140°F (inon-operating), file of the Interview. []. Please note that [[]. Eliable hundity: (25% to 55% H (porc) perating]. Please note that [[]. Eliable hundity: (25% to 55% H (porc) perating]. Please note that [[]. Eliable hundity: (25% to 55% H (porc) perating]. Please note that [[]. Eliable hundity: (25% to 55% H (porc) perating]. Please note that [[]. Eliable hundity: (25% to 55% H (porc) perating]. Please note that [[]. Eliable hundity: (25% to 55% H (porc) perating]. Please note that [[]. Eliable hundity: (25% to 55% H (porc) perating]. Please note that [[]. Eliable hundity: (25% to 55% H (porc) perating]. Please note that [[]. Eliable hundity: (25% to 55% H (porc) perating]. Please note that [[]. Eliable hundity: (25% to 55% H (porc) perating]. Please note that [[]. Eliable hundity: (25% to 55% H (porc) perating]. Please note that [[]. Eliable hundity: (25% to 55% H (porc) perating]. Please note that [[]. Please not that [[]. Please note that [[]. Please not

www.pc-ap.fujitsu.com

All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed. as may be expressly agreed.

Dealer: