

LifeBook A6020

- Value-priced, full-featured 15.4-inch notebook
- Brilliant SuperFine Wide XGA display for excellent movie and picture viewing
- Comprehensive connectivity with USB 2.0 x 5, Secured Digital/Memory Stick®/Memory Stick® PRO/xD, PC card Type I/II, ExpressCard™, IEEE1394 and S-Video out
- Health and environment friendliness with RoHS compliance⁶
- 7-button Easy-access Panel (Internet, Email, three other softwares, Volume Up, Volume Down)



AUSTRALIA & NEW ZEALAND:
Fujitsu PC Australia
Toll Free: 1800 288 283
Tel : (61-2) 8877 9500
Fax : (61-2) 9889 3360
www.lifebook.com.au

CHINA:
Fujitsu PC China Division
Tel : (86-21) 3310 0808
Fax : (86-21) 3310 0606
cn.fujitsu.com/pc

HONG KONG:
Fujitsu PC Asia Pacific Ltd
Tel : (852) 3101 8133
Fax : (852) 3101 0633

INDIA:
Fujitsu India Limited
Tel : (91-11) 2370 6070
Fax : (91-11) 2370 6079

INDONESIA:
Fujitsu Indonesia
Tel : (62-21) 570 9330
Fax : (62-21) 573 5150

MALAYSIA:
Fujitsu PC Asia Pacific Pte Ltd
Tel : (60-3) 2093 3997
Fax : (60-3) 2093 4245

PHILIPPINES:
Fujitsu Philippines Inc.
Tel : (63-2) 812 4001
Fax : (63-2) 817 7576

SINGAPORE:
Fujitsu PC Asia Pacific Pte Ltd
Tel : (65) 6776 0688
Fax : (65) 6776 0788

TAIWAN:
Fujitsu Taiwan Ltd
Tel : (886-2) 2311 2255
Fax : (886-2) 2311 2277

THAILAND:
Fujitsu Systems Business (Thailand) Ltd PC Division
Tel : (66-2) 263 7888
Fax : (66-2) 263 7880

VIETNAM:
Fujitsu Vietnam Ltd
Tel : (84-4) 831 3895
Fax : (84-4) 831 3898

Note: For countries not listed above, please contact our Singapore office.

Specifications	
Platform	Intel® Centrino® Duo Mobile Technology - Intel® Core™2 Duo Processor T5600 ¹¹ - Intel® PRO/Wireless 3945ABG/3945BG network connection - Intel® 945GM Express Chipset
Operating System	Genuine Windows Vista™ Home Premium (or Genuine Windows Vista™ Home Basic)
Display	15.4-inch SuperFine WXGA TFT, 1280 x 800 pixels
Built-in Bay Device	Dual Layer Super Multi Writer ⁵ / DVD/CD-RW Combo Drive
Memory	1GB DDR2 667MHz Max. Memory Supported ¹⁰ - 4GB DDR2 667MHz, Dual Channel
Hard Disk	100GB
Battery	Up to 3.2hrs ¹ (6-cell Li-Ion 4000mAh)
Weight	Approx. 2.9kg (w/ 6-cell battery)
Detailed Specifications	
Hard Disk Drive	Ultra ATA-100, S.M.A.R.T support, Two Partitions - 50/50 ⁹ , protected by Fujitsu 3D Shock Sensor ¹³
Graphics	Integrated Intel® Graphics Media Accelerator 950 with DVM ⁷ 3.0 delivers low-power, high-performance 2D/3D graphics, video and display capabilities at a maximum shared memory of 224MB
High Definition (HD) Audio	RealTek ALC262 HD audio codec with dual built-in stereo speakers HD Audio-in: External Mic-in HD Audio-out: Headphone-out
Communication	56K V.92 ² Global Modem MDC1.5, 1000/100/10Mbps ³ Gigabit Ethernet PCI Express x 1 and Intel® PRO/Wireless 3945ABG/3945BG network connection with dual antenna. Separate ON/OFF switch for wireless connection, Bluetooth® v2.0 + EDR (Optional)
User Interface	Spill-resistant Keyboard ⁸ : 86-key, 19mm key pitch, 2.7mm key stroke Intelligent Touch Pad with configurable vertical and horizontal scroll functions
Card Slot	PC Card Type I/II, ExpressCard™/34/54 support Secured Digital/ Memory Stick®/ Memory Stick® PRO/xD
Connector Interface	USB 2.0 x 5, VGA (external display), RJ45 (LAN), RJ11 (modem), IEEE1394, S-Video out, HD Audio-in, HD Audio-out, Power Adapter DC-in
Easy Access Panel	7-button Easy-access Panel (Internet, Email, three other softwares, Volume Up, Volume Down)
Security ⁴	BIOS Lock, Hard Disk Lock, Anti-theft Lock Slot, Fingerprint Sensor (Optional)
Dimensions	360mm (W) x 265mm (D) x 39.3mm (H)
Bundled Accessories	
AC Adapter	Input AC 100-240V, Output DC 19V 80W
Bundled Software	CyberLink PowerDVD™, CyberLink PowerProducer™, Roxio Easy Media Creator, Adobe Acrobat Reader, Fujitsu UpdateNavi ¹² , Fujitsu Hardware Diagnostic, Fujitsu Display Manager, Fujitsu 3D Shock Sensor Utility, Fujitsu Power Saving Utility, Sun Microsystems Java Runtime
Software on CD	1 year Full Licensed Norman Virus Control with Sandbox Technology and Norman Personal Firewall, Acronis True Image
Optional Accessories	
Floppy Disk Drive	External USB 1.44MB FDD
Mouse	USB Optical Scroll Mouse

The above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

- Results obtained from BAPCO MobileMark2005 (Productivity Workload 2002SE) performed on systems with maximum battery life settings. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences. Built-in bay devices or hard drive usage may also have a significant impact on battery life. Note: Up to 3.2hrs battery life is based on Intel® Core™2 Duo Processor T5600 configuration with standard 6-cell battery.
- Maximum 56Kbps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.
- This term does not represent actual data rate of 1000/100/10Mbps and simply indicates compliance with IEEE 802.3, IEEE 802.3u and IEEE 802.3ab standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices.
- BIOS Lock needs a supervisor/user password to access BIOS setup. BIOS settings can be configured to prompt for password at every first bootup or all bootup sequences. Access to BIOS setup is needed to configure Hard Disk Lock. Hard Disk Lock requires an access key to retrieve data on the hard disk. This is a Data Confidentiality security feature. Anti-theft Lock Slot allows the use of a lock to physically secure the LifeBook. Fingerprint sensor uses AuthenTec TruePrint™ Technology and Softex OmniPass to remember customer list of user IDs and passwords. Full security unlock sequence - Bootup Lock (BIOS Lock), Hard Disk Lock, Fingerprint Windows Logon.
NOTE: Loss of password requires the LifeBook to be returned to Japan factory for system refresh. Cost of shipment and lost data will be borne by the customer. Backup your user's profile before changing HDD. Without the user's profile associated with a document at the point of encryption, Softex OmniPass cannot decrypt the encrypted document. Loss of the Hard Disk Lock password means the HDD content cannot be retrieved. It is the customer's responsibility to ensure the safe keeping of the password for retrieval of data from the locked HDD.
- Supports DVD multi formats such as DVD-RAM, DL DVD±R, DVD±RW, DVD±R, CD-RW, DVD-ROM, CD-R and CD-ROM.
- RoHS (Restriction on Hazardous Substances) compliance means the system and its internal components comply with the EU RoHS directive (2002/95/EC) on the restricted use of six hazardous substances in the manufacture of the system and its internal components.
- Dynamic Video Memory Technology (DVM⁷) dynamically responds to application requirement and efficiently allocates the proper amount of memory (max. 224MB) for optimal graphics and system performance. The memory size available to the Operating System will be less than the size of installed memory module.
- Spill-resistant keyboard does not imply the system is water-proof. If liquid is split onto the keyboard, power off the system immediately and turn the notebook upside down to drain off the liquid.
- This refers to Windows Vista™ hard disk drives C:\ and D:\. 50/50 refers to approximate 50% allocation of user accessible hard disk storage to C:\ and D:\ drives.
- 4GB DDR2 667MHz maximum memory is supported when Fujitsu recommended 2GB DDR2 667MHz memory module is made available.
- Please check actual bundling with country local distributor. T5600 refers to (1.83GHz, 2MB L2 cache, 667MHz FSB).
- UpdateNavi is a Fujitsu Proprietary application that updates LifeBook drivers by connecting automatically to Fujitsu's server. This will help update your LifeBook with the latest software drivers and utilities to ensure compatibility between hardware and software, maintaining smooth operation anytime, anywhere.
- Fujitsu 3D Shock Sensor of a powered-up unit retracts hard disk read-write head to a secured zone upon detection of excessive vibrations or shocks. This greatly reduces the possibility of damage to the hard disk and its contents - example in the event of a sudden drop or impact. The sensor monitors movement from three axes and its sensitivity can be adjusted by user to accommodate different working environments using the Fujitsu 3D Shock Sensor Utility.

Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.

*PCI Express® and the PCI Express design marks are registered trademarks and/or service marks of PCI-SIG.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discolored dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5° to 35°C / 41 to 95°F (operating), -15° to 60°C / 5 to 140°F (non-operating). Relative humidity: 20% to 85% RH (operating), 8% to 85% RH (non-operating). Please note that GB = billion bytes.



All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.

Dealer: