

LifeBook E8210

- 15.4-inch wide top-of-the-line performance Intel[®] Centrino[®] Duo LifeBook at approximately 2.4kg*
- Superior data protection with dedicated Smartcard⁵ slot, 2-password Hard Disk Lock⁶ and Fingerprint **Recognition Technology**
- Superb 2D/3D graphics performance with ATI Mobility[™] Radeon X1400 256MB HyperMemory[™]
- · Hassle-free VoIP communications using built-in microphone
- Health and environment friendliness with RoHS compliance⁸
- Windows Vista[™] Capable¹⁵

* with weight saver option

AUSTRALIA &

CHINA:

Division

NEW ZEALAND:

Fujitsu PC Australia

Toll Free: 1800 288 283 Tel : (61-2) 8877 9500

Fax : (61-2) 9889 3360 www.lifebook.com.au

Fujitsu PC China

Tel : (86-21) 3310 0808

Fax : (86-21) 3310 0606

cn.fujitsu.com/pc

HONG KONG:

Asia Pacific Ltd

Tel : (852) 3101 8133

Fax : (852) 3101 0633

Fujitsu India Limited

: (91-11)23706070

Fax : (91-11) 2370 6079

Fujitsu PC

INDIA:

INDONESIA:

MALAYSIA: Fujitsu PC Asia

Pacific Pte Ltd

PHILIPPINES:

SINGAPORE:

TAIWAN:

THAILAND:

Fujitsu Systems

Fuiitsu PC Asia Pacific Pte Ltd Tel : (65) 6776 0688

Fax: (65) 6776 0788

Fuiitsu Taiwan Ltd Tel : (886-2) 2311 2255

Fax : (886-2) 2311 2277

Business (Thailand) Ltd PC Division Tel : (66-2) 263 7888

Fax : (66-2) 263 7880 VIETNAM:

Fujitsu Vietnam Ltd Tel : (84-4) 831 3895 Fax : (84-4) 831 3898

Note: For countries not listed above, please contact

our Singapore office.

Fujitsu Indonesia

Tel : (62-21) 570 9330

Fax : (62-21) 573 5150

Tel : (60-3) 2093 3997 Fax : (60-3) 2093 4245

Fujitsu Philippines Inc.

Tel : (63-2) 812 4001

Fax : (63-2) 817 7576

- mmended Configurations Bec Intel[®] Centrind[®] Duo Mobile Technology - Intel[®] Core[™]2 Duo Processor T7400¹⁷ with Intel[®] 64 Architecture Intel[®] Centrino[®] Duo Mobile Technology - Intel[®] Core[™]2 Duo Processor T5600¹⁷ with Intel[®] 64 Architecture Platform - Intel® PRO/Wireless 3945ABG/3945BG network connection - Intel® PRO/Wireless 3945ABG/3945BG network connection Intel[®] 945PM Express Chipset - Intel[®] 945PM Express Chipset Genuine Windows[®] XP Professional (or Genuine Windows[®] XP Home Edition) OS Supported Display 15.4-inch WSXGA + TFT, 1680 x 1050 pixels 15.4-inch SuperFine WXGA TFT, 1280 x 800 pixels Dual Layer DVD Super Multi Writer⁷ Dual Layer DVD Super Multi Writer⁷/ DVD/ CD-RW Combo Drive Modular Bay Device Memory 1024MB DDR2 667MHz 512MB DDR2 667MHz 120GB 80GB Hard Disk v2.0 + EDR (Enhanced Data Rate) v2.0 + EDB (Enhanced Data Bate) Bluetooth⁰ Up to 3.1hrs1 (8-cell Li-lon 5200mAh) Up to 3.5hrs1 (8-cell Li-Ion 5200mAh) Battery Weight Approx. 2.5kg (w/ weight saver option) Approx. 2.4kg (w/ weight saver option) Specifications Max. Memory Supported¹⁴ 4GB DDR2 667MHz, Dual Channel ATA-150 5400rpm, S.M.A.R.T. support, Two Partitions – 50/50¹³, protected by Fujitsu 3D Shock Sensor¹⁶ ATI Mobility™ Radeon X1400 with 256MB HyperMemory™ ⁹, PCI Express x16 RealTek ALC262 HD audio codec with dual built-in stereo speakers Hard Disk Drive Graphics High Definition (HD) Audio HD Audio-in: External Mic-in, Line-in, Dual Built-in Microphones HD Audio-out: Headphone-out, Line-out, SPDIF Bluetooth® v2.0 + EDR, 56K V.92², Infrared IrDA 1.1 4Mbps³, Global Modern MDC1.5, 1000/100/10Mbps⁴ Gigabit Ethernet PCI Express x 1 and Communication Intel® PRO/Wireless 3945ABG/ 3945BG network connection with dual antenna. Separate ON/OFF switch for wireless network connection. Spill-resistant keyboard¹¹: 84-key, 19mm key pitch, 3mm key stroke, Quickpoint User Interface Intelligent Touch Pad with configurable vertical and horizontal scroll function Fingerprint Sensor with vertical scroll functions Fingerprint Sensor with vertical scroll functions PC Card Type II, Expresscal™/ 34/ 54, Smartcard⁵, Secured Digital/ Memory Stick[®]/ Memory Stick[®] PRO USB 2.0 x 4, VGA (external display), RJ45 (LAN), RJ11 (modem), IEEE1394, S-Video out, HDA-in, HDA-out, Serial, Parallel, Power Adapter DC-in, Card Slots Connector Interface Port Replicator Interface Quick Launch Panel Four Programmable Application Launch Buttons (Internet, Email and two other softwares) BIOS Lock, 2-password Hard Disk Lock, LifeBook Lock, Anti-theft Lock Slot, Smartcard⁵ Slot, Fingerprint Sensor, Trusted Platform Module Security⁶ (TPM v1.2) option 360mm (W) x 259mm (D) x 35.5mm (H) Dimensions Bundled Accessories AC Adapter Bundled Software Input AC 100~240V. Output DC 19V 80W Softex Omipass, CyberLink PowerDVD™, CyberLink PowerProducer™, Roxio Easy Media Creator, Sonix DLA, Adobe Acrobat Reader 6.0, Fujitsu UpdateNavi¹², Fujitsu Hardware Diagnostic Tool, Fujitsu Display Manager, Fujitsu Power Saving Utility, Fujitsu 3D Shock Sensor Utility, Sun Microsystems Java Runtime Software on CD 1 year Full Licensed Norman Virus Control with Sandbox Technology and Norman Personal Firewall, Acronis True Image 8.0 Personal Edition Optional Accessories Port Replicator Connector Interface: USB 2.0 x 4, Headphone-out, Microphone-in, DVI-D, VGA (external display), RJ45 (LAN), PS/2 (keyboard/mouse), Serial, Parallel, Power Adapter DC-in Modular Bay Options Replaceable with: Bay Battery, 6-cell Li-Ion 3800mAh, up to 6.0hrs1 battery life (Standard + Bay Batteries) - Dual Laver DVD Super Multi Writer - 2nd SATA HDD Fitting Kit¹⁰ - DVD/CD-RW Combo Drive - Weight Saver External USB 1.44MB FDD Floppy Disk Drive Mouse USB Optical Scroll Mouse
- ined from BAPCO MobileMark2005 (Productivity Workload) perfor and other customer preferences. Markelar her structure
- This term does not represent actual data rate of whilips and simply indicates compliance with IEEE 802.3, IEEE 802.3 and IEEE 802.3 as the standard spectra and t nected devices.

de the application for Smartcard solution. upervisor/user password to access BIOS st ata Confidentiality security feature. LifeBook BIOS Loci hard das. This is a bata Continentiaty security leature. Letekoo Look requires a supervisoriuse password to bootby the Letekook when if y on the Quick Landx-Teank. Artik-that Lock Scalakows the cal lock to physical secure the Lifebook. Somardard soft usage is dependent Full security unick sequence - Lifebook Lock, Bootby Lock (BIOS Lock), Hard Dak Lock, Fragmerint Windows Logon, NOTE: Loss of passo molto before changing HDD. Without the user's profile associated with a document at the point of encryption, Softex OmnPass cannot deci Password at the BGO settings under Hard Dak Security. H1DD Lock prompt is enabled; only the User Password can be used to boot up th ner list of user IDs and pa er custo word requires the LifeBook to be returned to Japan factory for system refresh. Cost of ship will be borne by the customer. Backup your The Master Password can be used to clear

- rts DVD multi form f data from the locked HDD. nats such as DVD-RAM, DL DVD±R, DVD±RW, DVD±R, CD-RW, DVD-ROM, CD-R and CD-ROM.
- Hazardous Substances) compliance means the system and its internal components comply with the EU RoHS dire Hazardous Substances) compliance means the system and its internal components comply with the EU RoHS dire (Mellers to a total of 128MB decidated video memory and 128MB shared system memory. The memory size ava (Rt and screws are provided, HDD is to be purchased secarate/v
- book upside down to drain off the liquid cting automatically to Eulitsu's server. This will belo upo late your LifeBook with the latest software drivers and util
- tely 50% allocation of user accessible hard disk storage to C:\and D:\drives
- 14 15
- 49. PF hard disk drives C1 and D2, 5050 refers to approximately 50% alcoation of user accessible hard disk stronge to C1 and D2 drives. Tanium memory is supported when Fujits recommended CBDPE 607Mc memory module is made analable. Tal¹¹ Meatures are available for use on al Windows Vista Capable PCs. All Windows Vista Capable PC will un the core experiences of Windows Vista, such as innovations in organize relations of Windows Vista. Teste then were Windows Obsen ¹¹ were for were interesting to the disk. For of a powerd-up unit reltacts hard disk read-write hard to a secured zone upon dutaction of accessine vibrations or thorize. This greatly reduces the possibility of damage to the hard disk and its cor anise and its sensitify can be adjusted by user to accommodate different advancements using the Fujitus OS Soci Samou Utility anding with county local distributor. TMO0 reflex to (1:G4Fz, 4MB 12 caphe, 66/Mrk T88); T5800 milers to (1:S3GHz, 2MB 12 caphe, 66/Mrk T88). ces of Windows Vista, such as innovations in organizing and finding information, security, and reliability. Some features 16 ujitsu 3D S
- 17

vice marks of PCI-SIG

nd the double-D symbol are registered trademarks of Dolby Laboratories

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small nu technology such as non-conforming pixels.

ies as well as hard ons of the notebook. Please check the compatibility rg animana, and an animana anim



All rights to the mentioned trademarks reside with their respective owners. Fujitsu

Dealer:

Printed by

1369 • 20...

JOB h

Ċ