

LifeBook P1510

- Ultra light at around 1kg*
- Versatile with convertible form factor and pen input capability
- Superior security features with biometric fingerprint sensor
- Comprehensive connectivity with SD and CF card slots

* with 3-cell battery and 60GB HDD



SINGAPORE:
Fujitsu PC Asia Pacific Pte Ltd
 Tel : (65) 6776 0688
 Fax : (65) 6776 0788

MALAYSIA:
Fujitsu PC Asia Pacific Pte Ltd
 Tel : (60-3) 2093 3997
 Fax : (60-3) 2093 4245

HONG KONG:
Fujitsu PC Asia Pacific Ltd
 Tel : (852) 3101 8133
 Fax : (852) 3101 0633

THAILAND:
Fujitsu Systems Business (Thailand) Ltd PC Division
 Tel : (66-2) 263 7888
 Fax : (66-2) 263 7880

AUSTRALIA & NEW ZEALAND:
Fujitsu PC Australia
 Toll Free: 1800 288 283
 Tel : (61-2) 8877 9500
 Fax : (61-2) 9889 3360
www.lifebook.com.au

CHINA:
Fujitsu PC China Division
 Tel : (86-21) 3310 0808
 Fax : (86-21) 3310 0606
www.pc-cn.fujitsu.com

PHILIPPINES:
Fujitsu Philippines Inc.
 Tel : (63-2) 812 4001
 Fax : (63-2) 817 7576

TAIWAN:
Fujitsu Taiwan Ltd
 Tel : (886-2) 2311 2255
 Fax : (886-2) 2311 2277

VIETNAM:
Fujitsu Vietnam Ltd
 Tel : (84-4) 831 3895-7
 Fax : (84-4) 831 3898

INDONESIA:
PT. Fujitsu Indonesia
 Tel : (62-21) 570 9330
 Fax : (62-21) 573 5150
www.fujitsu.com/id

Note: For countries not listed above, please contact our Singapore office.

P1510 Recommended Configuration		
Platform	Intel® Centrino® Mobile Technology - Intel® Pentium® M Processor 753 (1.20GHz, 2MB L2 cache, 400MHz FSB) - Intel® PRO/Wireless 2915ABG network connection - Intel® 915GMS Chipset	
OS Supported	Windows® XP Tablet PC Edition	Windows® XP Home Edition Windows® XP Professional
Display	8.9" Wide SVGA, 1024 x 600 pixels	
Graphics	Intel® Graphics Media Accelerator (GMA) 900 (up to 128MB)	
Memory	512MB DDR2 400	
Hard Disk	60GB	
Bluetooth™	Integrated v1.2	-
Battery	Up to 4.0hrs ¹ (3-cell Li-Ion 2600mAh)	
Weight	Approx. 1kg	
Specifications		
Max. Memory Supported	1GB	
Hard Disk Drive	Ultra DMA/100 and S.M.A.R.T. support	
High Definition (HD) Audio	RealTek ALC203 codec Built in microphone	
Communication	56K ² V.90 Global Modem ,100/10Mbps ³ Ethernet and Intel® PRO/Wireless 2915ABG ⁴ network connection with Dual Antenna Separate ON/OFF switch for wireless network connection	
User Interface	Keyboard with Quick Point: 82-key, 16mm key pitch, 2mm key stroke	
Card Slot	Compact Flash (CF-Type II) Slot x 1 SD Card x 1	
Connector Interface	USB 2.0 x 2, VGA (external display), RJ45 (LAN), RJ11 (modem), Headphone-out, Microphone-in, Port replicator interface, Power Adapter DC-in	
Quick Launch Panel	5 Application Buttons (Including 2 Programmable Applications Launch buttons)	
Security	BIOS Lock ⁵ , Hard Disk Lock, Anti-theft Lock Slot, Fingerprint Sensor, Trusted Platform Module	
Dimensions	232mm (W) x 167mm (D) x 34.5-37.5mm (H)	
Bundled Accessories		
AC Adapter	Input AC 100 ~ 240V, Output DC 16V 40W	
Bundled Software	Adobe Acrobat Reader 6.0, Fujitsu Update Navi ⁶ , Fujitsu Hardware Diagnostic Tool	Adobe Acrobat Reader 6.0, Fujitsu Update Navi ⁶ , Fujitsu Hardware Diagnostic Tool, PenOffice® Software. Copyright©1997-2002 Paragraph
Software on CD	Norman Virus Control, Norman Personal Firewall, Acronis True Image 8.0 Personal Edition	
Optional Accessories		
Port Replicator	Connector Interface: USB 2.0 x 2, VGA (external display), RJ45 (LAN), Power Adapter DC-in	
Optical Bay Device	External Combo Drive	
Mouse	USB Optical Scroll Mouse	

The above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

- Results obtained from Mobilemark 2002 performed on systems with maximum battery life settings. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences. Hard drive usage may also have a significant impact on battery life. Note: Up to 8hrs battery life is based on Intel® Pentium® M Processor 753 configuration with extended battery.
- Maximum 56Kbps performance varies according to your local service providers' services as well as line condition. V.90 performance is dependent on local service providers' services.
- This term does not represent actual data rate of 100/10Mbps and simply indicates compliance with IEEE 802.3 and IEEE 802.3u standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices.
- Configurations vary from country to country. Please check with your local distributor for actual configurations.
- BIOS Lock needs a supervisor/user password to access BIOS setup. BIOS settings can be configured to prompt for password at every first bootup or all bootup sequences. Access to BIOS setup is needed to configure Hard Disk Lock. Hard Disk Lock requires an access key to retrieve data on the hard disk. This is a Data Confidentiality security feature. LifeBook Lock requires a supervisor/user password to bootup the LifeBook when it powers up or resumes last session from suspend/hibernate mode. This is an anti-theft feature with more than 800,000 password combinations using the buttons on the Quick Launch Panel. Anti-theft Lock Slot allows the use of a lock to physically secure the LifeBook. SmartCard usage is dependent on customer's solution. Full security unlock sequence - LifeBook Lock, Bootup Lock (BIOS Lock), Hard Disk Lock. NOTE: Loss of password requires the LifeBook to be returned to Japan factory for system refresh. Cost of shipment and lost data will be borne by the customer.
- Update Navi is a Fujitsu Proprietary application that updates LifeBook drivers by connecting automatically to Fujitsu's server. This will help update your LifeBook with the latest software drivers and utilities to ensure compatibility between hardware and software, maintaining smooth operation anytime, anywhere.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5° to 35°C / 41 to 95°F (operating), -10° to 60°C / 14 to 140°F (non-operating). Relative humidity: 20% to 80% RH (operating and non-operating).



BLUETOOTH is a trademark owned by its proprietor and used by Fujitsu under license.

All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.

Dealer: