	P7120 Recommended Configuration
Platform	Intel® Centrino® Mobile Technology
	- Intel® Pentium® M Processor 753 (1.20GHz ULV, 2MB L2 cache, 400MHz FSB)
	- Intel® PRO/Wireless 2915ABG Network Connection
	- Intel® 915GMS Express Chipset
OS Supported	Windows® XP Home Edition
	Windows® XP Professional
Display	10.6° SuperFine Wide XGA TFT
Modular Bay Device	Dual Layer DVD Super Multi Writer (lightweight) ⁵
Memory	1GB/512MB DDR2 400MHz
Hard Disk	60GB
Bluetooth™	Integrated v1.2
Battery	Up to 7.8hrs on standard battery
Weight	Approx. 1.39kg [w/ 6-cell battery and Dual Layer DVD Super Multi Writer (lightweight)]
	Specifications
Max. Memory Supported	2GB DDR2 400MHz, Dual Channel
Hard Disk Drive	Ultra ATA-100, S.M.A.R.T support, Two Partitions - 50/50 ⁶
Graphics	Integrated Intel® Graphics Media Accelerator 900 with DVMT8 3.0 delivers low-power, high-performance 2D/3D graphics, video,
	and display capabilities at a maximum shared memory of 128MB
High Definition (HD) Audio	RealTek ALC260 HD audio codec with built-in dual Stereo Speakers; Internal dual microphones
	HD Audio-in: Mic-in
	HD Audio-out: Headphone-out. Line-out
Communication	56K V.90 Global Modem MDC1.5, 100/10Mbps3 Fast Ethernet and Intel® PRO/Wireless 2915ABG network connection with Dual Antenna.
	Separate ON/OFF switch for wireless network connection
User Interface	Keyboard: 82-key, 18mm key pitch, 2mm key stroke
	Intelligent Touch Pad with configurable vertical and horizontal scroll functions
	Fingerprint sensor with vertical scroll functions
Card Slot	PC Card Type II, SD/MS/xD, Smart Card support ⁴
Connector Interface	USB 2.0 x 3, VGA (external display), RJ45 (LAN), RJ11 (modem), IEEE1394, S-video out, HD Audio-in, HD Audio-out, Power Adapter DC-in, Port Replicator Interface
Quick Launch Panel	One Programmable Application Launch Button / ECO (Power saving) button
Security ⁵	BIOS Lock, Hard Disk Lock, Anti-theft Lock Slot, Fingerprint Sensor, Trusted Platform Module
Dimensions	271mm (W) x 209.5mm (D) x 24.3mm min (H)
Birrichsions	Bundled Accessories
AC Adapter	Input AC 100-240V, Output DC 16V 60W
Bundled Software	Softex OmniPass 3.0, CyberLink PowerDVD™, CyberLink PowerProducer™ 3, Roxio Digital Media SE,
	Roxio DLA, Adobe Acrobat Reader 6.0, Fujitsu Update Navi ⁷ , Fujitsu Hardware Diagnostic Tool, Fujitsu Display Manager
Software on CD	1 year Full Licensed Norman Virus Control with Sandbox Technology, Norman Personal Firewall, Acronis True Image 8.0 Personal Edition
CONTINUE ON OB	Optional Accessories
Port Replicator	Connector Interface:
	USB 2.0 x 3, S Video-out, Line-out, VGA (external display), RJ45 (LAN), Power Adapter DC-in
Modular Bay Options	Replaceable with
	neplaceable will - Bay Battery, 6-cel Li-lon 2300mAh, up to 11hrs¹ on standard + bay battery
	- bay battery, 0-cent Li-ion zoonnan, up to 1 mis- on standard + bay battery - Dual Layer DVD Super Multi Writer (normal weight) ⁵
	- Dual Layer Dvb Super mutu writer (normal weignty* - DVD/CD-RW Combo Drive
Floory Diels Drive	- Weight Saver External USB 1.44MB FDD
Floppy Disk Drive	
Mouse	USB Optical Scroll Mouse

The above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

- 1. Results obtained from Mobile Mark 2002 performed on systems with maximum battery life settings. Actual battery life will vary based on screen brightness, sound volume ettings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences. Modular Bay devices or hard drive usage may also have a significant impact on battery life.
- 2 Maximum 56Kbps performance varies according to your local service providers' services as well as line condition, V.90 performance is dependent on local service providers' services.
- 3 This term does not represent actual data rate of 100/10Mbps and simply indicates compliance with IEEE 802.3, IEEE 802.3 and IEEE 802.3 as standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices.
- Smart Card support requires a Smart Card adapter for the PC Card Slot. This is available as an accessory. Fujitsu does not provide the application for Smart Card solution.
- 5 Supports DVD multi formats such as DVD-RAM, DVD+RW, DVD+R DL, DVD-R DL, DVD-R, DVD-R, DVD-R, CD-RW, CD-R, CD-ROM and DVD-ROM.
- This refers to Window® XP hard disk drivers C.\ and D.\ 50/50 refer to approximate 50% allocation of user accessible hard disk storage to C.\ and D.\ drives.
- 7 Update Navi is a Fujitsu Proprietary application that updates LifeBook drivers by connecting automatically to Fujitsu's server. This will help update your LifeBook with the latest software drivers and utilities to ensure compatibility between hardware and software, maintaining smooth operation anytime, anywhere.
- 8 Úynamic Vídeo Memory Technology (DVMT) dynamically responds to application requirement and efficiently allocates the proper amount of memory (max. 128MB) for optimal graphics and system performance. The memory size available to vithe Operating System will be less than the size of installed memory module.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5° to 35°C / 41 to 95°F (operating), -10° to 60°C / 14 to 140°F (non-operating). Relative humidity: 20% to 80% RH (operating and non-operating).

Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.













All rights to the mentioned trademarks reside with their respective owners. Fuiltsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.



