LifeBook C2330

- Brilliant SuperFine LCD display for excellent movie viewing and rich multimedia playback
- Multi interfaces for accessories connection USB 2.0, SD, Memory Stick PRO, CF, PC Card and IEEE1394
- UPDATE NAVI™ preinstalled to keep your LifeBook drivers up-to-date for hassle-free computing
- The ideal desktop alternative notebook for home and office



	C2330 Recommended Configuration
Platform	Intel® Centrino™ Mobile Technology
	- Intel® Pentium® M Processor 745 (1.80GHz, 2MB L2 cache, 400MHz FSB)
	- Intel® PRO/Wireless 2200BG ⁶ Network Connection
	- Intel® 855GM Chipset
OS Supported	Microsoft® Windows® XP Home Edition
	Microsoft® Windows® XP Professional Edition
Display	15" SuperFine XGA TFT, 1024 x 768 pixels
Optical Bay Drive	DVD Super Multi Drive (Integrated)
Memory	512MB DDR266 (256MB On Board)
Hard Disk	80GB
Battery	Up to 2.06hrs1 (4-cell Li-lon 2000mAh)
Weight	Approx. 3.5kg
	Specifications
Max. Memory Supported	1280MB DDR266, 1 DDR DIMM slot
Hard Disk Drive	Ultra DMA/100 and S.M.A.R.T support
Graphics	Integrated Intel® Extreme Graphics 2 with DVMT2 delivers low-power, high-performance 2D/3D graphics, video,
	and display capabilities at a maximum shared memory of 64MB.
Audio	SigmaTel STAC9751T codec with built-in Stereo Speakers
Communication	56K V.92 ³ modem, IrDA 1.1 4Mbps ⁵ , 100/10Mbps ⁴ Fast Ethernet and Intel [®] PRO/Wireless 2200BG ⁶ network connection
	with Dual Antenna. Separate ON/OFF switch for wireless network connection
User Interface	Keyboard: 82-key, 19mm key pitch, 3mm key stroke
	Touch Pad with Scroll Buttons
Floppy Disk Drive	Built-in 1.44MB FDD
Card Slot	PC Card Type I/II x 2 / Type III X 1
	SD Card/Memory Stick PRO x 1
Connector Interface	USB 2.0 x 4, VGA (external display), RJ45 (LAN), RJ11 (modem), IEEE1394, Headphone-out, Microphone-in, S-Video terminal,
	Serial, Parallel, Power Adapter AC-in
Quick Launch Panel	Four Programmable Application Launch Buttons (Internet, Email and two other software)
Dimensions	329mm (W) x 285.5mm (D) x 45.2mm <i>min.</i> (H)
	Bundled Accessories
AC Adapter	Input AC 100 ~ 240V, Output DC 19V 60W
Bundled Software	Adobe Acrobat 6.0, CyberLink PowerDVD™, CyberLink PowerProducer™, Fujitsu UPDATE NAVI™, Fujitsu Hardware
	Diagnostic Tool
Software on CD	Norman Virus Control & Norman Personal Firewall

The above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors

- Results obtained from Ziff Davis (BusinessWinstone 2001) Battery Mark V1.0.1 performed on systems with maximum battery life settings. Actual battery life will vary based on screen brightness, sound volume riesuits obtained from Ziri Davis (Businessiviristone 2001) Battery Mark V1.0.1 performed on systems with maximum battery life settings. Actual battery life will vary based on screen brightness, sound volume settings, connected peripherals, power management settings, battery conditioning, and other customer preferences. Modular Bay devices or hard drive usage may also have a significant impact on battery life.

 Dynamic Video Memory Technology (DVMT) dynamically responds to application requirement and efficiently allocates the proper amount of memory (max. 64MB) for optimal graphics and system performance. The memory size available to the Operating System will be less than the size of installed memory module.

 Maximum 56Kbps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.

 This term does not represent actual data rate of 100/10Mbps and simply indicates compliance with IEEE 802.3 and IEEE 802.3 standards. Actual maximum data rate depends on network configurations,

- cable conditions as well as connected devices
- This term does not represent actual data rate of 4Mbps and simply indicates compliance with IrDA standard specification 1.1. Actual maximum data rate depends on local configurations and connected devices. Some country configurations may be bundled with 802.11b WLAN e.g. Malaysia. Please check the country configuration with your local distributors.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5' to 35°C/41 to 95°F (operating), -10' to 60°C/14 to 140°F (non-operating). Relative humidity: 20% to 80% RH (operating and non-operating).





All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.

SINGAPORE: Fuiitsu PC Asia Pacific Pte Ltd Tel: (65) 6776 0688

Fax: (65) 6776 0788

MALAYSIA: Fuiitsu PC Asia Pacific Pte Ltd

Tel: (60-3) 2093 3997 Fax: (60-3) 2093 4245

HONG KONG: Fujitsu PC Asia Pacific Ltd

Tel: (852) 3101 8133 Fax: (852) 3101 0633

THAILAND: Fujitsu Systems Business (Thailand) Ltd PC Division

Tel: (66-2) 263 7888 Fax: (66-2) 263 7880

AUSTRALIA:

Fujitsu PC Australia Toll Free: 1800 288 283

Tel: (61-2) 9004 7455 Fax: (61-2) 9004 7720 www.lifebook.com.au

CHINA: Fujitsu PC China Division

Tel: (86-21) 3310 0808 Fax: (86-21) 3310 0606 www.pc-cn.fujitsu.com

PHILIPPINES:

Fujitsu Philippines Inc. Tel: (63-2) 812 4001 Fax: (63-2) 817 7576

TAIWAN: Fujitsu Taiwan Ltd Tel: (886-2) 2311 2255

Fax: (886-2) 2311 2277 VIETNAM:

Fuiitsu Vietnam Ltd Tel : (84-4) 831 3895~7 Fax: (84-4) 831 3898

INDONESIA: PT Fujitsu Systems (Indonesia)

Tel : (62-21) 344 2601 Fax: (62-21) 344 2593

Note: For countries not listed above, please contact our Singapore office.

Dealer: