THE POSSIBILITIES ARE INFINITE

Fujitsu recommends Windows Vista® Business.

S7211

- LifeBook

 14.1-inch wide Intel® Centrino® Duo LifeBook at approximately 2.2kg*
 Genuine Windows Vista® Business

 - Instant converged communications using built-in 1.3 Mega Pixel camera and dual built-in stereo microphones
 - High brightness SuperFine LCD for perfect pictures and movie viewing
 - Hot-swappable modular bay device options for ultimate flexiblity
 - Health and environment friendliness with RoHS compliance

	Specifications
Platform	Intel® Centrino® Duo processor technology
	- Intel® Core™2 Duo Processor T7500⁵ (2.2GHz, 4MB L2 cache, 800MHz)
	- Intel® GM965 Express Chipset
	- Intel® PRO/Wireless 4965AGN/3945BG wireless connection
Operating System	Genuine Windows Vista® Business
	(or Genuine Windows Vista® Home Premium)
	(or Genuine Windows Vista® Home Basic)
Display	14.1-inch SuperFine WXGA TFT, 1280 x 800 pixels
Modular Bay Device	Dual Layer DVD Super Multi Writer ⁹ / DVD/CD-RW Combo Drive
Memory	1GB DDR2 667MHz
	Max. Memory Supported ³ - 4GB DDR2 667MHz, Dual-Channel
Hard Disk	160GB
Battery	Up to 4hrs¹ (6-cell Li-lon 5800mAh)
Weight	Approx. 2.2kg (w/ weight saver option)
	Detailed Specifications
Hard Disk Drive	SATA-150 5400rpm, S.M.A.R.T support, Two Partitions - 50/507
Graphics	Integrated Intel® Graphics Media Accelerator X3100 with Intel® Clear Video Technology ¹¹ and DVMT ⁶ 4.0 delivers low-power, high-performance 2D/3I
	graphics with Shader Model 3.0, video and display capabilities at a max. shared memory of 384MB
High Definition (HD) Audio	RealTek ALC262 HD audio codec with dual built-in stereo speakers
	HD Audio-in: External Mic-in, Dual Built-in Stereo Microphones
	HD Audio-out: Headphone-out
Communication	1.3 Mega Pixels CMOS camera, Bluetooth® v2.0+EDR, 56K V.922 Global Modem MDC1.5, 1000/100/10Mbps4 Gigabit Ethernet PCI Express x 1 and
	Intel® PRO/Wireless 4965AGN/3945BG wireless connection with three antenna. Separate ON/OFF switch for wireless network connection
User Interface	Spill-resistant Keyboard ¹² : 84-key, 19mm key pitch, 2.7mm key stroke
	Intelligent Touch Pad with configurable vertical and horizontal scroll functions
	Scroll Button
Card Slots	ExpressCard™ /34 /54, Secured Digital / SDHC / Memory Stick® /Memory Stick® PRO
Connector Interface	USB 2.0 x 3, VGA (external display), RJ45 (LAN), RJ11 (modem), HDA-in, HDA-out, Power Adapter DC-in
Quick Launch Panel	Four Programmable Application Launch Buttons (Internet, Email, and two other softwares)
Security ⁸	BIOS Lock, 2-password Hard Disk Lock, LifeBook Lock, Anti-theft Lock Slot
Dimensions	334mm (W) x 242mm (D) x 32/37mm (H)
	Bundled Accessories
AC Adapter	Input AC 100~240V, Output DC 19V 80W
Bundled Software	CyberLink PowerDVD™, CyberLink PowerProducer™, Roxio Easy Media Creator, Adobe Acrobat Reader, Fujitsu UpdateNavi³, Fujitsu Power Saving
	Utility, Fujitsu Hardware Diagnostic Tool, Fujitsu Display Manager, Sun Microsystems Java Runtime, Camera Capture Application, Microsoft Office
	Professional 2007 60-day Convertible Trial ¹⁵
Software on CD	1 year Full Licensed Norman Virus Control with Sandbox Technology and Norman Personal Firewall, Acronis True Image
	Optional Accessories
Modular Bay Options	Replaceable with
	- Bay Battery, 6-cell Li-Ion 3800mAh, up to 6.7hrs¹ battery life (Standard + Bay Batteries)
	- Dual Layer DVD Super Multi Writer ^a
	- 2nd SATA HDD Fitting Kit ¹⁴
	- DVD/CD-RW Combo Drive
	- Weight Saver
Floppy Disk Drive	External USB 1.44MB FDD
Mouse	Optical USB Black Mouse (Retractable)







- Hesuits obtained from IM4-D09 MobileMark®2001/Productivity Workload) performed on systems with maximum battery lie elegings under laboratory testing environment. Actual battery lie will vary based on screen brightness, source management settings, better conditioning, and other customer preferences in the real life situation. Built-in bay device or hard drive usage may also have a significant impact on battery life. Note: Battery life is based on Intel® Core™2 Duo Processor 17500.

 Maximum 66Vcps performance varies according to your local service providers' services as well as life condition. V92 performance is dependent on local service providers' services.

 46B DDP2 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP2 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported when Fullist uncommended 25B DDP3 66/HP4 zemainum memory is supported whe
- configurations, cable conditions as well as connected devices
- Please check actual bundling with country local distributor. T7500 (2.2GHz, 4MB L2 cache, 800MHz FSB)
- 6 Dynamic Video Memory Technology (DVMT) dynamically responds to application requirement and efficiently allocates the proper amount of memory (max. 384MB) for optimal graphics and system performance. The
- 6 Dynamic Video Memory Technology (DVMT) dynamically responds to application requirement and efficiently allocates the proper amount of memory (max. 384MB) for optimal graphics and system performance. The memory size available to the Operating System will be less than the size of installed memory module.

 7 This refers to Window Visitie hard disk drives C. And D.\Subformer and D\Subformer to approximate System of the operation of the proper amount of memory (max. 384MB) for optimal graphics and system performance. The memory will be reserved for internal recovery usage which is not shown.

 8 BIOS Lock needs a supervisor/user password to access BIOS setup. BIOS setup is needed to configure that Disk Lock. Hard Disk Lock requires an access key to retrieve data on the hard disk. This is a Data Confidentiality security feature. LifeBook Lock requires a supervisor/user password to bootup the LifeBook when it powers upor resumes slat session from suspend/filbernate mode. This is an anti-thet feature with more than 800,000 password combinations using the butters on the Quick Launch Panel. Anti-thet Lock Slot allows the use of a lock to physically secure the LifeBook. It is security mick sequence LifeBook Lock, Bootup Lock (BIOS Lock), Hard Disk Lock, Windows Logon.

 NOTE: Loss of password requires the LifeBook to be returned to Japan factory for system refresh. Cost of shipment and lost data will be bore by the customer. Backup your user's profile before changing HDD. Without the user's profile associated with a document at the point of encryption, Softex Normi-Sess cannot decrypt the encrypted document. 2 passwords refers to Master Password and User Password of the HDD Lock. The Master Password can be used to loan the later the password of the HDD Lock. The Master Password is not used to boot up the unit. Loss of these 2 passwords means the HDD content cannot be retrieved. It is the customer's responsibility to ensure the safe keeping of these 2 passwords for retrievel of data from the locked HDD.

 9 Supports DVD m

- manufacture of the system and its internal components
- maintacture of the system and is internal components
 II Intel® Gear Video Technology is a combination of video processing hardware and software technologies that delivers enhanced high-definition video playback, sharper images, precise color control and advanced support
 for a wide range of digital displays interfaces, including High-Definition Multimedia Interface(HOMI).
 If Spill-resistant keyboard does not imply the system is water-proof. If liquid is spill onto the keyboard, power off the system immediately and turn the notebook upside down to drain off the liquid.
 IS Updatelvals is a Fulliss Proprietary application that updates LifeBook with the latest software drivers and utilities to ensure
 compatibility between hardware and software, maintaining smooth operation anytime, anywhere.
- 14 Only the HDD Housing Kit and screws are provided. HDD is to be purchased separately
- 15 Microsoft Office Professional 2007 60-day Convertible Trial needs online activation to begin. 60-day starts from day of activation

"PCI Express" and the PCI Express design marks are registered trademarks and/or service marks of PCI-SIG.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discobured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature. 5° to 35°C / 41 to 95°F (operating), -15° to 60°C / 5 to 140°F (non-operating), Relative humidity-20% to 85% RH (operating), 8% to 85% RH (non-operating). Please note that GB = billion bytes. TGB is equivalent to 1,073,741,824 bytes.







