

LifeBook N3510

- Brilliant Crystal View™ SuperFine LCD display for excellent movie-viewing and rich multimedia playback
- Instant MyMedia for your instant DVD entertainment in Dolby™ Digital Surround Sound
- UPDATE NAVI™ preinstalled to keep your LifeBook drivers up-to-date for hassle-free computing
- A multimedia machine perfect for work and play



SINGAPORE:

Fujitsu PC Asia Pacific Pte Ltd
Tel : (65) 6776 0688
Fax : (65) 6776 0788

MALAYSIA:

Fujitsu PC Asia Pacific Pte Ltd
Tel : (60-3) 2093 3997
Fax : (60-3) 2093 4245

HONG KONG:

Fujitsu PC Asia Pacific Ltd
Tel : (852) 3101 8133
Fax : (852) 3101 0633

THAILAND:

Fujitsu Systems Business (Thailand) Ltd PC Division
Tel : (66-2) 263 7888
Fax : (66-2) 263 7880

AUSTRALIA:

Fujitsu PC Australia
Toll Free: 1800 288 283
Tel : (61-2) 9004 7455
Fax : (61-2) 9004 7720
www.lifebook.com.au

CHINA:

Fujitsu PC China Division
Tel : (86-21) 3310 0808
Fax : (86-21) 3310 0606
www.pc-cn.fujitsu.com

PHILIPPINES:

Fujitsu Philippines Inc.
Tel : (63-2) 812 4001
Fax : (63-2) 817 7576

TAIWAN:

Fujitsu Taiwan Ltd
Tel : (886-2) 2311 2255
Fax : (886-2) 2311 2277

VIETNAM:

Fujitsu Vietnam Ltd
Tel : (84-4) 831 3895-7
Fax : (84-4) 831 3898

INDONESIA:

PT Fujitsu Systems Indonesia
Tel : (86-21) 570 9330
Fax : (62-21) 573 5150
www.fujitsu.com/id

Note: For countries not listed above, please contact our Singapore office.

N3510 Recommended Configuration	
Platform	Intel® Centrino™ Mobile Technology - Intel® Pentium® M Processor 740 (1.73GHz, 2MB L2 Cache, 533MHz FSB) - Intel® PRO/Wireless 2200BG network connection - Intel® 915PM Chipset
OS Supported	Microsoft® Windows® XP Home Edition Microsoft® Windows® XP Professional Edition
Display	15.4" Crystal View™ SuperFine Wide XGA TFT, 1280 x 800 pixels
Built-in Optical Device	Dual Layer DVD Super Multi Writer
Memory	512MB DDR2 400MHz
Hard Disk	100GB ⁵
Battery	Up to 3.7hrs ¹ (9-cell Li-Ion 7200mAh)
Weight	Approx. 3.4kg
Specifications	
Max. Memory Supported	2048MB DDR2 400MHz, 2 DDR2 SO-DIMM slot
Hard Disk Drive	Ultra DMA/100 and S.M.A.R.T support
Graphics	ATI MOBILITY™ RADEON® X300 Graphic Controller 64MB VRAM PCI Express™ x16
Audio	Realtek ALC203 codec with built-in Stereo Speakers
Communication	56K V.92 ² modem, 100/10Mbps ³ Fast Ethernet and Intel® PRO/Wireless 2200BG network connection 802.11b/g with Dual Antenna. Separate ON/OFF switch for wireless network connection
User Interface	Keyboard: 86-key, 19mm key pitch, 3mm key stroke Touch Pad with Scroll Buttons
Card Slot	PC Card Type I/II x 1 SD Card/ Memory Stick PRO x 1 ExpressCard™/34/54 Support X 1
Connector Interface	USB 2.0 x 4, VGA (external display), RJ45 (LAN), RJ11 (modem), IEEE1394, Headphone-out, Microphone-in, S-Video terminal, SPDIF Digital Out, Power Adapter AC-in
Quick Launch Panel	Four Programmable Application Launch Buttons (Internet, Email and two other software), Instant MyMedia (DVD/CD) Launch Button
Security ⁴	BIOS Lock, Hard Disk Lock, Anti-theft Lock Slot
Dimensions	356mm (W) x 262mm (D) x 39.9mm (H)
Bundled Accessories	
AC Adapter	Input AC 100 ~ 240V, Output DC 19V 80W
Bundled Software	Adobe Acrobat 6.0, CyberLink PowerDVD, CyberLink PowerProducer™ Gold, Fujitsu UPDATE NAVI™, Fujitsu Hardware Diagnostic Tool, Sonic RecordNow™ DX
Software on CD	Norman Virus Control & Norman Personal Firewall
Optional Accessories	
Floppy Disk Drive	External USB 1.44MB FDD
Mouse	RF Wireless Optical Mouse ⁶ , USB Optical Scroll Mouse

The above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

- Results obtained from Ziff Davis (BusinessWinstone 2001) Battery Mark V1.0.1 performed on systems with maximum battery life setting. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences. Modular Bay devices or hard drive usage may also have a significant impact on battery life.
- Maximum 56Kbps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.
- This term does not represent actual data rate of 100/10Mbps and simply indicates compliance with IEEE 802.3 and IEEE 802.3u standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices.
- BIOS Lock needs a supervisor/user password to access BIOS setup. BIOS settings can be configured to prompt for password at every first bootup or all bootup sequences. Access to BIOS setup is needed to configure Hard Disk Lock. Hard Disk Lock requires an access key to retrieve data on the hard disk. This is a Data Confidentiality security feature. Anti-theft Lock Slot allows the use of a lock to physically secure the LifeBook. NOTE: Loss of password requires the LifeBook to be returned to Japan factory for system refresh. Cost of shipment and lost data will be borne by the customer.
- HDD Capacity available for users will be less than 100GB as some HDD capacity will be used for basic file system management and Instant MyMedia application.
- Available in Hong Kong, Malaysia and Singapore only.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weight as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5° to 35°C/ 41 to 95°F (operating), -10° to 60°C/ 14 to 140°F (non-operating). Relative humidity: 20% to 80% RH (operating and non-operating).

ATI, MOBILITY and RADEON are used under license and are registered trademarks of ATI Technologies Inc. in the United States and other countries.

Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.



www.pc-ap.fujitsu.com

All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.

Dealer: